



WING FEATHERWEIGHT UNIT HEATERS

The first light-weight, ceiling-suspended, unit heater. Eight different designs of outlets meet the requirements of every type, size and height of building or occupancy. Located near ceiling or roof, the accumulation of hot air in the upper spaces, with the accompanying costly waste of heat, is prevented. They project the air, comfortably warmed, downward to the working area. *Bulletin H-9.*




Type "HC" Fixed Discharge




Design No. 3



Design No. 4



Design No. 8



VARIABLE TEMPERATURE SECTIONS

Invaluable in supplying fresh air for space heating or process work. Close control of the delivered air temperature is obtained without danger of freezing. *Bulletin HS-2.*




DOOR HEATERS GARAGE HEATERS

WING originated the vertical cone-discharge heater in 1921 and today it is

still applicable for heating the intrush of cold air at large doorways and for garage heating. Often cuts heating costs in half. *Bulletins D-1 and G-1.*


FOR LOW CEILINGS

In this type of WING Unit Heater the position of fan and motor are reversed to meet conditions of ceiling or roof height, form and shape of building, coverage, etc. *Bulletins HR-1 and H-9.*



Type "LC"


WING UTILITY UNIT HEATERS



A lightweight suspended unit heater for delivering heated air in one general direction. Has the same powerful fan and rugged heating element as WING Featherweight Unit Heaters. This is the latest refinement of the original horizontal lightweight heater which was developed by WING. *Bulletin U-5.*


FEATHERFIN HEATER SECTIONS

For heating or cooling air for any purpose by steam, hot or cold water or refrigerant. The heating element is extremely light and, for equal heat transfer, offers little resistance to air flow. Available for any desired final air temperature. *Bulletin HS-2.*



WING INDUSTRIAL FOG ELIMINATORS

Eliminate fog, odor and fumes in dyeing, bleaching and finishing plants, creameries, pasteurizing, bottling, canning and packing plants, chemical works, paper mills, steel pickling plants, etc. No ducts are required. *Bulletin FE-12.*




TURBINE-DRIVEN HEATERS

Any WING Unit Heater can be furnished with steam turbine-driven fan for locations where high-pressure steam is available. Photo shows turbine-driven revolving unit heater. Can also be supplied for fixed discharge or utility type heater. *Bulletin HR-1 and H-9.*



WING-SCRUPLEX SAFETY VENTILATING FANS




A propeller type fan that will deliver air against static pressure, quietly and efficiently. Moves the air forward in straight lines with minimum eddy. Capacities to 100,000 cfm. *Bulletin F-8.*

WING FEATHERFIN PROCESS HEATING UNITS



For manufacturing processes such as drying, aging, etc., requiring the recirculation of the heated air. Motor or turbine located outside air current. *Bulletin P-2.*

WING-SCRUPLEX EXHAUSTERS



For economically moving air wherever ducts are used. It combines the efficient WING-Scruplex Propeller Fan with a housing which places the motor entirely outside the air duct. Motor and drive remain cool and clean and are easily accessible.

The powerful WING-Scruplex Fan delivers high air volume with low power consumption against any pressures for which duct systems should be designed. V-belt or direct drive.

Light, compact and easy to install. *Bulletin 78-A.*

WING SYSTEM OF CONTROLLED COMBUSTION

For low pressure heating boilers and small power boilers. Increases capacity and permits use of lowest cost fuel. Includes Type EM Blower equipped with fully enclosed dustproof motor with speed regulating rheostat and automatic control. Eliminates necessity of frequent firing, allowing intervals as great as 24 hours even in zero weather. *Bulletin M-96.*




Installation of Wing System of Controlled Combustion in a large school

WING TURBINE-DRIVEN BLOWERS


Applied to hand, stoker, oil or pulverized fuel fired boilers, increase boiler capacity, maintain constant steam pressure* and

permit complete combustion of low-cost fuels. The exhaust steam, free from oil, can be used for heating or processes. *Bulletin T-98.*



WING DRAFT INDUCERS


Installed in breeching or flue, or on chimney top; provide positive, exact draft regardless of weather conditions or inadequate chimney or breeching construction. Suitable for coal, oil, or gas-fired boilers; industrial furnaces and kilns. *Bulletin I-10.*



Chimney-Top Installation

WING MOTOR-DRIVEN BLOWERS

Type COM for static pressures up to 10 in. W. G. and volumes up to 50,000 cfm. Type EMD for moderate static pressures up to 2½ in. Both blowers have fully-enclosed dustproof constant speed motor and built-in adjustable control vanes. Type COM has double-staged axial flow fan; Type EMD, single stage fan. Extremely compact; discharge can be vertical, horizontal or inclined. *Bulletin CO-4.*



Type COM



Type EMD