

Rules and Regulations

Title 29—LABOR

Chapter I—National Labor Relations Board

PART 102—RULES AND REGULATIONS, SERIES 8

Subpart I—Service and Filing of Papers

PROOF OF SERVICE

Section 102.112 is amended to read as follows:

§ 102.112 Same; by parties; proof of service.

Service of papers by a party on other parties shall be made by registered mail, or by certified mail, or in any manner provided for the service of papers in a civil action by the law of the State in which the hearing is pending. Except for charges, petitions, exceptions, briefs, and other papers for which a time for both filing and response has been otherwise established, service on all parties shall be made in the same manner as that utilized in filing the paper with the Board, or in a more expeditious manner; however, when filing with the Board is accomplished by personal service the other parties shall be promptly notified of such action by telephone, followed by service of a copy by mail or telegraph. When service is made by registered mail, or by certified mail, the return post office receipt shall be proof of service. When service is made in any manner provided by the law of a State, proof of service shall be made in accordance with such law.

This section shall become effective upon date of publication (8-13-71).

OGDEN W. FIELDS,
Executive Secretary.

[FR Doc. 71-11719 Filed 8-12-71; 8:50 am]

Chapter XVII—Occupational Safety and Health Administration, Department of Labor

PART 1910—OCCUPATIONAL SAFETY AND HEALTH STANDARDS

Miscellaneous Amendments

On May 29, 1971, occupational safety and health standards were promulgated (36 F.R. 10466). Subsequent review of the standards, and comments and requests for information from the public have pointed up the need for some clarifications, corrections, and changes in effective dates of standards.

Reconsideration of "additional delay in effective date" provisions in various subparts of 29 CFR Part 1910 has shown that the scope of the provisions is too

broad, and includes standards for which no delay is necessary for compliance. The purpose of some of the amendments is to limit the additional delay provisions to the specific standards that need additional time, so that the other standards may become effective sooner. On the other hand, Subpart J of Part 1910 is amended to give for the first time an additional delay to specified provisions.

Section 1910.179(b)(2) has been revised in order to give some time for the modification of existing overhead and gantry cranes, and to reflect accurately the American National Standards Institute (ANSI) standard from which the provision is derived. Similar changes have been made in § 1910.180 (crawler, locomotive, and truck cranes) and in § 1910.181 (derricks), for the same reasons.

Section 1910.217(a)(2) has been revised in order to give 36 months for the modification of presently installed mechanical power presses. The delay is given in the ANSI standard adopted in the section.

Section 1910.93 (air contaminants) has been revised in its entirety, in the interest of greater intelligibility and accuracy.

Several different dates have been changed to August 31, 1971, in order to achieve greater uniformity throughout Part 1910. Other amendments are made to correct mistakes, supply omissions, and to provide greater clarity.

Accordingly, pursuant to authority in section 6(a) and 8(g) of the Williams-Steiger Occupational Safety and Health Act of 1970 (84 Stat. 1593, 1600; 29 U.S.C. 655, 357), 29 CFR Part 1910 is hereby amended as set forth below. The provisions of 5 U.S.C. 553 concerning notice of proposed rule making, public participation therein, and delay in effective date are inapplicable by virtue of the exception to 5 U.S.C. Chapter 5 provided in section 6(a) of the Act. In addition, notice and public procedure are unnecessary because of the nature of the amendments, and impracticable, because of the need to give as much advance notice as possible of the changes before August 27, 1971, when many standards in Part 1910 become effective.

Part 1910 is amended as follows:

1. Section 1910.93 of Subpart G is revised to read as follows:

§ 1910.93 Air contaminants.

An employee's exposure to any material listed in table G-1, G-2, or G-3 of this section shall be limited in accordance with the requirements of the following paragraphs of this section.

(a) Table G-1:

(1) *Materials with names preceded by "C"—Ceiling Values.* An employee's exposure to any material in table G-1, the name of which is preceded by a "C" (e.g., C Boron trifluoride), shall at no time

exceed the ceiling value given for that material in the table.

(2) *Other materials—8-hour time weighted averages.* An employee's exposure to any material in table G-1, the name of which is not preceded by "C", in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average given for that material in the table.

(b) Table G-2:

(1) *8-hour time weighted averages.* An employee's exposure to any material listed in table G-2, in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average limit given for that material in the table.

(2) *Acceptable ceiling concentrations.* An employee's exposure to a material listed in table G-2 shall not exceed at any time during an 8-hour shift the acceptable ceiling concentration limit given for the material in the table, except for a time period, and up to a concentration not exceeding the maximum duration and concentration allowed in the column under "acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift".

(3) *Example.* During an 8-hour work shift, an employee may be exposed to a concentration of Benzene above 25 p.p.m. (but never above 50 p.p.m.) only for a maximum period of 10 minutes. Such exposure must be compensated by exposures to concentrations less than 10 p.p.m. so that the cumulative exposure for the entire 8-hour work shift does not exceed a weighted average of 10 p.p.m.

(c) Table G-3: An employee's exposure to any material listed in table G-3, in any 8-hour work shift of a 40-hour work week, shall not exceed the 8-hour time weighted average limit given for that material in the table.

(d) Computation formulae:

(1) (i) The cumulative exposure for an 8-hour work shift shall be computed as follows:

$$E = \frac{C_1 T_1 + C_2 T_2 + \dots + C_n T_n}{8}$$

where:

E is the equivalent exposure for the working shift.

C is the concentration during any period of time T where the concentration remains constant.

T is the duration in hours of the exposure at the concentration C.

The value of E shall not exceed the 8-hour time weighted average limit in table G-1, G-2, or G-3 for the material involved.

(ii) To illustrate the formula prescribed in subdivision (i) of this subparagraph, note that isomyl acetate has an 8-hour time weighted average limit of 100 p.p.m. (table G-1). Assume that an

RULES AND REGULATIONS

employee is subject to the following exposure:

- Two hours exposure at 150 p.p.m.
- Two hours exposure at 75 p.p.m.
- Four hours exposure at 50 p.p.m.

Substituting this information in the formula, we have

$$\frac{2 \times 150 + 2 \times 75 + 4 \times 50}{8} = 81 \text{ p.p.m.}$$

Since 81 p.p.m. is less than eight, the 8-hour time weighted average limit, the exposure is acceptable.

(2) (i) In case of a mixture of air contaminants an employer shall compute the equivalent exposure as follows:

$$E_m = \frac{C_1}{L_1} + \frac{C_2}{L_2} + \dots + \frac{C_n}{L_n}$$

Where:

E_m is the equivalent exposure for the mixture.

C is the concentration of a particular contaminant.

L is the exposure limit for that contaminant, from table G-1, G-2, or G-3.

The value of E_m shall not exceed unity (1).

(ii) To illustrate the formula prescribed in subdivision (i) of this subparagraph, consider the following exposures:

Material	Actual concentration of 8-hour exposure	8-hour time weighted average exposure limit
Acetone (Table G-1)	500 p.p.m.	1,000 p.p.m.
2-Butanone (Table G-1)	45 p.p.m.	200 p.p.m.
Toluene (Table G-2)	40 p.p.m.	200 p.p.m.

Substituting in the formula, we have:

$$E_m = \frac{500}{1,000} + \frac{45}{200} + \frac{40}{200}$$

$$E_m = 0.500 + 0.225 + 0.200$$

$$E_m = 0.925$$

Since E_m is less than unity (1), the exposure combination is within acceptable limits.

(e) To achieve compliance with paragraph (a) through (d) of this section, administrative or engineering controls must first be determined and implemented whenever feasible. When such controls are not feasible to achieve full compliance, protective equipment or any other protective measures shall be used to keep the exposure of employees to air contaminants within the limits prescribed in this section. Any equipment and technical measure use for this purpose must be approved for each particular use by a competent industrial hygienist or other technically qualified person. Whenever respirators are used, their use shall comply with § 1913.134 of this chapter.

TABLE G-1

Substance	p.p.m.*	mg./M ³ †
Acetaldehyde	200	360
Acetic acid	10	25
Acetic anhydride	5	20
Acetone	1,000	2,400
Acetonitrile	40	70
Acetylene dichloride, see 1,2-Dichloroethylene		
Acetylene tetrabromide	1	14
Acrolein	0.1	0.25
Acrylamide—Skin		0.3
Acrylonitrile—Skin	20	45
Aldrin—Skin		0.2
Allyl alcohol—Skin	2	5
Allyl chloride	1	5
*C Allyl glycidyl ether (AGE)	10	45
Allyl propyl disulfide	2	12
2-Aminoethanol, see Ethanolamine		
2-Aminopyridine	0.5	2
*Ammonia	50	35
Ammonium sulfate (Am-mate)		15
n-Amyl acetate	100	525
sec-Amyl acetate	125	650
Aniline—Skin	5	19
Anisidine (o, p-isomers)—Skin		0.5
Antimony and compounds (as Sb)		0.5
ANTU (alpha naphthylthiourea)		0.3
Arsenic and compounds (as As)		0.5
Arsine	0.05	0.2
Azobenzene—Skin		0.2
Barium (soluble compounds)		0.5
p-Benzquinone, see Quinone		
Benzoyl peroxide	5	5
Benzyl chloride	1	5
Biphenyl, see Diphenyl		
Bisphenol A, see Diglycidyl ether		
Boron oxide		15
C Boron trifluoride	1	3
Bromine	0.1	0.7
Bromoform—Skin	0.5	5
Butadiene (1,3-butadiene)	1,000	2,200
Butanethiol, see Butyl mercaptan		
2-Butanone	200	590
2-Butoxy ethanol (Butyl Cellosolve)—Skin	50	240
Butyl acetate (n-butyl acetate)	150	710
sec-Butyl acetate	200	950
tert-Butyl acetate	200	950
Butyl alcohol	100	300
sec-Butyl alcohol	150	450
tert-Butyl alcohol	100	300
C Butylamine—Skin	5	15
C tert-Butyl chromate (as CrO ₃)—Skin		0.1
n-Butyl glycidyl ether (BGE)	50	270
*Butyl mercaptan	10	35
p-tert-Butyltoluene	10	60
Calcium arsenate		1
Calcium oxide		5
*Camphor	2	
Carbaryl (Sevin ®)		5
Carbon black		3.5
Carbon dioxide	5,000	9,000
Carbon monoxide	50	55
Chlordane—Skin		0.5
Chlorinated camphene—Skin		0.5
Chlorinated diphenyl oxide		0.5
*Chlorine	1	3
Chlorine dioxide	0.1	0.3
C Chlorine trifluoride	0.1	0.4
C Chloroacetaldehyde	1	3
α-Chloroacetophenone (phenacylchloride)	0.05	0.3
Chlorobenzene (monochlorobenzene)	75	350
o-Chlorobenzylidene malononitrile (OCBM)	0.05	0.4
Chlorobromomethane	200	1,050
2-Chloro-1,3-butadiene, see Chloroprene		
Chlorodiphenyl (42 percent Chlorine)—Skin		1
Chlorodiphenyl (54 percent Chlorine)—Skin		0.5
1-Chloro-2,3-epoxypropane, see Epichlorohydrin		
2-Chloroethanol, see Ethylene chlorohydrin		
Chloroethylene, see Vinyl chloride		
C Chloroform (trichloromethane)	50	240
1-Chloro-1-nitropropane	20	100
Chloropicrin	0.1	0.7
Chloroprene (2-chloro-1,3-butadiene)—Skin	25	90

TABLE G-1—Continued

Substance	p.p.m.*	mg./M ³ †
Chromium, sol. chromic, chromous salts as Cr		0.5
Metal and insol. salts		1
Coal tar pitch volatiles (benzene soluble fraction) anthracene, BaP, phenanthrene, acridine, chrysene, pyrene		0.2
Cobalt, metal fume and dust		0.1
Copper fume		0.1
Dusts and Mists		1
Cotton dust (raw)		1
Crag® herbicide		15
Crotonol (all isomers)—Skin	5	22
Crotonaldehyde	2	6
Cumene—Skin	50	245
Cyanide (as CN)—Skin		5
Cyclohexane	300	1,050
Cyclohexanol	50	200
Cyclohexanone	50	200
Cyclohexene	300	1,015
Cyclopentadiene	75	200
2,4-D		10
DDT—Skin		1
DDVP, see Dichlorvos		
Decaborane—Skin	0.05	0.3
Decaboron®—Skin		0.1
Diacetone alcohol (4-hydroxy-4-methyl-2-pentanone)	50	240
1,2-Diaminoethane, see Ethylenediamine		
Diazomethane	0.2	0.4
Diborane	0.1	0.1
Dibutylphthalate	5	5
C o-Dichlorobenzene	50	300
p-Dichlorobenzene	75	450
Dichlorodifluoromethane	1,000	4,950
1,3-Dichloro-5,5-dimethyl hydantoin		0.2
1,1-Dichloroethane	100	400
1,2-Dichloroethylene	200	790
C Dichloroethyl ether—Skin	15	90
Dichloromethane, see Methylenechloride		
Dichloromono fluoromethane	1,000	4,200
C 1,1-Dichloro-1-nitroethane	10	60
1,2-Dichloropropane, see Propylenedichloride		
Dichlorotetrafluoroethane	1,000	7,000
Dichlorvos (DDVP)—Skin		1
Dieldrin—Skin		0.25
Diethylamine	25	75
Diethylamino ethanol—Skin	10	50
Diethylether, see Ethyl ether		
Difluorodibromomethane	100	880
C Diglycidyl ether (DGE)	0.5	2.8
Dihydroxybenzene, see Hydroquinone		
Disobutyl ketone	50	290
Disopropylamine—Skin	5	20
Dimethoxymethane, see Methylal		
Dimethyl acetamide—Skin	10	35
Dimethylamine	10	18
Dimethylaminobenzene, see Xylidene		
Dimethylaniline (N-dimethylaniline)—Skin	5	25
Dimethylbenzene, see Xylene		
Dimethyl 1,2-dibromo-2,2-dichloroethyl phosphate, (Dibrom)		3
Dimethylformamide—Skin	10	30
2,6-Dimethylheptanone, see Diisobutyl ketone		
1,1-Dimethylhydrazine—Skin	0.5	1
Dimethylphthalate		5
Dimethylsulfate—Skin	1	5
Dinitrobenzene (all isomers)—Skin		1
Dinitro-o-cresol—Skin		0.2
Dinitrotoluene—Skin		1.5
Dioxane (Diethylene dioxide)—Skin	100	360
Diphenyl	0.2	1
Diphenylmethane diisocyanate (see Methylene bisphenyl isocyanate (MDI))		
Dipropylene glycol methyl ether—Skin	100	600
Di-sec, octyl phthalate (Di-2-ethylhexylphthalate)		5
Endrin—Skin		0.1
Epichlorohydrin—Skin	5	19
EPN—Skin		0.5
1,2-Epoxypropane, see Propyleneoxide		
2,3-Epoxy-1-propanol, see Glycidol		
Ethanethiol, see Ethylmercaptan		

See footnotes at end of table.

RULES AND REGULATIONS

15103

TABLE G-I—Continued

Substance	p.p.m.*	mg./M ² *
Ethanolamine	3	6
2-Ethoxyethanol—Skin	200	740
2-Ethoxyethylacetate (Cellosolve acetate)—Skin	100	540
Ethyl acetate	400	1,400
Ethyl acrylate—Skin	25	100
Ethyl alcohol (ethanol)	1,000	1,900
Ethylamine	10	18
Ethyl sec-amy ketone (6-methyl-3-heptanone)	25	130
Ethyl benzene	100	435
Ethyl bromide	200	890
Ethyl butyl ketone (3-Heptanone)	50	230
Ethyl chloride	1,000	2,600
Ethyl ether	400	1,200
Ethyl formate	100	300
O Ethyl mercaptan	10	25
Ethyl silicate	100	850
Ethylene chlorohydrin—Skin	5	16
Ethylenediamine	10	25
Ethylene dibromide, see 1,2-Dibromoethane		
Ethylene dichloride, see 1,2-Dichloroethane		
C Ethylene glycol dinitrate and/or Nitroglycerin—Skin	0.2	1
Ethylene glycol monomethyl ether acetate, see Methyl cellosolve acetate		
Ethyleneimine—Skin	0.5	1
Ethylene oxide	50	90
Ethylidene chloride, see 1,1-Dichloroethane		
N-Ethylmorpholine—Skin	20	94
Perbam		15
Ferrocyanide dust		1
Fluoride (as F)		2.5
Fluorine	0.1	0.2
Fluorotrichloromethane	1,000	5,600
Formic acid	5	9
Furfural—Skin	5	20
Furfuryl alcohol	50	200
Glycidol (2,3-Epoxy-1-propanol)	50	150
Glycol monoethyl ether, see 2-Ethoxyethanol		
Guthion, ® see Azinphos-methyl		
Helium		0.5
Heptachlor—Skin		0.5
Heptane (n-heptane)	500	2,000
Hexachloroethane—Skin	1	10
Hexachloronaphthalene—Skin		0.2
Hexane (n-hexane)	500	1,800
2-Hexanone	100	410
Hexone (Methyl isobutyl ketone)	100	410
sec-Hexyl acetate	50	300
Hydrazine—Skin	1	1.3
Hydrogen bromide	3	10
C Hydrogen chloride	5	7
Hydrogen cyanide—Skin	10	11
Hydrogen peroxide (90%)	1	1.4
Hydrogen selenide	0.05	0.2
Hydroquinone		2
C Iodine	0.1	1
Iron oxide fume		10
Isoamyl acetate	100	525
Isoamyl alcohol	100	360
Isobutyl acetate	150	700
Isobutyl alcohol	100	300
Isophorone	25	140
Isopropyl acetate	250	950
Isopropyl alcohol	400	980
Isopropylamine	5	12
Isopropylether	500	2,100
Isopropyl glycidyl ether (IGE)	50	240
Ketene	0.5	0.9
Lead arsenate		0.15
Lindane—Skin		0.5
Lithium hydride		0.025
L.P.G. (liquefied petroleum gas)	1,000	1,800
Magnesium oxide fume		15
Malathion—Skin		15
Maleic anhydride	0.25	1
C Manganese		5
Mesityl oxide	25	100
Methanethiol, see Methyl mercaptan		
Methoxychlor		15
2-Methoxyethanol, see Methyl cellosolve		
Methyl acetate	200	610
Methyl acetylene (propyne)	1,000	1,650
Methyl acetylene-propadiene mixture (MAFP)	1,000	1,800
Methyl acrylate—Skin	10	35
Methylal (dimethoxymethane)	1,000	3,100
Methyl alcohol (methanol)	200	260
Methylamine	10	12
Methyl amyl alcohol, see Methyl isobutyl carbinol		

TABLE G-I—Continued

Substance	p.p.m.*	mg./M ² *
Methyl (n-amy) ketone (2-Heptanone)	100	455
C Methyl bromide—Skin	20	80
Methyl butyl ketone, see 2-Hexanone		
Methyl cellosolve—Skin	25	80
Methyl cellosolve acetate—Skin	25	120
Methyl chloroform	350	1,900
Methylcyclohexane	500	2,000
Methylcyclohexanol	100	470
o-Methylcyclohexanone—Skin	100	460
Methyl ethyl ketone (MEK), see 2-Butanone		
Methyl formate	100	250
Methyl iodide—Skin	5	28
Methyl isobutyl carbinol—Skin	25	100
Methyl isobutyl ketone, see Hexone		
Methyl isocyanate—Skin	0.02	0.05
C Methyl mercaptan	10	20
Methyl methacrylate	100	410
Methyl propyl ketone, see 2-Pentanone		
C α Methyl styrene	100	480
C Methylene bisphenyl isocyanate (MDI)	0.02	0.2
Molybdenum:		
Soluble compounds		5
Insoluble compounds		15
Monomethyl aniline—Skin	2	9
C Monomethyl hydrazine—Skin	0.2	0.35
Morpholine—Skin	20	70
Naphtha (coal tar)	100	400
Naphthalene	10	80
Nickel carbonyl	0.001	0.007
Nickel, metal and soluble cmpds, as Ni		1
Nicotine—Skin		0.5
Nitric acid	2	5
Nitric oxide	25	30
p-Nitroaniline—Skin	1	5
Nitrobenzene—Skin	1	5
p-Nitrochlorobenzene—Skin	100	310
Nitroethane	5	9
Nitrogen dioxide	10	29
Nitrogen trifluoride	0.2	2
Nitroglycerin—Skin	100	250
1-Nitropropane	25	90
2-Nitropropane	25	90
Nitrotoluene—Skin	5	30
Nitrotrichloromethane, see Chloropicrin		
Octachloronaphthalene—Skin		0.1
*Octane	500	2,350
*Oil mist, mineral		5
Oxanium tetroxide		0.002
Oxalic acid		1
Oxygen difluoride	0.05	0.1
Ozone	0.1	0.2
Parquat—Skin		0.5
Petroleum distillates (naptha)	500	2,000
Propane	1,000	1,800
Silver, metal and soluble compounds		0.01
Sodium fluoroacetate (100%)—Skin		0.05
Sodium hydroxide		2
Stibine	0.1	0.5
*Stoddard solvent	500	2,950
Strychnine		0.15
Sulfur dioxide	5	13
Sulfur hexafluoride	1,000	6,000
Sulfuric acid		1
Sulfur monochloride	1	6
Sulfur pentafluoride	0.025	0.25
Sulfuryl fluoride	5	20
Systox, see Demeton ®		
2,4,5T		10
Tantalum		5
TEDP—Skin		0.2
Tellurium		0.1
Tellurium hexafluoride	0.02	0.2
TEPP—Skin		0.05
C Terphenyls	1	9
1,1,1,2-Tetrachloro-2,2-difluoroethane	500	4,170
1,1,2,2-Tetrachloro-1,2-difluoroethane	500	4,170
1,1,2,2-Tetrachloroethane—Skin	5	35
Tetrachloroethylene, see Perchloroethylene		
Tetrachloromethane, see Carbon tetrachloride		
Tetrachloronaphthalene—Skin		2
Tetraethyl lead (as Pb)—Skin		0.075
Tetrahydrofuran	200	590
Tetramethyl lead (as Pb)—Skin		0.075
Tetramethyl succinonitrile—Skin	0.5	3
Tetranitromethane	1	8

TABLE G-I—Continued

Substance	p.p.m.*	mg./M ² *
Tetryl (2,4,6-trinitrophenyl-methyl nitramine)—Skin		1.5
Thallium (soluble compounds)—Skin as Tl		0.1
Thiram		5
Tin (inorganic cmpds, except oxides)		2
Tin (organic cmpds)		0.1
C Toluene-2,4-dithiocyanate	0.02	0.14
o-Toluidine—Skin	5	22
Toxaphene, see Chlorinated camphene		
Tributyl phosphate		5
1,1,1-Trichloroethane see Methyl chloroform		
1,1,2-Trichloroethane—Skin	10	45
Parathion—Skin		0.1
Pentaborane	0.005	0.0
Pentachloronaphthalene—Skin		0.5
Pentachlorophenol—Skin		0.5
*Pentane	1,000	2,950
2-Pentanone	200	700
Perchloromethyl mercaptan	0.1	0.8
Perchloryl fluoride	3	13.5
Phenol—Skin	5	19
p-Phenylene diamine—Skin		0.1
Phenyl ether (vapor)	1	7
Phenyl ether-biphenyl mixture (vapor)	1	7
Phenylethylene, see Styrene		
Phenyl glycidyl ether (PGE)	10	60
Phenylhydrazine—Skin	5	22
Phosdrin (Mevinphos ®)—Skin		0.1
Phosgene (carbonyl chloride)	0.1	0.4
Phosphine	0.3	0.4
Phosphoric acid		1
Phosphorus (yellow)		0.1
Phosphorus pentachloride		1
Phosphorus pentasulfide		1
Phosphorus trichloride	0.5	3
Phthalic anhydride	2	12
Picric acid—Skin		0.1
Pival ® (2-Pivalyl-1,3-indandione)		0.1
Platinum (Soluble Salts) as Pt		0.002
Propargyl alcohol—Skin	1	
n-Propyl acetate	200	840
Propyl alcohol	200	500
n-Propyl nitrate	25	110
Propylene dichloride	75	350
Propyleneimine—Skin	2	5
Propylene oxide	100	240
Propyne, see Methylacetylene		
Pyrethrum		5
Pyridine	5	15
Quinone	0.1	0.4
RDX—Skin		1.5
Rhodium, Metal fume and dusts, as Rh		0.1
Soluble salts		0.001
Ronnel		10
Rotenone (commercial)		5
Selenium compounds (as Se)		0.2
Selenium hexafluoride	0.05	0.4
Titanium dioxide		15
Trichloromethane, see Chloroform		
Trichloronaphthalene—Skin		5
1,2,3-Trichloropropane	50	300
1,1,2-Trichloro-1,2,2-trifluoroethane	1,000	7,600
Triethylamine	25	100
Trifluoromono-bromomethane	1,000	6,100
2,4,6-Trinitrophenol, see Picric acid		
2,4,6-Trinitrophenylmethyl-nitramine, see Tetryl		
Trinitrotoluene—Skin		1.5
Triorthocresyl phosphate		0.1
Triphenyl phosphate		3
Turpentine	100	560
Uranium (soluble compounds)		0.05
Uranium (insoluble compounds)		0.25
C Vanadium:		
V ₂ O ₅ dust		0.5
V ₂ O ₅ fume		0.1
Vinyl benzene, see Styrene		
**C Vinyl chloride	500	1,300
Vinylcyanide, see Acrylonitrile		
Vinyl toluene	100	480
Warfarin		0.1
Xylene (xytol)	100	435
Xylidine—Skin	5	25
Yttrium		1
Zinc chloride fume		1
Zinc oxide fume		5
Zirconium compounds (as Zr)		5

See footnotes at end of table.

RULES AND REGULATIONS

*1970 Addition.

* Parts of vapor or gas per million parts of contaminated air by volume at 25° C. and 760 mm. Hg pressure.
 * Approximate milligrams of particulate per cubic meter of air.
 (No footnote "c" is used to avoid confusion with ceiling value notations.)

* An atmospheric concentration of not more than 0.02 p.p.m., or personal protection may be necessary to avoid headache.
 * As sampled by method that does not collect vapor.
 * For control of general room air, biologic monitoring is essential for personnel control.

TABLE G-2

Material	8-hour time weighted average	Acceptable ceiling concentration	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hour shift.	
			Concentration	Maximum duration
Benzene (Z37.4-1969)	10 p.p.m.	25 p.p.m.	50 p.p.m.	10 minutes.
Beryllium and beryllium compounds (Z37.29-1970)	2 µg./M ³	5 µg./M ³	25 µg./M ³	30 minutes.
Cadmium fume (Z37.5-1970)	0.1 mg./M ³	3 mg./M ³		
Cadmium dust (Z37.5-1970)	0.2 mg./M ³	0.6 mg./M ³		
Carbon disulfide (Z37.3-1968)	20 p.p.m.	30 p.p.m.	100 p.p.m.	Do.
Carbon tetrachloride (Z37.17-1967)	10 p.p.m.	25 p.p.m.	200 p.p.m.	5 minutes in any 4 hours.
Ethylene dibromide (Z37.31-1970)	20 p.p.m.	30 p.p.m.	50 p.p.m.	5 minutes.
Ethylene dichloride (Z37.21-1969)	50 p.p.m.	100 p.p.m.	200 p.p.m.	5 minutes in any 3 hours.
Formaldehyde (Z37.16-1967)	3 p.p.m.	6 p.p.m.	10 p.p.m.	30 minutes.
Hydrogen fluoride (Z37.28-1969)	do.	do.	do.	do.
Fluoride as dust (Z37.28-1969)	2.5 mg./M ³			
Lead and its inorganic compounds (Z37.11-1959)	0.2 mg./M ³			
Methyl chloride (Z37.18-1969)	100 p.p.m.	200 p.p.m.	300 p.p.m.	5 minutes in any 3 hours.
Methylene Chloride (Z37.3-1969)	500 p.p.m.	1,000 p.p.m.	2,000 p.p.m.	5 minutes in any 2 hours.
Organo (alkyl) mercury (Z37.30-1969)	0.01 mg./M ³	0.04 mg./M ³		
Styrene (Z37.15-1969)	100 p.p.m.	200 p.p.m.	600 p.p.m.	5 minutes in any 3 hours.
Trichloroethylene (Z37.19-1967)	do.	do.	300 p.p.m.	5 minutes in any 2 hours.
Tetrachloroethylene (Z37.22-1967)	do.	do.	do.	5 minutes in any 3 hours.
Toluene (Z37.12-1967)	200 p.p.m.	300 p.p.m.	500 p.p.m.	10 minutes.
Hydrogen sulfide (Z37.2-1966)		20 p.p.m.	50 p.p.m.	10 minutes once only if no other measurable exposure occurs.
Mercury (Z37.8-1971)		1 mg./10M ³		
Chromic acid and chromates (Z37.7-1971)		do.		

TABLE G-3—MINERAL DUSTS

Substance	Mppcf*	Mg/M ³
Silica:		
Crystalline:		
Quartz (respirable).....	250 ¹	10mg/M ³
Quartz (total dust).....	%SiO ₂ +5	%SiO ₂ +2 30mg/M ³
		%SiO ₂ +2
Cristobalite: Use ½ the value calculated from the count or mass formulae for quartz.		
Tridymite: Use ½ the value calculated from the formulae for quartz.		
Amorphous, including natural diatomaceous earth.....	20	80mg/M ³
Tremolite.....	5	%SiO ₂ 20mg/M ³
Silicates (less than 1% crystalline silica):		
Asbestos—12 fibers per milliliter greater than 5 microns in length or.....	2	
Mica.....	20	
Soapstone.....	20	
Talc.....	20	
Portland cement.....	50	
Graphite (natural).....	15	
Coal dust (respirable fraction less than 5% SiO ₂).....		2.4mg/M ³ or 10mg/M ³
For more than 5% SiO ₂		%SiO ₂ +2
Inert or Nuisance Dust:		
Respirable fraction.....	15	5mg/M ³
Total dust.....	50	15mg/M ³

NOTE: Conversion factors—
 mppcf×35.3=millions particles per cubic meter
 =particles per c.c.

* Millions of particles per cubic foot of air, based on impinger samples counted by light-field technique.

¹ The percentage of crystalline silica in the formula is the amount determined from air-borne samples, except in those instances in which other methods have been shown to be applicable.

² As determined by the membrane filter method at 430× phase contrast magnification.

³ Both concentration and percent quartz for the application of this limit are to be determined from the fraction passing a size-selector with the following characteristics:

Aerodynamic diameter (unit density sphere)	Percent passing selector
2	90
2.5	75
3.5	50
5.0	25
10	0

The measurements under this note refer to the use of an AEC instrument. If the respirable fraction of coal dust is determined with a MRE the figure corresponding to that of 2.4 Mg/M³ in the table for coal dust is 4.5 Mg/M³

2. Section 1910.98 of Subpart G is revised to read as follows:

§ 1910.98 Effective dates.

(a) The provisions of this Subpart G shall become effective on August 27, 1971, except as provided in the remaining paragraphs of this section.

(b) The following provisions shall become effective on February 15, 1972:

§ 1910.94 (a) (2) (III), (a) (3), (a) (4), (b), (c) (2), (c) (3), (c) (4), (c) (5), (c) (6) (1), (c) (6) (II), (d) (1) (II), (d) (3), (d) (4), (d) (5), and (d) (7).

(c) Notwithstanding anything in paragraph (a), (b), or (d) of this section, any provision in any other section of this subpart which contains in itself a specific effective date or time limitation shall become effective on such date or shall apply in accordance with such limitation.

(d) Notwithstanding anything in paragraph (a) of this section, if any standard in 41 CFR Part 50-204, other than a national consensus standard incorporated by reference in § 50-204.2(a) (1), is or becomes applicable at any time to any employment and place of employment, by virtue of the Walsh-Healey Public Contracts Act, or the Service Contract Act of 1965, or the National Foundation on Arts and Humanities Act of 1965, any corresponding established Federal standard in this Subpart G which is derived from 41 CFR Part 50-204 shall also become effective, and shall be applicable to such employment and place of employment, on the same date.

3. Section 1910.114 of Subpart H is revised to read as follows:

§ 1910.114 Effective dates.

(a) The provisions of this Subpart H shall become effective on August 27, 1971, except as provided in the remaining paragraphs of this section.

(b) The following provisions shall become effective on February 15, 1972:

§ 1910.101 (b).
 § 1910.102.
 § 1910.103 (a) (2), (b) (1) (I), (b) (1) (III), (b) (2) (II), and (b) (3).
 § 1910.105.
 § 1910.106 (b) (1), (b) (2), (b) (3), and (b) (4).
 § 1910.106 (b) (5), (c) (1), (c) (2), (c) (3), (c) (4), (c) (5), (c) (6), (d) (2), (d) (3) (II), (d) (4) (I), (d) (4) (III), (d) (4) (IV), (d) (5) (V), (d) (5) (VI) (a), (e) (3) (II), (e) (3) (V), (e) (4), (e) (7), (f) (2) (III), (f) (3) (I), (f) (4) (III), (f) (4) (IV), (f) (4) (VIII), (f) (5), (g), (h), and (i).
 § 1910.107 (b) (1), (b) (2), (b) (3), (b) (4), (b) (5) (I), (b) (5) (III), (b) (5) (IV), (b) (6), (b) (7), (b) (8), (b) (10), (c) (1), (c) (4), (c) (5), (c) (6), (c) (7), (d), (e) (2), (e) (8), (f) (1), (f) (2), (h), (i), (j), (l) (2), (l) (3), (l) (5), (l) (6), (l) (7), and (m) (1).
 § 1910.108 (b), (c), (e) (1), (g) (2), (g) (3), (g) (4), and (g) (5).
 § 1910.108 (g) (5) and (h).
 § 1910.110.
 § 1910.111.

(c) Notwithstanding anything in paragraph (a), (b), or (d) of this section, any provision in any other section of this subpart which contains in itself a specific effective date or time limitation shall become effective on such date or shall apply in accordance with such limitation.

(d) Notwithstanding anything in paragraph (a), or (b) of this section, if any standard in 41 CFR Part 50-204, other than a national consensus standard incorporated by reference in § 50-204.2(a) (1), is or becomes applicable at any time to any employment and place of employment, by virtue of the Walsh-Healey Public Contracts Act, or the Service Contract Act of 1965, or the National Foundation on Arts and Humanities Act of 1965, any corresponding established