Glass (*continued*)
design tables, 196–204
heat absorbent, 199
shading of, 205
solar heat transmitted, 194
window transmittance, 196

Glass block walls
coefficient of transmission, 133
solar heat gain, 201–204
Globe thermometer, 652
Graphical symbols for drawings, 9–12
air conditioning, 9, 11, 12
ductwork, 10–12
heating, 9–11
piping, 9, 10
refrigerating, 11, 12
ventilating, 10, 11
Grate area, 3

Greek alphabet, 6

Grille, grilles (see *Registers*), 247, 277, 285, 353
air supply noises, 353
attenuation, 353, 354
exhaust, 289
locations, 247, 286, 289
door, 289
floor, 289
wall, 289
mechanical furnace systems, 247
noises, 289, 353
railway car, 682
recirculating, 682
return, 247, 289
velocity, 247, 279, 289
Ground temperatures, 169

Guarded hot plate, 652
Gun type oil burners, 500

H

Hangers, pipe, 460

Hartford return connection, 368, 386, 387

Hay fever symptoms, 100
Hazards
high temperature, 66, 96, 709
Health, 93

Heat, 3
area transmitting surface, 773
auxiliary sources, 173, 207
balance, 493
combustion, 480, 485, 487
cramps, 66
emission of
appliances, 207, 210, 211
occupants, 68, 69, 207
pipe coils, 219, 432
exchange measurements, 64
flow resistance, 53
flow through glass, 133, 194
flow through roofs, 112–120, 188
flow through walls, 112–128, 188
gain, 177
generated by motors, 207
humid, 3
infiltration equivalent, 206
instantaneous load, 179, 201
introduced by outside air, 206
lag, 201
latent, 3, 172, 177, 206, 208, 214
liquid, 3
loss, pipe, 467
mechanical equivalent of, 4, 8
methods of, transfer, 49

Heat (*continued*)
radiant, 50, 53, 54
ratio, sensible, 209
removal, natural ventilation, 154
sensible, 3, 171, 208
gain, 177, 206
loss, 171
specific, 3
stroke, 66
total, 3
transfer, 49, 112–128, 310, 773
boiler rates, 516
convective, 2
overall coefficients, 103, 107, 112–128, 330, 773
surface coils, 330
symbols, 9, 52, 103
through building materials, 103
upper limits, 67
water coils, 778

Heat gain
appliances, 207, 210, 211
ceilings, 205
components of, 177
ducts, 204, 310
electrical heating equipment, 210
floors, 205
gas burning equipment, 210
glass, 194–199
glass blocks, 198–204
infiltration, 206
instantaneous, 179, 201
latent, 179, 206, 208
lights, 207
miscellaneous, 209
moisture, 208
occupants, 207, 208
outside air, 206
partitions, 205
people, 68, 208
roof, 188–194
sensible, 179, 206
shaded windows, 205
solar, 194
steam heated equipment, 211
various sources, 173, 209
ventilation, 206
wall, 188, 192, 193

Heat loss
air change, 171
bare pipe, 219, 467
basement, 170
building materials, 109–111
ceiling, 120, 122, 123
computations, 161
calculated method, 161
crack method, 172
exposure factors, 173
factors of safety, 173
number of air changes, 172
duct, 310
glass, 133
floor slab, 170
infiltration, 171
insulated pipe, 470–474
latent, 172
pipe, 219, 467
residence problems, 173
roofs, 124–128
sensible, 171
surface to air, 108, 109
through ceilings and roofs, 171
transmission, 103, 171
ceilings and roofs, 120, 122–128
walls, 112–119

Heat pump, 3, 581
application, 592
basic circuits, 583

Heat pump (*continued*)
coefficient of performance, 583
components, 590
cooling load, 593
criteria for feasibility, 592
design, 593
distribution system, 593
equipment selection, 590–593
heating load, 589
heat sink, 585–587
heat source, 585–587
heat storage, 593
history, 581
operating cost, 590
performance characteristics, 587
performance factor, 583
seasonal performance, 589
selection, 593
system balance, 588
types, 583, 584
Heat removal, 154
Heat stress index, 1, 710

Heater, heaters
blast, 1
direct-fired unit, 227, 228
electric, 227, 230, 242
gas, 529
design, 530
efficiency, 529
materials, 529
oil, 528
design, 529
materials, 528
rating, 529
testing, 529
radiant, 507
solar water, 784
solid fuel, 527
design, 528
material, 528
rating, 528
testing, 528
space, 527
installation, 530
unit, 227, 242
vertical blow unit, 228

Heating
air-conditioning units, 233
boilers, 515
surface, 1, 516
coil selection, 328
comfort, 161
district, 395
effect, radiator, 221
electric, 241
hot water, 779
load, 161, 271, 520
performance of coils, 330, 781
reversed cycle refrigeration, 581
steam systems, 367
surface, 5
square foot of, 4
symbols for drawing, 9
vacuum systems, 6, 367, 371
vapor, 6, 370
warm air system, 6, 247
water, 403, 421, 777
Heavy duty fan furnace, 524
High duty humidifiers, 609
High temperature hazards, 66, 96

High temperature systems, 421
basic system, 421
boilers for, 423
control, 425, 428
design, 421, 426
direct contact heaters, 425
expansion cushion, 423
features, 421

High temperature systems (*continued*)
fittings, 426
fitting pressure loss, 428
heat exchangers, 425
pipe, 426
pumps, 426
storage, 430
water treatment, 430
High velocity systems, 273, 305
design, 305
control, 306
Hood, hoods, 719
Hot process exhaust, 721
Horsepower, boiler, 1

Hospital, hospitals
air conditioning in, 93, 101
operating rooms, 96
air conditions, 97
reducing explosion hazard, 96
sterilization of air, 93
ventilation requirements, 97

Hot water
boiler supply load, 520, 772
coil surface, 777
demand per
fixture, 765, 766, 773
person, 772
distribution, 402
electric heating, 779
heat pump, 785
heating surface, 781
indirect heater, 780
methods of heating, 777
panel heating, 431, 436
safety devices, 783
service, 772
service piping, 782
solar heaters, 784
storage tank, 773
supply
boilers, 515, 777–781
piping, 782
temperature control, 783

Hot water heating systems, 3, 403
circulation head, 403, 404
direct return system, 2
elbow equivalents, 408, 428
expansion tank, 415
forced circulation, 403
friction heads, 405–408
gravity, 403
high temperature, 421
basic system, 421
boilers, 423
control, 425, 428
design, 421, 426
direct contact heaters, 425
expansion cushion, 423
features, 421
heat exchangers, 425
pipe fittings, 426
pumps, 426
storage, 430
water treatment, 430
mechanical circulators, 414, 426
one-pipe
forced circulation, 410
pipe sizes, 405–408, 427
piping design, 405, 426
relief valve, 420
reversed return system, 409
two-pipe, forced, 409

Human body
acclimatization, 66
adaptation, 64, 66
cold conditions, 65
hot conditions, 65

Human body (*continued*)
heat emission, 68
high temperature hazards, 66
metabolic rates, 64
odors, 64
temperature, 64
thermal interchanges, 64
zone of evaporative regulation, 65
Humid heat, 3

Humidification, 3, 234, 609, 612
control, 267, 639
direct, 612
evaporative pans, 526
forced furnace systems, 267

Humidifier, humidifiers
air washer, 609
atomizing, 609
cleaning, 526
evaporating pans, 526
high duty, 609
self-contained, 609
spray, 609
unit, 609
Humidistat, 3, 630

Humidity, 3
absolute, 3
control, 270, 639, 699, 705
influence of, 68, 98
measurement of, 651
nurseries for premature infants, 98
ratio, 3, 14
relative, 3, 14
specific, 3
Hygrometers, 651
Hygroscopic materials, 705
Hygrostat, 3

I

Impulse trap, 390
Inch of water, 3
Indoor temperature, 167, 177, 178
Induction units, 272, 273
high pressure types, 272

Industrial
air conditioning, 699
chimneys, 532
degree days, 556, 557
exhaust systems, 719

Infiltration
causes, 149
due to wind pressure, 149
heat losses, 171
latent, 172
sensible, 171
measurement, 651
prevention by sealing, 153
temperature differences, 152
through outside doors, 150, 151
through walls, 149
through windows, 150
Inflammability, 89
Instruments, 645
Insulated constructions, 121, 123, 129–131
Insulating materials, 118, 466
calculating coefficients, 121, 123
conductivities and conductances, 109–111

Insulation, 3, 465
economical pipe thickness, 473, 474
edge, 170
low temperature pipe, 475
pipe, 466
pipes to prevent freezing, 476

Insulation (*continued*)
reflective, 108, 110
sound, 354–356
thermal conductivity, 466
underground pipe, 490

Ionization, 64
Intermittently heated buildings, 173
Isobaric, 3
Isothermal, 3

J

Jets, 278
expansion, 279
radial, 281
velocity, 279
Joints, duct, 308, 309

K

Kata thermometer, 650
Kitchen hood, 723

L

Laboratories, 708

Latent heat, 3, 172, 177
loss, 172
Laws of thermodynamics, 6

Leakage of air, 149 (see *Infiltration*)
door, 150–152
window, 150, 151
Light heat gain, 207
Lignite, 481
Liquid
absorbents, 619
heat of, 3
Lithium bromide, 570, 571, 619
Lithium chloride, 619

Load
cooling, 177, 201, 271
design, 3, 177
factor, 557
heating, 161, 271
lighting, 207
maximum, 3, 520, 557
refrigeration, 177

M

Mach number, 40, 41

Machine vibration, 363
Manometer, 3, 647
Marine (see *Ship heating, ventilating, air conditioning*)
Mass, 4
Mean radiant temperature, 67, 433, 444

Meter, meters, 42, 401, 647
area, 42, 46, 401
condensate, 401
flow, 42, 46, 401
force, 42
head, 42, 45, 401
installation, 401
orifice, 46, 649
selection, 401
velocity, 401
Venturi, 649
Metering, liquids, 42, 401
Micromanometers, 647
Micron, 4
Mist, 75

Moist air, 13
properties, 13