

APL

G2J95

TIME 3 P.M.

See N 8900. A/C C-523; 317#

DUP050463939

EQUIP MENT		PAGE 2 OF 2 CG 20 CODE BT-425-D (F)	USE LBS	N-CODE	ACCT LBS
SV	7	RECORD: PH. <u>10.0</u> (8.5-10.0)			
1	8	IF NECESSARY, ADJ TO PH 8.5-10.0 ASSUME 50%		7-D	
CONT		& RECORD PH. _____ ASSUME 77%		27-D	

313	9	RUN 24" (355G) WATER INTO V-313			
2	10	TURN ON AGITATOR & HEAT TO 80-100 DEG F			
		NOTE: VENT ON SOD.DRESINATE TANK OR VAT			
		USED FOR THIS SOL'N SHOULD BE CHECKED FOR			
		DRAFT PRIOR TO DUMPING THE SOD.DRESINATE			
	11	SIFT IN (+/-1 MIN PER BAG)	320	530-A	320
	12	STIR 5 MIN & RECORD: PH. <u>10.2</u> (10.0-10.5)			
	13	STIR AN ADDITIONAL 15 MIN OR LONGER TO			
		DISSOLVE FOR S16			

304	14	RUN 10" (122G) WATER INTO V-304			
3	15	DUMP IN & STIR TO DISSOLVE FOR S17	100	20-A	100

SV	16	RUN V-313 THRU 20 MESH SCREEN INTO SV &			
4		STIR 5 MIN.			
	17	RUN IN V-304 IN 5-10 MIN & STIR 15 MIN			
	18	RECORD: PH. <u>9.9</u> (9.0-10.0)			
	19	FLOOD TO <u>5.2</u> & STOP AGITATOR			
		SV 200 202 204 210 213 201			
		S19 77" 87" 88" 74" 52" 60"			
		GAL 5205 5150 5174 5143 5153 5220			

START	FIN	OPTR
<u>3.22</u>	<u>7.22</u>	<u>3.72</u>
_____	_____	_____
_____	_____	_____