Consistency Liquid | Laboratory No.

For use on | Cost Class. | Date 3/29/49

Customer | Strainer | Grind 7-8

Mill

Code Number	One Gallon Batch Pints	Lbs.	Ozs.	Large Batch Guls.	Lbs.
40-W-127-E	8				
93-R-250			1-9/16		
93-R-21			3/16		
93-R-18			3-1/2		

Changed to improve hiding & viscosity

Standard Formula. Not to be taken from File.

DISCONTINUED SEE #174 GFH 7/27/51

Yield

Is agitator required

Wt. or Be 11.0# Temp.

Viscosity 110-120" Temp.

Viscosimeter #4 Cup

Color Rose Sheen Gloss

Non Vol. Flash Pt. 100°

Match for Std- Y-1253

Reducer S-43

Amt. for brushing only as needed

Spraying Tumbling

Dipping Drip time

Bake Temp.

Air dries in 6 hrs

A. D. to recoat in Overnite

Remarks:

Formulator H G H

N12088

GLD059617

Code	Date	Analysis		Customers
		Pigment 38.8	%	
		Vehicle 61.2	%	
		100.0	%	
		Pigment		
		Lithopone		63.4%
		Titanium Oxide		29.3
		Basic Carbonate White Lead		2.4
		Calcium Carbonate		4.9
				100.0%
		With necessary tinting color		added
		Vehicle		All plants 4-8-49
	*	Varnish	93 %	
		Mineral Spirits	5	
		Liquid Drier	3	
			100 %	
		* Non Volatile	51.5%	

GLD059618

480-D 3644 4-44 PRINTED IN U. S. A. (8)

FORMULA RECORD

Goods Japalac Enamel Dusty Rose — Formula No. Y-1253A

Consistency Liquid — Date 6-13-47 — Laboratory No.

For Use on — Cost Classification

Code Number	One Gallon Batch Pints	One Gallon Batch Lbs.	One Gallon Batch Ozs.	Gallon Batch Gals.	Gallon Batch Lbs.	Gallon Batch Ozs.	Gallon Batch Gals.	Gallon Batch Lbs.	Gallon Batch Ozs.	Manufacturing Specifications
40W127D	8									Grind Mill
93R250			1/4							Kind of Mill
87R21			5/32							Strainer
93R18			27/8							Weight per Gallon 11 1/4
										Light Baume Temp.
										Heavy Baume Temp.
										Viscosity 80-90 Temp.
										Viscosimeter #4 Ford Cup
										Flash Point
										Is Agitator Required
										Remarks Match Std Chip Y1253 Johnston
	Changed to new quality									
				DISCONTINUED SEE Y12-53B 3/29/49						
Yield										

GLD059619

Characteristics and Method of Using	Cost Data				Customers
Type of Goods					
Color					
Luster					
Match for					
Kind of Reducer					
Amount of Reduction for	Pigment			37.6	All plants 6-24-47
Brushing	Vehicle			62.4	
Spraying Pressure				100.0 %	
Dipping Drip Time	Analysis				
Flowing Drip Time	Pigment				
Tumbling	Titanium Oxide			27.0 %	
Air dry to recoat	Lithopone			70.3	
To Sand or Rub Basic	Lead Carbonate			2.7	
Bake Time Temp With	necessary Tinting Color added			100.0 %	
Rub with					
Polish with					
Schedule	Vehicle				
	X Varnish			91.7	X Non Vol 51.35%
	Mineral Spirits			5.3	
	Liquid Drier			3.0	
				100.0%	

GLD059620

ABS-D 50M 2-44 PRINTED IN U.S.A. (B)

FORMULA RECORD

Goods Asphalt Enamel Dusty Rose — Formula No. M 1253

Consistency Liquid — Date 10-5-45 — Laboratory No. 0

For Use on — Cost Classification

Code Number	One Gallon Batch			Gallon Batch			Gallon Batch			Manufacturing Specifications
	Pints	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	Gals.	Lbs.	Ozs.	
40 W 127C	8									Grind Fine
						OLD	NEW			Kind of Mill
93R250			1 1/4			M 1253A				Strainer
87-R-21			5/32			10/13/47				Weight per Gallon 10.5#
93-R-18			2 7/8							Light Baume Temp.
										Heavy Baume Temp.
										Viscosity 80-90" Temp.
										Viscosimeter #4 Zahn
										Flash Point
										Is Agitator Required
										Remarks Hayward
										Match tin chip
										M 4404
				Standard Formula. Not to be taken from File.						1.48 #0.2
Yield										J.P.W.

GLD059621

Characteristics and Method of Using	Cost Data				Customers
Type of Goods					
Color					
Luster					
Match for					
Kind of Reducer					
Amount of Reduction for					
Brushing					All plants 10-16-45
Spraying Pressure					
Dipping Drip Time	Analysis				
Flocoing Drip Time	Resyne				35.0%
Tumbling	Velsol				6.0%
Air dry to recoat					100.0%
To Sand or Rub	Lacquer				
Bake Time Temp.	Laminac				7.0%
Rub with	Solvesso #150				25.0%
Polish with					100.0%
Schedule	Velsol				
*	Varnish				70.5 * Non-Vol 52.5%
	Boiled Linseed Oil				5.0%
	Mineral Spirits				1.2%
	Liquid Driers				3.3%
					100.0%

GLD059622