



Glidden

FLATTING OIL



ONE GALLON
U. S. MEASURE

N-20

Everywhere on Everything

THE GLIDDEN COMPANY
CLEVELAND 2, OHIO

FACTORIES AND BRANCHES
— IN PRINCIPAL CITIES THROUGHOUT AMERICA —

TIME-TESTED
REG. U. S. PAT. OFF.
*This product has been tested and approved by Time-Tested
Laboratories for dependable service, uniform color and
consistent high quality.*

COPYRIGHT 1945 THE GLIDDEN COMPANY

FLATTING OIL

A dependable mixing vehicle for White Lead in Oil to produce Flat and Semi-Gloss effects for interior wall decorations. Flattening Oil does not destroy the binding qualities of the liquids in White Lead in Oil but rather increases them, eliminating all danger of chipping or powdering of the film. It produces a close adhering, durable, sealed surface that will withstand repeated washings.

DIRECTIONS

FLAT FINISH—Reduce 100 pounds of White Lead in Oil with from 1½ to 2 gallons of Flattening Oil.

SEMI-GLOSS FINISH—To the mixture recommended for a Flat Finish add from four to six gallons of Speed-Wall Interior Base-Coat. The resultant gloss is governed by the amount added.

STIPPLING FLAT—Reduce 100 pounds of White Lead in Oil with from 1 to 1½ gallons of Flattening Oil.

ENAMEL UNDERCOATER—White Lead in Oil and Flattening Oil mixed for flat wall work constitutes an excellent Enamel Undercoater much superior in its sealing properties than White Lead mixed with Linseed Oil.

Everywhere on Everything

THE GLIDDEN COMPANY
CLEVELAND 2, OHIO

FACTORIES AND BRANCHES
— IN PRINCIPAL CITIES THROUGHOUT AMERICA —