

Monsanto

plasticizers

uses

properties

specifications

extrusions

plastic free films

molding compounds

surface coatings

adhesives

synthetic rubber

textile and paper coati

0014621

TOWOLDMON0038698

WATER_PCB-00023167

I

BACKGROUND INFORMATION ON PLASTICIZERS



Introduction

3



The Monsanto Line of Plasticizers

5

7



How a Plasticizer Works

9

II

SELECTING THE RIGHT PLASTICIZER



Choose the Right Plasticizer — To Build Quality

15

17



Monsanto Plasticizers for Vinyl Resins

21



Monsanto Plasticizers for Thermosetting Resins

27



Monsanto Plasticizers for Cellulosics

29



Monsanto Plasticizers for Other Resins

33

III

APPLICATION DATA ON VARIOUS PLASTICIZERS



TABLE I

Comparative Performance, Permanence and Cost of Various Plasticizers in Polyvinyl Chloride

35

37



TABLE II

Plasticizer Properties Imparted to Various Compatible Resins

39



TABLE III

Plasticizers Most Useful With Various Compatible Resins

41

0614622

TOWOLDMON0038699

WATER_PCB-00023168

IV

DATA ON INDIVIDUAL MONSANTO PLASTICIZERS



TABLE IV

Chemical and Physical Properties and Specifications of Monsanto Plasticizers



GRAPH I

Viscosity Curves for Phosphate Plasticizers: Tricresyl Phosphate, Santicizer 140 and Santicizer 141



GRAPH II

Viscosity Curves for Phthalyl Glycolates: Santicizer B-16, Santicizer E-15 and Santicizer M-17



GRAPH III

Viscosity Curves for Phthalate Plasticizers: Di(n-Octyl, n-Decyl) Phthalate, Diisooctyl Phthalate, Dioctyl Phthalate and Disodecyl Phthalate



GRAPH IV

Viscosity Curves for Phthalate Plasticizers: Dibutyl Phthalate, Diethyl Phthalate, Dimethyl Phthalate and Santicizer 160

V

SUPPLEMENTARY INFORMATION




Literature Available on Monsanto Plasticizers



Technical Service Available

background information on plasticizers





a introduction

b the Monsanto line of plasticizers

c how a plasticizer works

introduction

Plasticizers are low melting solids or high boiling organic liquids.

They are added to plastic compositions and surface coatings to extend or modify the natural properties of the resins and to develop new, improved properties not present in the resins themselves.

Plasticizers have grown in importance with the growth of the plastics and surface coating industries. New basic resins have required new plasticizing agents; older materials have found wider application because of improved properties developed through the use of unique plasticizers or plasticizer combinations.

As one of the major producers of chemicals for industry, Monsanto offers manufacturers of resin-based products a complete line of plasticizing agents. These plasticizers range from "standard" products to new, specialty plasticizers formulated to create improved properties in plastics and surface coatings. These properties range from flame retardancy to improved low temperature flexibility. Monsanto plasticizers can impart such properties as improved flexibility, higher gloss, better weather resistance, good electrical properties, solvent and abrasion resistance, and many others.

the Monsanto line of plasticizers

SANTICIZER®, HB-20: Trade Marks for
Monsanto resin plasticizers.

AROCOR®: Trade Mark for Monsanto
chlorinated polyphenyls.



For free film, lacquers, paper and textile coatings, rubber, and molded products - Monsanto supplies plasticizers that will extend or modify the properties of substantially any resin or combination of resins, natural or synthetic. Special properties not present in base resins can be added, processing expedited, and the performance of the finished product vastly improved when plastics are compounded with plasticizers exactly suited to the need.

Monsanto offers the trade a complete line of quality plasticizers. Raw materials, processing, and quality control -- the three factors most important to purity and stability -- are closely supervised to assure optimum, dependable performance of Monsanto plasticizers serving the diverse requirements of the plastics industry.

More than half a century of experience in the manufacture of organic chemicals enables Monsanto to produce the finest quality plasticizers for natural or synthetic resin applications. Both liquid and solid plasticizers are available. These compounds are of five chemical types:

Adipates

Phthalates

Phthalyl Glycolates

Phosphates

Sulfonamides

In addition, Monsanto supplies a number of specialty plasticizers with outstanding performance characteristics in specific applications.

how a plasticizer works



The entire plastics industry is based upon the art of obtaining plasticity of one kind or another in high molecular weight resins. Aside from possible modifications of the molecule itself, base resins may be plasticized by heat, solvents, or plasticizers.



Heat contributes plasticity at some processing stage for practically all thermoplastic resins. However, once a thermoplastic is cooled — this plasticizing effect disappears. Solvents, too, are employed during the initial compounding of some thermoplastic molding materials and in the manufacture of lacquers and surface coatings. But like heat, the effect of solvents is temporary — once they have evaporated, the resin is left in its original state.

Plasticizers impart relatively permanent flexibility, toughness, and improved flow. They are chemically related to solvents — the usual basis for classification is the degree of volatility; plasticizers being relatively nonvolatile compounds, solvents possessing much higher volatility.


Thermosetting resins in their final infusible, insoluble state are held together in a three dimensional network by primary chemical bonds. This structure strongly resists outside forces, whether these forces be heat or the "separating" action of a solvent or plasticizer.

Thermoplastic resins, on the other hand, are held together by primary chemical bonds in a longitudinal direction only. These chemical bonds operate only along the length of the polymer chain. The binding forces between chains are the Van der Waal forces or secondary bonds. These between-chain bonds are of a physical rather than chemical nature and thus are more susceptible to modification by external

PER CENT OF PLASTICIZER



R I G I D



P L I A N T

forces than primary chemical bonds. Consequently, plasticizing a thermoplastic resin consists basically of a controlled modification of the attractive forces between molecular chains. The extent of plasticizing action depends in part upon the molecular structure of the polymer and in part on the molecular structure of the plasticizer.


○

○

○

○

RESIN MOLECULES



The attractive forces or bonds between the chains vary in magnitude and number with the resin. The polymer chains of some resins are strongly bonded together by many cross-tying attractive forces, others are more loosely knit. The stronger the bonding forces between the polymer, the more highly polar must be the plasticizer. Rubber and neoprene, for example, are less strongly bonded than cellulose acetate or polyamide resins. Compounds such as hydrocarbons can be used to plasticize the more weakly bonded resins, but polyvinyl chloride or cellulose acetate require polar plasticizers plus heat and sometimes solvents to aid in compounding.

Plasticizers, like solvents, are attracted by the polar groups on the polymer chain and replace polymer-polymer bonds with polymer-plasticizer bonds. In addition, the sheer bulk of a plasticizer molecule and the configuration of its grouping disrupts the forces between chains. At high concentrations the plasticizer forms a continuous phase in which the separated chains can move. In such concentrations, the state of the plasticized mass is apt to be a soft gel.

Because of the size of most plasticizer molecules, it is frequently necessary to use heat, solvents, or a combination of both to aid in "loosening up" the resin structure to incorporate the plasticizer. Polyvinyl chloride, for example, is compounded with plasticizers at elevated temperatures. At room temperatures, the plasticizer does not adequately separate the polymer chains because of the strong secondary linkages or Van der Waal forces. Thus the incorporation of camphor in cellulose nitrate is aided by the action of heat and, in addition, solvents.



Plasticizers are an essential aid in processing most resins and to impart flexibility and added toughness to the finished product. Without the softening action of the plasticizer, many resins could not be fabricated into films, sheets or useful molded articles. Plasticizers are used to improve the flow of resins through a die or into a mold. Plasticizers have made possible many uses of resins in the molding of intricate forms. By improving resin adhesion, flexibility, and outdoor durability, plasticizers also made possible the development of lacquers for automobile and household uses.

Mechanically, a plasticizer reduces somewhat the tensile strength, and increases the elongation and elasticity of a resin. To possess really high elasticity, the polymer chain must be able to kink readily. In cellulose derivatives, the chains are themselves relatively stiff and no amount of plasticizing can ever produce the flexible elastomers that can be obtained with the more extensible molecules such as polyvinyl chloride.

By decreasing the forces holding the chains together, the plasticizer also lowers the vitrification point, sometimes called the "flex temperature," or brittle point.

Although in practice all efficient plasticizers are polar compounds, the polarity characteristics are not a complete guide to the evaluation of a plasticizer. Other considerations such as compatibility, permanence, efficiency and economy determine its suitability. In addition, certain plasticizers are used to impart special properties not inherent in the resin -- flame retardance, for example.

selecting the right plasticizer



a
CHOOSE THE RIGHT PLASTICIZER—TO BUILD QUALITY

1. Compatibility
 2. Processing ease
 3. Performance
 4. Permanence
 5. Special properties
- | |
|---|
| Flame Resistance
Nontoxicity
Better Gloss
Good Adhesion
Solvent Resistance
Electrical Properties |
|---|

b
MONSANTO PLASTICIZERS FOR VINYL RESINS

1. Extrusions
2. Milled and calendered stocks
3. Plastisols and organosols
4. Polyvinyl acetate

c
MONSANTO PLASTICIZERS FOR THERMOSETTING RESINS

1. Phenolics
2. Melamines
3. Ureas
4. Polyesters

d
MONSANTO PLASTICIZERS FOR CELLULOSES

1. Cellulose nitrate
2. Cellulose acetate and acetate-butyrate
3. Ethyl cellulose

e
MONSANTO PLASTICIZERS FOR OTHER RESINS

1. Polystyrene latex
2. Chlorinated rubber
3. Polyamides and nylon
4. Casein and zein

choose
the **right** **plasticizer –**
to build quality



The quality of the plasticizer and the properties it imparts are as important to the final product as the resin itself. Frequently (unless the plasticizer is carefully selected) a desired resin modification may be obtained at the expense of other properties inherent in the base resin. Compounding ingredients such as fillers, colors, lubricants, stabilizers, etc., are all of secondary importance. If the plasticizer is not perfectly suited to a specific commercial application, the other modifying agents are of little use. Choosing the right plasticizer involves consideration of all the following factors:

1. compatibility

The compatibility of a plasticizer with a resin is a function of its polarity, molecular size and structural configuration. Slightly incompatible plasticizers may often be made compatible through the use of mutual solvents or other plasticizers.

2.

processing ease

Plasticizers differ in their solvating effects on a given resin. Those which have a strong solvating effect speed up the rates of calendaring, banbury mixing, extrusion, plastisol fusion and other processing. Choosing a plasticizer which will give increased processing efficiency is an important means of reducing manufacturing costs, or of increasing production with existing equipment.

3.

performance

Plasticizer choice has a profound effect on such performance characteristics of a plastic as the following: Hardness, flexibility, tensile and tear strength, abrasion resistance, flame resistance, odor, and color. The expected end-use of a plasticized resin determines the relative importance of the above factors.



a

CONTINUED

4.

permanence

The "in service" performance of a plasticizer involves the factors which affect permanence; namely, low volatility, solvent resistance, good heat and light stability and resistance to migration. Generally, volatility decreases as plasticizer molecular weight increases. Heat and light stability and odor of a plasticizer depend upon its chemical type and its purity. Purity also determines plasticizer color and taste. Optimum performance qualities can be obtained by proper selection of raw materials, modern methods of manufacture and close quality control. These practices characterize Monsanto plasticizer production.

5.

special properties

flame resistance
nontoxicity
better gloss
good adhesion
solvent resistance
electrical properties

Beyond meeting basic requirements, a number of Monsanto plasticizers are designed to add specific properties to the end product. Wider application of resin materials and more merchandisable finished products are possible through special properties imparted to end products by proper selection of plasticizers. Monsanto plasticizers may be chosen to impart flame resistance, improved electrical properties, greater low temperature flexibility, nontoxicity, improved solvent and abrasion resistance, etc. The information which follows will aid in the selection of Monsanto plasticizers for given applications and resins.

Monsanto plasticizers

for

vinyl resins

1.

extrusions**wire and cable coatings**

Monsanto's *Diocetyl Phthalate* possesses excellent electrical properties in vinyl wire and cable insulations. It is the major plasticizer for formulating Underwriter's type T and type TW 60° C. wire compound. Extender plasticizers are used to reduce cost in these formulations. *Tricresyl Phosphate* is recommended for flame retardant jacket stock and for 80° C. wire compounds. *Santicizer 160* is of value in type SPT wire insulation where advantage can be taken of its excellent processing characteristics and low cost. *HB-20* can also be used as an extender type plasticizer in these formulations. *Diisodecyl Phthalate* and *Di(n-Octyl, n-Decyl) Phthalate* are of value for compounds requiring good electrical and heat-aging properties.

hose and tubing

For garden hose a plasticizer combination of *Diocetyl Phthalate (DOP)*, *Santicizer 160* and *Diocetyl Adipate* gives top quality. Similar quality at less cost can be obtained with *Di(n-Octyl, n-Decyl) Phthalate* and *Santicizer 160*. For beverage and hospital tubing, *Santicizer B-16* and *Santicizer 141* are completely nontoxic and most useful. *Monsanto DOP* is nontoxic and acceptable for all food applications excepting those foods which have a high fat content.

**welting, gasket stocks and
miscellaneous extrusions**

Plasticizer combinations of *Diocetyl Phthalate*, *Santicizer 141* and a polymeric type plasticizer offer top quality, good processing formulations. For lower cost, quality formulations *Diocetyl Phthalate-Santicizer 160* plasticizer blends with high filler content and extended with secondary type plasticizers such as *HB-20* are useful. *Santicizer 160* is extremely useful in highly filled stocks because of its good filler-wetting and resin solvation characteristics.

2.

milled and calendered stocks

film and sheeting

For quality film a plasticizer blend of *Di(n-Octyl, n-Decyl) Phthalate* and *Santicizer 141*, stabilized with polymeric type plasticizers, offer maximum light-, flame- and extraction-resistance and ease of processing. *Santicizer 160* is used to reduce cost and improve resistance to extraction by oil and kerosene, as well as to speed up processing. *HB-20* is useful for reducing cost. A low cost flame resistant film of good quality can be made with a blend of *Diocetyl Phthalate* or *Disodecyl Phthalate* with *Santicizer 141* or *140*, plus *Santicizer 160* and *Diocetyl Adipate*.

nontoxic films

Santicizers 141, B-16 and *E-15* are fully approved by the U. S. Bureau of Animal Industry and the U. S. Food and Drug Administration as being nontoxic for use in packaging for all types of meat and food products. Monsanto *Diocetyl Phthalate* is approved for contact with all foods except those which are fatty in nature.



sheeting

In sheeting, *Di(n-Octyl, n-Decyl) Phthalate* is a superior plasticizer for imparting permanence and excellent flexibility at a moderate cost. *Diisodecyl Phthalate* or *Dioctyl Phthalate* combined with *Santicizer 160* and either *Santicizer 140* or *141* all permit good quality medium-cost formulations. (See Monsanto Technical Bulletin 0-70: "MONSANTO PLASTICIZERS in Polyvinyl Chloride Film and Sheeting.")

floor coverings

Santicizer 160 and *140* and *Tricresyl Phosphate* are most useful in all types of vinyl flooring. These plasticizers and combinations of them tolerate large amounts of filler, process well, impart excellent permanence characteristics such as low volatility, good heat and light stability and resistance to extraction by oils, water and soaps. *Santicizer 160* and the *Phosphate Plasticizers* do not have a bluing effect during heat degradation with asbestos fillers. These plasticizers resist staining by asphalt and common food staining agents.

3.

plastisols and organosols

Di(n-Octyl, n-Decyl) Phthalate imparts to vinyl plastisols and organosols low initial viscosity and slow viscosity build-up on aging.

Diisodecyl Phthalate, Diisooctyl Phthalate and Dioctyl Phthalate follow in this order of viscosity build-up. *Dioctyl Adipate* and *Diisodecyl Adipate*, while higher priced, are superior for low viscosity. *Santicizer 141* and *Santicizer 160* are useful in blends with *Dioctyl Phthalate* or *Di(n-Octyl, n-Decyl) Phthalate* for improving fusion characteristics and speeding up production cycles. *HB-20* is useful as an extender type plasticizer. *Ortho-Nitrobiphenyl (ONB)* finds a specialized use in plastisols for glove dipping because of its low cost and good fusion characteristics.



4.

polyvinyl acetate

coatings

For latex paint applications, *Dibutyl Phthalate* and *Santicizer 160* are recommended because of their good film formation characteristics, permanence and pigment stability. For paper coatings, *Santicizer B-16* and *Santicizer 141* are particularly recommended because of their grease resistance and nontoxicity.

adhesives

Dimethyl Phthalate, Diethyl Phthalate, Dibutyl Phthalate, Santicizer 160, Tricresyl Phosphate, Triphenyl Phosphate, Santolite MHP and *Santolite MS* all find utility in various adhesive formulations.

(For details, see Monsanto Technical Bulletin No. 0-99:

"MONSANTO PLASTICIZERS in Synthetic Resin Adhesives.")

Monsanto plasticizers

for

thermosetting resins



1. **phenolics**

Dibutyl Phthalate and Santicizer 160 are recommended for plasticizing phenolics where good cold- and hot-punch characteristics are desired. *Tricresyl Phosphate* is useful for making flame-retardant laminates.

2. **melamines**

Santicizer 9 may be reacted with the Melamines directly, or added after their condensation to impart better flow characteristics, stability and shock resistance. Normally, from 15% to 25% of *Santicizer 9* is used.

3. **ureas**

Santicizer 9 is used as flow aid in the molding of urea plastics (improvement results from as little as $\frac{1}{2}\%$ to 1%). *Santicizer 9* can also be used with ureas to improve flow characteristics and solution stability in coatings.

4. **polyesters**

Tricresyl Phosphate, *Santicizer 160* and *Santicizer M-17* can be used with Polyester laminating resins to improve flexibility and to lessen cracking around metallic inserts.

Monsanto plasticizers

for

cellulosics

1. cellulose nitrate

lacquers

Dibutyl Phthalate is the standard plasticizer for nitrocellulose lacquers. It possesses good solvent characteristics, good solvent release and satisfactory properties from the standpoint of volatility and cold check. Where lower volatility and better cold check characteristics are required, *Santicizer 160* and *Diocetyl Phthalate* are recommended. *Santicizer 160* combines low cost, excellent resistance to water and hydrocarbons, low volatility and good cold check properties. *Ortho-Nitrobiphenyl* is useful in low cost industrial coatings where good color and low odor are not prime requisites. *Santolite MHP* and *Santolite MS-80%* are particularly useful because of their clarity, adhesive qualities and heat-sealing characteristics in such applications as fingernail lacquers, and heat-sealing adhesives. (See Monsanto Technical Bulletin 0-94: "SANTOLITE MHP AND SANTOLITE MS-80% Industrial Resins.")

moldings and sheeting

Camphor is the traditional plasticizer, although it has been partly replaced or extended in some instances by *Ortho-Nitrobiphenyl*.

2.

cellulose acetate and acetate-butyrate

moldings

A plasticizer blend of *Dimethyl Phthalate*, *Diethyl Phthalate* and *Triphenyl Phosphate* in approximately equal proportions offers optimum molding characteristics and physical properties as well as economy for cellulose acetate moldings. *Ortho-Nitrobiphenyl* is useful for reducing costs while imparting good properties.

sheeting

Santicizer M-17 yields a top quality cellulose acetate sheeting with excellent resistance to outdoor aging and good flexibility.

A plasticizer blend of *Diethyl Phthalate* and *Triphenyl Phosphate* in the ratio of 2 to 1 is also useful for good quality sheeting.

coatings

Santicizer 8 and *Santicizer M-17* are useful for coatings which are resistant to grease and aliphatic hydrocarbons.

Plasticizers of good efficiency such as *Dioctyl Phthalate* and *Dioctyl Adipate* are useful in cellulose acetate-butyrate sheeting and coatings.



3.

ethyl cellulose

moldings and sheeting

Dibutyl Phthalate and *Triphenyl Phosphate* are most useful as primary plasticizers. Low cost oils and petroleum products are used as extenders.

coatings

The phthalyl glycolates and the sulfonamide plasticizers are useful for coatings where advantage can be taken of their low toxicity and extraction resistance characteristics. Solid plasticizers such as *Diphenyl Phthalate* and *Santicizer 1-H* are useful with ethyl cellulose for making delayed-tack heat sensitive adhesives.

hot melts

Diethyl Phthalate, *Di(n-Octyl, n-Decyl) Phthalate* and *Santicizer 160* are useful in ethyl cellulose hot melts for paper coatings, shoe adhesives, bookbinding adhesives, etc.

Monsanto plasticizers

for

other resins

1. polystyrene latex

Santicizer 160 is most useful as a plasticizer for polystyrene latices because of its good solvation characteristics, low volatility and excellent weathering properties. Plasticizer combinations of *Diethyl Phthalate* and *Aroclor 1248* are also useful as a reduced cost system with good properties.

2. chlorinated rubber

Dibutyl Phthalate and *Santicizer B-16* are useful for imparting flexibility, *Monsanto Aroclors* are useful for their chemical resistance, flexibilizing properties and low cost. (See *Monsanto Technical Bulletin No. P-126: "Aroclors in—Pliolite S-5 Resins"*)

3. polyamides and nylon

The sulfonamide plasticizers (particularly *Santicizer 8*) are most useful as plasticizers which impart additional flexibility. *Santicizer 9*, a high melting point sulfonamide, is of interest in hot melt type adhesives.

4. casein and zein

Santicizer 8 is a solvent type primary plasticizer for these resins. *Santicizer B-16* and *Santicizer 141* are useful in combination with oleic acid in zein paper coatings.

application data on various plasticizers



**a****Table I**

Comparative Performance, Permanence and Cost of Various
Plasticizers in Polyvinyl Chloride

b**Table II**

Plasticizer Properties Imparted to Various Compatible Resins

c**Table III**

Plasticizers Most Useful With Various Compatible Resins

**comparative
performance,
permanence
and cost
of Monsanto plasticizers
in polyvinyl chloride***



a

TABLE I

PLASTICIZER	PHTHALATES					PHOSPHATES			ADIPATES		PHTHALYL GLYCOLLATES	
PROPERTY AND METHOD	DIBUTYL	DIOCTYL	BUTYL BENZYL (SANTICIZER 160)	DI (n-OCTYL n-DECYL)	DIISODECYL	TRICRESYL	CRESYL DIPHENYL (SANTICIZER 140)	ALKYL DIARYL (SANTICIZER 141)	DIOCTYL	DIISODECYL	SANTICIZER B-16	SANTICIZER M-17
LOW TEMPERATURE FLEXIBILITY, °C. (Method of Clash and Berg Ind. & Eng. Chem. 34, 1218)	-39	-37	-23	-46	-35	-10	-16	-37	-65	-61	-26.5	-18
SHORE HARDNESS, "A" SCALE	72	73	72	75	75	78	77	73	70	73	76	76
FLAME-OUT TIME, SECONDS (After Heating 30 Secs. with Bunsen Burner)	—	100	45	—	—	0	0	38	100	—	—	—
VOLATILITY, % PLASTICIZER LOST (Heated 24 Hrs. at 105° C. in Freas Circulating Air Oven)	60.5	4.5	12.0	1.8	1.6	1.0	3.4	6.0	13.0	3.4	12.0	30.3
WATER EXTRACTION, % PLASTICIZER LOST (ASTM D57C-42)	0.11	0.02	0.05	0.03	0.02	0.01	0.01	0.02	0.10	0.07	0.13	0.52
KEROSENE EXTRACTION, % PLASTICIZER LOST (Extracted 96 Hrs. at 27° C.)	25.1	80.0	6.1	85.6	87.0	3.0	8.0	20.6	91.0	92.0	—	—
PLASTICIZER MIGRATION, % ABSORBED (Linde Silica Test, 1 Day at 25° C. J. R. Geenty in Third Annual Proceedings SPI, 1951)	—	2.0	1.6	5.1	2.0	0.4	1.5	4.0	9.5	—	2.0	—
COST	MEDIUM	MEDIUM	LOW	MEDIUM	MEDIUM	MEDIUM	MEDIUM	MEDIUM	HIGH	HIGH	HIGH	HIGH

*Material Tested was 40 MIL Sheet at 40% Plasticizer Concentration.
SANTICIZER: Reg. U. S. Pat. Off.

38

C614659

TOWOLDMON0038736
WATER_PCB-00023205

PLASTICIZER		P H T H A L A T E S								PHTHALYL GLYCOLLATES		
C U S T O M E R P R O P E R T Y P E	PROPERTIES	DIMETHYL	DIETHYL	DIBUTYL	DIPHENYL	BUTYL BENZYL (S. 160)	DIOCTYL & DI- ISOCTYL	DI (n-OCTYL n-DECYL)	DIISO- DECYL	S. 5-15	S. 8-16	S. M-17
	LIGHT COLOR	X	X	X	X	X	X	X	X	X	X	X
	LOW ODOR			X			X		X	X	X	X
	NONTOXICITY			**	**		**			X	X	**
	SOFTENING EFFICIENCY	X	X	X		X	X	E	X	X	X	X
	FILM FORMATION OR PROCESSING EASE	X	X	X		E	X	X	X	X	X	X
	TENSILE AND TEAR STRENGTH	X	X	X	E	E	X	X	X	X	X	X
	LOW TEMP. FLEXIBILITY	X	X	X		X	X	E	X	X	X	X
	HEAT SEALABILITY OR SENSITIVITY	X	X	X	E	X	X	X	X	X	X	X
	ELECTRICAL PROPERTIES			X		X	X	X	X			
	FLAME RESISTANCE											
C U S T O M E R P R O P E R T Y P E	LOW VOLATILITY		X	X	X	X	X	E	E		X	
	LIGHT AND HEAT STABILITY	X	X	X	X	X	X	X	X	X	X	X
	WATER OR MOISTURE RESISTANCE			X	X	X	X	X	X	X	X	X
	GREASE RESISTANCE					X				X	X	X
	NONMIGRATION	X	X	X	X	X	X	X	X	X	X	X
	NONNUTRIENT FOR FUNGI	X	X	X	X	X	X	X	X	X	X	X
COST		LOW	LOW	MEDIUM	HIGH	LOW	MEDIUM	MEDIUM	MEDIUM	HIGH	HIGH	HIGH

*Properties considered for those resins most commonly used with the given plasticizer.
 **Toxicity work indicates these compounds have a low order of toxicity. They have not yet been approved by the BAI or FDA, however.

X Denotes special value.
 E Denotes exceptional value.
 S. SANTICIZER: Reg. U. S. Pat. Off.

0614660

**plasticizer properties imparted
to various compatible resins***



b

TABLE II

P H O S P H A T E S				S U L F O N A M I D E S				A D I P A T E S		M I S C E L L A N E O U S	
TRIPHENYL	TRICRESYL	S. 140	S. 141	S. 1-H	S. 3	S. 8	S. 9	DIOCTYL	DI-ISODECYL	HB-20	ORTHO-NITRO-BIPHENYL (ONB)
X	X	X	X	X	X	X	X	X	X	X	
X			X	X	X		X	X	X		
			X	**							
			X			X		E	E	X	X
X	E	E	E			X				X	X
E	X	E	E	E	E	X	E	X	X	X	X
	X	X	X			X		E	E	X	
X	X	X	X	E	E	X	E	X	X	X	X
	X									X	
X	X	X	X								
E	E	E	X	X	X	X	E	X	E		
X		X	X				X	X	X		
X	X	X	X					X	X	X	X
X	X	X	X	X	X	X	X				
X	X	X		X	X	X	X			X	X
X	X	X		X	X	X	X	X	X	X	X
MEDIUM	MEDIUM	MEDIUM	MEDIUM	HIGH	MEDIUM	MEDIUM	MEDIUM	HIGH	HIGH	LOW	LOW

PLASTICIZER		P H T H A L A T E S							PHTHALYL GLYCOLLATES				
RESIN		DIMETHYL	DIETHYL	DIBUTYL	DIPHENYL	BUTYL BENZYL	DIOCTYL & DI- ISOCTYL	DI (n-OCTYL n-DECYL)	DISO DECYL	S. B-15	S. B-16	S. M-17	
THERMOPLASTIC	VINYLS												
	POLYVINYL CHLORIDE AND COPOLYMERS				X	X	X	X	X		X	X	
	POLYVINYL ACETATE	X	X	X	X	X					X	X	
	POLYVINYL BUTYRAL					X					X		
	POLYVINYLIDENE CHLO- RIDE AND COPOLYMERS									X	X		
	CELLULOSES												
	NITROCELLULOSE			X		X	X				X		
	CELLULOSE ACETATE	X	X								X		X
	CELLULOSE ACETATE- BUTYRATE			X			X	X					
	ETHYL CELLULOSE			X	X		X	X	X		X	X	X
OTHER	ACRYLICS			X		X					X	X	
	POLYSTYRENE				X	X	X						
	CHLORINATED RUBBER										X		
	POLYAMIDES AND NYLON										X		
ZEIN AND CASEIN											X		
THERMOSETTING	PHENOLICS			X		X							
	MELAMINES												
	UREAS												
	POLYESTERS					X							

**plasticizers most useful
with various compatible resins**



C

TABLE III

P H O S P H A T E S				S U L F O N A M I D E S				A D I P A T E S		M I S C E L L A N E O U S	
TRIPHENYL	TRICRESYL	S. 140	S. 141	S. 1-H	S. 3	S. 8	S. 9	DIOCTYL	DIISO- DECYL	HB-20	ORTHO- NITRO- BIPHENYL (ONB)
	X	X	X					X	X	X	X
X	X	X	X	X	X	X	X				X
			X					X	X		
X	X	X	X		X	X					X
X						X					X
X	X	X						X	X		
X	X	X	X	X	X	X	X	X	X	X	X
			X								X
			X			X					
	X	X				X	X				
								X			
			X								

data on individual Monsanto plasticizers



a

Table IV

Chemical and Physical Properties and Specifications of
Monsanto Plasticizers

b

Graph I

Viscosity Curves for Phosphate Plasticizers: Tricresyl Phosphate,
Santicizer 140 and Santicizer 141

c

Graph II

Viscosity Curves for Phthalyl Glycolates: Santicizer B-16, San-
tizer E-15 and Santicizer M-17

d

Graph III

Viscosity Curves for Phthalate Plasticizers: Di (n-Octyl, n-Decyl)
Phthalate, Diisooctyl Phthalate, Dioctyl Phthalate and Diiso-
decyl Phthalate

e

Graph IV

Viscosity Curves for Phthalate Plasticizers: Dibutyl Phthalate,
Diethyl Phthalate, Dimethyl Phthalate and Santicizer 160

PLASTICIZER		P H T H A L A T E S				
PROPERTY	DIOCTYL PHTHALATE	DIBUTYL PHTHALATE	DIETHYL PHTHALATE	DIMETHYL PHTHALATE	DIPHENYL PHTHALATE	SANTICIZER 160
PHYSICAL FORM	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, MOBILE LIQUID	CLEAR, MOBILE LIQUID	WHITE POWDER	CLEAR, MOBILE LIQUID
MOLECULAR WEIGHT	390.5	278.3	222.2	194.2	318.3	312.4
SPECIFIC GRAVITY 25°/25° C.	0.982	1.045	1.120	1.189	1.28 DENSITY	1.116
POUNDS PER GALLON	8.2	8.75	9.35	10		9.3
CRYSTALLIZING POINT	-55° C. (GEL)	LESS THAN -35° C.	-0.3° C.	0° C.	69° C.	LESS THAN -35° C.
BOILING POINT (760 MM)	386° C. (APP.) 230° C. 5MM	340° C.	298° C.	282° C.	405° C.	370° C. (APPROX.)
FLASH POINT, CLEVELAND OPEN CUP	425° F.	340° F.	305° F.	300° F.	435° F.	390° F.
REFRACTIVE INDEX, 25° C.	1.4840	1.4915	1.5002	1.5138	1.572	1.5355
APPEARANCE	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, WATER-WHITE OILY LIQUID	CLEAR, WATER-WHITE OILY LIQUID	ESSENTIALLY WHITE FUSED SOLID	CLEAR, OILY LIQUID
COLOR, APHA	25 MAX.	20 MAX.	10 MAX.	10 MAX.		40 MAX.
ODOR	CHARAC- TERISTIC	SLIGHT	SLIGHTLY AROMATIC	SLIGHTLY AROMATIC		SLIGHT, CHARAC- TERISTIC
REFRACTIVE INDEX, 25° C.	1.4810- 1.4880	1.4905 ±0.001	1.5000 ±0.0001	1.5133 ±0.001		1.534 TO 1.538
SPECIFIC GRAVITY 25°/25° C.	0.980- 0.985	1.045 ±0.001	1.117 ±0.005	1.189 ±0.001		1.113 TO 1.120
ACIDITY	AS PHTHALIC ACID, 0.01% MAX.	0.01% MAX. AS PHTHALIC ACID	0.01% MAX. AS PHTHALIC ACID	0.01% MAX. AS PHTHALIC ACID	0.20% MAX. AS PHTHALIC ACID	0.02% MAX. AS PHTHALIC ACID
OTHER		ESTER ASSAY 99% MIN.	ESTER ASSAY, 99% MIN.	ESTER ASSAY 99% MIN.	FREE PHENOL 0.20% MAX. ASH 0.05% MAX. MOISTURE 0.50% MAX.	ESTER ASSAY 98% MIN.

			P H O S P H A T E S				S U L F O N A M		
DIISOCTYL PHTHALATE	DIISODECYL PHTHALATE	DI(n-OCTYL, n-DECYL) PHTHALATE	TRICRESYL PHOSPHATE	TRIPHENYL PHOSPHATE	SANTICIZER* 140	SANTICIZER 141	SANTICIZER 3	SANTICIZER 8	SANTIC 9
OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, MOBILE LIQUID	WHITE FLAKES	CLEAR, MOBILE LIQUID	CLEAR, MOBILE LIQUID	PRACTICALLY WHITE SOLID	CLEAR, VISCIOUS LIQUID	FINE GRANU- LARS
390.5	446.3	418.3	368.4	326.4	340.3	362.4	199.3	199.3	171.1
0.982	0.9650	0.9730	1.162	1.268 (AT 60/20° C.)	1.208	1.090	1.253 DENSITY	1.190	1.35 DENSITY
8.2	8.05	8.1	9.7	 10 (APPROX.)	9.1		9.92		
-45° C.	-53° C.	-30° C.	LESS THAN -35° C.	49° C.	LESS THAN -35° C.	59.0° C. (MELT- ING POINT)	LESS THAN 0° C.	105° (MELTING)	
233° C. AT 5 MM	249°-256° C. AT 4 MM	232°-267° C. AT 5 MM	420° C.	370° C.	390° C.	375° C.	340° C.	340° C.	360°
430° F.	450° F.	426° F.	470° F.	437° F.	450° F.	435° F.	371° F.	345° F.	420°
1.4840	1.4844	1.4820	1.556	1.550 (AT 60° C.)	1.560	1.508	1.522 (AT 65° C.)	1.540	
CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	WHITE FLAKES	CLEAR, MOBILE LIQUID	CLEAR, MOBILE LIQUID	PRACTICALLY WHITE SOLID	LIGHT YELLOW, VISCIOUS LIQUID	
35 MAX.	100 MAX.	50 MAX.	40 MAX.	20 MAX. (MOLTEN)	40 MAX.	100 MAX.	60 MAX. (MOLTEN)	200 MAX.	
CHARAC- TERISTIC	SLIGHT, CHARAC- TERISTIC	SLIGHT, CHARAC- TERISTIC	SLIGHT CHARAC- TERISTIC	VERY FAINTLY AROMATIC	ESSENTIALLY ODORLESS	SLIGHT, SWEET		SLIGHT, CHARAC- TERISTIC	
1.4810- 1.4880	1.4794- 1.4864	1.4785- 1.4855			1.560 ±0.010	1.507- 1.510	1.512- 1.532 (AT 65° C.)		
0.980 TO 0.985	0.9645- 0.9665	0.968 TO 0.977	1.157 TO 1.173		1.208 ±0.005	1.089- 1.093	1.166- 1.176 (AT 65°/65° C.)		
0.01% MAX. AS PHTHALIC ACID	0.01% MAX. AS PHTHALIC ACID	0.01% MAX. AS PHTHALIC ACID	0.01% MAX. AS H ₃ PO ₄	0.003% MAX. AS H ₃ PO ₄	0.01% MAX. AS H ₃ PO ₄	0.01% MAX. (AS PHOSPHORIC)	0.1% MAX. (AS ACETIC)	0.1% MAX. AS ACETIC	
.....			PERMANGANATE TEST NO CHANGE WITHIN 1/2 HOUR	PERMANGANATE TEST NO CHANGE WITHIN 1/2 HOUR					

0614667

*REG. U. S. PAT. OFF.

46

chemical and physical properties and specifications of Monsanto plasticizers



I D E S		PHTHALYL GLYCOLLATES				SPECIALTY PLASTICIZERS		ADIPATES	
	SANTICIZER I-H	SANTICIZER E-15	SANTICIZER B-16	SANTICIZER M-17	ORTHO- NITROBIPHENYL (ONB)	HB-20	DI(2-ETHYL- HEXYL) ADIPATE	DIISODECYL ADIPATE	
	WHITE CRYSTALS	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, MOBILE LIQUID	LIGHT YELLOW TO REDDISH CRYSTALLINE SOLID, OR LIQUID	PRACTICALLY COLORLESS, OILY LIQUID	CLEAR, OILY LIQUID	CLEAR, OILY LIQUID	
	253	280.3	336.4	266.3	199.2		370.6	426.6	
	1.125 DENSITY	1.180	1.097	1.220	1.203		0.927	0.919	
		9.85	9.15	10.2	10.0	8.1	7.7	7.6	
	86°- 87° C.	20° C.	LESS THAN —35° C.	LESS THAN —35° C.	34.5° C. MIN.				
	350° C.	320° C.	345° C.	310° C.	330° C. (APPROX.)	BOILING RANGE 320-360° C.	214° C. AT 5 MM.	240° C. AT 5 MM.	
		386° F.	390° F.	380° F.	289.5° F.	160° C.	377° F.	425° F.	
		1.498	1.490	1.504	1.613 (APPROX.)	1.5470	1.446	1.450	
	YELLOWISH- BROWN FUSED MASS	CLEAR, WATER-WHITE, OILY LIQUID	CLEAR, PRACTICALLY WHITE, OILY LIQUID	CLEAR, MOBILE LIQUID	LIGHT YELLOW TO DARK BROWN SOLID OR LIQUID	PRACTICALLY COLORLESS OILY LIQUID	CLEAR LIQUID	CLEAR LIQUID	
	250 MAX. (MOLTEN)	20 MAX.	45 MAX.	20 MAX.		110 MAX.**	100 MAX.	100 MAX.	
		SLIGHT	CHARAC- TERISTIC, SLIGHT ODOR	SLIGHT CHARAC- TERISTIC		FAINT AND PLEASANT	MILD	MILD	
		1.498 ±0.002	1.490 ±0.002	1.504 ±0.002		0.968 0.974 (25°/15.5° C.)	1.444— 1.448	1.4503— 1.4507	
		1.182 ±0.003	1.098 ±0.005	1.220 ±0.005		1.5475 ±0.0005	0.927 ±0.003 (20°/20° C.)	0.919 ±0.003 (20°/20° C.)	
		0.02% MAX. AS ACETIC	0.02% MAX. AS ACETIC	0.02% MAX. AS ACETIC			0.5 MEQ. PER 100 GM. MAX.	0.5 MEQ. PER 100 GM. MAX.	
	CRYSTALLIZING POINT 83.5° C. MIN.				CRYSTALLIZING POINT 34.5° C. MIN.				

**DARKENS ON EXPOSURE TO SUNLIGHT

0614668

47

**chemical and physical properties and specifications
of Monsanto plasticizers**

IV

a

TABLE IV

◀ PLEASE TURN PAGE

48

0014669

TOWOLDMON0038746
WATER_PCB-00023215

viscosity curves for PHOSPHATE PLASTICIZERS:


Tricresyl Phosphate

Santicizer 140

and Santicizer 141

VISCOSITY CURVES FOR PHOSPHATE PLASTICIZERS

ASTM STANDARD VISCOSITY-TEMPERATURE CHART [D 341-39] MODIFIED



viscosity curves for PHTHALYL GLYCOLLATES:


Santicizer B-16

Santicizer E-15

and Santicizer M-17

VISCOSITY CURVES FOR PHTHALYL GLYCOLLATES

ASTM STANDARD VISCOSITY-TEMPERATURE CHART (D 341-39) MODIFIED



viscosity curves for PHTHALATE PLASTICIZERS:

Di(n-Octyl, n-Decyl) Phthalate


Diisooctyl Phthalate

Dioctyl Phthalate

and Diisodecyl Phthalate

VISCOSITY CURVES FOR PHTHALATE PLASTICIZERS

ASTM STANDARD VISCOSITY-TEMPERATURE CHART (D 341-39) MODIFIED



viscosity curves for PHTHALATE PLASTICIZERS:

Dibutyl Phthalate


Diethyl Phthalate

Dimethyl Phthalate

and Santicizer 160

VISCOSITY CURVES FOR PHTHALATE PLASTICIZERS

ASTM STANDARD VISCOSITY-TEMPERATURE CHART (D 341-39) MODIFIED



supplementary information





Literature Available on Monsanto Plasticizers



Technical Service Available

literature available on Monsanto plasticizers



a

The following technical bulletins, data sheets and booklets give technical information on the properties and applications of various Monsanto plasticizers and resins. Literature items are available upon request.

ADIPATE PLASTICIZERS

Technical Bulletin O-108: DIOCTYL ADIPATE (DOA)
Technical Bulletin O-113: DIISODECYL ADIPATE

PHthalate PLASTICIZERS

Technical Bulletin O-82: DIOCTYL PHTHALATE (DOP)
Technical Bulletin O-108: DIISODECYL PHTHALATE (DIDP)
Technical Bulletin O-109: DI(n-OCTYL, n-DECYL) PHTHALATE (DNODP)
Technical Bulletin O-92: SANCIZER 160 (Butyl Benzyl Phthalate)

PHOSPHATE PLASTICIZERS

Technical Bulletin O-88: SANCIZER 140
Technical Bulletin O-89: SANCIZER 141 -The Nontoxic Plasticizer

SULFONAMIDE PLASTICIZERS

Technical Bulletin O-81: SANCIZER 3
Technical Data Sheet: SANCIZER 8-Use in Adhesives
Technical Data Sheet: SANCIZER 8-Use in Coatings
Technical Data Sheet: SANCIZER 8-Use in Moldings

Other Plasticizers

Technical Bulletin O-78: Ortho-NITROBIPHENYL Plasticizer and Chemical Intermediate
Technical Bulletin OD-700: Ortho-NITROBIPHENYL Toxicity Data
Bulletin O-P-115: AROCLORS
Bulletin O-P-153: HB-20, EXTENDER TYPE VINYL PLASTICIZER

Application Literature

Technical Bulletin O-69: BULK TANK STORAGE OF PLASTICIZERS
(Describes mechanical and safe handling procedures)
Technical Bulletin O-70: MONSANTO PLASTICIZERS in Polyvinyl Chloride Film and Sheetting
Technical Bulletin O-99: MONSANTO PLASTICIZERS in Synthetic Resin Adhesives
Booklet: Faster Processing of Polyvinyl Chloride With Monsanto Plasticizers
Technical Bulletin O-94: SANTOLITE MHP and SANTOLITE MS-80%
(Monsanto Industrial Resins)
Technical Bulletin O-16: SANTOMASK II (odor masking agent)

technical service available



b

The Plasticizer Sales Department of Monsanto's Organic Chemicals Division is organized to furnish you technical assistance with plasticizing and processing problems. Staffed by men chosen for their knowledge and practical experience with plasticizers, the Plasticizer Sales Department is equipped to study your problem thoroughly and to give advice based on the latest developments in the plasticizer field. From such practical advice you may discover that newly developed plasticizers may enable you to build into your product the exact qualities desired, or they may permit you to boost production with the same equipment you are using. The right combination of plasticizers may allow important processing simplifications.

Augmenting this technical assistance on a personal basis is an increasing amount of technical literature which brings to you the latest developments from Monsanto's plasticizer research laboratories.

Technical assistance is offered to all who use plasticizers in their manufacturing processes. For prompt technical assistance, simply write or call MONSANTO CHEMICAL COMPANY, Plasticizer Sales Department, 800 North Twelfth Boulevard, St. Louis 1, Missouri.



The information contained in this booklet is to our best knowledge true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. Monsanto Chemical Company disclaims any liability incurred in connection with the use of these data or suggestions.

Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.



MONSANTO

CHEMICAL

COMPANY

ORGANIC CHEMICALS DIVISION
800 N. 12TH BLVD. • ST. LOUIS 1, MO.

0614685

TOWOLDMON0038762
WATER_PCB-00023231