

70, 11, 82 12383 4038
(DATE) (LOT) (EST WT)

COMTYP JOB NAME: 01YC016BMD

BLENDED BACK: CG 01, PQ 94, YC-16-B, 34399, 100
(CODE) (LOT) (POUNDS)

EQUIP MENT	NAME: MOLYBDATE ORANGE	USE LBS	N-CODE (RMCON)	ACCT LBS
PREP 1	1 WEIGH FOR S 33 2 WEIGH FOR S-41 3 WEIGH IN DRUM FOR S-37 4 WEIGH FOR S-27	117 100 185 315	3-A 3-A 32-D 4-A	117 100 185 315
356 2	5 RUN 25" (451 G) WATER INTO V-356 6 TURN ON AGITATOR AND STEAM 7 WEIGH AND SIFT IN 8 HEAT TO AND MAINTAIN 60-66* C FOR S 35	345	131-B	345
359 3	9 WEIGH IN. OPTR 126, MK 61, T 360.3431% OPTR _____, MK _____, T- _____%	796	423-D	273
351 4 4	10 WEIGH IN OPTR 126, MK 343, 37.98% OPTR _____, MK _____, _____% 11 RUN IN V-359	3839	10-D	1458
358 5	12 RUN 10" (473 G) WATER INTO V-358 13 PUMP V-351 INTO V-358 14 ADJ TO 68" (3216 G) AT 67-69*F. RECORD 68" 15 STIR 3 MIN. RECORD: 69 *F & PH 9.9 16 IF NECESSARY, ADJ TO PH 9.8-9.9 ASSUME 50% RECORD: PH 9.9 ASSUME 66% 17 RECORD: G/ML 4060 (1.060-1.062)		7-D 33-D	
SV 6	18 RUN 40" (1908 G) WATER INTO V-242 19 RUN IN FROM V-354 OPTR _____, MK _____, _____*F, _____% OPTR _____, MK _____, _____*F, _____% 20 ADJ TO 3142.5 AT 67-69*F (64" IN V-240 & V-246; 66" IN V-241, V-242, & V-245) 21 STIR 3 MIN. RECORD: _____*F 22 RECORD: PH 3.0 (2.8-3.6) 23 ADJ TO PH 3.8-3.9 ASSUME 66% RECORD: PH 3.8 & VOL 66" ASSUME 50% NOTE: DILUTE N-7 10:1 WITH WATER 24 RECORD: G/ML 1125 (1.124-1.127) 25 OBTAIN 1 QT SAMPLES OF S-17 & S-24 SOLUTIONS & TITRATE TWICE RECORD: LOWEST PH _____ & ML N-10-D _____ LOWEST PH _____ & ML N-10-D _____ NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 7.0-7.5 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS) DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE	41-D 57-A 33-D 7-D	3893	

OCT 15 1982

10/11

PROCEED TO PAGE 2

OCT 15 1982

10/14

EQUIP MENT		PAGE 02 OF 2 CG 01 CODE YC-016-B	USE LBS	N-CODE	ACCT LBS
	26	RUN V-358 AT 67-69°F THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV AT 67-69°F IN 17-19 MIN			
		RECORD: START <u>6:50 P</u> M & TOTAL MIN <u>18</u>			
		NOTE: V-358 STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS MT			
SV 6	27	WHEN S 26 COMPLETED AND BEFORE WASHING IN V-358, DUMP IN N-4-A FROM S-4			
(CONT)	28	RUN IN USING WEIGHT AND FLOW CONTROL PANEL			
		OPTR <u>126</u> , MK <u>2</u> , <u>31.91%</u>	<u>94</u>	28-D	29
		OPTR _____, MK _____, _____%		28-D	
	29	DURING S'S 27 AND 28 (IF ALONE, AFTER S'S 27 & 28) WASH IN V-358			
	30	STIR 2 MIN			
	31	RECORD: PH <u>1.8</u> (2.2-2.5) & PB XS <u>+</u> (+)			
	32	STIR TOTAL OF 15 MIN FROM COMPLETION			
		S 26 RECORD: START <u>7:00</u> TOTAL MIN <u>18</u>			
	33	DUMP IN N-3-A FROM S 1			
	34	STIR 3 MIN			
	35	RUN IN N-131-B FROM S 3 IN 7 MIN			
	36	STIR 3 MIN			
	37	POUR IN N-32-D FROM S-3			
	38	STIR 2 MIN			
	39	RUN IN USING BADGER METER	580	115-D	290
	40	STIR 3 MIN & FLUSH ALUM LINE WITH WATER			
	41	DUMP IN N-3-A FROM S 2			
	42	STIR 3 MIN			
	43	RECORD: PH <u>6.0</u> (5.8-6.0)			
	44	IF NECESSARY, ADJ TO PH 5.8-6.0 ASSUME 50%		7-D	
		RECORD: PH _____ ASSUME 66%		33-D	
	45	DUMP IN THE SUB-STANDARD TO BE BLENDED BACK (IF ANY IS SHOWN ON TOP FRONT OF CARD)			
	46	STIR 20 MINUTES AFTER DUMPING SUB-STANDARD			
	47	FLOOD TO 153" (7298 G) & STOP AGITATOR			
		START <u>3:00 PM</u> FINISH <u>8:30 P</u> OPTR <u>126-138</u>			

YC-16-B, 34399, 100 H