

Form Approved OMB
No. 44-R1387
Approval Expires
July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971
81092

MATERIAL SAFETY DATA SHEET

SECTION I					
MANUFACTURER'S NAME MONSANTO COMPANY				EMERGENCY TELEPHONE NO. (314) 694-1000	
ADDRESS (City, State, and Zip Code) 800 North Lindbergh Boulevard, St. Louis, Missouri 63166					
CHEMICAL NAME AND SYNONYMS Chlorinated aromatics				TRADE NAME AND SYNONYMS Inerteen PPO	
CHEMICAL FAMILY Chlorinated aromatics				FORMULA Mixture	
SECTION II. HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
SECTION III PHYSICAL DATA					
BOILING POINT (°F.)		760 mm	200-415°C	SPECIFIC GRAVITY (H ₂ O = 1) (15.5/15.5°C)	
VAPOR PRESSURE (mm Hg.)		Not Avail		PERCENT VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR = 1)		Not Avail		EVAPORATION RATE (BuAc = 1)	
SOLUBILITY IN WATER		20°C negligible		Not Avail	
APPEARANCE AND ODOR		colorless to yellow oil		aromatic odor	
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (Method used)		None		245° F	
EXTINGUISHING MEDIA		N.A.		FLAMMABLE LIMITS	
SPECIAL FIRE FIGHTING PROCEDURES		Respiratory protection when fighting fires where exposure to vapors or gases is possible.		LFL	
UNUSUAL FIRE AND EXPLOSION HAZARDS		Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.		UFL	

DSW 009560

Inerteen PPO SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE	Not available.
EFFECTS OF OVEREXPOSURE	
Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.	
EMERGENCY AND FIRST AID PROCEDURES	
Remove from exposure. Remove contaminated clothing. Wash contacted area with large amounts of water and soap. Refer to physician.	

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE	CONDITIONS TO AVOID
	STABLE	X
INCOMPATIBILITY (Materials to avoid)		
HAZARDOUS DECOMPOSITION PRODUCTS		
CO, CO ₂ , smoke, soot, chlorides and chlorine		
HAZARDOUS POLYMERIZATION	MAY OCCUR	CONDITIONS TO AVOID
	WILL NOT OCCUR	X

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.
WASTE DISPOSAL METHOD
Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (See 1910.136)		
Bureau of Mines approved respirator for organic vapors		
VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER
PROTECTIVE GLOVES	rubber	EYE PROTECTION
		chemical goggles
OTHER PROTECTIVE EQUIPMENT		

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Avoid skin and eye contact.
Avoid inhalation of vapors.
OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP

1/26/72

195600 MSO

LEXOLDMON006366