


For
"TEST-RUN"
FIRING CONDITIONS
ALL OF THE TIME—

Equip your stokers with CONICAL Non-Segregating Coal Distributors and obtain these desirable results immediately:

—Elimination of coal segregation
—Reduced stoker and arch maintenance
—More uniform fires for improved boiler performance
—No coal dust nuisance. (ALL CONICAL Distributors are dust-tight.)

CONICAL
Non-Segregating
DISTRIBUTORS

Write for bulletins . . . address
STOCK ENGINEERING COMPANY,
715 Hanna Bldg., Cleveland 15, Ohio

STOCK ENGINEERING CO.

CONICAL
Non-Segregating
Coal Distributors

S.E.CO.
Coal Valves and Coal Scales

hot cathode to anode, which is assumed to do here.

When light shines on the photoelectric tube's cathode, Fig. 13, the tube conducts and current flows from battery *D* through resistor *R*, as indicated. Current flowing through resistor *R* causes a voltage drop across it equal to the current times the resistance. If we assume a 5-megohm resistor (5,000,000 ohms) and a 2-microampere current, voltage drop across resistor *R* is 10 v.

This voltage opposes that of battery *C*, just as if the photoelectric tube were eliminated and resistor *R* replaced by a 10-v battery. This battery connected in circuit to give the polarity shown in *R* would oppose grid battery *C* and reduce potential on the grid by an equal amount. The tube can now conduct as indicated for battery *B* to energize the relay coil and cause it to close its contact. *Interrupting the light beam* on the photoelectric-tube cathode restores the conditions in Fig. 12, and the relay opens.

This is one of many ways photoelectric tubes control circuits. Others will be explained later.

Alabama Power Co expects to install a new 60,000-kw unit in the Gorgas steam plant, according to President Thomas W. Martin. This unit and the 40,000-kw unit to be installed in the Mobile district have been contracted for earlier delivery. These two units bring to 242,000 kw the total capacity that the company now has on order. Martin pointed out that the new capacity to be added to the company system means a total investment of $50,000,000, including transmission lines, substations and other facilities.

Aluminum Co of America plans construction of an aluminum-producing plant at Point Comfort, near Port Lavaca, Texas, and construction of an 80,000-kw capacity electric-generating plant. The new plant, which will use natural gas for fuel, will be the first peacetime use by Alcoa of electricity generated by other means than water power. I W Wilson, vice-president in charge of operations, and Thomas D. Jolly, vice-president and chief engineer, say it will require about two years to complete the plant.

Canadian General Electric Co has been awarded a contract by B. C. Power Commission for fabrication and installation of two 12,500-kva generators at the new Bridge-shan-Arrow Lakes hydro project. Contract price of $348,535 includes spare parts, air coolers and certified factory tests. The first unit will be delivered in 18 months, the second in 19 months. H G Acres & Co. have been retained as general consultants. The generators will be 15,000-hp 720-rpm units with wheels operating under 690-ft head. The plant is being designed for four units, only two of which are to be installed in the initial development.

THERE'S A GRINNELL HANGER FOR EVERY PIPING REQUIREMENT



GRINNELL ADJUSTABLE SWIVEL PIPE RING

(Split Ring Type)



Enlarged section showing locking feature.

- Hinging of ring is off-center. This provides sufficient seating to hold pipe before closing ring. Wedge-type pin is loosely but inseparably cast into the hinged section for fastening after pipe is in place.
- To obtain proper adjustment, swivel shank can be turned easily by hand when the weight of the pipe is temporarily taken off the ring.
- When weight is returned, patented swivel shank locks automatically, preventing change of adjustment due to vibration. Wire retaining ring prevents separation of the swivel shank from the pipe ring or yoke . . . makes assembly a single unit.
- 12 sizes have load range of 80 lbs. for ¾" size to 1510 lbs. for 8" size. May be used in connection with practically any building attachment.

SAVE MONEY ON ASSEMBLY. Cut installation time, get better, stronger installations, with Grinnell Engineered Pipe Hangers.

NO SAG . . . NO WATER TRAP. Grinnell Hangers permit adjustment after pipe is installed. This makes it possible to prevent sagging pipe and water traps, and assures positive drainage for the entire system.

FOR EVERY INSTALLATION. There is a stock Grinnell Hanger for every need from simple water pipe to high pressure, high temperature steam line. Where necessary there is a hanger to compensate for thermal movement.

Don't waste time or take chances on inadequate pipe hangers and supports. All Grinnell hangers comply with piping code requirements.

GRINNELL COMPANY, INC.
Providence 1, R. I.

Branch Warehouses

Atlanta 2, Ga.
Charlotte 1, N. C.
Chicago 9, Ill.
Cleveland 14, O.
Cranston 7, R. I.
Fresno 1, Cal.
Houston 1, Tex.
Kansas City 16, Mo.
Long Beach 10, Cal.
Los Angeles 13, Cal.
Milwaukee 3, Wis.
Minneapolis 15, Minn.
New York 17, N. Y.
Oakland 7, Cal.
Philadelphia 34, Pa.
Sacramento 14, Cal.
St. Louis 10, Mo.
St. Paul, Minn.
San Francisco 7, Cal.
Seattle 1, Wash.
Spokane 15, Wash.

GRINNELL
where to use PIPING to advantage