



UNION CARBIDE CORPORATION
Nuclear Division

New York, N. Y.

MEMORANDUM

To: Messrs. T. Dougherty
R. A. Miller
R. Stobaeus
T. R. van Fleet

cc: Messrs. K. W. Lentz
A. E. Pufahl

G. S. Jordan
H. F. Reichard
N. J. Setter
R. G. Woolery

✓ J. A. Riddle

Dr. C. U. Dernehl

Subject: ASBESTOS TOXICOLOGY REPORT

DISTRIBUTION

W. T. Cohan ☐
J. A. Riddle ☒ JAR
E. W. Haskins ☒ JAR
L. F. Crow ☒ JAR
G. C. Brice ☐
D. S. Kamens ☐
K. West ☐
G. Vessels ☐
Shifters ☒ JAR
January 12, 1965
File

Gentlemen:

Recently several reports were given at technical meetings and summaries of them carried by the national wire services concerning possible carcinogenic properties of asbestos. Some of you may have received questions from your customers on this subject.

In order to counteract any serious problems or worries before they get out of hand, we have asked Dr. C. U. Dernehl, Director of Toxicology, Union Carbide Corporation, to formulate a statement for us. A copy of his statement is enclosed. Additional copies can be obtained from me or you may make your own copies if you wish to pass them on to interested customers. You will note that, in essence, the report states that good housekeeping -- such as would be required in any dust-producing operation -- should be sufficient to prevent any problem with asbestosis. You will also note that he mentions use in a wet system -- which certainly applies to the paper mill -- and a pellet form -- one of the strong points of our asbestos -- as additional means of minimizing any potential problem with the product.

Further, other asbestos producers and those acquainted with the subject feel that the original data upon which the cancer-producing report was based did not take into account any outside influences, such as smoking or corrosive atmospheres, which also might produce cancer. Here, it should be noted that much asbestos usage considered in the technical papers is in conjunction with tar and pitch compounds which are known to contain carcinogenic materials.

407003



THE DISCOVERY COMPANY

UNION CARBIDE CORPORATION
CHEMICALS & PLASTICS
P. O. BOX 'K' - KING CITY, CA. 93930

Calidria ASBESTOS

ASBESTOS TOXICOLOGY REPORT

It has been known for many years that some persons working in asbestos production were prone to develop a disabling lung disease. In time this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level. It is now generally accepted that a man can work a 40-hour week for a lifetime without developing asbestosis if the asbestos dust particle count is kept at or below 5 million particles per cubic foot of air. This dust concentration of 5 million particles per cubic foot of air is the Threshold Limit Value for asbestos, and no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, despite large-scale utilization (now approaching one million tons per year in the U.S.A.). This concentration of dust is generally not visible in the average work area unless a beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value. A major manufacturer of asbestos products who also mines asbestos has not been able to show an increase in cancerous growths in men working where dust concentrations were maintained at the Threshold Limit Value.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems, wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In paper manufacturing, it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the pulp slurry. Concentrations should also be determined where dusting occurs in finishing products. While initial dust determinations

A07009

should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

Pre-employment and periodic physical examinations for workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of paper products would be harmless to the consumer. Total dusting would have to be well in excess of any levels acceptable to the consumer for the asbestos concentration to approach the Threshold Limit Value.

In conclusion, while asbestos dust in excess of the Threshold Limit Value is potentially harmful, as are many other dusts encountered in industry, it is as readily controlled as other such dusts and it can be used safely with appropriate precautions.

Carl U. Dernehl, M.D.
Director of Toxicology
Union Carbide Corporation

K. S. Lane, M.D.
Assistant Director of Toxicology
Union Carbide Corporation

retyped
JLM/cg
1/7/69

407010

INTERNAL CORRESPONDENCE

UNION CARBIDE CORPORATION

270 PARK AVENUE, NEW YORK, NEW YORK 10017

To (Name) Messrs: C. Benjamin
 Division T. F. Frangos
 Location B. E. Godard
 J. L. Myers
 J. A. Riddle ✓
 Copy to N. J. Setter
 J. T. Sinclair
 J. R. Stickney
 W. S. Young

Date April 3, 1969
 Originating Dept. Medical Department
 Answering letter date
 Subject Asbestos

RECEIVED

APR 7 1969

U.C.C. CHEM. & PLASTICS

Gentlemen:

Both because of changes in regulations and availability of data developed after the issuance of our report in 1964, Dr. Dernehl and I have revised the asbestos memorandum. A copy of the revision is enclosed.

The major changes are the decrease in the Threshold Limit Value from 5 million particles per cubic foot of air to 2 million particles per cubic foot of air. (There is also a provision for another method of counting but it does not appear applicable to our short fiber asbestos.) We briefly discuss mesotheliomas, but data is too scanty as yet for a definite policy to be established. It is worth mentioning that the American Conference of Governmental Industrial Hygienists considered in 1968 a requirement that airline respirators be required for all contact with crocidolite asbestos. The resolution did not pass, but may come up again in future meetings.

Any questions or comments will be welcome.

Very truly yours,

K. S. Lane
 K. S. Lane, M. D.

Assistant Medical Director

KSL:lk
 Enclosure

407084

ASBESTOS TOXICOLOGY REPORT

It has been known for years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level.

It has been generally accepted that a worker will not develop asbestosis if he is exposed to no more than 5 million particles per cubic foot of air, even if this exposure continues for his entire working lifetime. Although no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, the ACGIH (which sets the threshold limit value (TLV) in the U. S. A.) has indicated they intend to lower the TLV for asbestos to 2 million particles per cubic foot in an effort to increase the safety factor incorporated in the limit. The U. S. Department of Labor has already issued a regulation under the Walsh-Healy Act placing the TLV for asbestos at 2 million particles per cubic foot for public contracts in which they have jurisdiction. This concentration of dust is generally not visible in the average work area unless a

407085

beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cuibe foot (MPPCF) before its presence it visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value.

A type of cancer named mesothelioma has been noted to be associated with asbestos exposure in recent years. These tumors, while rather few in number to date, may occur in individuals with histories of only slight exposures, and that as much as twenty to forty years earlier. There is considerable evidence that crocidolite is most frequently associated with mesotheliomas. From the data available it appears that the TLV of 5 MPPCF is not low enough to protect against mesothelioma, and it is quite possible that 2 MPPCF is not, either. Research on the problem continues.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems,

407086

wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In paper manufacturing, it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the pulp slurry. Concentrations should also be determined where dusting occurs in finishing products. While initial dust determinations should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

Pre-employment and periodic physical examination of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of paper products would be harmless to the consumer. Total dusting would

A07087

have to be well in excess of any levels acceptable to the
const. or for the asbestos concentrations to approach the
Threshold Limit Value.

In conclusion, while asbestos dust in excess of the
Threshold Limit Value is potentially harmful, as are many
other dusts encountered in industry, it is as readily
controlled as other such dusts and it can be used safely
with appropriate precautions.


Industrial Medicine And
Toxicology Department
Union Carbide Corporation

407088

You should have this statement available for any questions which might arise from your customers. If appropriate in your judgment, perhaps it should be discussed with certain customers who have not yet raised the subject. I do not feel we should make a big issue of it thereby drawing unnecessary attention to the subject since the conclusions are still questionable.

If you have any questions, please discuss them with me.

Very truly yours,

A handwritten signature in dark ink, reading "Thomas J. Hall". The signature is written in a cursive style with a large, stylized "T" and "H".

T.J.Hall/dk

enc.

A07004



UNION CARBIDE CORPORATION

270 PARK AVENUE, NEW YORK, N. Y. 10017

ASBESTOS TOXICOLOGY REPORT

It has been known for many years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level. It is now generally accepted that a man can work a 40-hour week for a lifetime without developing asbestosis if the asbestos dust particle count is kept at or below 5 million particles per cubic foot of air. This dust concentration of 5 million particles per cubic foot of air is the Threshold Limit Value for asbestos, and no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, despite large-scale utilization (now approaching one million tons per year in the U.S.A.). This concentration of dust is generally not visible in the average work area unless a beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value. A major manufacturer of asbestos products who also mines asbestos has not been able to show an increase in cancerous growths in men working where dust concentrations were maintained at the Threshold Limit Value.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems, wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In paper manufacturing, it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the pulp slurry. Concentrations should also be determined where dusting occurs in

A07005

finishing products. While initial dust determinations should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

Pre-employment and periodic physical examinations of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of paper products would be harmless to the consumer. Total dusting would have to be well in excess of any levels acceptable to the consumer for the asbestos concentration to approach the Threshold Limit Value.

In conclusion, while asbestos dust in excess of the Threshold Limit Value is potentially harmful, as are many other dusts encountered in industry, it is as readily controlled as other such dusts and it can be used safely with appropriate precautions.

Carl U. Dernehl, M.D.
Director of Toxicology

K. S. Lane, M.D.
Assistant Director of Toxicology

A07006



THE DISCOVERY COMPANY

Caution ASBESTOS

ASBESTOS TOXICOLOGY REPORT

It has been known for years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level.

It has been generally accepted that a worker will not develop asbestosis if he is exposed to no more than 5 million particles per cubic foot of air, even if this exposure continues for his entire working lifetime. Although no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, the ACGIH (which sets the threshold limit value (TLV) in the U. S. A.) has indicated they intend to lower the TLV for asbestos to 2 million particles per cubic foot in an effort to increase the safety factor incorporated in the limit. The U. S. Department of Labor has already issued a regulation under the Walsh-Healy Act placing the TLV for asbestos at 2 million particles per cubic foot for public contracts in which they have jurisdiction. This concentration of dust is generally not visible in the average work area unless a beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot (MPPCF) before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value.

A type of cancer named mesothelioma has been noted to be associated with asbestos exposure in recent years. These tumors, while rather few in number to date, may occur in individuals with histories of only slight exposures, and that as much as twenty to forty years earlier. There is considerable evidence that crocidolite is most frequently associated with mesotheliomas. From the data available it appears that the TLV of 5 MPPCF may not be low enough to protect against mesothelioma. Research on the problem continues.

A07007

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems, wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In manufacturing industries it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the process. Concentrations should also be determined where dusting occurs in finishing products. While initial dust determinations should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

Pre-employment and periodic physical examination of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of products would be harmless to the consumer. Total dusting would have to be well in excess of any levels acceptable to the consumer for the asbestos concentrations to approach the Threshold Limit Value.

In conclusion, while asbestos dust in excess of the Threshold Limit Value is potentially harmful, as are many other dusts encountered in industry, it is as readily controlled as other such dusts and it can be used safely with appropriate precautions.

Industrial Medicine And
Toxicology Department
Union Carbide Corporation

5/8/69

407008