

API TOXICOLOGICAL REVIEW

BENZENE

SECOND EDITION, 1960



The information and recommendations contained in this publication have been compiled from sources believed to be reliable and to represent the best current opinion on the subject. No warranty, guarantee, or representation is made by the American Petroleum Institute as to the absolute correctness or sufficiency of any representation contained in this and other Toxicological Reviews, and the Institute assumes no responsibility in connection therewith; nor can it be assumed that all acceptable safety measures are contained in this and other Toxicological Reviews, or that other or additional measures may not be required under particular or exceptional conditions or circumstances. The American Petroleum Institute, as sponsor of this review, takes no position as to whether or not any method contained herein is covered by an existing patent, nor as to the validity of any patent alleged to cover any such method. Furthermore, nothing contained in this review grants any right, by implication or otherwise, for the manufacture, sale, or use in connection with any method, apparatus, or product covered by letters patent.

This review was prepared at the Harvard School of Public Health, Boston, Mass., under the direction of Professor Philip Drinker. Anyone desiring to submit additional information or proposed changes for consideration prior to reissuance of this review is requested to send them to the American Petroleum Institute.

AMERICAN PETROLEUM INSTITUTE

1271 AVENUE OF THE AMERICAS

NEW YORK 20, N. Y.

Price 25 Cents

DO 067884
CONFIDENTIAL

YZ0077431

API TOXICOLOGICAL REVIEW OF BENZENE

I. Substance

Benzene

Formula: C_6H_6

Structural formula:



Molecular weight: 78.11

Synonyms: benzol
 phene

II. Properties and Characteristics ^{14, 15, 16}

Boiling point = 80.1 C (176.2 F) at 760 mm.
Melting point = 5.4 C to 5.5 C (41.7 F to 41.9 F).
Vapor pressure = 74.6 mm of mercury at 20 C (68 F).
Liquid density = 0.899 g per milliliter at 0 C (32 F).
Explosive limits = 1.4 to 8 per cent.
Flash point = 12 F (closed cup).
Refractive index = 1.5016 at 20 C (68 F).
Specific gravity = 0.8787 at 15 C (59 F).
1 mg per liter = 313 ppm; 1 ppm = 0.00319 mg per liter.

Benzene is a clear, colorless liquid with a characteristic pleasant odor at low concentrations and a disagreeable odor at higher concentrations. It forms a highly flammable and explosive mixture with air at concentrations ranging from 1.4 to 8.0 per cent benzene by volume. Pure benzene burns with a yellow, luminous, smoky flame and is a fire hazard unless proper care is taken in handling and storage.

Benzene is relatively insoluble in water (0.08 g in 100 ml of water at 22 C) but is readily miscible in all proportions with alcohol, ether, acetic acid, chloroform, carbon disulfide, carbon tetrachloride, and similar organic solvents. Commercial benzene is practically never pure and usually contains varying amounts of xylene, phenol, and toluene; commercial benzene also contains traces of carbon disulfide (0.2 to 1.0 per cent), thiophene (0.1 to 0.2 per cent), olefins, naphthalene, and similar substances.

Chemically, benzene is the simplest of the aromatic hydrocarbons. It is relatively stable but is capable of a variety of substitution reactions such as chlorination, nitration, sulfonation, and alkylation. Benzene is an excellent solvent for most organic substances.

¹⁴ Figures refer to BIBLIOGRAPHY on p. 6.

III. Manufacture, Uses, and Possible Sources of Exposure

Benzene is usually manufactured from catalytically reformed light naphthas from which it is isolated by distillation or solvent extraction.

Benzene is used as a solvent in many applications. It is also used as a component of some motor fuels and as the raw material for the manufacture of a host of synthetic chemicals. Examples are: styrene, phenol, aniline, DDT, chlorobenzene, cumene, nitrobenzene, diphenyl, cyclohexane, adipic acid, and detergents.

Because of its volatility, benzene presents a vapor hazard. The vapor may arise from numerous handling operations, as well as from leaks and accidental spills. Skin contact is a possibility when handling or packaging.

IV. Toxicology

a. Acute Effects

Acute benzene poisoning generally results from the inhalation of relatively high concentrations of vapor. Exposure to air containing benzene in concentrations of 19,000 ppm to 20,000 ppm (61 to 65 mg per liter of air) may cause death within 5 to 10 min, whereas concentrations of 7,500 ppm (25 mg per liter) are dangerous to life in one-half to one hour.⁴ Severe toxic effects may be caused by 1-hour exposure to concentrations of 1,500 ppm (4.8 mg per liter). Concentrations of 500 ppm (1.6 mg per liter) may lead to symptoms of illness when exposure continues for more than a short time.⁵

Inhalation of 50 ppm to 150 ppm (0.10 to 0.48 mg per liter) of benzene for 5 hours caused slight headache, weariness, and lassitude. The red-blood count decreased, the white-blood count was unchanged except for mild lymphocytosis, eosinopenia, and monocytopenia. The albumin-globulin ratio increased slightly at lower concentrations but decreased with higher concentrations. The urinary coproporphyrins were increased, whereas the urinary sulfate ratio was decreased.⁶

Skin contact will cause dehydration and defatting which may lead to dermatitis. Systemic intoxication by cutaneous absorption is unlikely.

Drinking benzene causes acute symptoms with local evidence of acute irritation of the mouth, throat, and stomach. A tablespoonful or less of benzene when swallowed has been known to cause serious collapse. Subse-

quently, it may result in bronchitis or pneumonia which is probably caused by benzene entering the air passages.⁷

Acute exposure to benzene exerts a toxic action on the central nervous system. Benzene first behaves as a stimulant—in the early stages of acute poisoning, persons show excitement, euphoria, hilarity; then quite suddenly this changes to weariness, fatigue, and sleepiness, followed by coma and death.⁸

Acute exposure to benzene produces rapidly increasing symptoms of dizziness, excitation, and pallor, followed by flushing, weakness, headache, breathlessness, constriction in the chest, and fear of impending death. Visual disturbances, tremors, and muscular weakness are also encountered. The victim may lose consciousness and pass into coma or may develop acute mania and delirium. Convulsions occur frequently. Death may supervene almost at once or several hours to several days following exposure.⁹

Recovery from acute benzene poisoning requires from one to four weeks. Immediately after exposure there are temporary symptoms of chest and head pains, shortness of breath, giddiness, nausea, and loss of appetite. Evidence of unsteady gait, nervous irritability, and breathlessness may persist for two or three weeks, whereas cardiac distress and a peculiar yellow pallor to the skin may last for as long as a month. Recovery from acute poisoning is generally complete after this period, although evidences of chronic benzene poisoning may be encountered later.⁹

Benzene also sensitizes the heart muscle to the action of epinephrine, so that instant death may occur as a result of ventricular fibrillation.¹ Muscular activity increases the rate and severity of acute benzene poisoning. Persons dying of acute benzene poisoning generally show absence of clotting of the blood and widespread petechial hemorrhages in the brain, pleura, pericardium, urinary tract, intestinal tract, mucous membranes, and skin. There are no specific lesions of diagnostic importance.⁹

Local effects from acute exposure are seldom severe. Continued skin contact with benzene results in defatting of the skin and leads to erythema, dry scaling, and, in some cases, the formation of vesicular papules. Prolonged exposure may produce lesions resembling first- or second-degree burns. It may cause considerable irritation of the eyes or mucous membranes of the nose and throat on contact.

Benzene poisoning by skin absorption has received scant attention in the literature. The possibility of percutaneous absorption of benzene has been studied in three cases. Immersion of the hands and forearms from 25 to 35 min showed no evidence of skin absorption.¹⁰

Unquestionably, small amounts of benzene can be absorbed through the skin, but it is very doubtful that enough would be absorbed by this route to cause systemic poisoning.⁷

b. Chronic Effects

Chronic benzene poisoning results from repeated or continuous exposure to relatively low concentrations of benzene vapor. The level and degree of exposure necessary to produce poisoning vary widely. There are at least two well-authenticated cases of poisoning by repeated exposures to 75 ppm.¹¹

The toxic action is exerted mainly on the hematopoietic system. It may take months or even years to show harmful effects. Symptoms may be present over long periods, i.e. headaches, dizziness, fatigue, anorexia, and dyspnea. They may be varied and vague and not obviously connected with benzene poisoning.

During the early stages of poisoning, Heinz bodies may be present in the red-blood cells and a neutropenia is often seen. At this stage the blood picture may return to normal after removal from contact with benzene.

As chronic poisoning progresses, nausea and vomiting, burning sensations of the eyes and throat, and hemorrhages from mucous membranes, tongue, and gums become manifest. Purpuric spots and ecchymoses may follow the slightest injury, and epistaxis may occur. Menorrhagia, metrorrhagia, and spontaneous abortion may develop in otherwise healthy women. Blood examination at this point may show leukopenia (below 4,000 white cells), neutropenia, and a severe anemia. Later the platelet count falls so that thrombopenia is marked. The blood condition, at this stage, may have become irreversible. The clinical picture of a worker with chronic benzene poisoning at this stage is characteristic—he complains of headaches, giddiness, drowsiness, lassitude, loss of appetite, and nausea with occasional vomiting. He looks pale; is short of breath; has a rapid pulse, a low blood pressure, and a mildly elevated temperature. He may also have epistaxis, bleeding from the gums, a purpuric rash, or subconjunctival hemorrhages. The condition progresses slowly to acute leukopenia ending in fatal aplastic anemia.⁴ Repeated small doses of benzene by mouth can produce the same type of chronic poisoning.⁷

Repeated contact of benzene with the skin will cause dehydration and delipidization predisposing to dermatitis.

Benzene is relatively insoluble in body fluids and tissues. Therefore, only small amounts are absorbed by the body. Equilibrium between blood and air is approached within a few minutes after exposure is begun, and practically complete elimination of benzene from the

blood occurs within a few minutes after exposure is terminated. Higher concentrations of benzene are obtained in tissues with a greater fat content, and saturation and elimination are more gradual.¹⁵

Human subjects inhaled benzene in concentrations of 340 micrograms per liter of air for 5 hours. Between 33 and 65 per cent of the inhaled benzene was retained (385 mg). During the desaturation period 3.8 to 27.8 per cent of retained benzene was excreted through the lungs and 0.1 to 0.2 per cent in the urine and other body excreta. Of the absorbed benzene, 9.7 to 42 per cent was excreted in the urine as phenol, 0 to 5.4 per cent as pyrocatechol, and 0.1 to 3.3 per cent as hydroquinone. Excretion of phenol and pyrocatechol was highest during the first 24 hours and complete in 48 hours, whereas hydroquinone took more than 48 hours. Excretion of organic sulfates in urine of exposed subjects was increased. The opinion was expressed that benzene affects the metabolism of proteins, the metabolites of which are excreted in urine as ethereal sulfates.¹⁶

Benzene is unique in its myelotoxicity. It has been shown that the introduction of an alkyl group into the aromatic ring results in a loss of its myelotoxic property. This difference may be a result of the difference in the metabolic pathway. Benzene is metabolized to phenols and quinones which inhibit cell production. The *in vivo* metabolites of alkyl benzenes are alcohols and carboxylic acids resulting from side chain oxidations. These compounds have a low-order toxicity and are devoid of specific cell destructive effects.¹⁴

A variety of reactions may be encountered as the result of the chronic effect of benzene poisoning. There is little correlation between the degree and duration of exposure and the severity or nature of the findings in the blood on microscopic examination.¹⁵ They may consist of a reduction in red-cell, white-cell, or platelet levels—in any two of these or in all three. These changes may develop gradually or suddenly. The blood usually shows a moderate reduction in red cells (below 3.5 million), white cells (below 4,500), and platelets. Blood examinations for evidence of benzene poisoning should consist of a complete study of red, white, and platelet fractions. Progressive changes are more significant than the absolute levels.

In anemia caused by benzene, it has been shown that there is a constant increase in serum iron (average increase, 213 micrograms) which is associated with a reduction of transferrin (average reduction, 225 micrograms). The iron saturation of transferrin is above normal and is matched by iron saturation of the tissue. The cause of the disturbance of iron metabolism in benzene poisoning is the failure of the marrow to utilize

iron as well as increased intake of iron supplied parenterally by transfusion.¹⁶

There is some evidence that chronic benzene poisoning produces a blood-clotting defect which is caused by functional and morphological as well as a quantitative alteration of the platelets.¹⁷ The marrow cells exhibit a decrease in peroxidase in benzene poisoning. Because benzene inhibits granulocyte maturation, it may act on peroxidase metabolites, or the peroxidase may be used up in detoxifying benzene.¹⁸

The bone marrow may be hypoplastic, fairly normal, or hyperplastic in appearance. Abnormal forms of young cells may abound, and leukemia as a result of chronic benzene exposure has been reported. Various individuals differ in their bone marrow response to benzene—cases with symptoms fairly soon after exposure usually have fewer cells in the marrow, whereas cases developing later are more apt to have an increased number of cells in the marrow. It is believed that this represents an early weeding out of those who develop hypoplastic changes, rather than a gradual shift from one type of response to the other.^{19, 20}

In a long-term follow-up of chronic benzene poisoning 4,538 cases were studied from 2 to 12 years after cessation of work involving exposure. There has been only one fatal case, six cases involving bone marrow changes, and one case of lowered resistance to infection.²¹ The others were practically well but show varying degrees of neutropenia.

Benzene is eliminated from the body via the lungs and the kidneys. In one study C-14 labeled benzene was given orally to rabbits. In 2 days 45 per cent of the dose was eliminated in the expired air (43 per cent as unchanged benzene and 1.5 per cent as carbon dioxide), and 35 per cent was eliminated as metabolites in urine (23 per cent as phenol, 4.8 per cent as quinol, 2.2 per cent as catechol, 0.3 per cent as hydroxyquinol, 0.5 per cent as L-phenylmercapturic acid, and 1.3 per cent as *trans*-, *trans*-muconic acid). Five per cent of the administered radioactivity was found in the tissues occurring mainly as metabolites.²²

Certain factors have been noted which influence individual variation in susceptibility to benzene. Overweight individuals are more commonly affected,²³ and a low-protein, high-fat, low-Vitamin C diet is said to promote the disease. The presence of heart or lung disease and liver or kidney damage are believed to predispose to the condition.²⁴ Pregnant women may be more susceptible to benzene poisoning.⁴ Pathological changes in ovaries, testes, thyroid, and pituitary are attributed to benzene; and changes in women workers leading to sterility are emphasized.²⁵

DO 067887
CONFIDENTIAL

YZ0077434

c. Recommended Limit of Atmospheric Exposure

The generally recognized maximum acceptable concentration for benzene vapor is 25 ppm by volume in air (0.08 mg per liter of air) for an 8-hour daily exposure.⁷ In Germany the maximum permissible concentration to which workers may be exposed is 31.3 ppm by volume in air (0.1 mg per liter of air).²⁰ The Massachusetts laws have established 25 ppm as a maximum benzene concentration.²¹

V. Treatment

Acute benzene poisoning should be considered an acute emergency. Remove the victim from further exposure at once and call a physician immediately. The patient should be kept warm and quiet in the recumbent position. If breathing has stopped, artificial respiration should be started at once. Oxygen should be administered by a qualified person as long as necessary to maintain the normal color of skin and mucous membranes. This may prevent the development of severe pulmonary edema. Stimulants will rarely be necessary when adequate oxygenation is maintained.¹

Care should be taken that rescuers are not also overcome by vapors.

Chronic benzene poisoning is extremely refractory to treatment. It is most important that the condition be diagnosed early and the individual withdrawn from further contact with the hydrocarbon. Blood transfusions are temporarily useful in combating severe anemia.

VI. Examination

The pre-employment examination should include a detailed history, physical examination, chest X-ray, and complete blood count. Workers with organic disease of the heart, lungs, liver, or kidneys should be eliminated, as should those with a history of previous benzene intoxication or evidence of an abnormality of the blood or blood-clotting mechanisms.^{22, 24}

Periodic re-examinations should be carried out regularly, the frequency being determined on the basis of the probable degree of exposure. The examination should include a brief interval history and physical examination, together with a complete blood study. The presence of any of the blood changes described require re-examination at least twice at intervals of one week and a thorough study of the working conditions. Unless there is noticeable improvement on re-examination, the worker should be withdrawn from further exposure. The following changes call for re-examination: white-blood count less than 4,000, red-blood count less than

4,000,000, hemoglobin less than 12 g per 100 ml (80 per cent), blood platelets less than 100,000 per cu mm, differential count less than 50 per cent polymorphonuclear-leukocytes, and more than a very few immature blood cells. The urine sulfate test may be used, not as a diagnostic test, but as a measure of the degree of the current benzene exposure. It does not measure the degree of benzene poisoning nor the blood changes present.¹

VII. Precautionary Measures

The safety measures necessary for the prevention of benzene poisoning are primarily those designed to prevent the inhalation of benzene vapor. Proper ventilation, local exhaust, and closed systems should be used to maintain a concentration below the maximum acceptable concentration of 25 ppm by volume in air. All apparatus and piping should be inspected regularly and systematically for leakage. When excessive concentrations are unavoidably encountered in operations such as the cleaning of tank cars, vats, or storage tanks, air masks and protective clothing should be employed.²⁵ Employees should be fully instructed regarding health hazards which may be present in the handling of benzene and should immediately report any unusual symptoms or illness. Clothing wet with benzene should be removed promptly.

If the hands are likely to have contact with benzene, impervious gloves or protective creams should be used. Proper ventilation, routine plant inspection, control of benzene air concentration, and periodic medical examinations are all of the utmost importance.²⁶

The concentration of benzene vapor in the air should be checked regularly in locations where the possibility of excessive exposure may be encountered. This may be done by a variety of procedures among which are the butanone method,² the *m*dinitrobenzene reduction method,³ an absorptiometric method, and a photocolometric determination. The latter method involves the nitration of benzene with Stepanov mixture which forms *m*dinitrobenzene. This gives a color reaction with acetone in alkaline solutions. Under similar conditions toluene gives a faint violet color. Based on these photocolometric methods small quantities of benzene and toluene can be determined in air.²⁷ More recently a silica gel adsorption method has been reported.²⁸ Accurate quantitative study of atmospheric benzene as low as 0.003 mg per ml (0.9 ppm) may be determined by adsorption on activated silica gel and elution with absolute alcohol. The benzene content is then determined spectrophotometrically according to *ASTM Designation D 1017: Method*

DO 067888
CONFIDENTIAL

YZ0077435

of Test for Benzene and Toluene by Ultraviolet Spectrophotometry. The range of measurement is 0.003 mg to 1.28 mg per liter. The mean yield was approximately 98 per cent.

There are a number of instruments on the market which measure hydrocarbon air contamination. The presence of more than one hydrocarbon vapor, however, produces erratic results.

VIII. Bibliography

- ¹ E. Browning, *Toxicity of Industrial Organic Solvents, Industrial Health Research Board Report No. 80*, London (1937).
- ² M. G. Jacobs, *The Analytical Chemistry of Industrial Poisons, Hazards, and Solvents*, 399, Interscience Publishers, Inc., New York (1944).
- ³ C. D. Hodgman and H. N. Holmes, *Handbook of Chemistry and Physics*, 25th edn., Chemical Rubber Publishing Co., Cleveland (1941).
- ⁴ Y. Henderson and H. W. Haggard, *Noxious Gases and the Principles of Respiration Influencing Their Action*, 164, Chemical Catalog Co., New York (1943).
- ⁵ M. W. Goldblatt, "Research in Industrial Health in the Chemical Industry," *Brit. J. Ind. Med.* 12 1 (1955).
- ⁶ Genichi Watanabe, Jun Yashioka, Haruo Hondo, Masao Matouchi, and Takero Sakaguchi, *J. Sci. Labour (Japan)* 29 70 (1953); from *Chem. Abstr.* 6051 (1954).
- ⁷ "Threshold Limit Values for 1959," American Conference of Governmental Industrial Hygienists, *A.M.A. Arch. Ind. Health* 20 266 (1959).
- ⁸ J. B. Lurie, "Occupational Health Hazards in the Manufacture of Insecticides," *S. Afr. Jour. Clin. Sci.* 3 212 (1952).
- ⁹ J. L. Svrbely, R. C. Dunn, and W. F. von Oettingen, "The Acute Toxicity of Vapors of Certain Solvents Containing Appreciable Amounts of Benzene and Toluene," *J. Ind. Hyg. Toxicol.* 25 366 (1943); and "The Chronic Toxicity of Moderate Concentrations of Benzene and Mixtures of Benzene and Its Homologues for Rats and Dogs," *J. Ind. Hyg. Toxicol.* 26 37 (1944).
- ¹⁰ G. L. Conca and A. Maltaglioti, "Study On Transcutaneous Absorption of Benzene," *Med. lavoro* 46 194 (1955); from *Chem. Abstr.*, 16232 (1955).
- ¹¹ M. Bowditch and H. B. Elkins, "Chronic Exposure to Benzene-I: The Industrial Aspects," *J. Ind. Hyg. Toxicol.* 21 321 (1939).
- ¹² H. H. Schrenk, W. P. Yant, S. J. Pearce, F. A. Patty, and R. R. Sayers, "Absorption, Distribution, and Elimination of Benzene by Body Tissues and Fluids of Dogs Exposed to Benzene Vapor," *J. Ind. Hyg. Toxicol.* 23 20 (1941).
- ¹³ J. Teisinger, V. Bergerova-Fiserova, and J. Kudrna, "Metabolism of Benzene in Man," Charles Univ. (Prague), *Pracovní Lékařství* 4 175 (1952); from *Chem. Abstr.*, 4181 (1955).
- ¹⁴ H. W. Gerarde, "Toxicological Studies on Hydrocarbons," *A.M.A. Arch. Ind. Health* 13 468 (1956).
- ¹⁵ L. A. Erf and C. P. Rhoads, "The Hematological Effects of Benzene Poisoning," *J. Ind. Hyg. Toxicol.* 21 421 (1939).
- ¹⁶ B. Pernis and L. Mareo, "Metabolism of Iron in Hemopathies Due to Benzene," *Med. lavoro* 46 325 (1955); from *Chem. Abstr.*, 14996 (1955).
- ¹⁷ G. Saita, E. Sartarelli, and F. Calaresu, "The Blood Clotting Process in Chronic Benzene Poisoning," *Med. lavoro* 45 313 (1954); from *Chem. Abstr.*, 11652 (1954).
- ¹⁸ V. Prato and G. F. Rubino, "Bone Marrow Peroxidase in Benzene Poisoning," Univ. Turin (Italy) *Minerva med.* II, 357 (1954); from *Chem. Abstr.*, 5662 (1955).
- ¹⁹ T. B. Mallory, E. A. Gall, and W. J. Brickley, "Chronic Exposure to Benzene-III: The Pathological Results," *J. Ind. Hyg. Toxicol.* 21 356 (1945).
- ²⁰ F. H. Hunter, "Chronic Exposure to Benzene-II: The Clinical Effects," *J. Ind. Hyg. Toxicol.* 21 331 (1939).
- ²¹ Karel Rejsek and Maria Rejkova, "Long Term Observation of Chronic Benzene Poisoning," *Acta Med. Scand.* 152 71 (1955).
- ²² D. V. Parke and R. T. Williams, "Studies in Detoxication 49, Metabolism of Benzene Containing C¹⁴ Benzene," *Biochem. J.* 54 231 (1953).
- ²³ A. Feil, "Le benzolisme professionnel," *Presse med.* 41 6, 129 (1933).
- ²⁴ C. E. A. Winslow, "Summary of the National Safety Council Study of Benzol Poisoning," *J. Ind. Hyg.* 9 61 (1927).
- ²⁵ J. L. Gutierrez de Alles, "Sterility in Laborers Caused by Benzene and Other Solvents" *Med y seguridad trabajo* 31 4 (1954); from *Chem. Abstr.*, 13556 (1955).
- ²⁶ R. W. van Hoesen Korndorffer, "Toxicology of Solvents," *Plastica* 4 11 (1951); from *Chem. Abstr.*, 11178 (1955).
- ²⁷ *Mass. Div. of Occup. Hyg. Bull.*, Maximum Allowable Concentrations (1957).
- ²⁸ *Occupation and Health Encyclopedia of Hygiene, Pathology and Social Welfare*, International Labor Office, Geneva 1, 228 (1930).
- ²⁹ F. I. Berezovskaya, B. E. Reznik, and S. S. Gitis, "Photometric Determination of Benzene and Toluene," *Nauch. Zapiski, Dnepropetrovsk. Gosudarst. Univ.* 43 45 (1953); from *Chem. Abstr.*, 783 (1955).
- ³⁰ "Per Ovrum, Determination of Atmospheric Benzene Concentration by Displacement Following Adsorption on Silica Gel," *Brit. J. Ind. Med.* 13 210 (1956).

API TOXICOLOGICAL REVIEWS

SECOND EDITION

Benzene (1960)	\$.25
Butadiene (1959)	.25
Copper Naphthenate (1959)	.25
Naphthalene (1959)	.25
Naphthenic Acids (1959)	.25
Toluene (1960)	.25
Xylene (1960)	.25

DO 067890
CONFIDENTIAL

YZ0077437

AT THE MARCH 3, 1981, PUBLIC HEARING

TEXAS CHEMICAL COUNCIL TESTIMONY
ON EPA'S PROPOSED NEW SOURCE PERFORMANCE
STANDARDS FOR VOLATILE ORGANIC
COMPOUND FUGITIVE EMISSION SOURCES

My name is A. H. Nickolaus and I represent the Texas Chemical Council (TCC). The TCC is an association of 87 chemical companies having more than 67,000 employees and representing approximately 90% of the chemical industry in Texas. Since over half of the nation's petrochemicals are produced by member companies operating in Texas, the proposed regulation is of vital concern to us.

The Texas Chemical Council has joined with the Chemical Manufacturers Association (CMA) in the preparation of detailed comments on the proposed regulation, and our combined written comments will be submitted prior to April 6, 1981. Today, I would like to highlight some of our concerns about this standard.

A. Definition Of Modification

First, to start off on a positive note, at our request the EPA has added an annual allowance of up to 5 1/2% for "process improvements" so that small, routine changes made to an existing process unit will not in themselves subject it to the new source standards. We thank the EPA for this consideration.

B. Performance Versus Equipment Standards, Etc.

When dealing with facilities broader than a specific process or installation, the TCC believes the EPA should set both a performance standard and an equivalent equipment or work-practice standard. If a performance standard is not possible, then at least an equipment and an equivalent work-practice should be set. This would allow the Synthetic Organic Chemicals Manufacturing Industry (SOCMI) the flexibility necessary to design and implement the most efficient and cost effective compliance program. The EPA has failed to do this for pumps, compressors, and valves in the proposed standard; although the TCC believes it is feasible to do so.

1. Pumps & Compressors

For both pumps and compressors, the EPA states in the preamble to this regulation (FR p. 1143 & 1144, Jan. 5, 1981) that a performance standard is not feasible because the application of measurement technology is not technologically impractical. Yet in the January 1981 Preliminary Draft Control Technique Guideline for "Control of Volatile Organic Fugitive Emissions from Synthetic Organic Chemical, Polymer, and Resin Manufacturing Equipment", they specify measurement of emissions from these pieces as the means of determining compliance.

DO 067891
CONFIDENTIAL

YZ0028967

The TCC recommends and requests that a similar monitoring option for pumps and compressors be added to this standard.

2. Valves In Gas & Light-Liquid Service

Contrary to the EPA's opinion, the TCC believes that a performance standard for valves in gas and light-liquid service is feasible. Snee and Kittleman of Du Pont have shown (Letter from T. A. Kittleman, Du Pont, to Glynda E. Willins, Radian Corporation, November 13, 1980) that a leak level of 2% is equivalent to the basis used by the EPA in the BID to estimate the leak reduction effectiveness of the proposed regulation.

The TCC recommends that the EPA specify 2% of valves leaking as a "good performance" level that is equivalent to the prescribed monitoring program.

C. Emissions Abatement

The proposed standard requires that emissions be transported through a "closed vent system" to an "enclosed combustion device" or vapor recovery system and then defines an "enclosed combustion device" so as to exclude flares. We take particular exception to this. The TCC in our June 30, 1980, comments to the EPA on the Draft BID provided data showing 99+% efficiencies for a properly designed flare system. The EPA has taken a position, without any data, that flares may be only 60% efficient and that the burden of proof of better is on the SOCOMI. We disagree. We have provided necessary data which should not be rejected arbitrarily. Further, since flares are standard abatement devices of long standing in both the chemical and petroleum-refining industries, we believe the burden of proof, with data, is on the EPA. The SOCOMI has a heavy investment in flares and will strongly resist EPA's position that they are not acceptable emission control devices.

We recommend that the definition of "closed vent system" be modified as follows:

"Closed Vent System means a system which is not open to the atmosphere and which is composed of piping, connections, and, if necessary, flow inducing devices that transport gas or vapor from fugitive emission sources to a device which provides 95% abatement or to an enclosed combustion device, vapor recovery system, properly designed flare system, or an equivalent control device as determined by paragraph 60.484."

D. Monitoring Frequency

The rational approach to how frequently monitoring for leaking valves should be performed (60.482f) would be based on a cost-effective analysis of leak occurrence and recurrence data. The EPA

DO 067892
CONFIDENTIAL

YZ0028968

has not done this. Instead, in the preamble (FR p. 1146, Jan. 5, 1981) they state clearly their basic commitment to a monthly monitoring schedule - apparently as an article of faith. In the BID the EPA has assumed an occurrence frequency biased to favor a monthly program (see attached Figure 1). In the absence of definitive data, the TCC finds it difficult to justify anything but the assumption of a linear leak occurrence with time. Using a linear relationship, a quarterly monitoring frequency gives the same results as the EPA claims for their monthly program (again see Figure 1).

The TCC has and continues to recommend that the required data be obtained and that a rational analysis of monitoring requirements be made. Until that time, the TCC believes the data in the BID cannot justify anything more frequent than quarterly monitoring.

The TCC recommends that monitoring requirements in the proposed standard be changed to a true quarterly frequency.

E. Leak Definition

As the EPA has correctly pointed out, most leakage comes from only a few valves, and the problem is to find and repair these. The EPA has proposed 10,000 ppmv as the definition of a leak. Recent EPA data show variations of nearly an order of magnitude in repeat measurements of leak rates on the same valve. For this and other reasons more fully developed in our written comments, the TCC again recommends that a leak be defined as 20,000 ppmv or greater. The leakage reduction attained will be essentially the same as at the 10,000 ppmv cut-off; but maintenance will be reduced by up to 30% as less maintenance effort will be spent on valves with inconsequential leak rates.

F. Alternative Standards

We commend the EPA for providing in paragraph 60.483 provisions for alternative standards. But in terms of monitoring programs, what the EPA giveth with one hand it taketh away with two. The problem is that an allowable percentage of valves leaking must be determined after the plant is built. Quality control experience shows that quality must be built into a product; it cannot be inspected in. Thus, the time to assure a low-leakage plant is in the original design before the plant is built. But a plant providing the best leak prevention options would have to meet a much lower allowable percentage valves than one not so well designed, and consequently, it would have much less opportunity for a reduced monitoring program than a poorly designed plant. This doesn't make sense; low-leak plants should require less inspection - high-leak plants more.

DO 067893
CONFIDENTIAL

YZ0028969

What is needed is an incentive for owners to build low-leak plants. Some assurance of an opportunity for reduced monitoring requirements in such plants ~~would provide this~~. In our written comments (60.483c - Good Performance Incentive), we detail a statistical monitoring plan which results in reduced monitoring requirements for those who meet a "good performance" level equivalent to the BID basis.

The TCC strongly advocates the adoption of this proposal. The advantages of a quality control approach is (1) greater emission reductions will be realized industry-wide because there is an incentive to do so, (2) the monitoring burden will be lessened on low-leak plants and increased on high-leak ones, and (3) well defined rules on what can and cannot be done will be available to the owner at the design stage.

G. Determination Of Equivalence (60.484)

Although the TCC believes guidelines for approval of equivalent or alternate means of emission limitation should be specific so that, having met them, approval by the EPA Regional Offices is more or less automatic; the proposed paragraph 60.484 seems to be overly detailed without accomplishing this purpose. The procedure in Subpart Ka, paragraph 60.114a for Standards of Performance for Storage Vessels for Petroleum Liquids Constructed After May 18, 1978, is simpler, more straight forward, and we prefer it to the present proposal.

H. Reporting, Recordkeeping, Etc.

The TCC believes that the proposed tagging, recordkeeping, and reporting is excessive and goes beyond that necessary to implement the required program and also beyond that required for compliance. In our written comments, we make detailed recommendations to correct this.

I. Need & Costs

In closing, whether it is legally appropriate or not, we cannot resist again stating our belief that this regulation is unnecessary and that the costs have been under-estimated. We re-affirm the comments we made to the EPA on June 30, 1980, and we recommend them to your attention.

Finally, on costs the EPA is still basing monitoring costs on two man-minutes per source despite their own data in Table C4 of the BID showing it took highly motivated contract workers an average of 3.4 minutes to perform this task.

AHN/rtg

2-20-81

DO 067894
CONFIDENTIAL

YZ0028970

BEFORE THE
ENVIRONMENTAL PROTECTION AGENCY

COMMENTS OF THE
CHEMICAL MANUFACTURERS ASSOCIATION
AND TEXAS CHEMICAL COUNCIL
ON

EPA'S PROPOSED RULEMAKING OF
NEW SOURCE PERFORMANCE STANDARDS
FOR VOLATILE ORGANIC COMPOUND
FUGITIVE EMISSION SOURCES UNDER
THE CLEAN AIR ACT

Proposed Standards of Performance)
for New Stationary Sources; VOC)
Fugitive Emission Sources; Synthetic)
Organic Chemicals Manufacturing)
Industry, 46 Federal Register)
1136 (January 5, 1981))

DOCKET NO. A-79-32

Geraldine V. Cox, Ph. D.
Vice President and
Technical Director

Janet S. Matey
Manager, Air Programs

Edmund B. Frost
Vice President and
General Counsel

David W. Carroll
Assistant General Counsel

Chemical Manufacturers
Association, Inc.
2501 M Street, N.W.
Washington, D.C. 20037
(202) 887-1100

April 6, 1981

DO 067895
CONFIDENTIAL

YZ0028463

§60.480(c)

In earlier drafts to subject proposed regulations, a problem was surfaced with the definition of modification as set forth in 40 CFR §60.14 as it might apply to fugitive emissions. A concern was expressed that continuing small changes routinely made to a process unit made for a variety of reasons might subject the entire existing unit to the NSPS fugitive emissions requirements. ~~The Agency's proposed §60.480(c), satisfactorily resolves this earlier concern.~~

[We understand the Agencies' proposal in 60.480(c) to mean that process improvements, as defined in 60.481, costing up to 5 1/2% annually of the original investment in the affected SOCMF facility shall not by itself be considered a modification. This would satisfactorily resolve our earlier concern.

§60.481 -- "Closed Vent System".

In discussions with EPA's OAQPS staff we were led to believe that the regulations would not preclude safety valve emergency releases to flaring systems or the atmosphere. In this regard, the preamble at page 1140 attempted to clarify that closed vent systems can be used to transport relief valve discharges and fugitive emissions to a control device, such as a flare. The proposed regulations, however,

These comments are also submitted on behalf of the Texas Chemical Council (TCC) whose offices are located at 1000 Brazos Street, Austin, Texas 78701. The TCC is an association of 87 chemical companies having more than 67,000 employees and representing approximately 90% of the chemical industry in Texas. Like the CMA, the TCC has also worked with the EPA over the past several years in the furtherance of responsible environmental regulation. The TCC also requests that the comments made by them which are referenced in Appendix A of the EPA's "VOC Fugitive Emissions in Synthetic Organic Chemicals Manufacturing Industry - Background Information for Proposed Standards" be incorporated as part of the administrative record in this matter.

The comments we are submitting today make certain recommendations that attempt to clarify, and/or modify the Agency's proposed regulatory program to make technically more sound several substantive provisions, and to simplify procedures, recordkeeping, and reporting where the proposed requirements are either redundant, unnecessary, to demonstrate compliance with applicable control requirements, and/or would reduce the paper workload.

Nevertheless, we believe that the Agency has made significant progress in addressing many of the concerns raised by CMA in our earlier submittals to the Agency on earlier drafts of the subject proposal, and on various other Clean Air Act fugitive emissions programs. We believe, however, that additional modifications are still necessary in order to achieve a viable and reasonable technical fugitive emissions program..

DO 067897
CONFIDENTIAL

YZ0028465

§60.481 -- "Fugitive Emission Source."

The definition of "fugitive emission source" includes compressors and pumps. Unfortunately the Agency has not included a definition

as to the types of pumps and compressors not subject to the fugitive emissions NSPS requirements. As a result of this apparent oversight reciprocating pumps and compressors are included in the regulatory program. The potential problem we have with the inclusion of reciprocating pumps and compressors are their inability to accommodate double seals or any type of seal that EPA may ultimately require. Accordingly, we recommend that in order for EPA to avoid sealing problems associated with reciprocating pumps and compressors that such pumps and compressors be expressly excluded from the definition of "fugitive emission source."

§60.482(a)(1) - "dual mechanical seals"

As we have commented on several times in the past, it is inappropriate to require use of dual mechanical seals for pumps. We recommend that EPA cease using the term "mechanical" and merely define the seals to be used in pumps as dual seals. Such a modification would provide industry with some flexibility for a source to use any properly designed dual seal. This modification would allow for the use of either pressure or level control devices.

We compliment the Agency on adopting an equivalency regulation in §60.484(b) that will allow companies to demonstrate the equivalence of single seals where adequate and permanent monitoring will result in equivalent degree of controls.

DO 067898
CONFIDENTIAL

YZ0028466

limit closed vent systems to transporting emergency releases to an enclosed combustion device or vapor recovery system.

We are concerned that the clear language of the proposed regulations contradicts statements made by EPA's OAQPS, the preamble, and various support documents that emergency releases can be transported by a closed vent system to not only an enclosed combustion device and vapor recovery system, as well as, a properly designed flare system, and other equivalent control devices. Failure to correct this inconsistency and revise the regulatory language could result in unanticipated enforcement initiatives based on the language of the proposed regulations. In addition, failure to revise the definition of closed vent system would arbitrarily exclude other control devices and properly designed flare systems which in many instances can achieve or approach the same degree of hydrocarbon reduction as enclosed combustion devices or vapor recovery system at significantly lower costs.

In order to clarify this matter we would recommend that the definition of "closed vent system" be modified, as follows:

"Closed Vent System" means a system which is not open to the atmosphere and which is composed of piping, connections, and, if necessary, flow inducing devices that transport gas or vapor from a fugitive emission source to an enclosed combustion device, vapor recovery system, a properly designed flare system, or an equivalent control device as determined by §60.484.

DO 067899
CONFIDENTIAL

[In this regard we wish to reaffirm the position taken and made in the Texas Chemical Council's letter of 30 June 1980 to the EPA (comments on the Draft BID and Recommended SOCOMI Standard) regarding flares and their use.

YZ0028467

in order to remedy this inconsistency.

As we discussed above, we believe that a closed vent system should be defined generally enough so that VOC fugitive emissions can be transported to appropriately designed enclosed combustion devices, vapor recovery systems, as well as, properly designed flare systems, or an equivalent control device. As presently drafted, fugitive emissions from pumps would be initially precluded from being controlled by catalytic combustion units unless a time consuming and costly equivalency demonstration can be made. Several of our member companies indicate that such control devices achieve equal or better control than the two systems presently recognized in §60.482(a)(3)(ii). To preclude catalytic combustion units without an adequate justification by EPA for requiring equivalency demonstration would have to be characterized as an arbitrary action.

The comments set forth above are equally applicable to pumps fugitive emissions regulated under §60.482(a)(7). We would hope that appropriate modifications consistent with a revised definition of closed vent system would be incorporated by EPA in the final version of §§60.482(a)(3)(ii) and (a)(7).

§60.482(a)(6) - delayed compliance

The proposed regulation requires that a leak be repaired as soon as practicable, but not later than 15 days after its detected, except as provided in §60.482(h). The exception allows extensions only where the repair is technically infeasible without a complete or partial process unit shutdown. The extension, however, cannot exceed the process unit shutdown.

The instant delay of compliance provision significantly improves on earlier drafts which imposed arbitrary deadlines and meaningless reporting requirements. We, nevertheless, have several commendations

60.482(a)(4) - Liquid Leaks

This paragraph defines liquid dripping from a pump seal as a leak. However, the barrier fluid could be water so there would be no reason to repair a seal operated per 60.482(a)(3)(i) where the barrier fluid pressure is higher than the pump pressure so long as this higher pressure is maintained. We recommend that this paragraph be reworded to say:

"Each pump shall be checked by visual inspection each calendar week for indications of liquids dripping from the pump seal. If indications of liquids dripping from the pump are seen, the vapor emissions shall be monitored by the methods specified in 60.485. A vapor concentration greater than 200 ppm above background shall constitute a leak."

560.482(a)(3)(ii) and (a)(7) - "residence time."

In our review of this section we noticed an inconsistency between the proposed residence time and the technical data on residence time set forth at page 4-18 of the technical support document. See VOC Fugitive Emissions in Synthetic Organic Chemicals Manufacturing Industry - Background Information for Proposed Standards, EPA-450/3-80-033a, at 4-18 (November 1980). An appropriate modification of this requirement in the final regulations is necessary

special order and take up to one year (for delivery), and/or unforeseen manufacturers and/or delivery delays (e.g., strikes, fires, raw material delays in delivery). Any one or a combination of the above scenarios would result in the necessary replacement part(s) not be available until after the next scheduled shutdown.

Since the proposed regulations would make continued operation after such a shutdown a violation of the Clean Air Act, we strongly recommend that a limited extension provision be incorporated by EPA into the regulations. We envision placing the burden of requesting such a request upon industry by requiring a formal submittal to EPA in which the source would have to justify the need for the further delay in repair and the projected time frame for achieving compliance. We recommend that §60.482(h) be amended to include the following regulatory language:

"Delay of repair will be allowed beyond a process unit shutdown only where and for the period of time a source demonstrates to the satisfaction of the Regional Administrator or delegatee that repair of a leak by replacing physical equipment by replacing physical equipment exceeded the normal stock of spare parts and cannot be delivered until after the next shutdown, a special order of a part is required and cannot be delivered until after the next shutdown, and/or because of unforeseen manufacturers and/or delivery delays, the replacement parts cannot be delivered until after the next shutdown."

The consequences of not including such a provision in the final regulations would result in unanticipated and costly continuances of a shutdown until the repair parts are obtained, or in the exposure

which would further clarify the regulations and more accurately reflect real world operations.

First, we would recommend a definition of what situations qualify as technically infeasible in order to be accorded an extension after the initial 15 day compliance period. Such a clarification would minimize uncertainties and would reduce any unwarranted enforcement proceedings resulting where such an ambiguity in the regulations. Accordingly, we recommend that §60.482(h) be revised to include a definition of technical infeasibility, as follows:

"For purposes of §60.482(h), technically infeasible shall mean where a repair within 15 days of leak detection would constitute an unsafe practice, could result in premature total process failure, or could cause an unscheduled complete or partial process until shutdown."

The second part of our recommendation on delayed compliance concerns the agency requirement that all repairs may not be delayed under any circumstances beyond a process unit shutdown. We concur that many

if the remaining delayed repair actions will be remedied during a shutdown where repair actions can not be technically or safely be conducted while the process unit is in operation. As the Agency is aware, most scheduled shutdowns are on an annual basis or based upon operating performance of the process unit. As a result, there may be some limited instances where replacement of leaking equipment may not be available until after the shutdown is completed. Such instances include (but are not all inclusive) abnormal near term demands for replacement parts that exceed the quantity of replacement parts that are normally maintained in stock and can not be replaced on short notice, the replacement parts/equipment are not off the shelf items and require long lead time for delivery (i.e., some pumps require

the process unit would be greater than the missions from the fugitive emissions source(s)."

We believe such a revision would remedy an unnecessarily narrow and environmentally counterproductive requirement.

\$60.482(b) - Compressor Standards.

As a general comment, the comments, issues, and recommendations we raised on pump standards are generally equally applicable to compressors. We do want to point out one inconsistency in the compressor standards which we believe should be clarified. In \$60.482(b)(1) and (3) we are happy to note that the Agency only requires a seal system with certain characteristics be used for all compressors. This requirement would be consistent with our comment on \$60.482(a)(1) and (3) dealing with pumps, in which we objected to the Agency's requiring dual mechanical seals and not providing the necessary flexibility with a dual seal system requirement. The inconsistency exists because the Agency at \$60.482(b)(4) then reverts to referring to dual mechanical seal systems.

Our substantive comments on \$60.482(b)(3)(ii) and (b) are reflected in our comments on \$60.482(a)(3)(ii) and (a)(2) above.

Our substantive comments on \$60.482(b)(5) and its interrelationship with \$60.482(h) are reflected in our comments on \$60.482(a)(6) above.

Finally, our substantive comments on \$60.482(b)(8) are reflected in our comments on \$60.482(a)(9) above.

\$60.482(c)(5) - safety/relief valves in gas/vapor service.

As proposed, the section requires each safety/relief valve to return to emitting less than 200ppm above background after an emergency pressure release no later than five calendar days after each episode of pressure release. As proposed the regulation leaves a tremendous loophole which had to be an oversight. If a process unit is down five days after the release, it by definition will be in compliance.

t significant criminal and civil penalties for resuming operation without repairing all leaks. We would consider it an arbitrary and capricious action of the Administrator to not provide such a remedy where the source has acted in good faith to repair all remaining leaks at the next scheduled shutdown, but solely because of uncontrollable events the necessary repair parts are not available.

§60.482(a)(9) - "Operation of Control Systems."

This provision essentially requires that all existing proposed fugitive emission control systems be operated at all times VOC emissions may occur. We are concerned that a conservative and narrow reading of this provision will essentially preclude a process unit operation where expected or unexpected maintenance of the control system is required, or an emergency requires the control system to go down for repairs. It makes little sense to require the entire process unit to shutdown where the control system has to go out of service for a short period of time to conduct maintenance and/or correct an emergency condition. In fact the start-up and shutdown of the process unit in most instances will probably result in greater emissions of VOC than if the process unit continued operation for the short period of time until the emission control system is back on line.

We recommend that this provision be modified to essentially allow a by-pass of VOC emissions where the control systems must be taken out of service for maintenance or an emergency only where the net VOC emissions that will be bypassed would not exceed the excess emissions that would result from a shutdown and start-up of the process unit. We recommend that §60.482(a)(9) be revised to added a second sentence, as follows:

"A source, however, may bypass the applicable control device set forth in §60.482(a)(3)(ii) and (iii) where emissions from an associated shutdown and startup of

§60.482(d)(2) b rev: id, as follows:

"(2) Each closed purge system as required by §60.482(d)(1) shall return the purged process fluid directly to the process line, or shall collect the purged process fluid for recycle or disposal by means of a closed vent system."

The technical support document does not support the proposed regulations. Unless a modification is made, the Administrators actions must be characterized as arbitrary and capricious.

§60.482(f)(2) - "definition of valve leak"

The EPA has proposed 10,000 ppmv as the definition of a leak. In addition to being the same action level as set forth in the refinery CTG, we understand from a July 17, 1980, EPA meeting with the TCC that this particular level was also chosen because it is the top of the scale on the Century Volatile Organic Analyzer. Apparently EPA felt 10,000 ppmv would make compliance easier for the chemical industry. We have some significant disagreements with these underlying assumptions. We believe a higher trigger level would achieve essentially the same control with much improved maintenance efficiency.

The scale on the Century GC is a minor consideration. Readings higher than 10,000 can be obtained readily with a dilution apparatus. In addition, we are confident that equipment manufacturers will be able to supply instruments with direct reading scales to whatever level we require.

As the EPA has correctly pointed out, most of the leakage comes from only a few valves and the problem is to locate and repair these. Based on the refinery data, about 98% of the emissions from valves in gas/vapor service will be from those having leak concentrations greater than 10,000 ppmv. Similarly, about 97% of the emissions will come from valves with screening values above 20,000 ppmv (Fig. 4-7A, EPA 600/2-79-044, "Emission Factors and Frequency of Leak Occurrence For Fittings in Refinery Process Units"). In a previous letter to

We assume EPA means five calendar days for resumption of normal operations after each episode of pressure release.

We want to ~~comment~~ the Agency for establishing a performance standard for safety/relief valves in gas/vapor service rather than specifying inflexible design standards. We would encourage the Agency to rethink the proposed pump and compressor standards to establish a performance standard for pumps and compressors (i.e., 10,000ppm). It is our view that a performance standard is more a simplistic regulatory program to implement and provides necessary flexibility for sources to install the most cost-efficient and effective emission controls and process systems.

\$60.482(d)(2) - sampling systems.

As proposed the regulation limits the means of disposing of process emissions. The proposal provides the option of returning the fluid directly to the process line, or in the alternative, collecting the purged process fluid for recycle or disposal without VOC emissions to the atmosphere. This requirement amounts to a zero emissions requirement. As a fundamental concept the closed loop sampling system may be inappropriate or technically infeasible (i.e., low pressure process or tankage, safety requirements). Accordingly, this would require a collection system be used with no emission allowed. We note that no support for this premise is provided in the Agency's technical support document (see 4-22 to 23). In fact, the support document mentions that such fluids could be directed to a control device such as a properly designed flare.

In light of the lack of technical support for the proposed regulation, we recommend that the Agency include the use of closed vent systems to minimize emissions from sampling systems. We recommend that

DO 067907
CONFIDENTIAL

YZ0028475

\$60.482(f)(3) - "monit ring frequency"

The proposal essentially requires that a monit ring program for valves be on a monthly basis for leakers and quarterly basis for non-leakers. We strongly endorse this proposal and caution against treating to mandating monthly monitoring.

One rationale the Agency might consider for requiring monthly monitoring is a reliance on refinery fugitive emissions data where the Agency ultimately required monthly monitoring.

The leak frequency data developed by EPA for the chemical industry are NOT similar to the refining data as EPA indicates on page 1141 of the proposal. The differences are summarized, as follows:

Source Type	Difference in leak frequency between SOCFI and refining data.
Valves	
*Gas service	Similar
*Light liquid service	SOCFI 50% of refining
*Heavy liquid service	Similar
Pumps	
*Light liquid	SOCFI 33% of refining
*Heavy liquid	Similar
Compressors	SOCFI 72% of refining
Relief Valves	SOCFI 74% of refining
Process Drains	Similar
Flanges	Higher

(See Attachment B & C for greater detail and discussion on this issue.)

The above differences do not account for the fact that the chemical industry studies were conducted using a Century OVA-108 instrument calibrated on methane while the refining studies were conducted using a Bacharach TLV instrument calibrated on hexane. Studies by Exxon Chemical (see Attachment D) on both instruments using both calibration gases show that 29 percent more leaks are found using the

the Agency, (see Attachment A) the TCC has shown that using a 20,000 ppmv action level versus 10,000 results in only 1% more emissions but reduces maintenance costs by 30%. This factor is of major significance since Section 111 requires the Administrator to take into consideration the cost of achieving continuous emission reductions.

In §60.482⁽⁵⁾(a)(4)(ii) methane at 10,000 ppmv is specified as the calibration gas. This requirement differs from the refinery data on which most of the technical support is based where hexane was used for this purpose. A study of the relative response of various gases with respect to methane and hexane indicates that a methane calibration will, in effect, lower the trigger point to about 8,000 ppm with the Century GC and even lower with the Bacharach TLV meter. This means more maintenance effort will be spent on valves with inconsequential leak rates.

Recent data (Problem-Oriented Report, "Frequency of Leak Occurrence for fittings in Synthetic Organic Chemical Plant Process Units", EPA, Sept. 1980, DCN 80-231-372-05-35, Data Listing For EPA Project #68-03-2776, Radian Corporation, December 19, 1980) from EPA's studies on leak occurrence and recurrence in the SOCOMI show a wide variability in repeat screening values for the same source. For example in Figure 4-3 of the Problem-Oriented Report, on the second day, values of approximately 2000, 6000 and 15000 were obtained from repeat measurements on the same valve. It is important that maintenance efforts be spent on the large leakers and not on the small ones since some data indicate that attempts to repair these only made matters worse. Thus the trigger point should be set high enough to insure isolating only the bad leakers. For these reasons - maintenance efficiency, the effect of methane calibration, and measurement variability, we again recommend that a leak be defined at §60.482(f)(2) as 20,000 ppmv or greater.

DO 067909
CONFIDENTIAL

YZ0028477

TCC recommends using a linear 1 k recurrence rate with time in the absence of data. Second the assumption that all the source types will have a uniform recurrence rate (20% per year) is not a logical assumption nor is it supported by the record. In the absence of data, a more logical assumption is that recurrence will vary in proportion to occurrence.

EPA, given the lack of data on valve leak recurrence and occurrence with time, has structured a monitoring program for valves as gas/vapor and light liquid service which calls for monthly monitoring for leakers and quarterly monitoring for non-leakers. EPA states that straight monthly monitoring for all valves may be required if recurrence is found to be important. We submit that the existing chemical industry data shows initial occurrence to be less (by 50% in the case of light liquid valves) than the refinery data. Because of this difference, we recommend that EPA require the monthly monitoring scheme only for those owner operators desiring to show equivalence demonstration.

Since EPA has acknowledged that limited data are available on occurrence/recurrence, we submit that EPA can only reserve the right to require more frequent monitoring when the data are available from those owner operators desiring equivalence.

§60.482(f)(4) - delayed compliance.

Our substantive comments on this section and its interrelationship with §60.482(h) are reflected in our comments on §60.482(a)(6) above.

§60.482(f)(7) - Accessibility Exclusion.

~~As we reviewed the proposed regulations, we identified an area dealing primarily with modified sources that will be subject to the new source performance standards, that EPA apparently has overlooked in the proposed regulations. As the Agency is well aware, at older facilities many valves are not routinely accessible because of safety~~

Century calibrated on methane as compared to the Bacharach calibrated on hexane. Thus the SOCOMI Data is probably even less than the refining data as shown above.

Since the above data show initial leak occurrence frequency within the chemical industry to be less than the refining sector, we feel that EPA should require only true quarterly monitoring. We are of the opinion that the lower leak occurrence frequency within SOCOMI will more than offset the, admittedly, unknown effects of leak recurrence. EPA has offered as a reason for possibly requiring monthly monitoring to be the potential importance of leak recurrence between valve monitoring intervals.

This analysis was performed without the benefit of review of EPA's chemical industry valve maintenance study which may provide further information on the importance of valve leak recurrence.

The above conclusions are discussed in further detail below and in the attachments.

The EPA continues to base occurrence and recurrence leak rate assumptions on Table 4-2 from the final technical support document (copy attached as Attachment E) which is the same as taken from the draft technical support document. The Texas Chemical Council (TCC) commented on the issue of occurrence/recurrence in comments submitted to EPA in June of 1980. These comments have not been addressed by EPA and cannot be ignored. We wish to emphasize the points raised in TCC's comments on this issue are still valid. In addition to TCC's earlier comments, we offer the following additional comments.

First, EPA's assumption of non linear leak recurrence with time is not based on any data but rather an "engineering judgment". The assumption that twice as many leaks will be found annually as compared to quarterly and twice as many leaks will be found quarterly as compared to monthly is simply not logical and is not supported by the record.

As the Agency is well aware, in existing facilities many valves are not routinely accessible because of elevation or because access to the valve bonnet is restricted, etc. Most, if not all of these, can be eliminated in an entirely new plant. But they become a problem in an older plant that becomes subject to this regulation because of modification.

To correct these problems, we propose valves that are inaccessible for safety reasons and that valves that are inaccessible for other reasons in modified sources be excluded from the requirement of 60.482(f)(1)-(6)

but subject to the new 60.482(f)(7)-(8). Accordingly, we recommend that the new 60.482(f)(7) and 60.482(f)(8) be added as follows:

"(7)(i) An owner or operator of a new or modified source subject to the requirements of 60.482(f)(1)-(6) may for valves that are routinely inaccessible for safety reasons monitor each inaccessible valve for leaks after a process unit overhaul prior to startup by pressuring with nitrogen to the system process pressure or 100 psig, whichever is less, and checking with a soap solution for bubbles, or other equivalent test method pursuant to 60.484."

"(ii) When a leak is detected, it shall be repaired as soon as practicable, but no later than the next scheduled shutdown, or consistent with 60.482(h)."

"(iii) For purposes of 483 or 484, inaccessible valves shall not be included."

DO 067912
CONFIDENTIAL

YZ0028480

considerations.

We propose that valves, at modified facilities subject to these requirements, that are inaccessible for safety reasons be excluded from the requirements of §560.482(f)(1)-(6) but subject to a new §60.482(f)(7). This new provision would only apply to modified sources and not apply to new facilities. Accordingly, we recommend that a new §60.482(f)(7) be added, as follows:

"(i) An owner or operator of a modified source subject to the requirements of §560.482(f)(1)-(6), may for valves, that are routinely inaccessible for safety reasons, monitor each inaccessible valve for leaks after a process unit overhaul prior to start-up by pressuring with nitrogen the system process pressure, or 100 psi, whichever is less, and checking with a soap solution for bubbles, or other equivalent test methods pursuant to §60.484."

"(ii) When a leak is detected, it shall be repaired as soon as practicable, but no later than the next scheduled shutdown or consistent with §60.482(h).

"(iii) For purposes of §§483 or 484, inaccessible valves shall not be included."

As we reviewed the proposed regulations, we identified an area which the EPA has apparently overlooked in the proposed regulations. This area is inaccessible valves. These fall into two general categories, valves inaccessible for safety reasons and valves inaccessible because of elevation and/or configuration.

Certain chemical processes are carried out at such extreme conditions of temperature or pressure, or the chemicals themselves are so unstable or hazardous that the operation is done behind barricades and the like, and, for safety reasons, personnel are not allowed in these areas while the unit is in operation.

DO 067913
CONFIDENTIAL

YZ0028481

emissions. If properly implemented we believe this concept will provide assurance the necessary flexibility to adopt a control program that is the most cost-effective for a specific site. In many instances a company will now be able to either implement the valve standards contained in §60.482(f) or adopt a alternative percentage valve approach that more appropriately can be implemented at a site. We recommend that the Agency retain this concept and needed flexibility in the final regulations.

Although we wholeheartedly support this concept, we have a few comments and questions, that need clarification by EPA, in order to improve upon the proposed alternative standard.

One matter we believe needs clarification is the criteria the Administrator will use in either approving or disapproving the request for an alternative standard as set forth in §60.483(a)(5). We are unclear if the criteria are set forth in only §§60.483(a)(1) and (2), or in §§60.483(a)(1)-(4). Or in the alternative, are there other conditions and criteria not set forth in the proposal that the Administrator might consider/use in approving or disapproving the use of the alternative standard. We believe the Agency has a duty to clearly set out all the criteria it proposes to consider, the basis for each criteria, and limit approval/disapproval activities to this list of criteria.

In our discussion above concerning accessibility of valves, we indicated that for certain ^{NEW AND} modified facilities subject to these requirements, it was infeasible for safety reasons to subject all the valves to the provisions of §60.482(f). Should a facility seek an alternative standard pursuant to §60.483(a), the accessibility of certain valves would create a problem in calculating a meaningful allowable percentage of leaking valves. We recommend that these valves not be included as part of the alternative program and be

"(B)(i) ~~An owner or operator~~ of a modified source subject to the requirements of 60.482(f)(1)-(6) may for valves that are routinely inaccessible because of elevation or configuration monitor each inaccessible valve annually using test methods pursuant to 60.485 or a soap solution for bubbles."

"(ii) When a leak is detected, it shall be repaired as soon as practicable, but no later than the next scheduled shutdown, or consistent with 60.482(h)."

"(iii) For purposes of 483 or 484, inaccessible valves shall not be included."

§60.482(g)(2) - delayed compliance.

Our substantive comments on this section and its interrelationship with §60.482(h) are reflected in our comments on §60.482(a)(6) above.

§60.482(h) - delay of repair

Our substantive comments on this section are set forth in detail in our comments on §60.482(a)(6) above.

§60.483 - alternative standards - percentage of valves leaking

Q) The proposed alternative standard for valves in gas/vapor and valves in light liquid service establishes an allowable percentage of valves leaking approach for ascertaining compliance. As we have recommended in earlier submissions to the Agency, the chemical industry wholeheartedly supports the concept of using allowable percentages of valves leaking as a vehicle for regulating fugitive

New §60.483(a)(7) and (b)(5) should be added, as follows:

"An owner or operator may terminate complying with an alternate standard, by writing the Administrator informing of this decision and immediately complying with the requirements of §60.482(f)."

~~§60.483(b) - Alternate Work Practices~~

Although we believe §60.483(b) is intended to provide industry with the flexibility they need to carry out this program most efficiently the present wording of some provisions will greatly inhibit its use. In §60.483(b)(3) the request to implement an optional work practice program must show a percentage of valves leaking that is equal to or less than that under the §60.482(f) program. Taken literally this would rule out any statistical or any probability based inspection programs. These alternatives are mathematically exact and the uncertainty or tolerance in their performance levels is explicitly stated. Thus it is not possible to achieve equivalence at all times with 100% certainty. We recommend that a sentence be added at the end of §60.483(b)(3) stating - "Statistical and/or probability based monitoring programs shall be soundly based mathematically and shall show equivalence to the required program within a plus or minus 10% variation".

This modification does not either loosen or tighten the requirement. It assures, however, that "on-the-average" the alternate work practice will equal the §60.482(f) standards although individual process units may be over or under the standard by a little bit at any particular time. It is worth noting that the percentage leaking under the §60.483(a) program is not truly an exact number either. It is obtained by averaging a specific six months data base so that for any given month, a process unit might or might not meet the standard. In fact, since it is an arithmetic average, the percentage leakers under the required program will exceed the standard half the time.

DO 067916
CONFIDENTIAL

YZ0028484

regulated pursuant to our proposed §60.482(f)(7). This solution would require a modified source applying for an alternative standard to clearly identify in the §60.483(a)(2)(iii) data those valves that will remain subject to §60.482(f)(7).

In determining compliance with the proposed §60.482 requirements, EPA clearly sets out in §60.482(i) the standard to be used in determining compliance. No similar provision exists for either §60.483(a) or (b). We are uncertain what, if anything, triggers a violation of the Clean Air Act. Or does the Agency mean, if you fail the test set forth in §60.483(a)(4), the provisions of proposed §60.482 are reinstituted? In order to make §60.483 enforceable, we recommend that a provision similar to §60.482(i) be added that sets forth the vehicle for the regulatory agencies measuring compliance with §60.483, as follows:

"(c) Compliance with §60.483(a) in this subpart shall be determined by the performance test set forth in §60.483(a)(4). Compliance with §60.483(b) in this subpart shall be determined by review of records and inspection."

Another area of uncertainty concerns a source's ability to formally switch from an approved alternative standard back to the requirements set forth in §60.482(f). For a variety of reasons, at a point in time it may no longer be cost-effective for a source to comply with a §60.483 alternative standard. We recommend that EPA accord these sources the flexibility and ability to switch back to the §60.482(f) valve standards, after notifying the Administrator in writing that they no longer wish to be subject to an approved alternative standard, and will comply with the §60.482(f) standards.

percentage of valves leaking under §60.483(a)(3)".

The advantages of the quality control approach advocated here is that: (1) greater emission reductions will be realized industry-wide because there is an incentive to do so, (2) the monitoring burden will be lessened on low leak plants and increased on high leak ones, and (3) well defined rules on what can and cannot be done will be available to the owner at the design stage.

60.483(c) - Good Performance Incentive

Although we believe 60.483(b) is intended to provide industry with the flexibility they need to carry out this program most efficiently, the present wording of some provisions will greatly inhibit its use. In 60.483(b)(3) optional work practice programs must show a percentage of valves leaking that is equal to or less than that under the 60.482(f) program. Taken literally this would rule out any statistical or probability based inspection system in new plants if they provide the best leak prevention options in their original design. The time to assure a low-leakage plant is when it is being designed and built. Quality control experience shows that quality must be designed into a product; it cannot be inspected in.

But the owner needs some incentive to put in more expensive high performance equipment. In establishing a fixed-period, 100% monitoring program the EPA has provided no incentive to reduce emissions by equipment design since the better a plant is controlled and engineered initially, the less chance there is to reduce monitoring through an alternate work practice. In fact, the required monitoring program does not directly address the real problem of preventing leakage which can be drastically affected by valve and packing selection. This is unfortunate. The regulation should encourage the owner to put in the best leak prevention options available.

DO 067918
CONFIDENTIAL

Quality control experience shows that quality must be designed into a product; it cannot be inspected in. Thus the time to assure a low leakage plant is when it is being designed and built. But the owner needs some incentive to put in more expensive high performance equipment. In establishing a fixed-period, 100 percent monitoring program, the EPA has provided no incentive to reduce emissions by equipment design since the better a plant is controlled and engineered initially, the less chance there is to reduce monitoring through an alternate work practice. In fact, the required monitoring program does not directly address the real problem of preventing leakage which can be drastically affected by valve and packing selection. What is needed is some "good performance level" which, if designed to and met, would result in reduced monitoring requirements.

Snee and Kittleman of E. I. du Pont de Nemours & Company presented a paper describing statistical inspection plans for monitoring fugitive emissions from leaking valves on April 16-17, 1980, to the National Air Pollution Control Techniques Advisory Committee and then followed this up with a second paper (Letter from T. A. Kittleman (Du Pont) to Glynda E. Willins (Radian Corporation), November 13, 1980) on choosing a good performance level. These papers provide a sound technical base for both statistical inspection plans and performance levels. They show that the required inspection program results in essentially a two percent of valves leaking based on the technical support document model plant examples. It seems reasonable then to allow operators to adopt inspection plans that will assure a two percent leakage rate within a plus or minus ten percent variation.

We recommend that §60.483(b)(3) have added to it a second paragraph stating - "(ii) Owners or operators may commit to an inspection program that will assure a two percent of valves leaking within a ten percent plus or minus variation without determining the

DO 067919
CONFIDENTIAL

We recommend that the EPA include a third alternative as follows:

"60.483(c) Valves in gas/vapor and valves in light liquid service - good performance incentive.

- (1) Owners or operators may commit to an inspection plan which allows annual inspection after not more than 2% leaks are detected in five successive quarters.
- (2) Inspection requirements under 60.482(f) (1) and (3) are reinstated whenever the 2% good performance level is exceeded.
- (3) All leaks found will be repaired and inspected monthly until repair effectiveness is demonstrated in two successive months.
- (4) Any other inspection plan will be allowed by the Administrator if it can be shown to be equivalent to 60.483 (c) (1), (2), and (3)."

The advantages of the quality control approach advocated here is that:

- (1) greater emission reductions will be realized industry-wide because there is an incentive to do so, (2) the monitoring burden will be lessened on low-leak plants and increased on high-leak ones, and (3) well defined rules on what can and cannot be done will be available to the owner at the design stage.

DO 067920
CONFIDENTIAL

YZ0028488

A major incentive would be less inspection for low-leak plants. This makes sense; low-leak plants should require less inspection, high-leak plants more. Quality control inspection plans provide this option while at the same time including a check for deterioration in performance which, when detected, results in the requirement to return to more frequent inspection. But before these plans can be used some means of rewarding, rather than penalizing, those who build low-leak plants must be provided. What is needed is some "good performance level" which, if designed to and met, would result in reduced monitoring requirements.

Snee and Kittleman of Du Pont presented a paper describing statistical inspection plans for monitoring fugitive emissions from leaking valves on April 16-17, 1980 to the National Air Pollution Control Technique Advisory Committee and then followed this up with a second paper (Letter from T. A. Kittleman, Du Pont, to Glynda E. Willins, Radian Corporation, November 13, 1980) on choosing a good performance level. These papers provide a sound technical base for both statistical inspection plans and performance levels. They show that a good performance level of 2% leaks is equivalent to EPA's BID basis used to estimate the leak reduction effectiveness of EPA's proposed regulation. It seems reasonable then to allow operators to adopt inspection plans that will assure a 2% leakage rate will not be exceeded.

In their papers Snee and Kittleman illustrated the use of a skip-period monitoring concept with a plan which would be widely used for monitoring fugitive emissions. Skip-period inspection plans have been used to inspect the quality of manufactured products for more than 25 years. These plans are widely used throughout industry and have a solid mathematical and statistical basis. Their proposed plan calls for five successive quarters of good performance to be followed by yearly inspection as long as good performance is continued to be demonstrated. If the specified level of good performance is exceeded, then the plant must return to quarterly inspection. Any leaks found must be repaired and monitored until the repair effectiveness has been demonstrated for two consecutive months. The proposed regulation should be amended to provide for the use of this, or any equivalent, alternative.

DO 067921
CONFIDENTIAL

YZ0028489

a means of obtaining an equivalency determination of alternative test methods and procedures. We recommend that a new §60.485(e) be added that authorizes seeking equivalency determinations of test methods and procedures and sets forth the criteria the Agency will use in evaluating an equivalency application. (The procedure would mirror that set forth in §60.484 for equivalence of alternative means of emission limitation.

§60.486(c) - Recordkeeping Requirements

This subsection requires that various technical data dealing with detailed schematics, structural designs, and design specifications shall be kept in a log, that is readily accessible, ostensibly at the site. We have no reservations about making this data/information available upon a reasonable request of EPA. We do, however, have reservations about being required to collect all this data and house it in one location. As a matter of corporate operations much of this information/data are not always kept together, nor are they needed to be kept together for purposes of assuring and/or demonstrating compliance with the fugitive emission standards.

As the Agency is well aware, the Agency under Section 114 has the authority to require a source to "establish and maintain such records" in order to determine whether a person is complying with any standard under Section 111, or carrying out any provision of the Act. The Agency has not demonstrated how the required reports are necessary to ascertain and/or carry out Section 111 of the Clean Air Act. Further, the Agency has not demonstrated why all the proposed information must be kept in a readily accessible location when industry indicates it will make such data available upon request by EPA. We believe the provisions in §60.486(c) as proposed exceed the authority vested under Section 114 to the Administrator, and imposes an arbitrary and capricious requirement unless modified to reflect industry's willingness

DO 067922
CONFIDENTIAL

YZ0028490

§60.484(b)(1) - Equivalence Determination

As proposed §60.484(b)(1), limits applying for an equivalence determination for an alternative means of emission limitations to the owner or operator of a facility. We are concerned that this artificial limitation may limit the incentive for or ability to use innovative technology. We believe that the manufacturers and/or vendors of new and/or innovative technology should also be authorized to apply for an equivalence determination. In a real world context few companies are going to purchase such a system unless the manufacturer and/or vendor will state that EPA has essentially approved the system. Accordingly, if EPA truly desires to encourage the use of innovative technology, it should authorize the manufacturers and/or vendors to also request equivalency determinations. We recommend that the first line of §60.484(b)(1) be modified, as follows:

"(1) Each facility owner or operator, a manufacturer, or a vendor applying . . ."

§60.485 - Test Methods and Procedures

The test methods and procedures set forth in the proposed regulations are essentially based on the state of technology as of this date. We are concerned that the regulations do not provide the necessary flexibility to approve in the future the use of new instruments that may use different calibration systems which provide equivalent or more accurate results. We believe the regulations must provide

DO 067923
CONFIDENTIAL

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

217

218

219

220

221

222

223

224

225

226

227

228

229

230

231

232

233

234

235

236

237

238

239

240

241

242

243

244

245

246

247

248

249

250

251

252

253

254

255

256

257

258

259

260

261

262

263

264

265

266

267

268

269

270

271

272

273

274

275

276

277

278

279

280

281

282

283

284

285

286

287

288

289

290

291

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

367

368

369

370

371

372

373

374

375

376

377

378

379

380

381

382

383

384

385

386

387

388

389

390

391

392

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

441

442

443

444

445

446

447

448

449

450

451

452

453

454

455

456

457

458

459

460

461

462

463

464

465

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

491

492

493

494

495

496

497

498

499

500

501

502

503

504

505

506

507

508

509

510

511

512

513

514

515

516

517

518

519

520

521

522

523

524

525

526

527

528

529

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

573

574

575

576

577

578

579

580

581

582

583

584

585

586

587

588

589

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

615

616

617

618

619

620

621

622

623

624

625

626

627

628

629

630

631

632

633

634

635

636

637

638

639

640

641

642

643

644

645

646

647

648

649

650

651

652

653

654

655

656

657

658

659

660

661

662

663

664

665

666

667

668

669

670

671

672

673

674

675

676

677

678

679

680

681

682

683

684

685

686

687

688

689

690

691

692

693

694

695

696

697

698

699

700

701

702

703

704

705

706

707

708

709

710

711

712

713

714

715

716

717

718

719

720

721

722

723

724

725

726

727

728

729

730

731

732

733

734

735

736

737

738

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

764

765

766

767

768

769

770

771

772

773

774

775

776

777

778

779

780

781

782

783

784

785

786

787

788

789

790

791

792

793

794

795

796

797

798

799

800

801

802

803

804

805

806

807

808

809

810

811

812

813

814

815

816

817

818

819

820

821

822

823

824

825

826

827

828

829

830

831

832

833

834

835

836

837

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

863

864

865

866

867

868

869

870

871

872

873

874

875

876

877

878

879

880

881

882

883

884

885

886

887

888

889

890

891

892

893

894

895

896

897

898

899

900

901

902

903

904

905

906

907

908

909

910

911

912

913

914

915

916

917

918

919

920

921

922

923

924

925

926

927

928

929

930

931

932

933

934

935

936

937

938

939

940

941

942

943

944

945

946

947

948

949

950

951

952

953

954

955

956

957

958

959

960

961

962

963

964

965

966

967

968

969

970

971

972

973

974

975

976

977

978

979

980

981

982

983

984

985

986

987

988

989

990

991

992

993

994

995

996

997

998

999

1000

data for EPA should EPA want this data, they can either request it in writing directly from the source or review it at the facility. As the Agency is well aware, ease of enforcement is not a legitimate grounds for requesting the reporting of data/information unless it is also necessary for purposes of determining compliance. As will be noted below, this data/information also duplicates data/information that must be reported under §60.487(b). The duplication of data/information should be avoided by EPA as much as possible. We recommend that §60.487(a) be deleted.

As to the specific information required under §60.487(b) we have the following comments. As a general point, we are only commenting on the specific information requested on in §60.487(b) since the Agency has indicated that the forms and data requested therein are not requirements of the proposed standards. If, however, the Agency changes its mind on this issue, we reserve our right to subsequently submit comments on the example forms on pages 1158 and 1159.

The leakless valve data requested in §60.487(b)(2) is irrelevant for purposes of determining compliance with §60.482(f)(6). It is irrelevant the number of leakless seals that exist at a specific process unit. Accordingly, §60.487(b)(2) should be deleted.

The data requested in §60.487(b)(4) is irrelevant for purposes of determining compliance with §60.482(f). Compliance can be determined adequately by evaluating the data submitted as required by §§60.487(B)(3)(5) and (6). Accordingly, §60.487(b)(4) should be deleted.

In both §60.487(b)(7) and (8) the Agency has not requested the critical point of whether or not the pump/compressor leak was repaired similar to §§60.487(b)(5) and (6). If the Agency wants truly meaningful data it should consider adding a new provision that would require this data.

(8) Reasons for non-repair of pumps and/or compressors within 15 days as required in §§60.482(a)(6) and/or (b)(5).

(9) Number of pumps, compressors, and/or valves not repaired pursuant to the delayed compliance time schedule of §60.482(h).

(10) Statement signed by the owner or operator stating whether all provisions of 40 CFR 60 Subpart VV had been fulfilled during the reporting quarter.

(b) The provisions of §60.8(d) do not apply to affected facilities subject to the provisions of this subpart.

(c) In the first report submitted as required in §§60.487(a), the report shall include a reporting schedule stating the months that quarterly reports shall be submitted. Subsequent reports shall be submitted according to that schedule unless a revised schedule has been submitted in a previous quarterly report.

Conclusion

Although the Agency has made substantial progress in addressing the numerous issues the chemical industry has raised on earlier drafts of the proposed fugitive emissions NSPS, we still have several reservations with the subject proposal. We still have reservations as to the inflexibility of several of the proposed requirements and it still is procedurally more burdensome than necessary for sources to expeditiously and cost-effectively identify and repair fugitive emissions. In this regard, CMA has presented several recommendations in these comments which we believe would further clarify and make more flexible the fugitive emissions NSPS program. We urge EPA to give serious consideration to the CMA proposals and modify the proposed regulations to reflect the concerns expressed herein.

As we discussed earlier, delayed compliance may in some instances occur after the fifteen day period after leak detection (i.e., next scheduled shutdown) or in a few limited instances by necessity after the next scheduled shutdown (i.e., CMA recommended regulatory language for discretionary extensions after the next scheduled shutdown). In order for EPA to have meaningful data to accurately appraise a sources compliance status new provisions should be added to ascertain the number of pumps, compressors, and valves not repaired by the next scheduled shutdown, and the number of valves, pumps, and compressors not repaired consistent with a time schedule approved by the Regional Administrator after the next scheduled shutdown.

We recommend that §60.487(a) be revised, as follows:

§60.487 Reporting requirements.

Each Owner or operator subject to the provisions of this subpart shall comply with the following reporting requirements.

(a) Quarterly reports shall include the following information:

- (1) Process unit identification.
- (2) Number of valves for which leaks were detected by the monitoring method specified in §60.485(a) during each month of the reporting quarter.
- (3) Number of valves not repaired within 15 days as required in §60.482(f)(4).
- (4) Reasons for non-repair of valves within 15 days as required in §60.482(f)(4).
- (5) Number of pumps for which leaks were detected during the reporting quarters as specified in §60.482(a)(4) and (a)(5).
- (6) Number of compressors for which leaks were detected during the reporting quarter as specified in §60.482(b)(4).
- (7) Number of pumps and/or compressors not repaired within 15 days as required in §60.482(a)(6) and/or (b)(5).

DO 067927
CONFIDENTIAL

YZ0028495

Respectfully submitted,

Edmund B. Frost
General Counsel and
Vice President

Geraldine V. Cox, Ph. D.
David W. Carroll, Esquire
Janet S. Matey

Chemical Manufacturers
Association
2501 M Street, N.W.
Washington, D.C. 20037
(202) 887-1100

April 6, 1981

cc: [TO BE ADDED LATER]

DO 067928
CONFIDENTIAL

YZ0028496

long-term survival among patients with Stage III disease is 25 percent (two of eight). Among patients with Stage IV disease, 6 of 34 (18 percent) have survived overall; of the 23 patients with bone metastasis and bone marrow involvement at diagnosis — a group generally considered to have a particularly poor prognosis, 5 (22 percent) have survived. The survival of these five patients indicates that marrow "purging" may not always be needed.

There has been a price for survival — considerable treatment-related chronic toxicity. Six of the eight children have auditory injury affecting their hearing range³ and wear hearing aids. Five patients have reduced glomerular filtration rates,⁴ two of whom have chronic renal failure; one of them requires antihypertensive therapy. Apart from these handicaps, the eight children (now 6.3 to 12.4 years old; median, 8.2) are leading full and active lives, including normal school attendance.

This series is relatively small, but a comparable rate (71 percent) of response to this chemotherapeutic regimen plus surgery has been observed in a larger study by the European Neuroblastoma Study Group.⁵ Previous reports state or imply that no progress has been made over the past 10 years in treating advanced neuroblastoma and that the number of survivors who are more than one year old at diagnosis is negligible.^{6,7} We challenge these assertions. Our experience suggests that the median survival of patients in Stage III and IV has been extended. High-dose melphalan is probably an important component of this improved prognosis⁸; therefore, the long-term results at centers using more intensive "consolidation" regimens⁹⁻¹⁰ will be awaited with great interest. Rather than adopt a negative attitude, those treating children with neuroblastoma should energetically search for better induction and consolidation regimens so that response rates can be improved.

J. PRITCHARD, E. KIELY, D.W. ROGERS,
L. SPITZ, E.A. SHAFFORD, R. BAZZATON,
C. MULLER, AND V.M. WRIGHT
Hospital for Sick Children

London, WC1N 3JH,
United Kingdom

1. Evans AE, D'Angio GJ, Randolph J. A proposed staging for children with neuroblastoma. *Cancer* 1971; 27:374-8.
2. Shafford EA, Rogers DW, Pritchard J. Advanced neuroblastoma: improved response rate using a multiagent regimen (OPEC) including sequential cisplatin and VM-26. *J Clin Oncol* 1984; 2:742-7.
3. McIlaney VA, Thibadour G, Hayes FA, Green AA. Hearing loss in children receiving cisplatin chemotherapy. *J Pediatr* 1983; 102:314-7.
4. Womer RB, Pritchard J, Barrett TM. Renal toxicity of cisplatin in children. *J Pediatr* 1985; 106:559-63.
5. Pritchard J, Germond S, Jones D, de Kraker J, Love S. Is high dose melphalan (HDM) of value in treatment of advanced neuroblastoma (AN)? Preliminary results of a randomized trial by the European Neuroblastoma Study Group (ENSG). *Proc Am Soc Clin Oncol* 1986; 3:205, abstract.
6. Grafeldt J. Neuroblastoma. Hays DM, ed. In: *Pediatric surgical oncology*. Orlando, Fla.: Grune & Stratton, 1986; 63-85.
7. Vouts PA, de Kraker J, Burgers JMV. Tumours of the sympathetic nervous system: neuroblastoma, ganglioneuroma and pheochromocytoma. In: Vouts PA, Barrett A, Bloom HJG, Lemerle J, Neithardt MX, eds. *Cancer in children: clinical management*. 2nd ed. Berlin: Springer-Verlag, 1986; 238-51.
8. August CS, Serun FT, Koch PA, et al. Treatment of advanced neuroblastoma with supralesional chemotherapy, radiation, and allogeneic or autologous marrow reconstitution. *J Clin Oncol* 1984; 2:509-16.
9. Hartmann O, Kalifa C, Beaumont P, Bayle C, Benhamou E, Lemerle J. Treatment of advanced neuroblastoma with two consecutive high-dose chemotherapy regimens and autologous bone marrow transplantation. In: Evans AE, D'Angio GJ, Seeger RC, eds. *Advances in neuroblastoma research*. New York: Alan R. Liss, 1983:565-8.
10. Phillip T, Blom P, Phillip I, et al. Autologous bone marrow transplantation for very bad risk neuroblastoma. In: Evans AE, D'Angio GJ, Seeger RC, eds. *Advances in neuroblastoma research*. New York: Alan R. Liss, 1983:569-86.

AIDS AND RENAL FAILURE

To the Editor: Rao et al. observed accelerated wasting and early death in patients with the acquired immunodeficiency syndrome (AIDS) who required maintenance hemodialysis for therapy of end-stage renal disease (April 23 issue).¹ The course appears to be more rapid than has been observed in patients with AIDS who do not

have renal failure. This observation may indicate that patients with renal involvement have more extensive human immunodeficiency virus-related disease and therefore die sooner. However, it is also possible that hemodialysis accelerates the progression of AIDS. Normal immune stimulation of T helper cells may trigger replication of the AIDS virus.² Furthermore, patients receiving maintenance hemodialysis have an increased proportion of activated T cells in peripheral blood, as defined by expression of interleukin-2 receptors.³ Whether such activation of T cells reflects long-term exposure to blood transfusions, infectious agents, or dialysis membranes or tubing, or is a manifestation of the uremic state itself, is unknown. Intravenous drug use, present in a high proportion of the patients studied by Rao et al., would also be associated with chronic immune stimulation. It might be interesting to see whether patients on long-term ambulatory peritoneal dialysis have increases in immune activation of T lymphocytes comparable to the increases observed in patients on maintenance hemodialysis. If increased T-cell activation is more marked in maintenance hemodialysis than in other forms of therapy of end-stage renal disease, survival of patients with this disorder and AIDS could be enhanced by an alternative therapy (such as long-term ambulatory dialysis, if feasible).

ALAN WAMBERSTEIN, M.D.
CAROLYN KELLY, M.D.
University of Pennsylvania
School of Medicine

Philadelphia, PA 19104

1. Rao TKS, Friedman EA, Nicotri AD. The types of renal disease in the acquired immunodeficiency syndrome. *N Engl J Med* 1987; 316:1062-8.
2. Nabel G, Baltimore D. An inducible transcription factor activates expression of human immunodeficiency virus in T cells. *Nature* 1987; 326:711-3.
3. Chastoud L, Dugas B, Benarain A, et al. Presence of preactivated T cells in hemodialyzed patients: their possible role in altered immunity. *Proc Natl Acad Sci USA* 1986; 83:7457-61.

BENZENE AND LEUKEMIA

To the Editor: In the study on benzene and leukemia by Rinsky et al. (April 23 issue),¹ there were but nine cases of leukemia and four cases of myeloma. These are very small numbers on which to base conclusions, especially when the overall mortality has been as expected and the mortality due to malignant neoplasms has also been as expected.

Of special interest is the authors' Table 4, which lists the cases. Some had minuscule exposure, and one wonders what other malignant disease-causing agents they may have been exposed to during their lives. Of special interest is the fact that no employee first exposed after 1954 had leukemia or myeloma, even though hiring continued for 11 years and even though 7 of the 13 cases had the onset of disease within 20 years of first exposure. (Cases were followed through 1981, so there should have been some cases.) In the study, two subjects died within 3½ years of exposure.

Looking at the year of initial exposure of the 13 cases, one can see that 9 had first exposures before the end of World War II. One wonders about the measuring instruments in that situation.

Having spent some time studying childhood malignant disease more than 25 years ago, I am very sensitive to the tendency to observe clusters of cases sometimes living within short distances of each other. Statisticians have generally attributed these to chance, and there is no reason why that may not be true in the cases in this study.

MAX BADER, M.D., M.P.H.
Seattle, WA 98115
6536 29th Ave. NE

*Rinsky RA, Smith AB, Hornung R, et al. Benzene and leukemia: an epidemiologic risk assessment. *N Engl J Med* 1987; 316:1044-50.

To the Editor: The paper by Rinsky et al. on workers in rubber hydrochloride plants exposed to benzene reports a cohort study, a case-control study, and a risk assessment for leukemia in relation to benzene. Table 1, which uses data from that paper, indicates a discrepancy between the cohort and case-control studies. The case-

DO 067929
CONFIDENTIAL

YZ0027906

Table 1. Deaths from Leukemia, the Standardized Mortality Ratio (SMR), and the Predicted Odds Ratio, According to Cumulative Exposure to Benzene.

CUMULATIVE EXPOSURE (ppm-yr)	DEATHS FROM LEUKEMIA	OBSERVED SMR	PREDICTED ODDS RATIO*
0-40	2	1.1	1.3
40-200	2	3.2	4.5
200-400	2	11.9	43.8
>400	3	66	423

*From the risk-assessment model of Rinsky et al., using the midpoint of each exposure category (400 ppm-years for highest category).

control risk assessment predicts, in the higher-exposure categories, odds ratios much larger than the standardized mortality ratios observed in the cohort. A possible explanation for the discrepancy is that the exposure of the controls was much lower than that of all cohort members without disease. In support of this, it can be inferred from the paper that the mean cumulative levels of benzene exposure of the 1156 subjects without disease and the 90 controls were about 67 and 50 parts per million (ppm)-years, respectively.

It is reasonable to ask why the case-control study was done. A case-control study within a cohort is usually done to reduce the cost of determining the exposure of all cohort members without disease. However, this reason is not applicable here, since the exposure to benzene of all cohort members was known. Rinsky et al. offer several reasons for doing the case-control study, but all the objectives could have been met effectively by a cohort analysis of all the data.

The disparity between the mean exposure level of all cohort members without disease (67 ppm-years) and that of the 90 controls (50 ppm-years) requires explanation. It is probably not the result of selection due to matching, since this should have raised the level in the comparison series. The investigators may have reviewed the information on the benzene exposures of cases and controls, with the result that the average level of the controls, but not that of the cases, was lowered. If such a review explains why the control exposure levels were lowered by 26 percent, then the validity of the cohort study is questionable. Finally, if chance explains the difference between the cohort data and the case-control risk assessment, a risk assessment based on the entire cohort would be superior. Irrespective of the explanation, it would be appropriate to evaluate the data further. Although this might involve reevaluation of the benzene exposures of all cohort members, the results should clarify the relation between benzene and leukemia.

The Occupational Safety and Health Administration (OSHA) proposes to reduce the benzene standard of a 10 ppm time-weighted average to 1 ppm. A principal basis for this is the results of the rubber hydrochloride study. However, the magnitude of the dose-response relation in this cohort is uncertain. We, in a review supported in part by Texaco, Inc., and others have done risk assessments based on this study and estimate that exposure to 300 ppm-years of benzene would cause 50 to 80 excess leukemia deaths per 1000 workers so exposed.⁸ The risk assessment of Rinsky et al. predicts 250.

HARLAND AUSTIN, D.Sc.

ELIZABETH DELZELL, D.Sc.

PHILIP COLE, M.D., Dr.P.H.

University of Alabama at Birmingham

School of Public Health

Birmingham, AL 35294

*Austin H, Delzell E, Cole P. Benzene and leukemia: a review of the literature and a risk assessment. *Am J Epidemiol* (in press).

To the Editor: In his editorial on new scientific evidence and public health imperatives (April 23 issue),¹ Dr. Ashford stated that "another example is the reanalysis of the National Cancer Institute data on human exposure to formaldehyde,² which now indicates a clear risk of cancer to humans." The authors of the study of humans exposed to formaldehyde² concluded that "these data provide little evidence that mortality from cancer is associated with formaldehyde exposure at the levels experienced by workers in this

study." Since substantial numbers of health workers are exposed to formaldehyde, it would be of considerable interest if Dr. Ashford could provide the evidence that indicates "a clear risk of cancer to humans."

M. HENRY GAULT, M.D.

St. John's, NF A1B 3V6,
Canada

Memorial University
of Newfoundland

1. Ashford NA. New scientific evidence and public health imperatives. *N Engl J Med* 1987; 316:1084-5.

2. Blair A, Stewart P, Oberg M, et al. Mortality among industrial workers exposed to formaldehyde. *JNCI* 1986; 76:1071-84.

To the Editor: The editorial by Ashford sounds a false alarm about the state of public health regulation today. Far from "waiting for the bodies to fall," federal agencies long ago adopted the "preventive public health policies" that Professor Ashford now pleads for. The Supreme Court's decision in the benzene case accepts this approach by authorizing OSHA to "risk error on the side of overprotection rather than underprotection."¹ The essence of the court's ruling is that this principle must be applied within realistic limits, so that instead of seeking "to eliminate completely and with absolute certainty any risk of serious harm," regulators must fairly evaluate all the available scientific data and "make a rational judgment about the relative significance of the risks" involved.¹ Federal agencies have recognized that prudence, rather than an ill-conceived rush to judgment, is crucial to sound public health regulation and have had no difficulty implementing the vital risk assessment and policy-making disciplines contemplated in the benzene decision.²⁻⁴ In fact, OSHA has already regulated asbestos⁵ and ethylene oxide⁶ as carcinogens and will shortly prescribe stricter limits for formaldehyde.⁷

The report by Rinsky et al. on a much-studied cohort of benzene workers, which Professor Ashford cites as "better science" requiring an immediate "governmental response," actually illustrates the pitfalls of reacting uncritically to a single publication. Indeed, it fails to meet the standard of scientific excellence to which he subscribes. During OSHA's public hearings on benzene last summer,⁸ major shortcomings in the paper by Rinsky et al. were uncovered, including selective use of the available data on industrial hygiene; substantial underestimation of exposures, particularly during the 1940s, at the work stations where the excess cases of leukemia occurred and where workers were known to have died from the acute blood-poisoning effects of benzene⁹; and failure to account for the prolonged, heavy exposures to benzene that many of the workers in this cohort experienced at work stations excluded from the analysis.^{9,10}

There is nothing to be gained and much to be lost by fomenting a crisis atmosphere based on a flawed analysis that greatly exaggerates the level of risk, especially since average benzene exposures in the petroleum industry and elsewhere have for some time been reduced to levels comfortably below the 1-ppm limit OSHA has proposed.¹¹ Instead, Professor Ashford should recognize, as the American Petroleum Institute does, that the best way to improve health protection against the hazards we face today — occupational and otherwise — is to insist on a thorough scientific review of all the available data, focusing on the question of what exposures pose significant risks.

WILLIAM F. O'KEEFE

American Petroleum Institute

Washington, DC 20005

1. AFL-CIO v. American Petroleum Institute. Industrial Union Department. 448 U.S., 1980:607, 636.
2. Rissot M, Oberg M. Risk assessment in environmental policy-making. *Science* 1987; 236:286-90.
3. Lave LB. Health and safety risk analysis: information for better decisions. *Science* 1987; 236:291-3.
4. Olcott D. The safety goals of the U.S. Nuclear Regulatory Commission. *Science* 1987; 236:294-300.
5. Department of Labor. Occupational exposure to asbestos, crocidolite, amphibole, and actinolite. *Fed Regist.* June 20, 1986; 51:23612-90.
6. Department of Labor. Occupational exposure to ethylene oxide. *Fed Regist.* June 22, 1984; 49:25734-87.

DO 067930
CONFIDENTIAL

YZ0027907

iceberg reveals the iceberg. We are very far from ill-conceived rushes to judgment. On the contrary, the regulatory agencies have sometimes been dragged kicking and screaming into action necessary for fulfilling their statutory mandates. In the meanwhile, workers and citizens are harmed.

An example is the evolution of science regarding the carcinogenicity of formaldehyde. The National Cancer Institute (NCI) study in 1986 asserted that there was "little evidence that mortality from cancer is associated with formaldehyde exposure at levels experienced by workers in this study." In a later publication¹ the same authors concluded that

Despite small numbers, the dose-dependent association of nasopharyngeal cancer with exposure to formaldehyde and particulates deserves further investigation through case-control studies, where the influence of formaldehyde and particulates may be evaluated with more statistical power than by standard cohort studies.

Further analysis of the NCI data by Sterling and Weinkam² reveals a clearly increased risk of lung cancer. At congressional hearings in 1986, the Director of the NCI, in commenting on the earlier work, testified that "in association with particulates, there is an association between formaldehyde and nasopharyngeal cancer, which clearly has to be followed up."³

The irony concerning the criticisms of the adequacy of the science is that the scientific evidence is essentially there. OSHA has just decided to reduce the permissible exposure level for benzene to 1 ppm. It waited far too long. Let there be a better governmental response to the new realities.

NICHOLAS A. ASHFORD

Cambridge, MA 02139 Massachusetts Institute of Technology

1. Blair A, Stewart P, Hoover RN, Fraumeni JF Jr, et al. Cancers of the nasopharynx and oropharynx and formaldehyde exposure. *JNCI* 1987; 79: 191-2.
2. Sterling TD, Weinkam JJ. Submitted for the record at the OSHA Hearings on Formaldehyde. Submission 1828, November 1986.
3. Formaldehyde Study. Hearing before the Subcommittee on Oversight and Investigations of the Committee on Energy and Commerce, House of Representatives, July 28, 1986:106.

THE EC-IC BYPASS STUDY

To the Editor: The recent discussion (March 26 issue)¹⁻⁴ of the extracranial-intracranial (EC-IC) arterial bypass study is very timely. I would like to speak to one statement in the editorial: "The conclusions of the EC-IC trial are valid for the population of patients studied."¹

The population that underwent surgery included patients who had only one episode of the transient ischemic attack. Most neurosurgeons who are experienced with the bypass procedure would not accept for surgical consideration any patient with a single transient ischemic attack. There is no discussion in the original report of the randomized study⁵ about how many of the patients who underwent surgery were in this ordinarily nonoperative group. Subsequent reports by the authors of the randomized study have never clarified this issue.

Regardless of whether the randomization of the patients was proper or not, the mere fact that patients with one transient ischemic attack were included in the study negates the concept that the conclusions of the EC-IC trial are valid for the population of the patients studied.

MILTON D. HEIFETZ, M.D.

Los Angeles, CA 90048 Cedars-Sinai Medical Center

1. Belman AS. The extracranial-intracranial arterial bypass study: What have we learned? *N Engl J Med* 1987; 316:809-10.
2. Smith TM Jr. Was the international randomized trial of extracranial-intracranial arterial bypass representative of the population at risk? *N Engl J Med* 1987; 316:314-6.
3. Goldring S, Zervas N, Langille T. The Extracranial-Intracranial Bypass Study: a report of the committee appointed by the American Association of Neurological Surgeons to examine the study. *N Engl J Med* 1987; 316:817-20.

4. Barrow RM, Sackett D, Taylor DW, et al. Are the results of the extracranial-intracranial bypass trial generalizable? *N Engl J Med* 1987; 316: 820-4.
5. The EC/IC Bypass Study Group. Failure of extracranial-intracranial arterial bypass to reduce the risk of ischemic stroke: results of an international randomized trial. *N Engl J Med* 1985; 313:1191-200.

To the Editor: The Special Reports in the *Journal* of March 26 on the validity of the international randomized trial of extracranial-intracranial arterial bypass, first published in the *Journal* in 1985,⁵ induce some thoughts about the findings. Specifically, the implication of the findings for a better understanding of the pathogenesis of ischemic stroke is of interest.

The results are fully consistent with the hypothesis that ischemic strokes are largely embolic in origin. The relations among transient ischemic attacks, completed strokes, and atherosclerotic plaques of the internal carotid artery were well established before the study was done.

Emboli from ulcerated plaques or occlusive lesions of the internal carotid artery or middle cerebral artery would presumably lodge in a brain vessel distal to the anastomosis, whose only effect could then be to improve marginal or collateral circulation to the periphery of the territory where the infarct occurred.

Is it too simplistic to assume that in the case of the carotid lesions, a natural bypass already exists — the circle of Willis?

One of the postulates of the study was that lesions of the middle cerebral artery would be especially suitable for bypass surgery. In fact, the existence of such lesions generally indicates more severe, widespread atherosclerotic disease, with the attendant risk of stroke from embolism originating in the internal carotid artery or aorta or death from coronary heart disease.

Montreal, PQ H3A 2B4,
Canada

SEAN MOORE, M.D.
McGill University

*The EC/IC Bypass Study Group. Failure of extracranial-intracranial arterial bypass to reduce the risk of ischemic stroke: results of an international randomized trial. *N Engl J Med* 1985; 313:1191-200.

To the Editor: The *Journal* is to be congratulated for its complete handling of the controversy surrounding the EC-IC operation.¹⁻⁴ However, we strongly disagree with the conclusions of both the neurosurgeons⁵ and the Editor,⁶ who seems to have been impressed by the neurosurgeons' arguments and to cast a shadow on the proper interpretation of such trials. We agree that generalizability is strengthened when most eligible patients are randomized, but we insist that the results should stand unless or until an even better study repudiates them. In the meantime, those who insist on using this now-discredited operation should not expect third-party reimbursement until they provide credible (i.e., well-controlled experimental) evidence that contradicts the EC-IC study.

The called-for retrospective review of the outcome in the nonrandomized patients would be as worthless as any uncontrolled historical survey. It would be impossible to sort out selection factors from treatment effects. Some patients selected for operation rather than randomization might do worse than those randomized, because the more threatened patients were treated surgically, and some might live longer because their good condition made them attractive surgical candidates. Whichever predominated, the result would be uninterpretable, as demonstrated by several published comparisons of survival of randomized and nonrandomized patients who seemed to have the same prognosis.⁷⁻⁹ If surgeons have reservations about the validity of randomized controlled trials because their patients were not entered, the problem is easily solved by including all eligible patients in future studies that have the prior approval of those surgeons.

In our experience, patients readily accept randomization when their physicians are convinced of its validity. When told of the results of the trial and the lack of any evidence favoring surgery, they would prefer randomization to an operation based on surgical judgment alone. As suggested by one of us,² the study could be paid for with the money saved by operating on only half as many patients. In the meantime, there is no acceptable evidence that the

DO 067932
CONFIDENTIAL

YZ0027909