

O'BRIEN'S

Squid Velvet
THE ORIGINAL VELVET WALL FINISH

WASHABLE FLAT
WALL ENAMEL



INSURES
UNEQUALLED
PERFORMANCE

WASHABLE FLAT
WALL ENAMEL

MADE BY THE O'BRIEN CORPORATION, 1000 WEST 10TH AVENUE, DENVER, CO. 80202

O'BRIEN'S LIQUID VELVET

Liquid Velvet is the very finest, the very best flat wall enamel that's ever been marketed. Now made with O'Brien's sensational new Alki-Therm alkyls combined with patented Thermolyzed oils, it imparts the rich, velvety beauty of all base paints; the smooth, easy flowing, easy application of latex base paints plus the extra washability and durability of enamels.

Better than ever, this alkyl wall finish may be used with excellent results over most any interior surface—over plaster, wood, wallboard, metal, wallpaper, etc. Its excellent hiding and sealing qualities insure satisfactory one coat jobs on most normal surfaces. Easily applied with brush or mohair roller. May also be sprayed. Has no objectionable odor. Comes ready mixed—ready to use.

"701" Clear Wall Sealer

A clear, long oil, neutral sizing material for use over both painted and unpainted surfaces. Has excellent adhesion, seals the most porous surfaces. May be used straight or intermixed with Liquid Velvet. Dries overnight. An excellent vapor barrier.

Sealer/Primer Wall Primer and Sealer

An ideal undercoat for Liquid Velvet where two coat work is necessary due to condition of surface to be painted. Combines the sealing properties of wall size with the full benefit of a solid covering coat of paint. Special directions for use are on the package.

COAT	THICKNESS	SPREAD	COVERAGE
1st	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
2nd	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
3rd	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
4th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
5th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
6th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
7th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
8th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
9th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.
10th	1/8" - 1/4"	100 sq. ft.	100 sq. ft.

CAUTION! COMBUSTIBLE FLAME
Keep Away from Heat and Open Flame.
CONTAINS MARIJUANA IF EATEN.
Do not apply on toys, furniture or interior surfaces which might be chewed by children. Use with adequate ventilation, and contact with skin. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

STIR THOROUGHLY BEFORE AND DURING USE

PREPARATION—remove all grease, loose dirt and soap residue from surface. Seal any plaster patches with "701" Clear Sealer or Liquid Velvet Primer.

ONE COAT WORK—over surfaces in good condition—over wallpaper, old paint, plaster, wallboard or metal. Apply one coat of Liquid Velvet. Note—If bare plaster is not perfectly dry or the surface to be painted is extremely porous, follow two coat system recommended below.

TWO COAT WORK—over unsealed surfaces—over fresh plaster or wallboard. One coat Liquid Velvet Primer tinted to approximate shade of finish coat or a mixture of equal parts "701" Clear Sealer and Liquid Velvet. Finish with one coat Liquid Velvet.

TINTING—Use O'Brien's Pure Liquid Oil Colors for light tints — or Liquid Velvet Deep Colors for either light or deep tints.

THINNING—where necessary use Odorless Thinner. Turpentine, O'Brien's Reducit or Mineral Spirits may also be used—not to exceed one pint per gallon.

SPRAYING—thin as required with odorless thinner or V.M. & P. Naphtha.

DRYING—do not recoat Liquid Velvet or Liquid Velvet Primer until they have dried hard. Normally allow 24 hours at temperature of not less than 68° F., with good ventilation.

IMPORTANT—USE OF DEEP COLORS

Surfaces to be coated with Deep Colors normally require two coats—a prime coat consisting of a mixture of equal parts O'Brien's 701 Clear Sealer and Liquid Velvet of the finish color. Whenever practicable, stipple or roller-coat the finish coat of Liquid Velvet for maximum uniformity.

THE O'BRIEN CORPORATION
SOUTH BEND, IND. OKLAHOMA CITY, OKLA.
BALTIMORE, MD. SAN FRANCISCO, CAL.