


ONE



O'BRIEN'S

"75"

HOUSE PAINT

FOR ANY EXTERIOR SURFACE

PRIMING WHITE

MADE IN U.S.A. BY THE O'BRIEN CORPORATION • SOUTH BEND, INDIANA • BALTI

DIRECTIONS FOR USE FOR NEW UNPAINTED SURFACES

1st Coat—O'Brien's "75" House Paint Priming White, thinned with two or three pints of raw linseed oil. Tint to approximate shade of finish coat.*

FOR OLD PAINTED SURFACES

One Coat Work — one coat "75" House Paint will give a satisfactory result providing the surfaces are reasonably clean — in good condition and there is no radical change of color.

Two Coat Work — over badly weathered or extremely dirty surfaces, follow two coat system listed above under "New Unpainted Surfaces." Apply Primer as it comes from can. Do not thin with raw linseed oil.

GENERAL RECOMMENDATIONS

WEATHER — Outside painting should never be done when the weather is damp or the temperature below 60° F.

SURFACES — Surfaces to be painted should be perfectly dry and free of grease, oil, dust and loose dirt.

SPRAYING — "75" House Paint may be sprayed by an experienced operator.

DRYING — Allow at least 48 hours good drying weather between coats. When temperature is low, allow at least 96 hours drying.

— Stir Paint Well Before and During Use. When Necessary — Thin with Turpentine or O'Brien's Reducit.

THE O'BRIEN CORPORATION

**SOUTH BEND, IND. BALTIMORE, MD.
OKLA. CITY, OKLA. SAN FRANCISCO, CAL.
LOS ANGELES, CAL.**

**CAUTION: COMBUSTIBLE
KEEP AWAY FROM HEAT**

AND OPEN FLAME

CONTAINS LEAD OR OTHER COM-
PONENTS HARMFUL IF EATEN

to not apply on toys, furniture or interior surfaces which might be chewed.

children. Use with adequate ventilation.
Avoid breathing vapor or spray.

ist. Avoid prolonged contact with the
in. Wash thoroughly after handling

and before eating or smoking. Keep out of reach of children. Do not use if seal is broken or when not in use.

1990-1991

[illegible]

REGISTERED
REC'D. NO. 4513
DATE 8-5-1954