


Young Regulator Company

5209 Euclid Avenue, Cleveland 3, Ohio
DAMPER REGULATORS; REMOTE CONTROLS SYSTEMS
Sales Representatives in Principal Cities



No. 1A



No. 301A




No. 201A




No. 605



No. 401A



No. 403A



No. 915

Young Regulators meet practically every condition where damper regulators are required for controlling air volume.

No. 1A—For installation on finished wall. May be locked in any position.

No. 700A—For remote control of one or more dampers at distances up to 250 ft.

No. 704—Corner pulley eliminates friction where there are many turns.

No. 301A and 201A—For imbedding in plaster. Cover plate flush with finished wall.

No. 605 and 602—Bearing set used in place of CRS rod when regulator is mounted on side of duct.

No. 656—End bearing provides a bearing for the damper rod at side away from regulator and has a rubber gasket which prevents air leakage.

No. 401A—Valcalox regulator for mounting on duct. May be locked in any position.

No. 4—Adapter for connecting different sizes and shapes of damper rods to various models of regulators and to adjust length of rod.

No. 403A—Valcalox for mounting on duct, lever adjustment. May be locked in any position.

No. 910—Convactor regulator for operating damper hinged on back of an enclosure.

No. 900A—Air split regulator for operating a splitter damper.


No. 914—Concealed air split regulator with mitre gears used when the regulator is operated from a suspended ceiling.

No. 915—Volume control grille gives equal distribution of air over entire grille and directional flow.


No. 807—Register with damper for operation by remote control No. 700A.

No. 805—Damper only for operation by remote control No. 700A.


No. 815—Relief damper with motor and remote bulb thermostat controls temperature of individual rooms.




No. 900A



No. 914



No. 807



No. 805



No. 700A



No. 704



No. 605




No. 656



No. 4-1"



No. 910



No. 815

Armco Steel Corporation

Executive Offices, Middletown, Ohio

ATLANTA 3, GA. 1437 Citizens & Southern Natl. Bank Bldg.	HOUSTON 2, TEXAS..... 1640 Commerce Bldg.
BALTIMORE 13, MD..... 3400 E. Chase St.	INDIANAPOLIS 4, IND..... 800 Fletcher Trust Bldg.
BERKELEY 10, CALIF..... Seventh and Parker Streets	KANSAS CITY 3, MO..... 7100 Roberts St.
BOSTON 16, MASS..... 439 Park Square Bldg.	LOS ANGELES 15, CALIF..... 328 Petroleum Bldg.
BUFFALO 2, N. Y. 504 Buffalo Industrial Bank Bldg.	LOUISVILLE 2, KY..... Starks Bldg.
CHICAGO 4, ILL..... 310 S. Michigan Ave.	MILWAUKEE 2, WIS. 627 First Wisconsin Natl. Bank Bldg.
CINCINNATI 26, OHIO..... 823 Delta Ave.	MINNEAPOLIS 1, MINN. 919 Metropolitan Life Bldg.
CLEVELAND 15, OHIO 1516-20 B. F. Keith Bldg.	NEW YORK 5, N. Y..... 120 Broadway
COLUMBUS 15, OHIO..... 724 Atlas Bldg.	PHILADELPHIA 7, PA. 1808 Lincoln-Liberty Bldg.
DALLAS 1, TEXAS 1820 M and W Tower Bldg.	PITTSBURGH 22, PA. 1627 Henry W. Oliver Bldg.
DAYTON 2, OHIO 1802 The Hulman Bldg.	ST. LOUIS 1, MO..... 817 Ambassador Bldg.
DETROIT 2, MICH. 5-261 General Motors Bldg.	SOUTH BEND 21, IND..... 3202 W. Sample St.
	TULSA 3, OKLA..... 501 Mayo Bldg.



Choose the Correct ARMCO Grade

There is a grade of Armco Sheet Steel especially suited to each air conditioning application. For detailed information get in touch with the nearest district office or write direct to Armco Steel Corporation, 481 Curtis St., Middletown, Ohio.

ARMCO ZINCGRIP

A special zinc-coated sheet that can be severely formed without peeling or flaking of the tightly adherent zinc coating. The coating is 15-45 per cent more atmospheric corrosion-resistant than equal-weight coatings on regular galvanized sheets.

Used for:
Ducts (severe fabrication)
Squirrel Cage Type Blowers
Fan Housings
Casings

ARMCO ZINCGRIP-PAINTGRIP

Same as ARMCO ZINCGRIP, but with a mill-Bonderized finish for immediate painting without pre-treatment. Preserves life and beauty of paint and enamel.

Used for:
Ducts (painted)
Exterior Casings

All parts to be painted
Armco Cold-Rolled PAINTGRIP: For painted applications under less corrosive conditions. Takes and holds paint.

ARMCO Stainless Steel

Armco Stainless Steel is available in a variety of types and finishes in sheets, strip, bars, wire, plates and angles.

Used for:

Oil Burner Nozzles
Worm Feed for Stokers
Ribbon Type Burners
Combustion Chambers
Heat Flues and Tubes
Humidifier Pans
Fan and Blower Blades
Parts of Controls
Vaporizing Oil Burner
Trim

Special grades have excellent resistance to destructive heat-scaling up to 2000°F. Also highly corrosion-resistant.

ARMCO ALUMINIZED Steel

An aluminum-coated sheet steel with exceptional resistance to a combination of heat and corrosion. Resists heat discoloration up to approximately 900°F, and will withstand heat scaling up to 1250°F. Also offers exceptional heat reflectivity.

Used for:

Combustion Chambers
Heat Exchangers
Inner Casings on Floor Furnaces
Reflective Baffles on Radiant Heaters.