





*AD-EL-ITE PAINT AND VARNISH REMOVER Y-70

A top-quality remover. Contains no alkalies, acids, oils, or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan

*ALKALI-RESISTING PRIMER Y-5041

An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat

APPLICATION—Brush, Spray THINNER—Turpentine

DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal.

(Also See SPRED Primer-Sealer Alkali-Resisting Primer)

ALKYD ENAMELS

See: Brush-Day-Lite Alkyd Flat and Tint White; Japalac; Flor-enamel; Rustmaster; Ripolin; SPRED Lustre.

*ALUMINUM ASPHALT ROOF PAINT Y-605

Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum in one coat. Made with selected asphalts, finest grade aluminum flakes and solvents

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp.

DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface.

ALUMINUM PAINTS

See: Metallite; Japalac Spray Enamel

ASBESTOS SHINGLE PAINT

See: SPRED House Paint; SPRED Glide-On

BARN PAINT

See: Endurance Barn Paint

BASECOATS (Primers)

For Exteriors—See SPRED House Paint Primecoat #1; Rustmaster Metal Primer; Rustmaster Galvanized Primer, Endurance House Paint

For Interiors—See: Gliddencoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Ripolin Undercoat, Alkali-Resisting Primer.

BASEMENT PAINTS

For Floors—See: Florenamel

For Walls—See: SPRED SATIN; SPRED Glide-On

*BLACK ASPHALTUM Y-67

A weather resisting, quick drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal sash and other exterior metal surfaces where an economical finish is desired

APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours

THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal.

*AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

Gals.

Qts.

Pts.

½ Pts.

3.45

1.22

.77

.59

8.45

2.57

—

—

5.62

—

—

—

3.75

1.33

.84

.56



GLD027011



*ENDURANCE EXTERIOR BASECOAT Y-1851

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs

APPLICATION—Brush, Spray

DRYING TIME—48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—450 to 500 Sq. Ft. per gallon

*ENDURANCE HOUSE PAINT Y-1800 LINE

For Siding, Trim and Shutters

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew, magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

Outside White, Y1800	—	—	—	—
Regular Colors and Black, Y1800 Line	—	—	—	—
Non-Chalking Trim White, Y1892	—	—	—	—
Crylite Green, Y1828	—	—	—	—
Deep Turquoise, Y1870	12.89	3.72	2.01	—
Shutter Green, Y1861	8.89	2.68	1.51	—
Dark Walnut; Dark Blue, Y1872, Y1871	7.59	2.33	1.37	—

APPLICATION—Brush, Spray, Roller

DRYING TIME—16 hours; recoat in 72 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

*ENDURANCE HOUSE PAINT Y-1850

Mildew and Fume-Resistant

A deluxe, Super White House Paint—ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather

APPLICATION—Brush, Spray

THINNER—Mineral Spirits or Turpentine

DRYING TIME—16 hours; 72 hours for recoating

COVERAGE—Up to 550 Sq. Ft. per gallon

ENDURANCE HOUSE PAINT, PASTEL COLORS Y-1800 line

Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or NON-CHALKING TRIM WHITE Y1892 with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card.

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



*ENDURANCE IMPERIAL ONE-COAT Y-1867

White House Paint (Alkyd Fortified)

Premium quality self-cleaning white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty

APPLICATION—Brush, Spray

THINNER—Mineral Spirits or Turpentine

DRYING TIME—48 hours

COVERAGE—550 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

8.99

2.68

—

—

*ENDURANCE VELVET (Flat Exterior Finish) Y-2700 line

FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture.

White and Colors

APPLICATION—Brush, Spray

DRYING TIME—Dust-free 1 hr.; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

6.75

2.13

—

—

*EVERON HOUSE PAINT (White) Y-2200

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT

APPLICATION—Brush, Roller, Spray

DRYING TIME—16 hours; recoat in 48 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

—

—

—

—

FARM BUILDING PAINTS

For Exteriors—See: Endurance Paints; Metallite; SPRED House Paint; SPRED Glide-On; Stock Farm White

For Interiors—See: SPRED Products

FENCE PAINTS

See: Stock Farm White; Metallite; Rustmaster; Black Asphaltum

FILLER, WOOD

See: Glid-Tone Wood Filler

FLOOR FINISHES

See: Florenamel; Glid-Tone Gloss Varnish; Xpert Clear Gloss

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



*FLORENAMEL (Alkyd) Y-850 line

An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings — inside and outside. Will not waterspot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scrubbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMATONE Tinting Colors. All colors

APPLICATION—Brush, Spray

DRYING TIME—12 hours

THINNER—Turpentine or Mineral Spirits

COVERAGE—500 to 600 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

7.50

2.38

—

—

*GLIDDENCOAT (White Enamel Undercoat) Y-555

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with Colors-In-Oil or DRAMATONE Tinting Colors

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

6.35

2.03

1.19

.80

GLIDE-ON, SPRED

See: SPRED Products Section

GLID STRIP (Non-Flammable) Y-74

Wash Away Paint and Varnish Remover

A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal

7.20

2.40

1.26

.81

GLID-TONE CRYSTALACQ (Brushing Lacquer) Y-2840

A crystal clear, quick-drying, water and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc.

APPLICATION—Brush

DRYING TIME—1 to 6 hours, depending on surface

THINNER—Glid-Tone Crystalacq Reducer

COVERAGE—300 Sq. Ft. per gallon

7.55

2.32

1.34

—

GLID-TONE CRYSTALACQ REDUCER, Y2822

Special Thinner for Crystalacq

—

—

1.07

—

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

GLD027014



GLID-TONE GLOSS VARNISH Y-1

A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed

APPLICATION—Brush

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

*GLID-TONE REDWOOD STAIN Y-31

A penetrating flat Redwood Stain and Sealer designed especially to protect and beautify natural exterior wood such as siding, shingles, shakes, panels, doors, fences, picnic tables and yard furniture. If gloss finish is desired use Clear Redwood Finish Y30

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon, first coat. 2nd Coat: Up to 600 Sq. Ft. per gallon. 3rd Coat: Up to 800 Sq. Ft. per gallon.

*GLID-TONE REDWOOD FINISH Clear Polyurethane Y-30

A brilliant gloss finish for redwood, red cedar, pine and other exterior wood surfaces. Mildew and fume resistant. Provides a tough, erosion resistant film that maintains flexibility and resists checking, cracking, hardening

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First coat on rough new wood; 200 to 300 Sq. Ft. per gallon. Finished wood; 300 to 400 Sq. Ft. Second coat; 500 to 600 Sq. Ft. Third coat; 600 to 800.

GLID-TONE RE-GRAIN GROUND COAT Y-260

An enamel undercoater that produces a firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Regrain Process Folder

GLID-TONE SATIN-SHEEN VARNISH Y-47

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains, DO NOT USE ON FLOORS

APPLICATION—Brush

DRYING TIME—2 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

Gals.	Qts.	Pts.	½ Pts.
8.75	2.62	1.47	.91
5.35	1.72	—	—
8.10	2.38	—	—
—	2.03	1.19	.80
7.95	2.35	1.35	.85



GLID-TONE SPAR VARNISH Y-48

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use — spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces

APPLICATION—Brush

DRYING TIME—8 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

GLID-TONE VARNISH STAIN Y-1201-02-03

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof

APPLICATION—Brush, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

GLID-TONE WOOD STAIN Y-242 line

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

APPLICATION—Wiping Cloth, Brush

DRYING TIME—12 hours Stains, All Colors

THINNER—Glid-Tone Stain Reducer

GLID-TONE STAIN REDUCER Y-251

Gals.	Qts.	Pts.	½ Pts.
9.40	2.73	1.54	.98
7.30	2.28	1.29	.85
5.95	1.87	1.13	.75
3.45	1.28	.82	.63

SPRED SATIN

AND SPRED RELATED PRODUCTS



SPRED SATIN Y-3400 line (100% Latex Interior Paint)

Original 100% latex base paint for interior walls, ceilings, woodwork. Excellent for masonry, interior plaster, porous wallboards, acoustical tile, wallpaper. The ideal latex paint for schools, hospitals, residences, offices, motels, hotels, apartments, housing projects, etc. Extremely fast, easy application; self priming, cuts painting time in half. No disagreeable odor. Guaranteed washable. May be tinted with DRAMATONE Tinting Colors.

3418 Decorator White	6.69	2.15	1.20	.79
3470 Ceiling Flat White and Standard Colors	6.69	2.15	—	—
3480 Dramatone Tint Base	6.00	1.90	—	—
3487 Int. Tint Base	6.05	1.92	—	—

DEEP COLORS

3434 Charcoal Black	6.69	2.15	1.20	.79
---------------------------	------	------	------	-----

APPLICATION—Brush, Roller, Spray

DRYING TIME—20 minutes; may be recoated in 4 hours

THINNER—Water

COVERAGE—Up to 500 Sq. Ft. per gallon over most surfaces

*SPRED LUSTRE SEMI-GLOSS ENAMEL Y-4600 line (Interior-Exterior Washable Alkyd Enamel)

Ready to use. Covers most surfaces in One Coat. Requires no other primer on new plaster or new wood. Ideal for kitchens, bathrooms, hallways — walls, furniture, plaster, woodwork and metal. Washes like tile. Colors match SPRED SATIN. May be tinted with DRAMATONE Tinting Colors.

4600 White and Colors; 4618 SPRED Lustre Pastel Tinting White....	8.35	2.53	1.44	—
4680 SPRED Lustre Dramatone Tint Base	7.45	2.18	—	—
4687 Int. Tint Base	7.75	2.31	—	—

APPLICATION—Brush, Roller, Spray

DRYING TIME—Dust free 3 to 4 hours; recoat overnight

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 550 Sq. Ft. per gallon

DRAMATONE MULTI-PURPOSE TINTING COLORS Y-1781 line

(For Tinting Latex, Alkyd and Other Paints)

Tinting colors for use with SPRED SATIN Latex Paint, Alkyd Semi-Gloss Enamel, Alkyd Flat Enamel and Other Paints. See Dramatone displays for wide range of colors.

1781 Blue; 1782 Lamp Black; 1783 Umber Brown; 1784 Green; 1786 Red Oxide; 1787 Ruby Red; 1788 Ferrite Yellow

1791 Hansa Yellow; 1792 Light Green; ‡1793 Bright Orange

2 Oz. Paks	1 Oz. Paks	¼ Oz. Paks	⅛ Oz. Paks
Per Pak. .60	Per Pak. .50	Per Pak. .40	Per Pak. .38
.70	.58	.47	.45

*AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

‡FOR INTERIOR USE ONLY.



*SPRED HOUSE PAINT Y-3600 line

(100% Latex Exterior Paint)

A new blister-resistant house paint for exterior wood and masonry. May be applied without primer over sound previously painted surfaces which are in good condition. Has a remarkable fast drying time of thirty minutes, which practically eliminates damage from bugs, rain and dust. May be applied over damp surfaces. Has long lasting velvet-like sheen. Once the Spred House Paint system is used on a house, future paintings will require only one coat.

White and Colors

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—4 hours for recoating

THINNER—Water

COVERAGE—Approx. 450 Sq. Ft. per gal. on smooth surface

*SPRED HOUSE PAINT WHITE TINT BASE—Y3625

*SPRED PRIMECOAT #1 Y-3651

(Thin With Mineral Spirits)

Spred Primecoat #1 provides a firm foundation on new or unpainted exterior surfaces. The ideal undercoat that creates the finest possible two coat paint job when used under Spred House Paint. Excellent also for recoating badly weathered or porous surfaces that have been previously painted. This primecoat has been especially formulated for Spred House Paint

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—48 Hours

THINNER—Turpentine or Mineral Spirits

COVERAGE—450-550 Sq. Ft. per gallon

*SPRED GLIDE-ON Y-3500 line

(Vinyl-Latex Exterior Masonry Paint)

An exterior vinyl-latex masonry paint, unaffected by the alkalinity found in all masonry surfaces. Designed for use on stucco, concrete, brick, concrete block, cinder block, asbestos shingle and panel siding, unglazed tile and primed metal. Keeps out moisture yet the surface "breathes" to let vapor escape from inside. A tough vinyl film that resists driving rains, hottest sunshine, mildew, snow and ice, sea air and salt water spray, strangest smog, dust and chemical fumes. Resists cracking, peeling, fading, blistering, acid and alkali action.

White and Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Water

COVERAGE—Up to 400 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

Gals.	Qts.	Pts.	½ Pts.
7.98	2.45	—	—
7.98	2.45	—	—
7.98	2.45	—	—
6.90	2.13	—	—



*SPRED PRIMER-SEALER Y-3416

(A Latex Vapor-Barrier)

An excellent latex primer for porous surfaces of dry-wall construction, plaster, masonry and asbestos covered pipes. Seals high-suction plaster, most water stains, "hot spots" and discolored surfaces. Assures positive sealing and holdout for succeeding finishing coats of either latex or oil base paints. May be intermixed with latex paints for color, or tinted with DRAMATONE Tinting Colors. An approved vapor barrier which helps to prevent outside paint failures

APPLICATION—Brush, Roller, Spray

THINNER—Water

DRYING TIME—20 minutes; may be recoated in 4 hours

COVERAGE—Up to 400 Sq. Ft. per gallon on plaster;
100 Sq. Ft. per gallon on porous wallboard

Gals.

Qts.

Pts.

½ Pts.

5.85

1.88

—

—

*SURFACE BOND Y-55

(Seals Powdery Masonry Surfaces)

A high quality, clear finish bonding coat. Designed to penetrate deeply into chalky surfaces left by previous coats of cement bondings or powder type paints on masonry surfaces. Dries hard to help prevent further chalking. Anchors old surface to make a perfect bond for SPRED GLIDE-ON, as well as other exterior and interior masonry paints

APPLICATION—Brush, Spray

DRYING TIME—1 to 4 days depending upon drying conditions

THINNER—Turpentine or Mineral Spirits

COVERAGE—300 to 400 Sq. Ft. per gallon

6.10

1.95

—

—

*SPRED STIPPLE-TEXTURE AND BLOCK FILLER Y-3090

(Silicated Latex For Masonry and Dry-Wall Construction)

Ready to use on new or old surfaces. Gives all the advantages of texture and all the beauty of paint in one application. Hides irregular surfaces on plaster, wallboard, masonry blocks and wallpaper, seals spackled nail heads and tape joints. Easily applied with brush or roller. May be stippled or lightly textured in a variety of patterns and techniques. Especially made for texturing and stippling and for filling masonry blocks, pores and voids, to eliminate "pinholing" in finish coat, to assure better water repellency and to develop excellent appearance on interior and exterior masonry. May be tinted with DRAMATONE Tinting Colors.

White

APPLICATION—Brush for texturing, followed by stipple brush, sponge, trowel, whisk broom, comb, etc., as desired. Use roller for stipple effect. Brush, roll or spray when used as a block filler.

DRYING TIME—Overnight

THINNER—Water

COVERAGE—Texturing and filling blocks—75 to 100 Sq. Ft. per gallon. Stippling: 175 to 200 Sq. Ft. per gallon

5.65

1.75

—

—

SPRED SURFACENE Y-66

(Liquid Surface Conditioner and Brush Cleaner)

A clear liquid that can be applied to old enameled, painted or varnished surfaces to clean the surface, dull the gloss and insure good adhesion for a new finish coat. Eliminates the work and dust of sanding and prepares surfaces for refinishing in one easy operation. SURFACENE may also be used as a brush cleaner

APPLICATION—Cloth or Brush

4.90

1.63

1.01

—

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.



SPRED PATCH Y-3475

(100% Latex Spackling Compound)

A ready-to-use spackling compound. Will not bleed through paint, or flash. Does not shrink. Dries to a "puff" which may be easily sanded. Does not clog sandpaper. Excellent adhesion.

APPLICATION—Putty Knife

DRYING TIME—30 minutes

THINNER—Water

SPRED FLAT Y-3000

(Oil-Emulsion Interior Paint)

One gallon makes six quarts of paint when mixed with two quarts of water. Easy to apply over wallpaper, new or old plaster, wallboard, painted surfaces, cement and rough tile walls. Has limited washability.

White

APPLICATION—Brush, Roller, Spray

DRYING TIME—30 minutes; recoat 4 to 12 hours, depending upon surface

THINNER—Water

COVERAGE—Up to 650 Sq. Ft. per gallon

Gals.	Qts.	Pts.	½ Pts.
4.60	1.63	4 oz. Tube .49	.67
5.70	1.80	—	—



GLID-TONE WOOD FILLER Y-700

For use on all open-grained wood such as oak, chestnut, walnut and mahogany. Has pure siliceous base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine

APPLICATION—Brush, Cloth

THINNER—Turpentine, Naphtha

GLOSS FINISHES

See: Japalac; Ripolin; Florenamel; Rustmaster

HEAT RESISTING ALUMINUM

See: Metallite

HOUSE PAINT

See: SPRED House Paint; Endurance Paints; SPRED Glide-On; Everon

IRON PRIMER

See: Liquid Red Lead; Rustmaster Metal Primers

IMPERIAL ONE-COAT WHITE HOUSE PAINT

See: Endurance Imperial

INTERIOR ALUMINUM

See: Metallite All-Purpose Aluminum

JAPALAC SCREEN AND IRON ENAMEL Y-1222

Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters, andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting

APPLICATION—Brush, Spray or Special Applicator

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

JAPALAC ENAMEL Y-1200 line

Quick-Drying, Alkyd Gloss

An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces — walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors.

Ultra White, Brilliant Black, Flat Black and Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 500 Sq. Ft. per gallon

Gals.	Qts.	Pts.	½ Pts.	
5.88	1.85	—	.69	
5.00	1.66	1.01	.68	
9.79	2.88	1.62	1.00	.65



JAPALAC SPRAY ENAMEL Y-4000-line

In Ready-To-Spray Cans

All-purpose, interior-exterior enamel in pressurized, aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold, and a clear finish.

White, All Colors, and Clear

APPLICATION—Spray

DRYING TIME—Ten minutes

LACQUER

See: Glid-Tone Crystalacq (Brushing Lacquer)

LATEX PAINTS

See: SPRED Products Section

LINOLEUM COATING

See: Glid-Tone Crystalacq

*LIQUID RED LEAD (Modified) Y-506

Recommended whenever a shop coat of red lead is specified. Comes ready to apply, is extremely elastic and is an excellent rust preventative

APPLICATION—Brush, Spray

DRYING TIME—16 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 to 600 Sq. Ft. per gallon

MACHINERY ENAMEL

See: Rustmaster Enamel; Japalac

MASONRY FINISHES

See: SPRED House Paint; Silicone Driwall; SPRED Glide-On

*METALLITE ALL PURPOSE ALUMINUM Y-592

An extremely smooth, chrome-like aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Will not tarnish under ordinary conditions. It maintains its brilliance. Makes an excellent sealer over asphalt. Retards corrosion caused by fumes and moisture. Withstands heat up to 500°F. Hides with one coat. Easily cleaned. Reflects light

APPLICATION—Brush, Roller, Spray

DRYING TIME—2 to 4 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

Gals.	Qts.	Pts.	½ Pts.
—	16 Av. Oz. Can 1.59	—	—
8.80	2.66	1.54	.98
6.89	2.15	1.27	.81



METAL PRIMER

See: Liquid Red Lead; Rustmaster Metal Primer

MILDEW-RESISTING PAINTS

See: SPRED Glide-On; Endurance Mildew and Fume-Resistant Paint

METAL PROTECTIVE PAINTS

See: Rustmaster; Metallite; Liquid Red Lead

*NEVA-ROT Y-1502

(Wood and Canvas Preservative)

A preservative that combats mold, fungus, mildew, termites, ants, beetles, bacteria, rot and decay. Equally effective on wood, canvas and rope. Highly recommended for new or old lumber, handrails, porches, columns, stairways, fence posts, cribs, barns, foundation timbers, ropes, lines, canvas awnings — wherever non-metal surfaces require protection from insects and bacterial damage. NEVA-ROT has been tested and approved by the U. S. Navy as a preservative. It is odorless and non-toxic to humans, will not irritate eyes or skin.

Neva-Rot Green Y-1502

APPLICATION—Brush, Spray, Dip, Swab

DRYING TIME—Overnight

THINNER—None Required

COVERAGE—200 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

5.05

1.74

—

—

ONE-COAT HOUSE PAINT

See: Endurance Imperial

OIL COLORS IN TUBES

See: Colors-In-Oil

PAINT AND VARNISH REMOVER

See: Glid-Strip; Ad-El-It

PATCHING PLASTER

See: SPRED Patch

PORCH AND DECK ENAMEL

See: Florenamel

PRIMERS AND SEALERS

See: Alkali-Resisting Primer Y5042; Endurance Exterior Basecoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Glidden-coat Enamel Undercoat; Ripolin Undercoat; Surface Bond

RED LEAD (Liquid)

See: Liquid Red Lead

RIPOLIN ENAMEL (Quick-Drying White) Y-2900, Y-2950

One of the oldest and finest enamels with world-wide acceptance. Architects and painters recognize RIPOLIN as the finest enamel for interior and exterior decorating. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors.

Gloss, Semi-Gloss (White Only)

APPLICATION—Brush, Roller, Spray

DRYING TIME—6 to 8 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

10.10

3.13

1.77

1.02

*AVAILABLE IN 5-GAL CANS

AT 15¢ PER GALLON LESS THAN 1-GAL PRICES.

GLD027023



RIPOLIN UNDERCOAT Y-2555

A perfect first coater for new wood or previously painted surfaces. Dries to a firm opaque film. Especially designed for use with Ripolin Semi-Gloss and Gloss Enamels. Completely hides and seals a surface so that finishing coats of Ripolin Enamel produce full luster and depth of gloss. Requires only light sanding. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

RIPOLIN YACHTING FINISHES

(PRICES UPON REQUEST)

*ROCKSPAR VARNISH Y-50

Heavy bodied varnish for all interior surfaces. One coat equivalent to two coats of ordinary varnish. No shrinkage on drying. Dries with deep high gloss

APPLICATION—Brush

DRYING TIME—Overnight; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 700 Sq. Ft. per gallon

RUSTMASTER GLOSS ENAMEL Y-470 line

A high quality versatile enamel of excellent quality. It has exceptional ease of application and may be applied by brushing, or spraying as a finish coat over metal with Y470 or Y471 Rustmaster Primer. Rustmaster Gloss Enamel guards against rusting of machinery and equipment in the factory and on the farm as well as metal surfaces around the home and schools such as metal window frames and casings, iron fences, railings, bicycles, lawn mowers, playground equipment, etc.

Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum.....

Suntone, Flare Red

White

APPLICATION—Brush or Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for Brushing; VM & P
Naphtha for Spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

RUSTMASTER METAL PRIMER Y-470

A new, unexcelled, fast drying corrosion resistant exterior and interior metal primer containing revolutionary Phenolic Resin Penetrating Liquid (U.S. Patent No. 2978424) that cuts through rust and seals metal pores, locking out air and corrosive moisture. A finish coat of Rustmaster Enamel will provide an exceptionally durable coating

APPLICATION—Brush or Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for brushing; VM & P
Naphtha for spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.



RUSTMASTER PRIMER Y-4030 (Spray Can)

Same quality as Rustmaster Metal Primer Y470, packed in handy spray can for easy, instant use. Ideal for hard-to-reach areas

APPLICATION—Spray

DRYING TIME—Overnight for recoating

RUSTMASTER GALVANIZED PRIMER Y-471

Provides longer-lasting protection for galvanized metal and aluminum. Use on new galvanized steel without chemical treatment. This prime coat may be used as a finish coat or recoated with Rustmaster Enamel, Endurance House Paint or Japalac....

APPLICATION—Brush, Roller, Spray

DRYING TIME—48 hours

THINNER—Turpentine, Mineral Spirits

COVERAGE—Approx. 350 Sq. Ft. per gallon

ROOF PAINTS

See: Aluminum Asphalt Roof Paint; Metallite All-Purpose Aluminum

SCREEN ENAMELS

See: Japalac Screen and Iron Enamel

SEMI-GLOSS ENAMELS

See: Ripolin; SPRED Lustre

SILICONE SLICK SPRAY Y-58

(Miracle Lubricant With 1001 Uses)

A new, spray lubricant that protects and preserves while it lubricates. An excellent ice and water repellent. Push button spray lubricates hard-to-reach parts and areas. Makes windows, drawers, doors and other sticking items slide freely. Stops squeaks

SPACKLING COMPOUND

See: SPRED Patch

SPAR VARNISH

See: Glid-Tone Spar Varnish

*SPEED-WALL ALKYD INTERIOR BASECOAT Y-4516

A ready-to-use, low odor, alkyd-type primer sealer for new and old interior wall surfaces of plaster, masonry or wallboard. Also for previously painted walls in poor condition and patched areas. Its remarkable ease of brushing and exceptional filling, sealing, hiding, and alkali-resisting properties are gained through the use of special resins, pigments, and oils

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 450 Sq. Ft. per gallon

SPRED PRODUCTS

See: SPRED Products Section

STAINS

See: Glid-Tone Stain

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

	Gals.	Qts.	Pts.	½ Pts.
16 Oz. Can 1.89		—	—	—
Gals. 8.70		2.63	1.51	.95
6 Oz. Can 1.59		16 Oz. Can 2.95	—	—
Gals. 5.80		Qts. 1.85	—	—



*STOCK FARM WHITE PAINT Y-596

An excellent low cost exterior paint for use on wood surfaces such as fences, barns, outbuildings, sheds, etc. This material, produced for use in stock farms, is formulated without lead pigments, and contains wood preservatives. The creosote-like odor tends to repel livestock

APPLICATION—Brush, Spray

DRYING TIME—Overnight; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 450 Sq. Ft. per gallon depending upon surface condition

Gals.

Qts.

Pts.

½ Pts.

6.00

—

—

—

STOVE AND IRON ENAMEL

See: Japalac Screen and Iron Enamel

SURFACE CONDITIONER

See: SPRED Surfacene; Surface Bond

TILE ROOF PAINT

See: SPRED Glide-On

TINTING COLORS

See: Dramatone Multi-Purpose Tinting Colors; Colors-In-Oil

TRIM AND SHUTTER COLORS

See: Endurance House Paint

TUBE COLORS

See: Dramatone Multi-Purpose Tinting Colors; Colors-In-Oil

UNDERCOATERS

See: Gliddencoat; Ripolin Undercoat; Surface Bond; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Endurance Exterior Basecoat; Rustmaster Metal Primer 470; Rustmaster Galvanized Primer 471.

VAPOR BARRIER

See: SPRED Primer-Sealer

VARNISHES

See: Glid-Tone Spar; Glid-Tone Satin Sheen; Glid-Tone Gloss; Rockspar, Xpert

VARNISH REMOVER

See: Ad-El-Ite; Glid-Strip

VINYL-LATEX PAINT

See: SPRED Glide-On

VISMATIC GREEN CHALKBOARD COATING Y-594

A lusterless matte finish, green in color. Extremely popular in a large number of America's finest school, college and university classrooms. It is used to paint black chalkboards in a new light-reflecting color that is easy on the eyes. This green finish achieves maximum visibility and minimum light wave vibration of chalk lines and letters. Easy to apply

APPLICATION—Brush, Spray

DRYING TIME—Overnight for recoating

THINNER—Mineral Spirits

COVERAGE—Up to 500 Sq. Ft. per gallon

9.05

2.64

1.53

—

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

**WOOD FILLER**

See: Glid-Tone Wood Filler

WOOD FINISHES

See: Glid-Tone Products, Xpert

WOOD PRESERVATIVE

See: Neva-Rot

WOOD STAIN

See: Glid-Tone Stain

YACHT AND BOAT FINISHES (Ripolin)

(PRICES UPON REQUEST)

Xpert Polyurethane Liquid Plastic Satin Sheen Y-37

Clear plastic satin-sheen finish for interior-exterior use. Outwears conventional interior finishes two to one. Provides 25% more durability for exteriors. For use on floors, furniture, paneling or exterior redwood, doors, shutters, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding.

11.00

3.20

1.79

—

Xpert Polyurethane Liquid Plastic Clear Gloss Y-51

Clear, high gloss plastic finish that will outwear conventional lacquers and varnishes two to one for interior use. Gives up to 25% greater durability for exteriors. May be used on floors, furniture, paneling or exterior redwood, cedar doors, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding.

9.05

2.72

1.56

—

Xpert Wood Finish Clear Y-2842

A water white lacquer; provides a clear, satin sheen finish for interior wood floors, paneling, trim, cabinets and fine furniture. Dries in thirty minutes and may be recoated in two hours. It is non-yellowing and has good resistance to water, alcohol and chemicals.

7.60

2.35

1.37

—

NOTE: Although the formulations and recommendations contained in this price list have been established through careful evaluation, users of Glidden paints are urged to obtain specific information concerning their painting requirements. Seller's liability shall in no event exceed value of this material, which is warranted only to conform to formula or sample. Seller hereby expressly excludes all other express or implied warranties whatsoever.

	Gals.	Qts.	Pts.	½ Pts.

GLD027028

CODE NUMBER AND DESCRIPTION

Y-1	Glid-Tone Gloss Varnish	Y-1270	Japalac Lemon Yellow	Y-3053	Craftsman Latex Pt. Azalea	Y-4016	Japalac Spray Enamel Greenbrier
Y-30	Glid-Tone Redwood Clear Finish	Y-1271	Japalac Greenbrier	Y-3054	Craftsman Latex Pt. Pewter Gray	Y-4017	Japalac Spray Flat White
Y-31	Glid-Tone Redwood Stain	Y-1502	Neva-Rot Green	Y-3055	Craftsman Latex Pt. Aqua	Y-4018	Japalac Spray Blue Turquoise
Y-37	Xpert Satin Sheen	Y-1701	Colors in Oil Yellow Ochre	Y-3056	Craftsman Latex Pt. Hemp	Y-4019	Japalac Spray Tan Bark
Y-47	Glid-Tone Satin Sheen Varnish	Y-1702	Colors in Oil Burnt Sienna	Y-3057	Craftsman Latex Pt. Brook Blue	Y-4030	Rustmaster Primer
Y-48	Glid-Tone Spar Varnish	Y-1703	Colors in Oil Burnt Umber	Y-3058	Craftsman Latex Pt. Maytime	Y-4516	Interior Base Coat
Y-50	Rockspar Varnish	Y-1705	Colors in Oil Med. Chrome Green	Y-3059	Craftsman Latex Pt. Bone White	Y-4550	Speedenamel White
Y-51	Xpert Clear Gloss	Y-1706	Colors in Oil Lt. Chrome Yellow	Y-3090	Spred Stipple Text. Bone White	Y-4551	Speedenamel Black
Y-55	Surface Bond	Y-1707	Colors in Oil Med. Chrome Yel.	Y-3401	Spred Satin Pale Ivory	Y-4552	Speedenamel Orange
Y-58	Silicone Slick Spray	Y-1708	Colors in Oil Raw Umber	Y-3405	Spred Satin Confetti Yellow	Y-4553	Speedenamel Deep Green
Y-66	Spred Surfacing	Y-1709	Colors in Oil Ivory Black	Y-3406	Spred Satin Light Apricot	Y-4554	Speedenamel Med. Green
Y-67	Black Asphaltum	Y-1711	Colors in Oil Prussian Blue	Y-3407	Spred Satin Pinefrost Green	Y-4556	Speedenamel Fire Red
Y-70	Adelite Paint & Varnish Remover	Y-1716	Colors in Oil Lt. Chrome Yellow	Y-3409	Spred Satin Tropic Green	Y-4560	Speedenamel Med. Yellow
Y-74	Glid-Strip Paint & Var. Remover	Y-1717	Colors in Oil Amer. Vermilion	Y-3410	Spred Satin Spray Blue	Y-4561	Speedenamel Light Gray
Y-242	Glid-Tone Stain—Honey Maple	Y-1718	Colors in Oil Venetian Red	Y-3412	Spred Satin Blue Azure	Y-4562	Speedenamel Machine Gray
Y-243	Glid-Tone Stain—Fr. Provincial	Y-1719	Colors in Oil Raw Sienna	Y-3413	Spred Satin Bone White	Y-4564	Speedenamel Imperial Blue
Y-244	Glid-Tone Stain—Mod. Red Mah.	Y-1720	Colors in Oil Lampblack	Y-3414	Spred Satin Moonmist	Y-4565	Speedenamel Bright Red
Y-245	Glid-Tone Stain—Walnut	Y-1742	Colors in Oil Dark Chrome Yel.	Y-3415	Spred Satin Blossom Pink	Y-4569	Speedenamel Hydro Blue
Y-246	Glid-Tone Stain—Wheat	Y-1745	Colors in Oil Perma Green	Y-3416	Spred Primer Sealer	Y-4570	Speedenamel Red Oxide
Y-247	Glid-Tone Stain—Blonde	Y-1746	Colors in Oil Perma Blue	Y-3418	Spred Satin Decorator White		Metal Primer
Y-248	Glid-Tone Stain—Brown Mah.	Y-1781	Dramatone Blue	Y-3434	Spred Satin Charcoal Black	Y-4571	Speedenamel Spring Green
Y-249	Glid-Tone Stain—Platinum	Y-1782	Dramatone Lampblack	Y-3441	Spred Satin Cheer	Y-4572	Speedenamel Neutral Gray
Y-250	Glid-Tone Stain—Suntan	Y-1783	Dramatone Umber Brown	Y-3443	Spred Satin Cotton Candy	Y-4573	Speedenamel EZC Green
Y-251	Glid-Tone Stain Reducer	Y-1784	Dramatone Green	Y-3447	Spred Satin Sandy Beige	Y-4574	Speedenamel School Bus Yel.
Y-252	Glid-Tone Stain—Maple	Y-1786	Dramatone Red Oxide	Y-3448	Spred Satin Silver Turquoise	Y-4575	Speedenamel Tint White
Y-254	Glid-Tone Stain—Cherry	Y-1787	Dramatone Ruby Red	Y-3449	Spred Satin Oyster White	Y-4576	Speedenamel Deep Orange
Y-255	Glid-Tone Stain—Ebony	Y-1788	Dramatone Ferrite Yellow	Y-3467	Spred Satin Pebble Beach	Y-4577	Speedenamel Mah. Brown
Y-257	Glid-Tone Stain—Driftwood	Y-1791	Dramatone Hansa Yellow	Y-3470	Spred Satin Ceiling Flat White	Y-4600	Spred Lustre White
Y-258	Glid-Tone Stain—Fruitwood	Y-1792	Dramatone Light Green	Y-3472	Spred Satin Medallion Gold	Y-4605	Spred Lustre Peach Glow
Y-259	Glid-Tone Stain—Butternut	Y-1793	Dramatone Bright Orange	Y-3475	Spred Patch	Y-4618	Spred Lustre Tinting White
Y-260	Glid-Tone Regrain Ground Coat	Y-1800	Endurance House Paint White	Y-3477	Spred Satin Biscayne Blue	Y-4641	Spred Lustre Crocus Yellow
Y-470	Rustmaster Primer	Y-1802	Endurance House Paint Black	Y-3478	Spred Satin Aquaglow	Y-4643	Spred Lustre Cotton Candy
Y-471	Rustmaster Galvanized Primer	Y-1813	End. H.P. Tobacco Brown	Y-3479	Spred Satin Sherwood Green	Y-4647	Spred Lustre Sahara
Y-472	Rustmaster Aluminum	Y-1828	End. H.P. Crylite Green	Y-3480	Spred Satin Dramatone	Y-4648	Spred Lustre Caribbean
Y-475	Rustmaster White	Y-1850	End. H.P. Mildew & Fume Res. White		Tint. Base	Y-4649	Spred Lustre Oyster White
Y-476	Rustmaster Black	Y-1851	End. Basecoat Mildew & Fume Res.	Y-3487	Spred Satin Int. Tinting Base	Y-4651	Spred Lustre Congo Ivory
Y-477	Rustmaster Flat Black			Y-3501	Spred Glide-On Bamboo	Y-4655	Spred Lustre Springtime
Y-478	Rustmaster Suntone	Y-1855	End. H.P. Castle Red	Y-3504	Spred Glide-On Silver Smoke	Y-4657	Spred Lustre Woodland
Y-479	Rustmaster Royal Blue	Y-1856	End. H.P. Ivory	Y-3506	Spred Glide-On Tang Red	Y-4659	Spred Lustre Meadow Green
Y-480	Rustmaster Greenfield	Y-1857	End. H.P. Cream	Y-3507	Spred Glide-On Sunflower	Y-4660	Spred Lustre Zircon
Y-481	Rustmaster Flare Red	Y-1859	End. H.P. Light Gray	Y-3510	Spred Glide-On Jewel Green	Y-4662	Spred Lustre Blue Ice
Y-482	Rustmaster Slate	Y-1860	End. H.P. Medium Gray	Y-3513	Spred Glide-On Gray Velvet	Y-4663	Spred Lustre Smoky White
Y-500	Endurance House Paint Barn Red	Y-1861	End. H.P. Shutter Green	Y-3515	Spred Glide-On Lt. Tangerine	Y-4664	Spred Lustre Plaza Gray
Y-506	Ready Mixed Red Lead	Y-1867	End. H.P. Imperial White	Y-3516	Spred Glide-On Mist Brown	Y-4665	Spred Lustre Pink Haze
Y-534	Silicone Drivall Clear	Y-1870	End. H.P. Deep Turquoise	Y-3519	Spred Glide-On Cascade	Y-4667	Spred Lustre Pebble Beach
Y-555	Gliddencat Enamel Und. White	Y-1871	End. H.P. Dark Blue	Y-3525	Spred Glide-On Tinting White	Y-4672	Spred Lustre Medallion Gold
Y-592	All-Purpose Metallite Alum. Paint	Y-1872	End. H.P. Dark Walnut	Y-3526	Sored Latex H.P. White	Y-4677	Spred Lustre Biscayne Blue
Y-594	Vismatic Green Chalkbd. Coating	Y-1886	End. H.P. Light Canary	Y-3602	Spred Latex H.P. Sunbeam Yel.	Y-4678	Spred Lustre Aquaglow
Y-596	Stock Farm Paint White	Y-1887	End. H.P. Pastel Green	Y-3603	Sored Latex H.P. Taffy	Y-4679	Spred Lustre Sherwood Green
Y-605	Aluminum Asphalt Roof Paint	Y-1892	End. H.P. Non-Chalking White	Y-3606	Spred Latex H.P. Dover Gray	Y-4680	Spred Lustre Dramatone
Y-700	Glid-Tone Natural Wood Filler	Y-2200	Everon House Paint White	Y-3607	Spred Latex H.P. Bayberry		Tinting Base
Y-854	Florenamel Tile Red	Y-2218	Craftsman House Paint White	Y-3608	Sored Latex H.P. Bark	Y-4687	Spred Lustre Int. Tinting Base
Y-871	Florenamel Tile Green	Y-2555	Ripolin Undercoat White	Y-3612	Spred Latex H.P. Evergreen	Y-5701	Brush-Day-Lite A.
Y-874	Florenamel Harbor Gray	Y-2750	End. Velvet H.P. White	Y-3613	Spred Latex H.P. Onyx		Flat Dutch Ivory
Y-875	Florenamel Chateau Gray	Y-2751	End. Velvet H.P. Mayflower Yel.	Y-3615	Sored Latex H.P. Fiesta	Y-5705	Brush-Day-Lite A. Flat Jonquil
Y-876	Florenamel Spice Wood	Y-2752	End. Velvet H.P. Sterling Gray	Y-3616	Sored Latex H.P. Pnto Tan	Y-5707	Brush-Day-Lite A. Flat Mint Green
Y-1201	Glid-Tone Var. Stain, Dark Oak	Y-2754	End. Velvet H.P. Gunmetal	Y-3620	Spred Latex H.P. Cape Cod Red	Y-5710	Brush-Day-Lite A. Flat Ocean Spray
Y-1202	Glid-Tone Varnish Stain Walnut	Y-2756	End. Velvet H.P. Cottage Ivory	Y-3625	Spred H.P. Tinting White		Brush-Day-Lite A.
Y-1203	Glid-Tone Varnish, Stain Mah.	Y-2758	End. Velvet H.P. Granada Red	Y-3651	Sored Prime Coat No. 1	Y-5712	Brush-Day-Lite A. Flat Chelsea Blue
Y-1207	Japalac Brilliant Black	Y-2759	End. Velvet H.P. Shrub Green	Y-4000	Japalac Spray Enamel White	Y-5713	Brush-Day-Lite A. Flat Buhrstone
Y-1208	Japalac Flat Black	Y-2761	End. Velvet H.P. Brown Antique	Y-4001	Japalac Spray Enamel Flat Black	Y-5714	Brush-Day-Lite A. Flat Smoketone
Y-1212	Japalac Bud Green	Y-2764	End. Velvet Shadow Green	Y-4002	Japalac Spray Enamel Gloss Bk.	Y-5718	Brush-Day-Lite A. Flat Tinting White
Y-1217	Japalac Ultra White	Y-2822	Glid-Tone Crystalac Reducer	Y-4003	Japalac Spray Enamel Delphinium		Brush-Day-Lite A. Cloud Pink
Y-1219	Japalac Dawn Gray	Y-2840	Glid-Tone Crystalac	Y-4004	Japalac Spray Enamel Dawn Gray	Y-5743	Brush-Day-Lite A. Flat Taupe
Y-1222	Japalac Screen Black	Y-2842	Xpert Clear Wood Finish	Y-4006	Japalac Spray Enamel Vermilion	Y-5747	Brush-Day-Lite A. Flat Beige
Y-1246	Japalac Rich Blue	Y-2900	Ripolin Ultra White	Y-4008	Japalac Spray Aluminum	Y-5767	Brush-Day-Lite A. Flat Aqua Surf
Y-1250	Japalac Delphinium	Y-2950	Ripolin Semi-Gloss Enamel White	Y-4009	Japalac Spray Gold	Y-5780	Brush-Day-Lite A. Flat Dramatone Tinting Base
Y-1255	Japalac Light Ivory	Y-3000	Spred Flat White	Y-4010	Japalac Spray Clear Plastic		Brush-Day-Lite A. Intermediate Tinting Base
Y-1256	Japalac Vermilion	Y-3050	Craftsman Latex Pt. Alaska White	Y-4011	Japalac Spray Copper Tone	Y-5787	
Y-1260	Japalac Rose Pink	Y-3051	Craftsman Latex Pt. Tusk Ivory	Y-4013	Japalac Spray Enamel Rose Pink		
Y-1263	Japalac Botany Brown	Y-3052	Craftsman Latex Pt. Spearmint	Y-4015	Japalac Spray Enamel Lemon Yel.		
Y-1267	Japalac Ribbon Blue						
Y-1269	Japalac Blue Turquoise						

THE GLIDDEN COMPANY

National Headquarters

900 Union Commerce Building
Cleveland 14, Ohio

SALES OFFICES AND FACTORIES: New York • San Francisco • Los Angeles
Minneapolis • Dallas • Chicago • St. Louis • New Orleans • Cleveland
Atlanta • Portland • Reading • Canada: Toronto and Montreal

Branches in principal cities throughout the United States and Canada.