FILE NAME: .ℕlˑ ĵŝă ó . wYú

DATE: мфpy CŜō

DOC#: . wYмyф

DOCUMENT DESCRIPTIONʏ LyŘdzăűℕȷlˑf I èƎȷŜyŜ Ⓦ2dzℕyƳˑf ! ℕűȷǑfŜ π ! ăōŜăű2ă

VOLUME 19, NUMBER 1

February 1958

AMERICAN

Industrial Hygiene

ASSOCIATION

Journal

PUBLISHED BY

THE WILLIAMS & WILKINS COMPANY

BALTIMORE 2, MARYLAND

C. RECOMMENDED CONTROL PROCEDURES: To prevent exposure to high concentrations of amorphous silica dust, process ventilation and/or enclosure are the best means of control. For some operations a dust respirator approved by the U. S. Bureau of Mines may be satisfactory.

IV. Specific Procedures

A. FIRST AID: None.

B. SPECIAL MEDICAL PROCEDURES:

(1) Preplacement: Clinical and chest radiographic examinations should be made on all persons prior to job assignment.

(2) Periodic: Since there is only limited information about the harmful effects of amorphous silica in industry, exposed personnel should have careful periodic medical examinations, including chest x-ray. Pulmonary function testing may be useful.

(3) Treatment: No satisfactory treatment other than removal from exposure, and therapy for any complicating infection.

V. Literature References

1. Cooper, W. C., et al: Industrial Hygiene Foundation Transaction Bulletin No. 30, 182–194.
2. Drinker, P. and Hatch, T.: Industrial Dust. McGraw-Hill Co., Inc. New York, 1954.
3. Fraser, D. A.: *AMA Arch. of Ind. Hyg. and Occ. Med., 8:* 413, 1953.
4. Lambie, J. S.: *Ind. Med., 7:* 470, 1938.
5. Palicard, A. and Collet, A.: *AMA Arch. of Ind. Hyg. and Occ. Med., 9:* 389, 1954.
6. Schepers, G. W. H., et al: *AMA Arch. of Ind. Health, 16:* 125, 1957; *ibid, 16:* 203, 1957; *ibid, 16:* 280, 1957; *ibid, 16:* 363, 1957; *ibid, 16:* 499, 1957.
7. Smart, R. H. and Anderson, W. M.: *Ind. Med. and Surg., 21:* 509, 1952.
8. Tebbens, B. D. and Beard, R. R.: *AMA Arch. Ind. Health, 16:* 55, 1957.
9. U. S. Public Health Service; California Department of Public Health; Nevada State Health Department; Oregon State Board of Health: Progress Report of Study of Pneumoconiosis Hazards in the Diatomite Processing Industry. 1955.

Asbestos

I. Hygienic Standards

A. RECOMMENDED MAXIMUM ATMOSPHERIC CONCENTRATION (8 hours): 5 million particles per cubic foot of air (MPPCF).[1]

(1) Basis for Recommendation: Experience in industry,[3, 4, 8, 12, 13] and animal experiments.[5, 7]

B. SEVERITY OF HAZARDS:

(1) Health: Long continued inhalation of asbestos dust results in a form of pneumoconiosis known as asbestosis. The primary effect of inhalation is an interstitial pulmonary fibrosis. The disease is characterized by asbestos bodies in the lungs and sputum. Based on roentgenological examinations, asbestosis can be classified as minimal, moderate, and advanced. It is a serious disease in some instances, but more frequently it remains nondisabling for many years, even without appreciable symptoms, as long as some other serious disease does not supervene to cause death.[2] Chief symptoms of advanced asbestosis are variable cough, dyspnea, substernal chest pains, decreased chest expansion, weakness, emaciation, clubbed finger tips, and curved fingernails. Any appreciable decrease in the amount of asbestos dust in the breathing atmosphere will cause a decrease in the incidence and severity of asbestosis. Individual susceptibility varies.[6] There have been reports of an increased incidence of lung cancer in persons with asbestosis.[9]

(2) Fire: None.

C. SHORT EXPOSURE TOLERANCE: Not applicable:

II. Significant Properties

A fibrous magnesium calcium silicate which occurs in various combinations as white, greyish or greenish masses, either compact or of long silky fibers, flax-like and readily separated. About 95% of commerical asbestos is chrysotile, which is derived from serpentine, and is a hydrous magnesium

silicate containing from 12 to 14 per cent water of crystallization.

III. Industrial Hygiene Practice

A. RECOGNITION: The spinning and weaving of asbestos, in combination with other textiles for fire proof and heat resistant cloth, results in dust exposure. It may be used by itself or combined with other materials for valve packings, gaskets, boiler lagging and pipe covering, protective clothing, shielding materials, and as automotive brake linings. In the building industry it is used in the manufacture of asbestos cement products, heat insulating, and fireproofing materials.

B. EVALUATION OF EXPOSURES: Asbestos dust may be sampled with the electrostatic precipitator or by the impinger methed using alcohol or alcohol and water, as the collecting medium,[4, 6] and dust counts made by the standard light field technique.[6] The recommended maximum atmospheric concentration of 5 MPPCF is based upon the impinger sampling procedure.

C. RECOMMENDED CONTROL PROCEDURES: Prevention of asbestosis depends entirely upon preventing exposure to concentrations of dust sufficiently high to produce the characteristic reaction. Enclosure or local exhaust ventilation are the principal means of dust control. U. S. Bureau of Mines approved dust respirators may be worn as protection for some operations.

IV. Specific Procedures

A. FIRST AID: None.

B. SPECIAL MEDICAL PROCEDURES:

(1) Preplacement: Clinical and radiographic chest examinations prior to job assignment.

(2) Periodic: Exposed personnel should have periodic clinical examination for signs and symptoms of asbestosis. These should include examination of the sputum for asbestosis bodies, and chest x-rays of good quality.

(3) Treatment: No satisfactory treatment other than removal from exposure and therapy for any complicating infection.

V. Literature References

1. American Conference of Governmental Industrial Hygienists: *AMA Arch. of Ind. Health, 16:* 261, 1957.
2. Cartier, Paul: *AMA Arch. of Ind. Health, 11:* 204, 1955.
3. Doll, R.: *Brit. J. Ind. Med., 12:* 1955.
4. Dreesen, W. C., et al: Public Health Bulletin No. 241, Supt. of Doc., Washington, D. C., 1938.
5. Drinker, P. and Hatch, T.: Industrial Dust. McGraw-Hill Book Co., Inc. New York, 1954.
6. Fairhall, Lawrence T.: Industrial Toxicology. The Williams & Wilkins Co., Baltimore, Md., 1957.
7. King, E. J., et al: Thorox I, p. 18 1946.
8. Lynch, K. M.: *AMA Arch. of Ind. Health, 11:* 185, 1955.
9. McPheeters, S. B.: *J. Ind. Hyg. & Tox., 18:* 229, 1936.
10. Page, R. T. and Bloomfield, J. J. *Pub. Health Repts. 52:* 1713, 1937.
11. Patty, Frank A.: Industrial Hygiene and Toxicology, Vol. 1. Interscience Publishers, Inc., New York, 1948.
12. Smith, K. W., *AMA Arch. of Ind. Health, 12:* 198, 1955.
13. Vorwald, A. J., et al: *AMA Arch. Ind. Hyg. and Occup. Med. 3:* 1, 1951.

Because of space limitations, it is impossible to list all methods of exposure evaluation. The selections have been made on the basis of current usage, reliability, and applicability to the usual industrial type of exposure. Any specific evaluation and/or control problem will involve professional judgment. This can best be done by professional industrial hygiene personnel.

Respiratory protective devices are commercially available. Their use, however, should be confined to emergency or intermittent exposures and not relied upon as primary means of hazard control.

A relative scale is used for rating the severity of hazards: nil, low, moderate, high, and extra hazardous.

clinical examinations
symptoms of asbes-
ould include exami-
putum for asbestosis
est x-rays of good

satisfactory treat-
n removal from ex-
rapy for any com-
on.

ce of Governmental
ts: *AMA Arch. of*
31, 1957.
MA Arch. of Ind.
955.
Ind. Med., 12: 8,

t al: Public Health
ept. of Doc., Wash-

ATCH, T.: Industrial
l Book Co., Inc.,

ICE T.: Industrial
illiams & Wilkins
., 1957.
Thorox I, p. 188,

MA Arch. of Ind.
55.
.: *J. Ind. Hyg. &*
).
BLOOMFIELD, J. J.:
52: 1713, 1937.
Industrial Hygiene
ol. 1. Interscience
r York, 1948.
IA Arch. of Ind.
55.
l: *AMA Arch. Ind.*
ed. 3: 1, 1951.

re evaluation.
applicability
ntrol problem
industrial hy-

wever, should
rimary means

ute, high, and

HYGIENIC GUIDES COMMITTEE

WILLIAM E. MCCORMICK, *Chairman*
HERVEY B. ELKINS, Ph.D.
DAVID W. FASSETT, M.D.
CLYDE M. BERRY, Ph.D.
H. W. SPEICHER
WILLIAM B. HARRIS
MELVIN W. FIRST, Sc.D.
H. E. STOKINGER, Ph.D.
PAUL D. HALLEY
EDWARD V. HENSON, M.D.

AMERICAN INDUSTRIAL HYGIENE ASSOCIATION
14125 Prevost, Detroit 27, Michigan.

Please send the following number of copies of hygienic Guides at $.25 each:

____Acetaldehyde	____Ethyl Alcohol	____Nitrogen Dioxide
____Acetic Acid	____Ethyl Benzene	____Ozone
____Acetone	____Ethylene Dibromide	____Pentachlorophenol and Sodium Pentachlorophenate
____Acrylonitrile	____Ethylene Glycol Monomethyl Ether	
____Amyl Acetate	____Fluoride-Bearing Dusts and Fumes	____Phenol
____Anhydrous Ammonia		____Phosphoric Acid
____Aniline	____Fluorine	____Pyridine
____Arsine	____Formaldehyde	____Silica (Amorphous)
____Asbestos	____Hydrogen Cyanide	____Silica (Free Silica, Silicon Dioxide)
____Benzene	____Hydrogen Fluoride	
____Beryllium	____Hydrogen Peroxide	____Sulfur Dioxide
____Butyl Alcohol	____Hydrogen Sulfide	____Sulfuric Acid
____Cadmium	____Hydrazine	____Toluene
____Carbon Disulfide	____Lead and its Inorganic Compounds	____Toluene 2,4 Diisocyanate
____Carbon Monoxide	____Mercury	____Trichloroethylene
____Carbon Tetrachloride	____Methyl Alcohol	____1,1,1,—Trichloroethane
____Chromic Acid	____Methyl Bromide	____Uranium (Natural)
____1,2-Dichloroethane	____Methyl Ethyl Ketone	____Vanadium Pentoxide
____Dimethylformamide	____Methylene Dichloride	____Xylene
	____Nickel Carbonyl	____Zinc Oxide

Please send____loose leaf binder(s) for the Hygienic Guides at $1.25 each.

Name _____

Address _____

City _____ Zone ____ State _____

Remittance must accompany orders for less than $2.00. Discount of 20% on orders of five or more Guides; 40% discount on orders of 100 or more Guides.