

NOTICE: If the information herein is not clear, then the
notice is due to the user of the document being filed.

CONFIDENTIAL

(File 46110BJ)
MATERIAL 46110BJ

Feb. 20, 1962

CEMENT, HEAT INSULATING (PLASTIC INSULATION)
FURNISHED BY -

- (A) Baldwin Ehret-Hill, Inc., 500 Klagg Ave, Trenton 2, N J
- (B) Philip Carey Mfg Co., Wayne, at Cooper, Cincinnati 15, Ohio
- (C) Eagle Picher Sales Co., 1355 American Bldg, Cincinnati 1, Ohio
- (D) Johns-Manville, 22 Eighth St, N Y C 16
- (E) Owens-Corning Fiberglass Corp, 717 5th Ave, N Y C 22

ORDER FROM SUPPLIER AS -

- (A) Baldwin #1 Insulating Cement
- (B) MW50 Insulating Cement
- (C) Eagle Picher Super 66 Plastic Insulation
- (D) J-M #50 Insulating Cement
- (E) Owens #60 Insulating Cement

CHARACTERISTICS - (Previous 3407-1)(User:PH) Loose fibrous heat
insulating cement, composed of black mineral wool derived from
slag, asbestos fiber and clay binder. Apply by mixing with water,

Printed in U.S.A.

(Over)

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92

PLAINTIFF'S
EXHIBIT

Wk-74

F

NOTICE: If the film is not clear, please check the quality of the document being scanned.

CONFIDENTIAL

throwing into position by hand, and troweling smooth as desired.
Serviceable to 816 C (1500 F) and is 100% reclaimable for reapplication when a temperature of 816 C (1200 F) has not been exceeded.

APPLICATION - Plastic heat insulating cement for steam turbines and steam piping.

SPECIFY AS : CEMENT 4611081

Issued by Std Dept, Matl Labs, E Pgh,

DOCUMENTS PRODUCED DALLAS COUNTY CASES 3/18/92