HM-CLASS

FLAMMABLE LIQUID

NOS. UN-1993

FLASH POINT _____ DEGREES

HWBU0012363



HM-CLASS

COMBUSTIBLE LIQUID

NOS. NA-1993

FLASHPOINT _____ DEGREES

HWBUI0012365

HM-CLASS

CORROSIVE LIQUID

NOS. UN-1760

FLASHPOINT _____ DEGREES

HWBU0012366


CORROSIVE
8

Allied Signal

BENDIX RESIN PRODUCTS

Friction Materials Division
P.O. Box 238
Troy, N.Y. 12181

WARNING: HAZARDOUS INGREDIENTS: SOLVENT, PHENOL AND/OR FORMALDEHYDE

- Vapor harmful.
- Possible cancer hazard based on tests with laboratory animals. Overexposure may cause cancer risk.
- Causes irritation to skin, eyes, nose and throat.
- May cause allergic skin reaction.

HANDLING:

- Do not get in eyes, on skin, on clothing.
- Use with adequate ventilation.
- Wear protective clothing, safety glasses, and resistant gloves.
- Wash thoroughly after handling.

WASTE DISPOSAL:

Follow federal, state, and local regulations.

FIRST AID:

- Eyes: In case of contact, flush eyes immediately with water for at least 15 minutes. Call a physician.
- Skin: Flush skin with water.

SPILL INFORMATION:

Absorb with suitable absorbant and dispose.

For further information, refer to MATERIAL SAFETY DATA SHEET

300-667/11-85

001

Bendix label 001

HWBUI0012368

Allied Signal

BENDIX RESIN PRODUCTS

Friction Materials Division
P.O. Box 238
Troy, N.Y. 12181

CAUTION:

HAZARDOUS INGREDIENT: PHOSPHORIC ACID

- Causes irritation of skin and eyes upon contact.

HANDLING:

- Do not get in eyes, on skin, on clothing.
- Wear protective clothing, safety glasses, and resistant gloves.
- Wash thoroughly after handling.

WASTE DISPOSAL:

Follow federal, state and local regulations.

FIRST AID:

- Eyes: In case of contact, flush eyes immediately with water for at least 15 minutes. Call a physician.
- Skin: Flush skin with water.

SPILL INFORMATION:

Absorb with suitable absorbant and dispose.

For further information, refer to MATERIAL SAFETY DATA SHEET

300-668/11-85

002

Bendix label 002

HWBUI0012369

Allied Signal

BENDIX RESIN PRODUCTS

Friction Materials Division
P.O. Box 238
Troy, N.Y. 12181

AQUEOUS EMULSION

May cause irritation of skin upon contact.

HANDLING:

- Avoid contact with eyes and prolonged contact with skin.
- Wear protective clothing, safety glasses, and resistant gloves.
- Wash thoroughly after handling.

WASTE DISPOSAL:

Follow federal, state and local regulations.

FIRST AID:

- Eyes: In case of contact, flush eyes immediately with water for at least 15 minutes. Call a physician.
- Skin: Flush skin with water.

SPILL INFORMATION:

Absorb with suitable absorbant and dispose.

For further information, refer to MATERIAL SAFETY DATA SHEET

300-669/11-85

003

Appendix label 003

HWBUI0012370

Bendix label 004



Allied Signal

BENDIX RESIN PRODUCTS

Friction Materials Division
P.O. Box 238
Troy, N.Y. 12181

WARNING:

HAZARDOUS INGREDIENT: FORMALDEHYDE

- Potential cancer hazard based on tests with laboratory animals. Overexposure may create cancer risk.
- Causes irritation to skin, eyes, nose and throat.
- May cause allergic skin reaction.

HANDLING:

- Do not get in eyes, on skin, on clothing.
- Use with adequate ventilation.
- Wear protective clothing, safety glasses, and resistant gloves.
- Wash thoroughly after handling.

WASTE DISPOSAL:

Follow federal, state, and local regulations.

FIRST AID:

- Eyes: In case of contact, flush eyes immediately with water for at least 15 minutes. Call a physician.
- Skin: Flush skin with water.

SPILL INFORMATION:

Absorb with suitable absorbant and dispose.

For further information, refer to MATERIAL SAFETY DATA SHEET

300-665/3-88

005

Bendix label 005

HWBUI0012372

Allied Signal

BENDIX RESIN PRODUCTS

Friction Materials Division
P.O. Box 238
Troy, N.Y. 12181

CAUTION:

HAZARDOUS INGREDIENT: PHENOL

- Causes irritation of skin, eyes, nose and throat.
- May cause allergic skin reaction.

HANDLING:

- Do not get in eyes, on skin, on clothing.
- Use with adequate ventilation.
- Wear protective clothing, safety glasses, and resistant gloves.
- Wash thoroughly after handling.

WASTE DISPOSAL:

- Follow federal, state and local regulations.

FIRST AID:

- Eyes: In case of contact, flush eyes immediately with water for at least 15 minutes. Call a physician.
- Skin: Flush skin with water.

SPILL INFORMATION:

Absorb with suitable absorbant and dispose.

For further information, refer to MATERIAL SAFETY DATA SHEET

300-666/11-85

006

Bendix label 006

HWBUI0012373

Ashland label CS-5190

HWBUI0012374

DO NOT USE WELDING OR CUTTING TORCH ON THIS DRUM (EVEN WHEN EMPTY)

Ashland Chemicals

WARNING! POISON!

- FLAMMABLE LIQUID
- CAUSES EYE AND SKIN IRRITATION
- MAY BE HARMFUL IF INHALED
- MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED OR ABSORBED THROUGH THE SKIN
- CONTAINS METHYL ALCOHOL
- MAY CAUSE ALLERGIC SKIN REACTION

HANDLING & STORAGE:

Vapors form explosive mixtures with air. Keep away from heat, sparks, flame, pilot lights and other sources of ignition. Store in flammable label area. Drum should be grounded and bonded when transferring liquid contents.

Avoid breathing (dust, vapor, mist, gas). Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, impervious gloves and other necessary protective equipment. Wash thoroughly after handling.

Use or store with adequate ventilation. Refer to applicable OSHA regulations. Keep workplace airborne concentrations below legal and recommended limits. Circumstances could require use of respiratory protection.

Do not transfer to unmarked container. Keep container closed. Never use pressure to empty. Empty containers may contain hazardous product residues. Keep closure end up. Loosen closure carefully.

BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS.

FIRST AID:

EYES: Immediately flush with water for at least 15 minutes while lifting upper and lower eyelids. Do not use chemical antidote. Get medical attention immediately.

SKIN: Immediately flush with water for at least 15 minutes. Do not use chemical antidotes. Get medical attention. Remove contaminated clothing and wash before reuse. Discard contaminated shoes.

INHALATION: If affected remove to fresh air. If not breathing, give artificial respiration and get medical attention immediately. If breathing is difficult, get medical attention.

INGESTION: Immediately drink two glasses of water and induce vomiting by either giving ipecac syrup or by placing finger at back of throat. NEVER give anything by mouth to an unconscious person. Get medical attention immediately.

FOR INDUSTRIAL USE ONLY

CS-5190

ASHLAND CHEMICAL COMPANY • DIVISION OF ASHLAND OIL, INC., COLUMBUS, OHIO 43216

24—HOUR EMERGENCY TELEPHONE: 606-324-1133

4/87

Ashland label CS-5270

HWBUI0012375

DO NOT USE WELDING OR CUTTING TORCH ON THIS DRUM (EVEN WHEN EMPTY)

Ashland Chemicals

WARI

HANDLING &
Vapors form ex
sparks, flame, p
flammable label
transferring liqui

Avoid breathing
skin and clothi
gloves and oth
oughly after han

Use or store wit
regulations. Kee
and recommend
spiratory protec

Do not transfer
Never use press
ardous product
carefully.

Keep in full clos
place, preferabl

BEFORE USE,
FOR FURTHE
HEALTH EFFE

CS-5270

WARNING!

- **FLAMMABLE LIQUID**
- **CAUSES EYE IRRITATION**
- **MAY CAUSE SKIN IRRITATION**
- **MAY BE HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH THE SKIN**
- **MAY CAUSE ALLERGIC SKIN OR RESPIRATORY REACTION**

HANDLING & STORAGE:
Vapors form explosive mixtures with air. Keep away from heat, sparks, flame, pilot lights and other sources of ignition. Store in flammable label area. Drum should be grounded and bonded when transferring liquid contents.

Avoid breathing (dust, vapor, mist, gas). Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, impervious gloves and other necessary protective equipment. Wash thoroughly after handling.

Use or store with adequate ventilation. Refer to applicable OSHA regulations. Keep workplace airborne concentrations below legal and recommended limits. Circumstances could require use of respiratory protection.

Do not transfer to unmarked container. Keep container closed. Never use pressure to empty. Empty containers may contain hazardous product residues. Keep closure end up. Loosen closure carefully.

Keep in full closed containers to prevent solvent loss. Store in cool place, preferably below 75°F.

BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS.

FIRST AID:
EYES: Immediately flush with water for at least 15 minutes while lifting upper and lower eyelids. Do not use chemical antidote. Get medical attention immediately.

SKIN: Thoroughly flush with water. If redness or irritation persists, get medical attention. Remove contaminated clothing and wash before reuse. Discard contaminated shoes.

INHALATION: If affected remove to fresh air. If not breathing, give artificial respiration and get medical attention immediately. If breathing is difficult, get medical attention.

INGESTION: Immediately drink two glasses of water and induce vomiting by either giving ipecac syrup or by placing finger at back of throat. NEVER give anything by mouth to an unconscious person. Get medical attention immediately.

FOR INDUSTRIAL USE ONLY

CS-5270

ASHLAND CHEMICAL COMPANY • DIVISION OF ASHLAND OIL, INC., COLUMBUS, OHIO 43216

8/84

24—HOUR EMERGENCY TELEPHONE: 606-324-1133

DO NOT USE WELDING OR CUTTING TORCH ON THIS DRUM (EVEN WHEN EMPTY)

Ashland Chemical

NOTICE: Contains Dipro
Monomethyl Ether, Formal
Cresol, Phenol and Pro
Monomethyl Ether Acetate.
to solvent vapors can irrita
tory tract and cause headac
drowsiness or other nervo
fects.

CAUTION!

- COMBUSTIBLE LIQUID
- CAUSES EYE IRRITATION
- MAY CAUSE SKIN OR RESPIRATORY IRRITATION
- MAY BE HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH THE SKIN
- MAY CAUSE ALLERGIC SKIN REACTION
- MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION

HANDLING & STORAGE:
Keep away from heat and flame. Drum should be grounded and bonded when transferring liquid contents.

Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, impervious gloves and other necessary protective equipment. Wash thoroughly after handling.

Use or store with adequate ventilation. Refer to applicable OSHA regulations. Keep workplace airborne concentrations below legal and recommended limits. Circumstances could require use of respiratory protection.

Do not transfer to unmarked container. Keep container closed. Never use pressure to empty. Empty containers may contain hazardous product residues. Keep closure end up. Loosen closure carefully.

BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS.

FIRST AID:
EYES: Immediately flush with water for at least 15 minutes while lifting upper and lower eyelids. Do not use chemical antidote. If redness or irritation persists, get medical attention.

SKIN: Thoroughly flush with water. If redness or irritation persists, get medical attention. Remove contaminated clothing and wash before reuse. Discard contaminated shoes.

INHALATION: If affected remove to fresh air. If not breathing, give artificial respiration and get medical attention immediately. If breathing is difficult, get medical attention.

INGESTION: Immediately drink two glasses of water and induce vomiting by either giving ipecac syrup or by placing finger at back of throat. NEVER give anything by mouth to an unconscious person. Get medical attention immediately.

FIRE:
In case of fire, use water spray (fog), foam, dry chemical, or CO_2.

SPILL OR LEAK:
Contain spill and keep out of sewer. Absorb with inert material (e.g., dry sand or earth), then place in a chemical waste container for later disposal. Dispose of wastes in accordance with applicable federal, state and local regulations.



DANGER
After this c
been emptie
tain explosiv
vapors and re
cut, puncture
near this con
reuse conta
purpose ur
cially recondi

FOR INDUSTRIAL U

SPA-5986

ASHLAND CHEMICAL, INC. • SUBSIDIARY OF ASHLAND OIL, INC., P.O. BOX 2219, COLUMBUS OHIO 43216

24—HOUR EMERGENCY TELEPHONE: 1-800-274-5263 OR 1-800-ASHLAND

HWBUI0012376

HWBUI0012377

Ashland label SPA-5986

DO NOT USE WELDING OR CUTTING TORCH ON THIS DRUM (EVEN WHEN EMPTY)

Ashland Chemical

NOTICE: Contains Dipropylene Glycol Monomethyl Ether, Formaldehyde, Ortho Cresol, Phenol and Propylene Glycol Monomethyl Ether Acetate. Overexposure to solvent vapors can irritate the respiratory tract and cause headache, dizziness, drowsiness or other nervous system effects.

CAUTION!

- **COMBUSTIBLE LIQUID**
- **CAUSES EYE IRRITATION**
- **MAY CAUSE SKIN OR RESPIRATORY IRRITATION**
- **MAY BE HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH THE SKIN**
- **MAY CAUSE ALLERGIC SKIN REACTION**
- **MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION**



HANDLING & STORAGE:
Keep away from heat and flame. Drum should be grounded and bonded when transferring liquid contents.

Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Wear chemical splash goggles, impervious gloves and other necessary protective equipment. Wash thoroughly after handling.

Use or store with adequate ventilation. Refer to applicable OSHA regulations. Keep workplace airborne concentrations below legal and recommended limits. Circumstances could require use of respiratory protection.

Do not transfer to unmarked container. Keep container closed. Never use pressure to empty. Empty containers may contain hazardous product residues. Keep closure end up. Loosen closure carefully.

BEFORE USE, REVIEW MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION, INCLUDING CHRONIC HEALTH EFFECTS.

FIRST AID:
EYES: Immediately flush with water for at least 15 minutes while lifting upper and lower eyelids. Do not use chemical antidote. If redness or irritation persists, get medical attention.

SKIN: Thoroughly flush with water. If redness or irritation persists, get medical attention. Remove contaminated clothing and wash before reuse. Discard contaminated shoes.

INHALATION: If affected remove to fresh air. If not breathing, give artificial respiration and get medical attention immediately. If breathing is difficult, get medical attention.

INGESTION: Immediately drink two glasses of water and induce vomiting by either giving Ipecac syrup or by placing finger at back of throat. NEVER give anything by mouth to an unconscious person. Get medical attention immediately.

FIRE:
In case of fire, use water spray (fog), foam, dry chemical, or CO_2.

SPILL OR LEAK:
Contain spill and keep out of sewer. Absorb with inert material (e.g., dry sand or earth), then place in a chemical waste container for later disposal. Dispose of wastes in accordance with applicable federal, state and local regulations.

DANGER:
After this container has been emptied, it may contain explosive and harmful vapors and residue. Do not cut, puncture or weld on or near this container. Do not reuse container for any purpose until commercially reconditioned.

FOR INDUSTRIAL USE ONLY

ASHLAND CHEMICAL, INC. • SUBSIDIARY OF ASHLAND OIL, INC., P.O. BOX 2219, COLUMBUS, OHIO 43216

24—HOUR EMERGENCY TELEPHONE: 1-800-274-5263 OR 1-800-ASHLAND

Bendix I.D. Label
(all boxes)

FROM:

Green Island, New York 12183

Bendix

Friction Materials Division

ALLIED SIGNAL - CERTIFIED
12730 WESTPORT ROAD
LOUISVILLE , KY, 40255

Bendix I.D. Label
(parts containing asbestos)

DANGER

CONTAINS ASBESTOS FIBERS

AVOID CREATING DUST

CANCER AND LUNG DISEASE HAZARD

Bendix I.D. Label
(non-asbestos parts)

CAUTION

AVOID CREATING OR BREATHING DUST

CONTAINS HAZARDOUS SUBSTANCES

WHICH MAY CAUSE LUNG INJURY