{200,000 gal
4,000 bbl/yr. — low pressure cable impr[illegible] & capacitor
100 visc 100 c low [illegible]

{1 M GAL
polybutene
& high vis mineral oil 2300 oil
2300 visc mineral oil 100 c. high vis
high pressure cable

Mobil Therm [illegible] HT oil
75,000 gal. Texas City.

Irv Lanier Amoco polybutene
C Ray Irons - Mobil low pressure cable oil
Jack Melchoire Sun Tex
~~Jack~~ Frank McCowan Sun [illegible]
Sun has 2300 high vis oil
Witco

Al Gates Phil Elec

Kinney GE would save about
4 [illegible] $5,000/yr [illegible] using 1260 vs 1254
~~Send Kinney statement that discontinuance of 1260 and adoption of 1254 is in right direction to alleviate pollution problem.~~
Write Raab that due to PCB prob.
we seek to discont. 1260

DSW 201701

STLCOPCB4059768

Monsanto

PRODUCT SPECIFICATION

MONSANTO INDUSTRIAL CHEMICALS CO.

PRODUCT Alkylate 225 CODE NO. 0510-225

GRADE Biodegradable DATE EFFECTIVE August, 1972

A water-white, iridescent, mobile, liquid, linear alkylbenzene having an average molecular weight of 238-248.

CHARACTERISTICS	LIMITS
Appearance	Water-white liquid
Color	15 APHA maximum
Turbidity	2 APHA maximum
Residue by volume	0.005 ml maximum
Water	100 ppm maximum
Bromine number	0.1 maximum
Organic chlorides	100 ppm maximum
Unsulfonatable oils	1.5% maximum
Homolog Distribution:	
C_{10} and less	15% maximum
$C_{10} + C_{11}$	30 - 50%
$C_{13} + C_{14}$	30% maximum
C_{14} and greater	10% maximum
Average molecular weight	238 - 248
2-Phenyl isomer	25% maximum

DSW 201702

STLCOPCB4059769