PLAINTIFF'S EXHIBIT
WH-883
PENGAD-Bayonne, N.J.

From : A-Unit Mfg. Engrg.
WIN :
Date : May 17, 1976
Subject: Substitutions for Asbestos

TO: A. M. Johnson, G-310
R. C. Shollenberger, A-203
M. P. Whittington, O-105
A. Glaudel, O-200
P. Weil, G-306
G. Wells, B-105
E. McCoy, U-101

RECEIVED
MAY 19 1976
SAFETY DEPT.

MISS. IN RE. ABRAMS et al 1993

Attached are specifications of two new products that will be used by L.T. Div. These products will replace existing material now stocked.

1. The .375 Braided Asbestos Sleeving, ID-951934, PDS-? will be replaced with .375 Braided Fiber Glass, ID-951953.

2. The 1.25 wide Asbestos Tape, ID-952014, PDS-41511AA, will be replaced with a 1.50 wide woven fiver glass tape, ID-952017.

Action Required

A. M. Johnson — Phase out existing stocks of asbestos products and cancel orders now pending. Order new fiber glass products as required for CEST.

R.Shollenberger — Remove the existing asbestos sleeving and tape products from your active files and assign PDS numbers to the new products.

W. Davis — Continue using the existing asbestos products till stocks are depleted - fiber glass products will then be available. Note that because asbestos sleeving is out of stock arrangements have been made thru Ledgers and Purchasing to acquire fiber glass sleeving from Pacor. This sleeving will be in Receiving Dept. on 5-17-76, P.O. 51-1-661621.

R. C. Wynn, Mfg. Engr.
A-Unit Erection & Test

FORM 3504 U

TENTH AND NORRIS STREETS • PHILADELPHIA, PENNA. 19122 • (215) 769-4545

Style 8411, 100% Fiberglass Braided Sleeving meets the requirements of Coast Guard Specification for incombustible materials, #164.009.

Style 8411 is specifically designed as replacement for insulation jacketing and gasketing material where the temperature of the insulated surface is between 125° F and 1000°F.

This Braided Sleeving is non-itching, non-irritating and eliminates the health hazards associated with asbestos.

MISC. IN RE: ABRAMS et al. 1993

PROPERTY DATA

STYLE	8411
Yield (Yards per pound)	20
Wall Thickness	30 mils
Inside Diameter	1/4"
Breaking Strength (pounds)	
Weave	Plain

NEW. ID- 951935

WILL REPLACE ASB. SLEEVING

28001937

Branch Office
1737 Fifth Street
Bethlehem, Penna. 18017
(215) 691-8510

Fabrication Department
6th & Berks Sts.
Phila., Pa. 19122
(215) -4545

Branch Office
74 Parker Avenue
Trenton, New Jersey 08610
(609) 695-2166

951934.

TENTH AND NORRIS STREETS - PHILADELPHIA, PENNA. 19122 - (215) 769-4545

MISS. - IN RE: ABRAMS, et al. 1993

WOVEN LAGGING TAPE

WOVEN EDGE - 100% FIBER GLASS

STYLE #7628

Thread Count	32 X 32 ± 2
Ounces/Square Yard	5.80 ± 10%
Thickness Inches	0.007 ± .001
Breaking Strength (Warp)	140 lbs. minimum

Meets Military Specification MIL-C-20079D
Type 2 Class 1

WIDTH	ROLLS PER CARTON (50 YARDS PER ROLL)
1-1/2"	32
2"	24
2-1/2"	20
3"	16
4"	12
6"	8

NOTE: Orders accepted for full cartons only.

MINIMUM ORDER: 1 Carton

CARTON DIMENSIONS: 25 1/4" X 4 1/4" X 8 1/2"

GROSS WEIGHT: 28 lbs.

NEW ID - 952017

28001938

WILL REPLACE 1.125 ASB. TAPE

Branch Office
1737 Fifth Street
Bethlehem, Penna. 18017

Fabrication Department
6th & Berks Sts
Phila., Penna. 19122

Branch Office
74 Parker Avenue
Trenton, New Jersey 08610