

The specification for a safe stage should be based not on the industrial or medical test and its result but on the loading curve. If the operation steps of rapidly, the practical loading is less,

There is a likelihood that a control action will not attack the control plane as it is not at all a series of tests at the control surface will almost always (loading) effect.

(c) The test with effector is conducted in a good manner and will be put in the standard testing program

7. Plan a series of tests with force in a good manner (all stages and find out the effect of the communication of force at different points of time is critical.

Let Keynes - & think
Public relations succeed
you a portable discussion
for this - ~~Free~~

12

and cycle - instead of the world before being
now - we are off of the disarming cycle for as
this should be determined & eventually - instead of initial stages
(Period between expansion to total?)

(5) Substantiated cause all elements of the language since

will there be a
is to state
one for
and lead total

George Colver
for Mrs Henderson

t of the future
Laurel Crampton

and cycle - with
effect of the de
this should be determined experimentally
(Reused between exposure -

(5) Established the causal character

The specification for a ca
not on our standard of initial
the leaching curve. If the extraction
logarithmic is low.

There is a likelihood that
attacked the colored glass as did the
tests at the Cavet Conference with

(6) The test with coffee as
which should be part of the

7. Plan a series of tests with
and find out the extent of the
at different levels of time

00000029

✓
X