

1975

PLAINTIFF'S EXHIBIT

GP-1740

Superior

SGP 0023280

DT
IN

DT
MF
PP
UA
OF
AI
MF
CS
TC
CC


SGP 0023281

DT DOCUMENT INDEX

DT	Document Index	3
MR	Manufacturer Testing Facilities	3-4
PP	Product Presentation	5
UA	Uses, Applications, Limitations	5
OP	Overall Production Place	6-27
AI	Construction, Assembly, Installation	14-27
MF	Materials, Finishes	28-34
CS	Coatings, Surfaces	28-34
TC	Technical Support	35
CC	Code Acceptability, Certification	35

Georgia-Pacific's Gypsum Product Development and Technical Service laboratory is located at Tigard, Oregon. This is where new products such as Pre-Dec®, tile backer board, sound deadening board, Dens-Cote®, veneer plaster, Denscal™, Densite®, and Firestop® had their beginnings. The G-P family of joint system products, the G-P sound control systems and the G-P fire rated systems, including the shaft wall systems, were also developed here. The increase in multi-family living has made fire safety and sound privacy of utmost importance.

The technical personnel at the Gypsum Lab also deal with quality and production problems. The effort to offer reliable products at the lowest possible cost is a never-ending task. Georgia-Pacific must be technically competent in these continually changing times in order to be able to furnish the products required by the construction industry.



MR MANUFACTURER

MINING AND MANUFACTURING
GYPSUM AND GYPSUM PRODUCTS



PP F

GEC

Georg
dome
tered
owne
grate
trees
hardt
worki
etc.),
help
mark
wood
and b
Bene
natur
cerar
sales
cente
and C
fleets
with
throu
right
pine
the F
and
with
the G
Geo



UA


LI

• C
loa
are
mc
usi

PP PRODUCT PRESENTATION

GEORGIA-PACIFIC—THE COMPANY

Georgia-Pacific began its history distributing lumber domestically and abroad from the South, then entered in the field of plywood manufacture and timber ownership and management. It believed in integrated manufacturing and each phase of using a tree's residue produced something new... lumber, hardboard, particleboard, pulp, paper (fine papers, working papers, containers, tissues, food board, etc.), chemicals from paper residues, chemicals to help make wood products, chemicals for broad market sales, new kinds of plywood, recycling of wood and chemical materials, development of new and better trees, better timber management methods. Beneath the soil... gypsum (gypsum products), natural gas, metallurgical and other coal, oil, silica, ceramic clays and many other minerals. It is also a sales company with 139 full service distribution centers in every major market in the United States and Canada. It is also a transportation company with fleets of trucks and rail cars to ensure good service with good products. Georgia-Pacific owns timber rights in Indonesia and the Republic of the Philippines. It also manufactures wood products in Brazil, the Philippines and Indonesia, selling to both Asia and America. G-P is a highly decentralized company with over 36,000 employees working in 47 states, the District of Columbia and several foreign countries. Georgia-Pacific... the growth company.



UA USES, APPLICATIONS

LIMITATIONS







- Georgia-Pacific interior gypsumboards are non-load bearing panels.
- Regular Gypsumboard panels are not recommended for use under extremely moist conditions. G-P Tile Backer Board is to be used in bathrooms or other high moisture areas.

- 1/4" gypsumboard should only be used as an application over existing walls or as the first layer in a sound rated system.
- Because of the limitations of manufacturing equipment, the maximum length available in gypsumboard is 16 feet.

SGP 0023284

OP OVERALL PRODUCT, IN PLACE

GYPSUM BOARD NAILS & SCREWS SELECTOR GUIDE

	Description	Applications
	1 1/4" GWB-54 Annular Ring Nail 12 1/2 ga.; with a slight taper to a small fillet at shank. Bright finish; med. diamond pt.	1/2", 3/8" and 1/4" Gypsum board, 1/2" and 3/8" Gypsum Backer Board to wood frame
	1 1/4" Annular Ring Nail (Same as GWB-54 except for length)	3/8" Gypsum board to wood frame
	2 1/2" 7d nail 13 ga., 1/4" diamond head	3/8" Firestop Gypsum board face layers over 1/2" Sound Deadening Board or 2 layers 3/8" Firestop to Wood Studs
	1 1/4" 6d Nail 13 ga., 1/4" diamond head	3/8" and 1/4" Gypsum board over existing surface, wood frame
	1 1/4" 6d Nail 13 ga., 1/4" diamond head	3/8" Firestop Gypsum board to wood frame
	5/8" 5d Nail 13 1/2 ga., 1/4" diamond head	1/2" Firestop Gypsum board to wood frame
	1 1/4" Matching Color Head Nail (Steel)	Predecorated Gypsum board to wood frame over existing surface, wood frame
	1 1/4" Matching Color Head Nail (Steel)	
	1 1/4" Matching Color Head Nail (Brass)	Predecorated Gypsum board (colors) to wood frame
	1" Gypsum board Screw Type S	Single Layer Gypsum board to 25 Gauge Steel Studs. Gypsum board to Resilient Channel. Gypsum board to Metal Furring.
	1 1/4" Gypsum board Screw Type S	1" core units to L Runner in 2" Solid and Semi-Solid Partition Systems
	1 1/4" Gypsum board Screw Type S	Double-Layer Gypsum board to 25 gauge Steel Studs. Double-Layer Gypsum board to Metal Furring.
	1 1/4" Gypsum board Screw Type S	Double-Layer Gypsum board
	1" Gypsum board Screw Type S-12. Also available in 3/4", 1 1/4" and 1 3/4" lengths	For single or multi-layer application of Gypsum board to heavy gauge steel (up to 12 gauge).
	1 1/4" Gypsum board Screw Type W	Single Layer Gypsum board to Wood Framing.
	1 1/2" Gypsum board Screw Type G	Gypsum board to Gypsum Ribs in Semi-Solid Partition Systems
	1 3/4" Gypsum board Screw Type G	
	1 1/4" Gypsum board Screw Type S Trim Head	Wood trim over single layer of Gypsum board on 25 gauge Steel Studs
	2 1/4" Gypsum board Screw Type S Trim Head	Wood trim over double layer Gypsum board on 25 gauge Steel Studs
	3/8" Gypsum board Screw S-12 Pan-Head	Metal Door frame to 12 gauge (max.) Steel Studs. Metal Studs to Metal Runners.
	3/4" Type S-18 Oval Head. Also available in 1/2", 1 1/4" & 1 3/4" lengths	Door hinges to door frame and aluminum components to metal.

Horizontal and Vertical Application: TYPE S—Metal studs or furring spaced 24" on center. Screws should be spaced 12" on center unless otherwise noted in the detailed assemblies shown in Georgia-Pacific literature.

TYPE G—Laminated systems and other gypsum to gypsum applications

TYPE W—Wood studs 16" or 24" on center. Screws should be spaced 12" on center unless otherwise noted in the detailed assemblies shown in G-P literature.

Selection of the proper nail for each application is extremely important, particularly for fire-rated construction. The nails recommended comply with performance standards adopted by the Gypsum Association.

G-P GYPSUM BOARD OR DENS-COTE VENEER PLASTER SYSTEMS.

The following tables are summaries only, based on tests at Underwriters' Lab., National Bureau of Standards, Univ. of Calif., Ohio State Univ., Geiger and Hamme, Riverbank Lab. and/or Ohio Research Corp. sponsored by the G-P Gypsum Division, Gypsum Association, or others. Fire rating, weight, and sound characteristics are based on a combination of specific details as tested and published. Where carpet and pad is used in sound tests, carpet is 44 oz. and pad 40 oz. weights. All systems are ranked by STC number in each category. Fire tests conducted according to ASTM E119. Sound tests conducted according to E90.

COST INDEX BASIS: For wood and gypsum partitions, 100 is for 2x4 studs, 16" o.c., 1/2" Regular Gypsum board each side. For metal stud partitions, 100 is for 2 1/2" studs, 24" o.c., 5/8" Firestop each side. Other assemblies are rated against those two. Allow for local differences in labor and material costs.

FIRE HAZARD (FLAME SPREAD) CLASSIFICATION: Official Underwriters' Tests. 1/2" and 5/8" Firestop, 10-15 (Labeled); 3/8", 1/2" and 5/8" G-P, 10-15 (Not Labeled). More complete listings and details are available. Tests conducted according to ASTM E84.

Inconsistencies in test results are due to tests over a period of many years and variations in laboratory facilities.

1. STC under sound characteristics is Sound Transmission Class.
2. Official Underwriters' Tests have proven joint finishing is not required for the rating in assemblies of Firestop under certain conditions.
3. Under "Building Code Approvals" (A) refers to International Conference of Building Officials; (B) refers to Southern Building Code Congress; (C) refers to Building Officials Conference of America. Additional approvals requested. Check with local building officials for verification of approvals as may be required.
4. Not all code jurisdictions belong to Model Code Groups. Therefore, we advise consultation with local building officials if acceptance of these test results are in doubt.

Combustible Assemblies: For all 45 minute and 1 hour ratings 5/8" structural interior plywood or particleboard underlayment grade, over building paper, over 1/2" structural interior plywood with exterior glue CD grade may be used over the wood joists with ceilings as detailed.

Noncombustible Assemblies: Ceilings for all 1 hour, 1 1/2 hour and 2 hour incombustible floor and ceiling construction assemblies with 2" or 2 1/2" concrete floor on metal lath over steel bar joints, unless otherwise specified, may be directly attached or suspended.

Firestop is listed by Underwriters for U.S.A. and Canada and carries the UL Label for 45 minutes, 1, 2 and 3 hour Fire Resistance in various designs and with a Fire Hazard Classification of Flame spread 15, fuel contributed 15, smoke developed 0.

SOUND CHARACTERISTICS: References: Geiger and Hamme, Inc.; Riverbank Labs; Kodaras. More complete listings and details are available. Inconsistencies in test results are due to tests over a period of many years and variations in laboratory facilities. All sound rated assemblies require caulking top and bottom, and other locations where sound leaks may develop.

TEC
WAL
G-P

G-P
Syr

W.C.

SGP 0023285

TECHNICAL DATA

WALLS AND COLUMN CONSTRUCTION

G-P GYPSUM BOARD OR DENS-COTE VENEER PLASTER SYSTEM

G-P Syst.	Fire Resist.		Sound Trans.		Cost Index	Construction		References	
	Rating	Test Refer.	STC	Test Refer.		Part. Thick-ness	Weight per Sq. Ft.	No. Details	Page

WOOD PARTITIONS (STUDS—2 x 4, 16" O.C.)

080	1 hr.	EST	31	EST		4 1/4"	5.2	3/8" Gypsum board Both Sides	—
082	1 hr.	EST	32	EST		4 1/4"	5.9	1/2" G-P Gypsum board Both Sides	—
084	1 1/2 hr.	U. 317	32	EST		4 1/2"	5.9	1/2" Firestop* Both Sides	—
086	1 hr.	U. 305 (U.L. 5)	34	OR-64-8		4 3/4"	7.0	5/8" Firestop* Both Sides Basic 1 Hr. Fire Rated Wall	—
087	1 hr.	U. 305 (U.L. 5)	34	OR-64-8		4 3/4"	7.0	5/8" G-P Tile Backer Board Both Sides	—
090	1 1/2 hr.	EST	37	CR-64-11		5 1/4"	9.5	5/8" Firestop, 1 Layer, One Side, 2 Layers Other Side	—
094	1 hr.	G.A.	38	EST		4 7/8"	8.2	3/8" G-P Gypsum board, 2 Layers, Both Sides	—
096	1 hr.	G.A.	39	NBS		5 3/8"	9.9	1/2" G-P Gypsum board, 2 Layers, Both Sides	—
098	2 hr.	T-194	41	OR-64-12		5 7/8"	12.0	5/8" Firestop, 2 Layers, Both Sides	—

WOOD PARTITIONS GYPSUM SOUND DEADENING BOARD—1/4" THICK

100	1 hr.	U. 312 (U.L. 30)	45	BW-27-ST		4 7/8"	7.96	1/2" Firestop, 1 Layer Strip Laminated Over 1/4" Gypsum Sound Deadening Board, 2 Sides	—
102	1 hr.	U. 312 (U.L. 30)	47	BW-28-ST		5 1/4"	8.3	5/8" Firestop, 1 Layer Laminated over 1/4" Gypsum Sound Deadening Board, Both Sides	—
104	1 hr.	EST	47	BW-29-ST		6 7/8"	8.79	1/2" Firestop, 1 Layer over 1/4" Sound Deadening Board, Both Sides Laminated, Staggered Studs	—
106	1 hr.	U. 312 (U.L. 30)	50	BW-35-ST		5 1/8"	8.7	5/8" Firestop, 1 Layer Strip Laminated over 1/4" Gypsum Sound Deadening Board, 2 Sides, 2" Insulation	—
108	1 hr.	EST	52	BW-30-ST		6 7/8"	8.92	1/2" Firestop, 1 Layer over 1/4" Gypsum Sound Deadening Board, 2 Sides, 2" Insulation, Staggered Studs	—

See Page 6 for Notes

*Firestop is a registered trademark of Georgia-Pacific Corporation.

OP OVERALL PRODUCT, IN PLACE

G-P Syst. =	Fire Resist.		Sound Trans.		Cost Index	Construction			References	
	Rating	Test Refer.	STC	Test Refer.		Part. Thick- ness	Weight per Sq. Ft.	Wall Surface	Bldg. Code App.	Detail Info Page
WOOD STUDS/RESILIENT CHANNELS										
112	1 hr.	T-3127	44	OR-64-7	135	5 1/8"	6.3	5/8" Firestop*, 1 Layer Nailed 1 Side, 1 Layer on Resilient furring other side	AEC	16
114	1 1/2 hr.	EST	48	OR-64-15	155	5 3/4"	8.8	5/8" Firestop, 2 Layer 1 Side, 1 Layer on Resilient furring other side	—	16
WOOD STUDS/RESILIENT CHANNELS INSULATING BLANKETS										
116	1 hr.	T-3127	50	OR-64-16	150	5 1/8"	6.4	5/8" Firestop, 1 Layer Nailed 1 Side, 1 Layer on Resilient furring other side, plus fiberglass insulation in stud space	AEC	16
STAGGERED STUD WALLS										
150	1 1/2 hr.	EST	43	EST	175	7 5/8"	11.0	1/2" G-P Regular, 2 layers, Both Sides	—	—
152	2 hrs.	EST	47	TL-69-210	191	8 1/8"	12.7	5/8" Firestop, 2 layers, Both Sides	—	—
154	1 hr.	Based on U. 305 (U.L. 5)	48	EST	140	6 7/8"	7.0	5/8" Firestop, 1 layer each side, 2x6 plate, 2" insulation	—	—
DOUBLE WOOD STUDS										
108	1 hr.	EST	50	BW-31-ST	225	10"	9.14	1/2" Firestop, 1 Layer Laminated over 1/4" Gypsum Sound Deadening Board, Both Sides, Double Studs	AEC	—
109	1 hr.	EST	55	BW-32-ST	240	10"	9.29	1/2" Firestop, 1 Layer Laminated over 1/4" Gypsum Sound Deadening Board, 2 Sides, 2" Insulation, Double Studs	—	15
120	1 hr.	EST	46	EST	215	9 1/4"	7.5	5/8" Firestop, 1 layer each side double row of studs 1" apart on separate 2x4 plates, insulation in stud space	—	—
125	2 hrs.	WP297 FM	57	RAL	—	11 1/2"	—	1/2" Firestop Gypsum board, 2 layers face each side of wall, 1 layer attached to each stud inside, with 1" space between inside layers Lot Line Wall	—	17
WOOD STUDS/FIBER SOUND BOARD										
113	1 hr.	T-3006	46	OR-64-73	105	5 5/8"	8.5	5/8" Firestop, 1 layer over 1/2" Fiber Sound Deadening Board, Both Sides	—	15

See Page 6 for Notes

*Firestop is a registered trademark of Georgia-Pacific Corporation.

SGP 0023287

G-P Syst. =	Fire Resist.		Sound Trans.		Cost Index	Construction			References	
	Rating	Test Refer.	STC	Test Refer.		Part. Thick- ness	Weight per Sq. Ft.	Wall Surface	Bldg. Code App	Detail Info Page
EXTERIOR WALLS										
500	2 hrs.	U302 (U.L. 23)	50	EST	—	5 3⁄8"	—	5⁄8" Firestop, 2 layers interior; 1⁄2" Gypsum Sheathing, Brick Exterior	ABC	—
501	1 hr.	U305 (U.L. 5)	—	—	—	4 3⁄4" plus siding	—	5⁄8" Firestop (Interior), 5⁄8" Firestop Tile Backer (Exterior) Wood Siding	—	—
SOLID GYPSUM BOARD PARTITIONS (NON-LOADBEARING)										
230	2 hrs.	G.A.	36	G.A.	90	2"	8.1	1⁄2" Firestop, 1 Layer Each Side, 1" Coreboard, height limit 9 ft. based on L/120, 5 lbs. PSF	ABC	17
232	2 hrs.	G.A.	36	G.A.	95	2"	8.1	1⁄2" G-P Gypsum board, 1 Layer Each Side, 1" Laminated Coreboard, height limit 9 ft. based on L/120, 5 lbs. PSF	ABC	—
234	2 hrs.	EST	37	G.A.	100	2 1⁄4"	9.1	5⁄8" Firestop, 1 Layer Each Side, 1" Coreboard	—	—
DOUBLE SOLID GYPSUM BOARD PARTITIONS (NON-LOADBEARING)										
224	2 hrs.	U502 (U.L. 7)	35	TR-57-42	—	4"	13.4	1⁄2" Firestop, 2 Layers Each Side, 1" Rib Coreboard	ABC	—
222	3 hrs.	U501 (U.L. 5)	40	TR-57-43	—	5"	13.4	5⁄8" Firestop, 2 Layers Each Side, 1" Rib Coreboard	ABC	—
200	2 hrs.	T-2575	47	OR-64-39	—	6"	13	1⁄2" G-P Gypsumboard over 1" Coreboard Each Side of 3" air space	ABC	17
TRIPLE SOLID GYPSUM BOARD PARTITIONS										
204	3 hrs.	EST	51	OR-64-58	—	6"	17	1⁄2" G-P Gypsum board, 1 Layer over 1" Coreboard both sides of 3" air space with 1" Coreboard	—	—
202	3 hrs.	EST	57	OR-64-59	—	6"	17.2	1⁄2" G-P Gypsum board, 1 Layer over 1" Coreb'd. Each side of 3" air space with 1" Coreb'd centered in air space and fiberglass insulation in space on 1 side	—	13
TRIPLE SOLID GYPSUM BOARD PARTITIONS (NON-LOADBEARING)										
206	2 hrs.	T-4958	—	—	—	2 5⁄8"	10.5	G-P 1 5⁄8" core unit plus two face layer 1⁄2" G-P regular screw-laminated, track and vertical "T" splines	—	—
208	2 hrs. Chase Wall	T-4991	—	—	—	7 3⁄4"	9.0	G-P 1 5⁄8" core unit, angle runners, 2 1⁄2" metal studs, one facing layer of 5⁄8" Firestop screwed to studs	—	—
210	1 1⁄2 hr.	T-4982	—	—	—	2 1⁄4"	8.4	G-P 1 5⁄8" core unit, plus face layer 5⁄8" Firestop screw-laminated. Track and vertical "T" splines on 24" centers	—	—

See Page 6 for Notes

SGP 0023288

OP OVERALL PRODUCT, IN PLACE

G-P Syst. =	Fire Resist.		Sound Trans.		Cost Index	Construction		References		
	Rating	Test Refer.	STC	Test Refer.		Part. Thick- ness	Weight per Sq. Ft.	Wall Surface	Divi. Code App.	Detail Info Page
METAL STUDS/INSULATING BLANKETS										
328	1 hr.	T-5316	41	OR-66-5	110	3½"	4.3	½" Firestop®, 1 layer each side, 2½" fiberglass insul. in stud space, 2½" studs, 24" o.c.	—	19
300	1 hr.	T-2316	44	OR-64-81	100	2⅞"	5.0	⅝" Firestop, plus 2" fiberglass insul. in stud space, 1⅝" studs	ABC	19
316	1 hr.	T-4848	48	OR-66-6	100	5⅛"	7.0	½" Firestop, 1 layer 1 side, ½" regular G-P Gypsum board, 2 layers other side (insulation in cavity for STC), 3⅝" studs	—	21
330	1 hr.	T-2316	48	OR-64-80	105	3⅜"	7.2	⅝" Firestop, 1 layer 1 side, 2 layers other side, 2" fiberglass insul. in stud space, 1⅝" studs	ABC	—
334	1 hr.	EST	48	OR-66-6	100	4"	6.3	½" Firestop, 1 layer 1 side, 2 layers other side plus 2" fiberglass insul. in stud space, 2½" studs	—	—
310	2 hrs.	T-3218	48	BW-12-FT	105	4½"	8.0	½" Firestop, 2 layers each side, STC based on 2" insul. in stud space, 2½" studs	ABC	20
318	1½ hrs.	T-3126	50	OR-64-51	100	5½"	8.0	⅝" Firestop, 1 layer 1 side, 2 layers other side plus 3" fiberglass insul. in stud space, 3⅝" studs	—	21
324	2 hrs.	T-2557	52	OR-64-50	100	6⅛"	11.1	⅝" Firestop, 2 layers both sides plus 2" fiberglass in stud space, 3⅝" studs	ABC	22
METAL STUDS, GYPSUM SOUND DEADENING BOARD										
304	1 hr.	U410 (U.L. 32))	45	BW-16-FT	100	4"	7.0	½" Firestop, 1 layer, laminated over ¼" S.D. Board, both sides screw attached, 2½" studs	ABC	19
306	1 hr.	U410 (U.L. 32))	50	BW-17-FT	100	4"	7.1	½" Firestop, both sides, 1 layer, laminated to ¼" S.D. Board, screw attached, 2" fiberglass friction fit in stud space, 2½" studs	ABC	19
308	1 hr.	U410 (U.L. 32))	54	BW-18-FT	105	4½"	8.1	⅝" Firestop, both sides, 1 layer laminated to ¼" S.D. Board, screw attached, 2" fiberglass friction fit in stud space, 2½" studs	—	19
METAL STUDS/FIBER SOUND DEADENING BOARD										
320	1 hr.	EST	44	OR-65-10	105	5⅜"	5.8	⅝" Firestop, 1 layer 1 side, other side, 1 layer over ½" fiber S.D. Board, 3⅝" studs	—	21
336	1 hr.	EST	49	OR-65-11	105	5⅝"	—	⅝" Firestop, 1 layer over ½" fiber S.D. Board, both sides 3⅝" studs	—	—
STEEL STUD CHASE WALL (1½" METAL STUDS 24" O.C.—6" x 12"—1½" GYPSUMBOARD SPACERS)										
326	1 hr.	EST	47	BW-33ST	—	7½"	6.7	½" Firestop, 1 layer laminated over ¼" S.D. Board, both sides	ABC	22
327	1 hr.	EST	52	BW-34ST	—	7½"	6.9	½" Firestop, 1 layer laminated over ¼" S.D. Board both sides, plus 2" insul. in stud space	ABC	—

METAL STUD PARTITIONS

340	35 min.	EST	35	OR-65-2	3½"	—	½" G-P Gypsum board, 1 layer each side, 2½" studs
302	1 hr.	T-2316	35	TL-62-72	2⅞"	5.2	⅝" Firestop®, 1 layer each side, 1⅝" studs
340	1 hr.	T-2898	35	OR-64-65	3¾"	—	⅝" Firestop, Eternawall™, 1 layer each side, 2½" studs
344	1 hr.	T-2069	39	OR-63-1	3¾"	—	⅝" Firestop, 1 layer each side, 2½" studs
346	1 hr.	T-2016	42	OR-63-11	4⅝"	6.0	⅝" Firestop, 1 layer each side, 3⅝" studs
342	1½ hr.	EST	43	OR-63-2	4⅝"	7.5	⅝" Firestop, 1 layer 1 side, 2 layers other side, 2½" studs
348	1½ hr.	EST	43	OR-64-32	5½"	8.0	⅝" Firestop, 1 layer 1 side, 2 layers other side, 3⅝" studs
344	2 hr.	T-2557	46	EST	5"	10.4	⅝" Firestop, 2 layers, 2 sides, 2½" studs
342	2 hr.	T-2557	47	OR-64-52	6⅝"	11.0	⅝" Firestop, 2 layers, 2 sides, 3⅝" studs
344	2 hr.	T-2406	47	EST	6⅝"	10.4	⅝" Firestop, 2 layers, 2 sides (face layer—Eternawall), 3⅝" studs

STEEL COLUMN FIRESTOPPING

—	1 hr.	G.A.	—	—	—	—	½" G-P Gypsum board, 2 layers
—	1 hr.	EST	—	—	—	—	⅝" Firestop, 1 layer
—	1½ hr.	G.A.	—	—	—	—	½" G-P Gypsum board, 3 layers
—	2 hr.	X520 (U.L. 20)	—	—	—	—	½" Firestop, 1 layer
—	2 hr.	X517 (U.L. 8)	—	—	—	—	⅝" Firestop, 2 layers
—	3 hr.	X513 (U.L. 39)	—	—	—	—	½" Firestop, 2 layers
—	3 hr.	X509 (U.L. 18)	—	—	—	—	⅝" Firestop, 3 layers
—	4 hr.	X501 (U.L. 26)	—	—	—	—	⅝" Firestop, 4 layers

See Page 6 for Notes

OP OVERALL PRODUCT, IN PLACE

SOUND CONTROL AND FIRE RESISTANCE TECHNICAL DATA

G-P Inst.		Weight Lb./ Sq. Ft.	Sound Rating		Fire Resistance		Bldg. Code App.	Detail Info Page
			Rating	Test Ref.	Rating	Test Ref.*		
WOOD JOISTS 16' O.C. FINISHED FLOOR ON ROUGH SUBFLOOR, EXCEPT AS NOTED								
400	3/8" G-P Regular, 1 layer	—	—	—	15 min.	—	ABC	—
401	1/2" G-P Regular, 1 layer	11.4	—	—	25 min.	—	ABC	—
402	1/2" Firestop*, 1 layer applied to metal furring channel 16" o.c. with 1" x 6" T. & G. subflooring, 1 layer of resin building paper, and 1" x 4" T. & G. finished flooring	—	STC 47 IIC 39	TL64-155 G.A.	1 hr.	L502 (UL-33)	ABC	23
403	1/2" Firestop, 1 layer	11.4	—	—	45 min.	U.L. No. 1	AB	—
404	5/8" Firestop attached to resilient metal furring 24" o.c. with 5/8" plywood subfloor and carpet and pad	—	STC 48/ IIC 68	L-224- 3 & 4	1 hr.	EST.	ABC	23
405	5/8" Firestop, 1 layer	12.0	STC 38, IIC 34 (EST.)	—	1 hr.	L501 (U.L. No. 1)	AB	—
406	5/8" Firestop, 1 layer attached to 2" x 8" joists 16" o.c. and 2" x 4" joists 16" o.c. 1/2" plywood subfloor attached to 2" x 8" joists 16" o.c. with rug and pad, 3" insulation in cavity	—	STC 51/ IIC 79	KAL-224- 14 + 15	1 hr.	—	—	23
407	5/8" Firestop, 1 layer nailed; 2nd layer 5/8" Firestop applied to resilient furring channel 24" o.c. between layers	16.0	—	—	2 hr.	L505 (U.L. No. 217)	ABC	—
408	5/8" Firestop, nailed, 1 5/8" lightweight concrete 5/8" plywood, wood joists, 16" o.c. insulation, resilient furring, carpet and pad	—	STC 53/ IIC 73	L-224- 27 & 28	1 hr.	EST.	A	—
409	1/2" Firestop, 1 layer nailed	13.0	STC 35 IIC 32	G.A.	1 hr.	L503 (U.L. No. 46)	ABC	—
411	3/8" G-P Regular, 2 layers	—	—	—	30 min.	EST.	—	—
412	1/2" G-P Regular, 2 layers	—	—	—	1 hr.	EST.	—	—
415	1/2" Firestop, 1 layer, laminated and nailed to 1/4" G-P Gypsum Sound Deadening Board, with floor of 5/8" CD plywood, 1/2" particleboard underlayment, carpet and pad	—	STC 41/ IIC 75	BW-2MT	1 hr.	EST.	A	22
417	5/8" Firestop, 1 layer laminated and nailed to 1/4" G-P Gypsum Sound Deadening Board with floor 5/8" CD plywood, 1/2" particleboard underlayment, carpet and pad	—	STC 42/ IIC 75	(EST.)	1 hr.	EST.	BC	—
421	1/2" Firestop, 1 layer screwed to resilient channel 24" o.c., 5/8" plywood subfloor with 5/8" particleboard over wood joists 16" o.c., 3" insulation, carpet and pad	—	STC 53/ IIC 72	OC 3-MT	1 hr.	FC 181 (FM)	—	23
422	5/8" Firestop, nailed, 1 5/8" lightweight concrete, 5/8" plywood, wood joists 16" o.c., insulation, carpet and pad	—	STC 47/ IIC 65	L-224- 29 & 30	1 hr.	EST.	A	—



G-P Syst.	Weight lb./sq. ft.	Depth in.	Span ft.	Fire Resistance Rating	U.L. File
--------------	-----------------------	--------------	-------------	------------------------------	-----------

WOOD JOISTS 24" O.C.

475	5/8" Firestop, 1 layer attached to resilient channel 16" o.c., 2 1/2" T. & G. plywood subfloor, glue-nailed, over 2"x10" joists 24" o.c.	—	STC 50	EST.	1 hr.	U.L. L513
-----	--	---	--------	------	-------	-----------

PREFABRICATED FLOOR PANELS SPACED 12" O.C. — COMBUSTIBLE

480	1/2" Firestop, 1 layer over 1/2" Sound Deadening Board (direct attached)	6.5	—	—	1 hr.	U.L. No. 47
-----	--	-----	---	---	-------	-------------

2" CONCRETE FLOOR ON METAL LATH OVER STEEL BAR JOISTS 24" O.C.

421	5/8" Firestop nailed or screwed to metal furring 16" o.c.	34.2	—	—	1 hr.	U.L. No. 2
423	5/8" Firestop Backer, nailed or screwed to metal furring 16" o.c.	34.2	—	—	1 hr.	U.L. No. 2
425	5/8" Firestop, 1 layer, metal furring 24" o.c.	32.0	—	—	1 hr.	G501 (U.L. No. 19)
427	1/2" Firestop, metal furring 24" o.c.	33.9	—	—	1 1/2 hr.	G502 (U.L. No. 17)
429	5/8" Firestop, metal furring 24" o.c.	36.4	—	—	2 hr.	G505 (U.L. No. 259)
431	5/8" Firestop, metal deck 24" o.c.	37.0	—	—	2 hr.	U.L. File R4024-12

2 1/2" CONCRETE FLOOR ON METAL LATH OVER STEEL BAR JOISTS 24" O.C.

440	1/2" Firestop, metal furring 24" o.c.	38.5	—	—	2 hr.	G504 (U.L. No. 237)
441	5/8" Firestop, metal furring 24" o.c.	39.3	—	—	2 hr.	U.L. No. 69

2 1/2" CONCRETE FLOOR ON METAL LATH OVER OPEN WEB STEEL JOISTS 24" O.C.

—	1/2" Firestop, Chicago metallic steel framing 48" o.c.	—	—	—	2 hr.	G523
---	--	---	---	---	-------	------

STEEL-WOOD COMBINATION JOISTS

—	5/8" Firestop, 18" deep combination steel-wood joists 32" o.c., 3" insulation, resilient furring, carpet and pad, 1 1/8" plywood subfloor	—	STC 47/ INR + 18	L-224- 35 & 36	1 hr.	EST.
400	5/8" Firestop, 18" deep combination steel-wood joists 16" o.c., 3" insulation, 5/8" plywood, lightweight concrete deck, carpet and pad	—	STC 46/ INR + 11	L-224- 37 & 38	1 hr.	EST.

BEAM PROTECTION

—	5/8" Firestop, 2 layers	—	—	—	2 hr.	N501, N502 (U.L. No. 254, 255)
---	-------------------------	---	---	---	-------	--------------------------------------

*Many of these are new numbers assigned by Underwriters' Laboratories. (Old numbers are in parentheses.)

See Page 6 for Notes

**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**

SYSTEM INSTALLATION DETAILS

**5/8" FIRESTOP® GYPSUM BOARD
1 LAYER BOTH SIDES
(BASIC 1 HR. FIRE RATED WALL)**


=086

**STC/34
SOUND TEST OR-64-8**

**FIRE RATING/1 HR. COMBUSTIBLE
FIRE TEST U.L. U305 (U.L. 5)**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 5/8" Gypsum board Firestop®
4. 5d Common Nails—7" spacing



**5/8" FIRESTOP® GYPSUM BOARD
2 LAYER 2 SIDES**


=098

**STC/41
SOUND TEST OR-64-12**

**FIRE RATING/2 HR. COMBUSTIBLE
FIRE TEST T-194**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 5/8" Firestop Type X Gypsum board
4. 6d and 8d Nails



**5/8" FIRESTOP® GYPSUM BOARD
1 LAYER BOTH SIDES
SOUND TEST G&H BW 27FT**


=100

**STC/45
SOUND TEST G&H BW 27FT**

**FIRE RATING/1 HR. COMBUSTIBLE
FIRE TEST U.L. U312 (U.L. 30)**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 1/4" Gypsum Sound Deadening Board
4. 1/2" Firestop Type XXX Gypsum board or Firestop Eternawall™
5. 5d cc Nails
6. 4d Finish
7. G-P Joint Compound



5/8" F
LAM
SOU

=100

**STC/
SOU
FIRE
FIRE**

Material

1. 2"
2. 2"
3. 1/4"
4. 1/2"
5. Jo
6. 4d
7. 5d

2x4 STI

5/8" FI
APPLIE

1/4" G
DEADE

5/8" F
LAM
SOU

=100

**ST
SC
FIR**

Material

1. 2"
2. 2"
3. 1/4"
4. 1/2"
5. Jo
6. 4d
7. 5d



5/8" FIRESTOP® GYPSUM BOARD LAMINATED TO 1/4" GYPSUM SOUND DEADENING BOARD

=102

STC/47


SOUND TEST G&H BW 28FT

FIRE RATING/1 HR. COMBUSTIBLE

FIRE TEST U.L. U312 (U.L. 30)

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 1/4" Gypsum Sound Deadening Board
4. 5/8" Firestop Type X Gypsum board or Firestop Eternawall™
5. Joint Compound
6. 4d Finishing Nails
7. 5d Nails



5/8" FIRESTOP® GYPSUM BOARD TYPE X, 1 LAYER LAMINATED TO 1/4" G.P. SOUND DEADENING BOARD

=103

STC/50


SOUND TEST G&H BW 35FT

FIRE RATING/1 HR. COMBUSTIBLE

FIRE TEST U.L. U312 (U.L. 30)

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 1/4" Gypsum Sound Deadening Board
4. 5/8" Firestop Type X Gypsum board or Firestop® Eternawall™ Gypsum board
5. Joint Compound
6. 4d Finishing Nails
7. 5d Nails
8. 2" Insulation Batts



1/2" FIRESTOP® GYPSUM BOARD LAMINATED TO 1/4" GYPSUM SOUND DEADENING BOARD

=105

STC/47


STC/52 WITH INSULATION

SOUND TEST G&H BW 28ST/G&H BW 30ST

FIRE RATING/1 HR. COMBUSTIBLE/EST.

Materials Used

1. 2" x 4" Wood Studs staggered 8" o.c. on opposite sides of 2" x 6" Wood Plate
2. 2" x 6" Wood Plate
3. 1/4" G-P Gypsum Sound Deadening Board
4. 1/2" Firestop® Type XXX or Firestop® Eternawall™ Gypsum board
5. G-P Joint Compound
6. 4d Finishing Nails and 4d Common Nails
7. 5d Common Nails
8. 2" Insulation Batts (on BW-30ST for STC/52)



1/2" FIRESTOP® GYPSUM BOARD TYPE XXX, 1 LAYER LAMINATED TO 1/4" G.P. SOUND DEADENING BOARD

STC/50


STC/55 WITH INSULATION

SOUND TEST G&H BW 31ST/G&H BW 32ST

FIRE RATING/1 HR. COMBUSTIBLE/EST.

Materials Used

1. 2" x 4" Wood Studs (double row) 16" o.c.
2. 2" x 4" Wood Plates—1" apart
3. 1/4" G-P Gypsum Sound Deadening Board
4. 1/2" Firestop Type XXX or Firestop® Eternawall™ Gypsum board
5. 4d Finishing Nails, 4d Nails
6. 5d Nails
7. G-P Joint Compound
8. 2" Insulation Batts (on BW 32ST with insulation for STC/55)



**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**

**5/8" FIRESTOP® GYPSUM BOARD
ON RESILIENT CHANNEL**

#112


STC/44

SOUND TEST OR-64-7

**FIRE RATING/1 HR. COMBUSTIBLE
FIRE TEST T-3127**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 5/8" Firestop Type X Gypsum board
4. Resilient Channels
5. 1 1/4" Type W Gypsum board Screws
6. 1" Type S Gypsum board Screws



**5/8" FIRESTOP® GYPSUM BOARD
2 LAYERS 1 SIDE/1 LAYER ON
RESILIENT CHANNEL OTHER SIDE**

#114


STC/48

SOUND TEST OR-64-15

FIRE RATING/1 1/2 HR. COMBUSTIBLE/EST.

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 5/8" Firestop Type X Gypsum board
4. Resilient Channels
5. 1 1/4" Type W Gypsum board Screws
6. 1" Type S Gypsum board Screws



**5/8" FIRESTOP® GYPSUM BOARD
ON RESILIENT CHANNEL WITH
INSULATION IN CAVITY**

#116


STC/50

SOUND TEST OR-64-16

**FIRE RATING/1 HR. COMBUSTIBLE
FIRE TEST T-3127**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 5/8" Firestop Type X Gypsum board
4. 2" Insulation
5. Resilient Channels
6. 1 1/4" Type W Gypsum board Screws
7. 1" Type S Gypsum board Screws





5/8" FIRESTOP® GYPSUM BOARD OVER FIBER SOUND DEADENING BOARD 2 SIDES


=118

**STC/46
SOUND TEST OR-64-73**

**FIRE RATING/1 HR. COMBUSTIBLE
FIRE TEST T-3006**

Materials Used

1. 2" x 4" Wood Studs 16" o.c.
2. 2" x 4" Wood Plates
3. 2" x 4" Wood Fire Blocks
4. 1/2" Fiber Sound Deadenng Board
5. 5/8" Firestop Type X Gypsum board
6. 5d Cement Coated Nails and 8d Box Nails
7. Laminating or Joint Compound



1/2" FIRESTOP® GYPSUM BOARD 1 LAYER EACH SIDE OVER T. & G. COREBOARD


=230

**STC/36
SOUND TEST G.A.**

**FIRE RATING/2 HR. NON-COMBUSTIBLE
FIRE TEST G.A.**

Materials Used

1. 1" T. & G. Coreboard, "V" edge
2. 1/2" Firestop Gypsum board
3. Metal Track
4. Laminating Adhesive



1/2" FIRESTOP® GYPSUM BOARD 2 LAYERS ON FACE, 1 LAYER INSIDE, BOTH SIDES


=175

**STC/57 STC/59 WITH INSULATION
SOUND TEST R.A.L.**

**FIRE RATING/2 HR. COMBUSTIBLE
FIRE TEST FM WP-297**

Materials Used

1. 2" x 4" Wood Studs 24" o.c.
2. Fireblocks—2" x 4" x 22 1/2"
3. 1/2" Firestop Type X Gypsum board
4. 8d Coated Box Nails
5. 6d Coated Box Nails
6. 6d Nails
7. 12d Common Nails



1/2" GYPSUM BOARD OVER COREBOARD


=200

**STC/47
SOUND TEST OR-64-39**

**FIRE RATING/2 HR. NON-COMBUSTIBLE
FIRE TEST T-2575**

Materials Used

1. 3" x 1 1/8" Wood Perimeter Framing
2. 1" x 24" Tongue & Groove Coreboard
3. 1/2" Gypsum board
4. Laminating Compound
5. 8d Nails



**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**

**1/2" GYPSUM BOARD OVER CORE-
BOARD WITH INSULATION IN CAVITY**

= 202


STC/57

SOUND TEST OR-64-59

FIRERATING/3HR. NON-COMBUSTIBLE/EST.

Materials Used

1. 1" x 1 1/2" Wood Strips
2. 1" x 24" Tongue & Groove Coreboard
3. 1/2" Gypsum board
4. 2" Insulation
5. Laminating or Joint Compound
6. 5d and 8d Nails



**1/2\" FIRESTOP\" GYPSUM BOARD
1 LAYER EACH SIDE**

= 200


STC/35

SOUND TEST OR-64-81

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST T-2316**

Materials Used

1. 1 1/2" Steel Studs, 24" o.c.
2. 1 1/2" Floor and Ceiling Track
3. 1/2" Firestop Type X Gypsum board
4. 1" Type S Gypsum board Screws



**1/2\" FIRESTOP\" GYPSUM BOARD
1 LAYER EACH SIDE WITH
INSULATION IN CAVITY**

= 328


STC/41

SOUND TEST OR-66-5

FIRERATING/1HR. NON-COMBUSTIBLE/EST.

Materials Used

1. 2 1/2" Metal Stud 24" o.c.
2. 2 1/2" Metal Track Top and Bottom
3. 1/2" Firestop Gypsum board
4. 2 1/2" Insulation
5. 1" Gypsum board Screws



**1/2\" FIRESTOP\" GYPSUM BOARD
1 LAYER EACH SIDE WITH
INSULATION IN CAVITY**

= 202


STC/44

SOUND TEST OR-64-81

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST T-2316**

Materials Used

1. 1 1/2" Steel Studs, 24" o.c.
2. 1 1/2" Floor and Ceiling Track
3. 1/2" Firestop Type X Gypsum board
4. 1 1/2" Insulation
5. 1" Type S Gypsum board Screws



**1/2" FIRESTOP® GYPSUM BOARD
1 LAYER OVER 1/4" GYPSUM SOUND
DEADENING BOARD EACH SIDE**

= 304


STC/45

SOUND TEST BW 16FT

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST T-3854 & U410 (U.L. 32)**

Materials Used

1. 2 1/2" Steel Studs, 24" o.c.
2. 2 1/2" G-P Steel Track
3. 1/4" Gypsum Sound Deadening Board
4. 1" Type S Gypsum board Screws
5. 1/2" Firestop® Type XXX Gypsum board or Firestop® Eternawall™ Gypsum board
6. 1 3/8" Type S Gypsum board Screws



Georgia-Pacific



**1/2" FIRESTOP® GYPSUM BOARD OVER
1/4" GYPSUM SOUND DEADENING
BOARD WITH INSULATION IN CAVITY**

= 306


STC/50

SOUND TEST BW 17FT

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST UL U410**

Materials Used

1. 2 1/2" G-P Steel Studs, 24" o.c.
2. 2 1/2" G-P Steel Track
3. 2" Insulation
4. 1/4" G-P Gypsum Sound Deadening Board
5. 1" G-P Type S Gypsum board Screws
6. 1/2" Firestop® Type XXX Gypsum board or Firestop® Eternawall™ Gypsum board
7. 1 3/8" G-P Type S Gypsum board Screws



**1/2" FIRESTOP® GYPSUM BOARD OVER
1/4" GYPSUM SOUND DEADENING
BOARD WITH INSULATION IN CAVITY**

= 308


STC/54

SOUND TEST BW 18FT

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST UL U410**

Materials Used

1. 2 1/2" G-P Steel Studs, 24" o.c.
2. 2 1/2" G-P Steel Track
3. 2" Insulation
4. 1/4" G-P Gypsum Sound Deadening Board
5. 1" G-P Type S Gypsum board Screws
6. 5/8" Firestop® Type X Gypsum board or Firestop® Eternawall™ Gypsum board
7. 1 3/8" G-P Type E Gypsum board Screws



**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**

**1/2" FIRESTOP® GYPSUM BOARD,
LAYERS 2 SIDES WITH INSULATION
IN CAVITY**

=310

STC/48

SOUND TEST BW 12FT


FIRE RATING/2 HR. NON-COMBUSTIBLE

FIRE TEST T-3218

(fiberglass insulation not required for fire rating)

Materials Used

1. 2 1/2" G-P Steel Studs, 24" o.c.
2. 2 1/2" Floor and Ceiling Tracks
3. 1/2" Firestop® Type XXX Gypsum board
4. 2" Insulation
5. Laminating or Joint Compound
6. 1" and 1 3/8" Type S Gypsum board Screws



**5/8" FIRESTOP® GYPSUM BOARD,
2 LAYERS 2 SIDES**


=314

STC/46 EST.

**FIRERATING/2 HR. NON-COMBUSTIBLE/EST.
FIRE TEST T-2557**

Materials Used

1. 2 1/2" G-P Steel Studs, 24" o.c.
2. 2 1/2" Floor and Ceiling Track
3. 5/8" Firestop® Gypsum board, 2 layers each side
4. 1" & 1 3/8" Type S Screws



**5/8" FIRESTOP® GYPSUM BOARD,
1 LAYER 1 SIDE, 2 LAYERS OTHER SIDE**

=312


STC/43

SOUND TEST OR-63-2

**FIRE RATING/1 1/2 HR. NON-COMBUSTIBLE/
EST.**

Materials Used

1. 2 1/2" G-P Steel Studs, 24" o.c.
2. 2 1/2" Floor and Ceiling Track
3. 5/8" Firestop® Type X Gypsum board
4. 1" and 1 3/8" Type S Gypsum board Screws



**1/2" FIRESTOP® GYPSUM BOARD,
1 LAYER 1 SIDE, 2 LAYERS OTHER SIDE**


=316

STC/48 EST.

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST T-4848**

Materials Used

1. 3 1/8" Steel Studs, 24" o.c.
2. 3 1/8" Track
3. 1/2" Firestop® Type XXX Gypsum board
4. 1/2" Regular Gypsum board, 2 layers
5. 1 1/2" Insulation (not required for fire rating)
6. 1" and 1 3/8" Type S Screws



**5/8" FIRESTOP® GYPSUM BOARD,
2 LAYERS 1 SIDE, 1 LAYER OTHER SIDE
WITH INSULATION IN CAVITY**

= 318


STC/50

SOUND TEST OR-64-51

**FIRE RATING/1½ HR. NON-COMBUSTIBLE
FIRE TEST T-3126**

Materials Used

1. 3½" Steel Studs, 24" o.c.
2. 3½" Floor and Ceiling Track
3. 5/8" Firestop® Type X Gypsum board
4. 3" Insulation
5. Laminating Compound
6. 1" and 1½" Type S Gypsum board Screws



**5/8" FIRESTOP® GYPSUM BOARD,
1 LAYER 1 SIDE, 1 LAYER OVER ½"
FIBER S.D. BOARD OTHER SIDE**

= 320


STC/44

SOUND TEST OR-65-10

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST T-2557**

Materials Used

1. 3½" Steel Studs, 24" o.c.
2. 3½" Floor and Ceiling Track
3. ½" Fiber Sound Deadening Board
4. Laminating Compound
5. 5/8" Firestop® Type X Gypsum board
6. 1" and 1½" Type S Gypsum board Screws



**5/8" FIRESTOP® GYPSUM BOARD,
2 LAYERS 2 SIDES**

= 322


STC/47

SOUND TEST OR-64-52

**FIRE RATING/2 HR. NON-COMBUSTIBLE
FIRE TEST T-2557**

Materials Used

1. 3½" Steel Studs, 24" o.c.
2. 3½" Floor and Ceiling Track
3. Laminating Compound
4. 5/8" Firestop® Type X Gypsum board
5. 1" and 1½" Type S Gypsum board Screws



**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**

**5/8" FIRESTOP® GYPSUM BOARD,
2 LAYERS 2 SIDES WITH INSULATION
IN CAVITY**


=324

**STC/52
SOUND TEST OR-64-50**

**FIRE RATING/2 HR. NON-COMBUSTIBLE
FIRE TEST T-2557**

Materials Used

1. 3 3/8" Steel Studs, 24" o.c.
2. 3 3/8" Floor and Ceiling Track
3. 5/8" Firestop® Type X Gypsum board
4. 2" Insulation
5. Laminating or Joint Compound
6. 1" and 1 1/2" Type S Gypsum board Screws




**1/2" FIRESTOP® GYPSUM BOARD,
OVER 1/4" GYPSUM SOUND
DEADENING BOARD**

=326

**STC/47 STC/52 WITH INSULATION*
SOUND TESTS: BW-33ST/BW 34ST
FIRE RATING/1 HR. NON-COMBUSTIBLE**

Materials Used

1. 1 1/2" Steel Studs, 24" o.c.
2. 1 1/2" Floor and Ceiling Track
3. 1/4" G-P 1/4" Gypsum Sound Deadening Board
4. 1/2" Firestop® Type XXX Gypsum board or Firestop® Eternawall™ Gypsum board
5. 1 1/4" Type S Gypsum board Screws
6. 1 1/4" Type S Gypsum board Screws
7. 1/2" x 6" x 12" Gypsum board Spacers
8. 2" Insulation Batts (on BW-34ST for 52 STC)



**1/2" FIRESTOP® GYPSUM BOARD,
OVER 1/4" GYPSUM SOUND
DEADENING BOARD**


=415

**STC/41; IIC 75 (WITH CARPET & PAD)
SOUND TEST G&H BW 2-MT**

**FIRE RATING/1 HR. NON-COMBUSTIBLE
EST. BASED ON L 503 (U.L. 46)**

Materials Used

1. 2" x 10" Wood Joists
2. Carpet and Pad
3. 1/2" Particleboard Underlayment
4. 5/8" CD Grade Plywood Subfloor
5. 1/4" G-P Gypsum Sound Deadening Board
6. 1/2" Firestop® Type XXX Gypsum board
7. 4d Ring Shank Nails; 6d Common Nails; 8d Common Nails



**1/2" FIRESTOP® GYPSUM BOARD
ON RESILIENT METAL FURRING
CHANNELS**


=402

**STC/47
SOUND TEST TL 65-155**

**FIRE RATING/1 HR. NON-COMBUSTIBLE
FIRE TEST L502 (U.L. 33)**

Materials Used

1. 2" x 10" Wood Joists
2. Resin Building Paper
3. 1" x 6" Tongue and Groove Subflooring
4. 1" x 4" Tongue and Groove Finished Flooring
5. Donn DG-8 Resilient Channels
6. 1/2" Firestop® Type XXX Gypsum board
7. 1" Type S Gypsum board Screws and 8d Nails





5/8" FIRESTOP GYPSUM BOARD ON RESILIENT METAL FURRING (FLOOR/CEILING)

#404


STC/48

SOUND TEST L-224-4

FIRE RATING/1 HR. COMBUSTIBLE/EST.

Materials Used

1. 2" x 8" Wood Joists—16" o.c.
2. 5/8" Plywood
3. 44 oz. Wool Carpet
4. 40 oz. All Hair Pad
5. 3" Insulation
6. Resilient Channels
7. 5/8" Firestop® Type X Gypsum board
8. 8d Nails
9. 1" and 1 1/4" Gypsum board Screws



5/8" FIRESTOP GYPSUM BOARD ON RESILIENT METAL CHANNEL 24" O.C.

#420


STC/53; IIC 72

FIRE RATING/1 HR. COMBUSTIBLE

FIRE TEST FC 181 (FM)

Materials Used

1. 2" x 10" Wood Joists
2. 5/8" Plywood Subflooring
3. 3/8" Particleboard
4. 1 1/4" Nails
5. 8d Nails
6. 1/2" Firestop® Type XXX Gypsum board
7. Resilient Channel
8. 8d Nails
9. 1" Gypsum board Screws
10. 3 1/2" Insulation
11. Carpet and Pad



5/8" FIRESTOP GYPSUM BOARD ON INSULATION WITH CARPET INDEPENDENT OF FLOOR

#406


STC/51; INR + 29

SOUND TESTS: KAL-224-14, KAL-224-15

FIRE RATING/1 HR. COMBUSTIBLE/EST.

Materials Used

1. 2" x 8" Wood Joists
2. 1/2" Plywood
3. 44 oz. Wool Carpet
4. 40 oz. All Hair Pad
5. 8d Nails
6. 2" x 4" Joists
7. 3" Insulation
8. 5/8" Firestop® Type X Gypsum board



5/8" FIRESTOP GYPSUM BOARD ON INSULATION WITH CARPET INDEPENDENT OF FLOOR


**STC/50/EST.; IIC/70/EST.
(WITH CARPET & PAD)**

FIRE RATING/1 HR. COMBUSTIBLE

FIRE TEST U.L. L513


Materials Used

1. 2 3/32" T. & G. Plywood
2. Adhesive
3. 5/8" Gypsum board Strips
4. 2" x 10" Wood Joists
5. Resilient Furring Channels
6. 5/8" Firestop® Type X Gypsum board



**OP OVERALL PRODUCT, IN PLACE
AI CONSTRUCTION, ASSEMBLY, INSTALLATION**




**5/8" FIRESTOP® GYPSUM BOARD—
2 HR. RATING—INCOMBUSTIBLE,
FLOOR/CEILING**



U.L. Design G505 (UL 259)—2 Hr. (with 2" concrete)

G-P produces lighter weight board and better fire resistance! 5/8" Firestop Gypsum board reinforced with glass fibers covers many rating listed by Underwriters' Laboratories for the 5/8" thick material. This means that G-P 5/8" fire-rated board can be used in most kinds of wall, floor and ceiling assemblies.

The 10% reduction in weight can result in savings in labor and materials in multiple story construction.



UL Design G505

attachment details

INSTALLATION DETAILS

**APPLICATION OF RIGID
PREDECORATED PANELS TO GYPSUM
SUBSTRATE**


Use 3/8" or 1/2" gypsum board. Attach to studs with 1 3/8" gypsum board nails, 1" gypsum board screws (metal studs) or drywall stud adhesive. Joints need not be taped or sealed. Install the gypsum board vertically with the edges centered on the framing members.

The rigid predecorated panels should be applied using a bead of panel adhesive over each stud. Secure paneling at top and bottom plates with 4d finishing nails 12" o.c. Field fasteners not required unless panels are bowed.

The addition of gypsum board as a substrate when using predecorated panels provides increased FIRE RESISTANCE and SOUND CONTROL.

TEST RESULTS


	Paneling no Gypsum	Paneling with 1/2" Gypsum	Paneling with 3/8" Gypsum
Burn thru Time	8 min.	42 min.	73 min. (plus)
Better Sound Rating	28 STC	40 STC	40 STC
Better Impact Resistance	26	82	82



APPLICATION OVER MASONRY WALLS


On masonry walls either above or below grade, be sure the wall is properly waterproofed before furring is applied. Although moisture barrier gypsum board are available—there is obviously no substitute for proper waterproofing.

Wood Strips or Metal Channels: Apply furring horizontally or vertically. Space 16" o.c. for $\frac{1}{4}$ " and $\frac{3}{8}$ " gypsum board, and 24" o.c. for $\frac{1}{2}$ " and $\frac{5}{8}$ " gypsum board. Use concrete stub nails or power driven fasteners to install furring. Gypsum board should be applied perpendicular to furring. Use G-P insulating Gypsum board.



Grabit, a Masonry Adhesive: Apply 1" ribbons of Grabit to each edge and 16" o.c. in field of back of each piece of gypsum board. Be sure face to be covered is reasonably straight, and free of fragments of mortar or other protrusions. The adhesive fills in irregularities in the masonry surface. Grabit may also be used to apply gypsum board to polystyrene insulation material that has been used against the masonry. Grabit may be used without waterproofing on exterior walls which are above grade. Temporary fasteners or bracing may be necessary until Grabit sets.

*Grabit is a trademark of Georgia-Pacific Corporation.






WATER RESISTANT GYPSUM BOARD

G-P Tile Backer Board is a water-resistant gypsum product with a light blue face paper, designed for use as a base for the adhesive application of ceramic, metal or plastic tile. The gypsum core consists of incombustible gypsum rock, combined with an emulsion giving high water resistance. This product is ideal for bathrooms, kitchens, powder rooms and all high moisture areas.

For fire rated partitions between bathrooms or interior areas subject to moisture use $\frac{5}{8}$ " Firestop® Tile Backer proven by Underwriters' Laboratories in a 1-hour assembly over wood studs.

The raw edges of Tile Backer Board (end joints, cut edges, cut-outs) are to be caulked with a coating of the waterproof compound used in applying the tile. As an alternate to caulking, G-P can provide a special 2½" wide self-adhering vinyl tape to place over edges and cut-outs.



*For fire and sound rated construction the Tile Backer Board must extend to the floor.

OP OVERALL PRODUCT, IN PLACE AI CONSTRUCTION, ASSEMBLY, INSTALLATION

SOLID AND SEMI-SOLID GYPSUM PARTITIONS


Partition systems composed entirely of gypsum board have the added values of increased fire resistance and maximum use of space.

In the following four systems the common factor in each is that they are all constructed (except for floor ceiling runners) entirely of gypsum incombustible materials.

2" SOLID LAMINATED— (NON-LOAD BEARING)

A 1" gypsum coreboard with 1/2" gypsum board laminated to each side; no air space. A 2" solid wall system has a 2 hour fire rating, an STC rating of 35, produces smooth monolithic walls and creates extra usable floor space.

2" SOLID LAMINATED FLOOR AND CEILING DETAILS



2 1/4" SEMI-SOLID LAMINATED GYPSUM BOARD

2 1/4" Semi-Solid Laminated—(Non-Load Bearing)—A center vertical rib (or stud) composed of 2 layers of laminated gypsum board (1"x6" rib, 24" o.c.) is the base upon which 5/8" gypsum board is laminated to each side. This leaves intermittent 1" dead spaces for wiring. The 2 1/4" system has a 1 hour fire rating, money saving simplicity of installation, a 30 decibel STC, creates smooth walls and provides extra floor space.

DOUBLE SOLID LAMINATED— (NON-LOAD BEARING)

Consists of laminating 1/2" gypsum board to a 1" tongue and groove coreboard homogenous or laminated on each side of a 3" air space. There is absolutely no connection over the air space except at the jams. This system has a 2 hour fire rating, greater strength than standard frame or thin solid wall, a 47 decibel STC and produces smooth wall surface.

TRIPLE SOLID LAMINATED— (NON-LOAD BEARING)

The center piece is a 1" gypsum core panel running the height and length of wall, on one side of which is dead space the other side is filled with fiberglass

insulation. Outer section of wall (on both sides) is 1/2" gypsum board laminated to 1" coreboard (this gives a 1 1/2" wall on both sides of center section). This system has a three hour fire rating, a 57 decibel STC and produces smooth monolithic walls.

COLUMN FIREPROOFING


Fireproofing with Firestop® Gypsum board provides a fast, efficient and economical method of protecting steel columns. Fire resistant assemblies of two, three and four hours are obtainable depending upon the number of layers of 5/8" or 1/2" Firestop Gypsum board used. These layers are held in place by a combination of screws and metal studs. The two, three and four hour fire rated assemblies of Firestop Gypsum board have passed Official Fire Tests conducted by the Underwriters' Laboratories.

Fire Resistance—For three hour protection, two layers of 1/2" Firestop Type XXX can be used. Test No. X513 (UL 39-3 hour). Two hour protection can be obtained using 1 layer of 1/2" Firestop Type XXX Gypsum board. Test No. X520 (UL 20-2 hour). These are for heavyweight columns (14 W.F. 228).


For lightweight columns (10 W.F. 49) use 4 layers of 5/8" G-P Firestop Type X for 4 hour protection, 3 layers for 3 hours. Test No. X509 (UL 18) and 2 layers for 2 hour, Test No. 517 (UL 8).

Lighter—As compared to other types of fireproofing, a dead load savings of from 50 to 75% can be realized with G-P Firestop Column Fireproofing.

Speed of Erection—Firestop Gypsum board can be installed quickly and easily when used for column fireproofing following G-P details. Minimum amount of the wire and adhesives are used.



THREE-HOUR fire rated steel column assembly with 5/8" Firestop. X509 (UL 18). Minimum size of column W10X49.



TWO HOUR fire rated steel column assembly with 5/8" Firestop. X517 (UL 8). Minimum size of column W10X49.

WOOD AND STEEL STUD APPLICATION

There are many different kinds of construction systems and all are based on the requirements of your particular building installation. Basically, the main considerations are usually: **Fire Resistance, Sound Transmission, Relative Strength of the installation, Dimensional Restrictions and Economy.**


After the wall and floor/ceiling constructions have been selected, it is important that they be installed properly. The following precautions should be taken during installation to avoid situations or conditions which will detract from the sound control properties of the assembly.

Avoid connecting plenum chambers, ducts, vents, etc. These permit the unrestricted flow of sound. Corrective measures are to make partitions full height, and use ducts lined with absorbent material.

Materials: All gypsum board shall be G-P Gypsum board $\frac{3}{8}$ ", $\frac{1}{2}$ " or $\frac{5}{8}$ " thick Regular or Firestop®, 4' wide x ceiling height for vertical application or up to 16' long for horizontal application, tapered edge. All joint treatment products are to be G-P materials.

Framing: Prior to the gypsum board application, all framing members should be true and firmly fastened in a plane surface. Provide double studs at all corners. Both inside and outside intersections are formed by extending one edge of a panel over the other edge in a flush position and covering with tape and joint treatment. In single ply installation, all ends and joints of gypsum board shall occur over framing members, except that this is not required for treated joints at right angles to framing members.

Application: Gypsum board may be applied horizontally or vertically to framing with nails or screws. (Alternate method-stud adhesive may be applied to studs before applying gypsum board.) The gypsum board shall be attached with nails meeting ASTM-C514 or with $1\frac{1}{4}$ " long G-P Type "W" gypsum board screws or 1" long G-P Type "S" gypsum board screws, for wood and metal or framing, respectively.



SINGLE PLY GYPSUM BOARD MAXIMUM FRAMING SPACING

Gypsum board Thickness	Application
$\frac{3}{8}$ " sidewalls	Horizontal or Vertical 16" o.c.
$\frac{1}{2}$ " sidewalls	Horizontal or Vertical 24" o.c.
$\frac{5}{8}$ " sidewalls	Horizontal or Vertical 24" o.c.
$\frac{1}{2}$ " ceilings	Parallel or Perpendicular 16" o.c.
$\frac{5}{8}$ " ceilings	Parallel or Perpendicular 16" or 24" o.c.

NOTE: If heavy spray texture or other heavy finish is applied to the ceiling, do not install gypsum board parallel to joists.



NAILING OR SCREW SPACING FOR SINGLE-PLY GYPSUM BOARD

Gypsum board Thickness	Framing 16" o.c. Single Nailing	Double Nailing
$\frac{3}{8}$ " sidewalls	8" o.c. Max.	12" o.c. Max.
$\frac{1}{2}$ " sidewalls	8" o.c. Max.	12" o.c. Max.
$\frac{5}{8}$ " sidewalls	8" o.c. Max.	12" o.c. Max.
ceilings	7" o.c. Max.	12" o.c. Max.

Gypsum board Thickness	Framing 16" o.c. Screw Spacing	Framing 24" o.c. Screw Spacing
$\frac{3}{8}$ " sidewalls	16" o.c. Max.	—
$\frac{1}{2}$ " sidewalls	16" o.c. Max.	12" o.c. Max.
$\frac{5}{8}$ " sidewalls	16" o.c. Max.	12" o.c. Max.
ceilings	12" o.c. Max.	12" o.c. Max.

NOTE: Nails or screws should be driven not less than $\frac{3}{8}$ " from edges or ends of panels. While fasteners are being driven, the gypsum board shall be held in firm contact with the underlying supports. Preferably, application of fasteners should proceed from the central portion of the gypsum board to the ends and edge. Dimple nails or screws without breaking the face paper. Joints: All joints should be taped and finished with tape and joint compound, nail or screw heads should be finished with joint compound. Exterior angles are covered with G-P Metal Casing Beads and finished with joint compound.



MF MATERIALS, FINISHES
CS COATINGS, SURFACES

GYPSON BOARD PRODUCTS

Georgia-Pacific Gypsum Division manufactures a full range of products to meet the needs of the construction industry. The versatile gypsum product provides builders with lightweight construction materials that are workable, fire and noise resistant and time saving. G-P research facilities have responded to the industry's requests and have developed the following multi-use, highly reliable, low cost products.

G-P GYPSUM BOARD EDGES

T—Tapered
S—Square
RE—Tapered with Round Edge
B—Beveled (Special Order)
T & G—Tongue and Groove
MB—Modified Beveled Edge

See page 30 for detailed description

G-P REGULAR GYPSUM BOARD

G-P Regular Gypsum board is faced with a strong, cream colored paper which will accommodate almost any type of decorative treatment. The back paper, which is gray, is as strong as the face paper. The ½" and ⅝" tapered and round edge gypsum board are recommended for single layer application in new construction. They are designed to be reinforced with G-P Joint System products resulting in a smooth, seamless surface.

Square edges are recommended for use where joints will be exposed. The resistance to fire exposure and sound transmission increase with thickness and the number of layers of board used. Bevel edges can be used where a panel effect is desired.

Thickness	Widths	Lengths	Edge
¼" ⅜" ½" ⅝"	4'	6' to 16' in even feet	T, S, B, RE

FIRESTOP GYPSUM BOARD

Firestop Gypsum board develops 45 minute to 3 hour fire resistant ratings in various wood and steel wall, floor/ceiling assemblies and column and beam protection. Textile glass filaments and other ingredients keep the core intact, even after the chemically combined water has been released.

Thickness	Widths	Lengths	Edge
½" ⅝"	4'	6' to 16' in even feet	T, S, B, RE

G-P ¼" GYPSUM SOUND DEADENING BOARD

G-P ¼" Incombustible Gypsum Sound Deadening Board meets the requirements of the most sophisticated sound control systems available with the added convenience of being one of the easiest sound control materials to install. When combined with other gypsum board, it reduces sound transmission, has high structural strength, is non-combustible. It has a distinctive green face paper. When applied over 2½" steel studs or 2 x 4 wood studs, one layer of ½" Firestop Type XXX Gypsum board over one layer of ¼" Gypsum Sound Deadening Board produces a 1-hour fire resistive wall and a 45 S.T.C.

Thickness	Widths	Lengths	Edge
¼"	4'	8'	T

G-P REGULAR TILE BACKER BOARD

This is a water-resistant gypsum product with a light blue face paper, designed for use as a base for the adhesive application of ceramic, metal or plastic tile. The gypsum core consists of non-combustible gypsum rock, combined with an asphalt wax emulsion giving high water resistance. Ideal for bathrooms, kitchens, powder rooms and other moisture areas.

G-P Tile Backer Board can be erected as easily as regular gypsum board and requires no finishing of joints or nail heads with joint treatment nor further waterproofing under tile applied adhesively unless required by local code.

Thickness	Widths	Lengths	Edge
½"	4'	8' to 12'	T

FIRESTOP® TILE BACKER BOARD

Same as Regular Tile Backer Board plus the addition of glass fiber reinforcement gives increased fire protection and strength. Where fire rated assemblies are required in areas subject to moisture, such as partitions between bathrooms and other interior areas, most building codes allow the use of Firestop Tile Backer Board. The use of ⅝" Firestop Tile Backer Board will give the same fire resistant rating as other Firestop board. Only in design 5—1 hr. rating.

Thickness	Widths	Lengths	Edge
⅝"	4'	8' to 12'	T

G-P REGULAR INSULATING GYPSUM BOARD

Regular Insulating Gypsum board with bright aluminum foil laminated to the back surface.

The foil paper provides a continuous vapor barrier on the warm side of the wall.

To have reflective insulation value, the foil must face a minimum air space of ¾". The aluminum foil, facing a ¾" minimum space, reflects 90% of radiant heat, providing insulation qualities equal to ½" of fibreboard insulation (tested by U.S. Bureau

of Standards). Panels must be installed with foil side against the studs.

Thickness	Widths	Lengths	Edge
3/8" 1/2" 5/8"	4'	8' to 16'	T, S, RE

FIRESTOP® INSULATING GYPSUM BOARD

This is the regular insulating gypsum board with the addition to the core of glass fiber for increased fire protection. Through the proper use of this product desired fire-rated assemblies can be achieved.

Thickness	Widths	Lengths	Edge
5/8"	4'	8' to 16'	T, S, RE

G-P REGULAR ETERNAWALL™— VINYL SURFACED GYPSUM BOARD

Standard Line. Colors—Avocado, Gold, Flax, White, Beige, Stucco, Buff, Willow Green, Fawn, Snowdrift White, Alabaster, Tangerine, Cherry, Pecan and American Walnut.

New Colors and Textures. Colors—Honey Maple, Shadow Beige, Teak, Rosewood, Oak, Desert Yellow, Smokey Mint, Spanish Haze, Winter Green, Tarnished Gold, Powder Brown, Chocolate Malt, Autumn Orange, Burnt Sugar, Pebble White.

This panel has the vinyl surface factory laminated to Regular Gypsum board. Available in a variety of colors and textures, it provides beauty and utility to commercial, institutional and home interiors. Eternawall is strong and resilient. The solid gypsum core is non-combustible. Eternawall color won't fade. The deep linen-textured vinyl surface can be scrubbed without damage to color, texture or design. Because of its ability to take hard wear and to resist stains, Eternawall Gypsum board is ideal for restaurants, hotels, clubs, and hospitals as well as home use. It is also ideally suited for movable partitions.

Thickness	Widths	Lengths	Edge
1/2" (Special order 3/8" & 5/8")	4'	8' (Other lengths available on special order.)	MB

FIRESTOP® ETERNAWALL™— VINYL SURFACED GYPSUM BOARD

This panel has the vinyl surface factory laminated to a Firestop panel which has glass fibers added to the core to give it additional fire resistance. With this technically designed gypsum core, a 1 hour or greater fire rating may be obtained on wall assemblies. Same colors available as with regular Eternawall Gypsum board.

Thickness	Widths	Lengths	Edge
1/2" 5/8"	4'	8' (Other lengths available on special order.)	MB

FIRESTOP® GYPSUM SHEATHING

Treated—G-P Firestop Gypsum Sheathing consists of non-combustible gypsum rock combined with an asphalt emulsion to provide high resistance to water. All G-P Firestop Gypsum Sheathing is manufactured to meet ASTM C79 including requirement for water resistance. This eliminates the need for building paper (except where required by local building code). An untreated (non-water resistant emulsion) gypsum sheathing is available.

The 2' wide sheathing, applied horizontally, is made with precision formed tongue and groove edges and square edges. The 4' wide square edge sheathing, applied vertically, completely eliminates the need for corner bracing. It is designed to meet requirements of FHA Technical Circular 12 (no corner bracing).

Thickness	Widths	Lengths	Edge
1/2"	2' 4'	8' 8' & 9'	T & G S

FIRESTOP® GYPSUM BACKER BOARD

5/8" Firestop Gypsum Backer is used as a backing for decorative surface treatments of acoustical plasters, tile, plywood and various veneers. A single layer application of 5/8" G-P Firestop Gypsum Backer on both sides of wood or steel framing, enables loadbearing or non-loadbearing wall assemblies to resist temperatures rising to 1700° F. in one hour following the ASTM standard time temperature curve.

Firestop Gypsum Backer consists of a gypsum core with literally miles of high tensile strength glass fibres, firmly bonded to a fibrous gray paper on both sides.

Thickness	Widths	Lengths	Edge
1/2" 5/8"	2' & 4'	8' to 16'	S, T & G

G-P REGULAR GYPSUM BACKER BOARD

G-P Gypsum Backer Board is designed for first or base layers in field lamination of gypsum board, for acoustical tile and other compatible materials. Provides low cost, even surfaces for further decorative treatments. It may be applied over loadbearing or non-loadbearing wood or metal framing with nails, screws or staples.

Thickness	Widths	Lengths	Edge
3/8" 1/2" 5/8"	2' & 4'	8' to 16'	S, T & G

PREDEC™ TEXTURED GYPSUM BOARD

This combination of non-combustible gypsum board with factory applied, distinctive, evenly balanced textures is a new development in the construction industry. The textures are baked on and are available in 2 patterns, sand and stucco. The panels are $\frac{5}{16}$ ", $\frac{1}{2}$ " and $\frac{5}{8}$ " thick with square edges. The texture is a thermo-set in White, Beige, Gold and Light Green water resistant paint.

This product eliminates job site finishing and installation time. It is impact and abrasion resistant and ideal for residential construction, factory built mobile and modular homes and movable or fixed partitions. It can be cleaned with a damp cloth and mild soap and water. PreDec has a flame spread rating of 20. Samples available on request.

Thickness	Widths	Lengths	Edge
5/16" ($\frac{1}{2}$ " & $\frac{5}{8}$ " special orders)	4'	cut to size	S

SHAFT LINER™ SYSTEM

The shaft liner system is a factory or field laminated gypsum board partition for enclosing elevator shafts, stairs, smoke towers and air ducts. It is a non-load bearing wall, designed for resistance to air pressures without excess deflection. This system can save over 20 lbs. per square foot compared to masonry and is non-combustible. It can be erected from one side, eliminating the need for scaffolding.

The partition consists of a basic prelaminate core $1\frac{5}{8}$ " thick by 24" wide which fits into a top metal "J" track and bottom "L" runner. Metal "T" splines separate each core unit; and the shaft liner is then secured to the "T" splines and both top and bottom runners. This system was fire tested in accordance with ASTM E119, and is the only U.L. approved shaft enclosure system on the market. G-P shaft liners available in lengths up to 16'. With G-P's own auxiliary bracing system heights beyond 16' are attainable. Various fire resistive and sound ratings available. Solid and cavity wall types available.

Thickness	Widths	Lengths	Edge
1$\frac{5}{8}$" Core plus taping layers	2'	cut to size	S

G-P 1" COREBOARD

- 1" Gypsum Coreboard is available in two styles.
- A homogenous core with a tongue and grooved joint.
 - Two layers of $\frac{1}{2}$ " backer board, laminated.
- 1" Gypsum Coreboard is used for the core material in various, all-gypsum partition assemblies.

Thickness	Widths	Lengths	Edge
1"	2'	Custom cut up to 14'	S, T & G

G-P SOFFIT BOARD

G-P Gypsum Soffit Board is used on exterior soffits where not exposed directly to the weather. It's an inexpensive soffit material for schools, shopping center malls, apartments and houses. It finishes and decorates like interior gypsum board with no nails or joints showing. It has light blue face paper for identification.

Thickness	Widths	Lengths	Edge
$\frac{1}{2}$", $\frac{5}{8}$"	4'	8'	RE

G-P FIRE FIGHTER GYPSUM BOARD

New product designed for use on roofs, over rafters, and under sheathing and roof covering. Tests prove it blocks roof fires from entering attic and living areas. It has a special core and paper.

Thickness	Widths	Lengths	Edge
$\frac{1}{2}$"	2'	8'	S

DENS-COTE® GYPSUM BASE

A 4' wide, long length, tapered edge, plaster base. For use as a base layer for G-P Dens-Cote® veneer plaster. It has a highly absorbent face with pinholed surface.

Thickness	Widths	Lengths	Edge
$\frac{3}{8}$", $\frac{1}{2}$" $\frac{5}{8}$" Reg. and $\frac{1}{2}$" and $\frac{3}{8}$" Firestop®	4'	8', 10', 12'	T


DENS-COTE® VENEER PLASTER

One coat and two coat systems give a strong durable finish with maximum speed and minimum material. Apply total thickness of $\frac{3}{32}$ ". Available in smooth or textured finishes. 80 lb. bags.

TAPERED EDGE


The tapered edge was originally called the "recessed edge" but is now commonly called tapered, because of the incline from the edge to about 2" into the board.

This taper allows space for tape and joint treatment to be applied and the completed job will be flat, smooth and monolithic.




SQUARE EDGE

The gypsum board square edge was the original wallboard edge. Initially designed to be a base with a final covering such as wallpaper, paneling, or tile, square edge can be finished with joint compounds to form a clean monolithic wall suitable for paint. Also can be used where an exposed joint is desired.




TAPERED w/ROUND EDGE:

Georgia-Pacific round edge (RE) gypsum board can be used for wall and ceilings in both new construction and remodeling. It is designed to reduce the beading and ridging problems commonly associated with standard type gypsum board. This edge formation provides a stronger, more rigid joint and reduces joint beading or ridging.




BEVELED EDGE:

The beveled edge is a suitable edge to give a paneled effect. After fasteners are covered with joint compound the board is ready for paint with grooves exposed.




"T & G" EDGE:

Georgia-Pacific's "tongue and groove" edge is used on 2" wide sheathing and backer boards.



MODIFIED BEVELED EDGE:

The modified beveled edge is available only on Eternawall™ panels. This particular edge more readily accommodates the vinyl surface decoration, which is delivered completely edge wrapped. The vinyl surface material is available in 15 standard patterns and colors and 15 new colors and textures.



JOINT SYSTEM PRODUCTS

G-P Joint System products are designed to conceal joints and nail heads and "surface-weld" gypsum board panels together. Properly used, these products assure smooth, seamless appearance of walls and ceilings, with joints stronger than the gypsum board itself.

G-P BEDDING COMPOUND

Bedding Compound is designed to provide maximum adhesion of tape to the joints and for initial application to nail heads and corner bead. It spreads smoothly and may be hand or machine applied. Coverage: 15 to 20 lbs. per 1,000 sq. ft. (Used in conjunction with 40 to 45 lbs. of Topping Compound.) 25 lb. bags.

G-P TOPPING COMPOUND

G-P Topping Compound is specifically designed for the second and third coats over the bedding compound. Since it is used only for topping, the amount of adhesive can be reduced and other materials incorporated which reduce the shrinkage and make it easier to sand and work. Coverage is approximately 40 to 45 lbs. per 1,000 square feet. (Used in conjunction with 15-20 lbs. of G-P Bedding.) Available in 25 lb. bags.

TRIPLE DUTY JOINT COMPOUND

Triple Duty Gypsum board Joint Compound is a vinyl multipurpose joint system product. A single

bag offers taping, topping and texturing. It can be used for all coats in the reinforcing and concealing of joints in gypsumboard construction. The binder, a vinyl, gives this product a wet life of 30 to 60 days duration. This allows premixing in large quantities prior to application. Triple Duty can be applied using standard hand or mechanical tools. There is low shrinkage and it is easily sanded. When the application is completed, the surface is ready for priming and decoration as desired with no further preparation necessary. Coverage: 60 lbs. per 1,000 sq. ft. 25 and 50 lb. bags. Can be used as a Texture. Coverage: 12-50 lbs. per 1,000 sq. ft.

G-P READY MIX JOINT COMPOUND

Ready Mix Joint Compound is an easy-working material for embedding the joint reinforcing tape and the filling and finishing of joints in gypsum board construction. Furnished in cans and cartons ready to use, this stable, all-purpose compound is also excellent for use in covering nail heads and forming interior and exterior angles. Ready Mix Joint Compound assures a standard mixture for uniform workability throughout the job. It has a long wet life and will not spoil even when the container is left open. Ready Mix Joint Compound produces an excellent surface for any type of decoration. Ready Mix Topping Compound also available. For best results, the surface should be primed before being decorated. Coverage: 5 gal. per 1,000 sq. ft. Package—1 and 5 gal. cans, 4 gal. cartons.

G-P ALL PURPOSE JOINT COMPOUND

G-P All Purpose Joint Compound is used for bedding tape, topping, corner bead, nail spotting and texturing. When taping be sure the compound under the tape, and the first coat over the tape is thoroughly dry before applying the next coat over the joints. When used for texturing, for best results, apply a vinyl primer to the entire area before texturing. The texture may be applied with a roller, sponge, brush or can be sprayed, depending on the type of configuration desired. Coverage: 60 lbs. per 1,000 sq. ft. 25 lb. bags and packaged 40 lbs. of compound plus 150 ft. of tape.

SPEED SET

Speed Set Joint Compound makes possible the taping and finishing of all gypsum board joints within a single day. It can be used for all coats. Speed Set is a setting rather than a drying type of compound, and will not shrink once it has set. Comes in two ways—"1 Hour Working Time" and "2 Hour Working Time". For best results, use a primer sealer over surface before painting or texturing. 25 lb. bags.

WALL TEXTURES

G-P Wall Texture is an unaggregated texture compound for hand tool or spray application. When applied with a spray, a splatter or orange peel texture is formed. When applied by hand, a stipple, swirl, or brocade texture can be produced.

G-P Wall Texture can be applied immediately after G-P Ceiling overspray wipedown. It is made for fast, volume application. Because of its formulation, G-P Wall Texture matches G-P Ceiling Textures, and allows them to blend together.

Coverage: 12-50 lbs. per 1,000 sq. ft. depending upon texture. 25 lb. Package.

*Throughout U.S. except Northeast

MF MATERIALS, FINISHES
CS COATINGS, SURFACES

CEILING TEXTURES

G-P Ceiling Textures are designed for spray application over ceilings constructed with gypsum board or concrete. The resulting texture simulates acoustical texture finish.

Vermiculite—A 40 lb. bag of this aggregate is available in 3 particle sizes (fine, medium and coarse). An ideal product for concealing surface defects. Coverage: 200-300 sq. ft. per bag. Texture samples available on request.

Polystyrene—A new powder product in a 32 lb. bag. This rich white texture finish has strong adhesion with maximum coverage and excellent hiding qualities. The fragments of this very rough texture retain their size and shape during mechanical mixing. Coverage: 200-300 sq. ft. per bag.

Especially designed for volume operations, these products give unsurpassed economy. The texture dries harder and tighter. The texture maintains a high quality white decorative finish, and gives exceptional coverage if used as instructed.

G-P GYPSUM BOARD TAPE

G-P Tape is a full 2" width, "Miracle Crease" spark perforated tape with skived edges and sanded surface both sides. Excellent bonding qualities.

GRABIT™ ADHESIVE

Grabit adhesive is an adhesive which permits direct attachment of gypsum board to masonry walls. It may be used on poured concrete, cinder block or concrete block walls which are reasonably straight and true and are free from surface treatment, decorations, or protrusions. Grabit adhesive may be used on exterior walls which are above grade level without waterproofing. Grabit adhesive can be used to adhere gypsum board to polystyrene insulation material.

Adhesion is secure and permanent, with no need for furring strips or fasteners. After being mixed with water as directed, Grabit adhesive can be applied with blade or caulking gun. Only four 1" ribbons are needed for each 4' wide gypsum board panel. The adhesive fills in all normal irregularities in the masonry. In 3 to 4 hours, Grabit adhesive sets hard, and joint taping and finishing operations may then be started. This adhesive may be used wherever there is need to attach gypsum board to masonry walls: in homes, apartments, hotels, offices, and plants. Coverage: Up to 1/4 lb. per sq. ft. depending on roughness of base surface. 50 Lb. Package.

Texture	Finish	Bag Size	Water Mix*	Mix	Average Coverage	
					Gypsum board	Concrete
Wall Texture	S†	25 lb.	Add 2½ Gallons	Do not exceed 3½ Gallons	Spray 1,000 sq. ft. Trowel 200 sq. ft.	
Vermiculite Ceiling Texture	FM & C†	40 lb.	Add 3½ Gallons	Do not exceed 5 Gallons	Spray 400 sq. ft.	300 sq. ft.
Polystyrene Ceiling Texture	C†	32 lb.	Add 6 Gallons	Do not exceed 8 Gallons	Spray 400 sq. ft.	300 sq. ft.

*Mix until dry powder is wetted and well dispersed. Then allow to soak for 20 minutes. Remix and adjust to desired consistency.

If desired, up to 1½ gallons of compatible water based paint may be added, per bag, to impart color.

†S—Smooth (no aggregate)
 Fine—

M—Medium
 C—Coarse

ETERNAWALL™ COMBINES GYPSUM BOARD WITH THE BEAUTY OF SHEET VINYL

These fire-resistant panels are factory laminated with a quality, washable vinyl sheet providing a permanent scuff, crack and chip-resistant surface. Colors are face-resistant and the texture or design will not be impaired when cleaned.

Eternawall panels are available in 12 standard colors

and 3 simulated woodgrains plus 15 new vinyl surfaces, including 10 colors in G-P's Burlap texture, 2 colors in weave and 3 new woodgrains. The long edge is completely wrapped with vinyl and eased to form a modified beveled edge*.

Georgia-Pacific Firestop® Eternawall™ Gypsum board is available for use when the wall construction requires the gypsum board to be of fire rated construction. Firestop® Eternawall™ has a gypsum board base containing greater glass fiber reinforcement and unexpanded vermiculite.

SPECIFICATIONS

All vinyl surfaced gypsum board scheduled and/or indicated on the drawings shall be Georgia-Pacific Eternawall™ as manufactured by the Gypsum Division of Georgia-Pacific Corporation. The panel construction shall consist of supported or unsupported vinyl of "wall surfacing grade" factory laminated to G-P Regular or Firestop® Gypsum board. The long panel edges shall be a modified bevel and completely wrapped with vinyl. The colors and patterns shall be as selected from the Eternawall™ Gypsum board Standard Line or special new colors and textures. (See page 4 for colors.)



DEMOUNTABLE PARTITIONS

Demountable wall systems are installed by using any of the appropriate or approved color-matched moldings. To laminate to existing wall surfaces, use G-P Laminating Compound and secure panels mechanically at top and bottom plates. Panels may be applied with adhesive directly to metal studs, wood framing or furring strips. For application directly to masonry walls, use G-P Grabit™ Masonry Adhesive.

* Colors are listed on Page 4. Swatches are available in Sweets Design Catalog or by writing Georgia-Pacific Corporation, 900 S.W. Fifth, Portland, Oregon 97204.

PRODUCT DATA

Thickness: 1/4", 3/8", 1/2" and 5/8" Regular Gypsum board, 1/2" and 5/8" Firestop® Gypsum board. 1/2" Regular Eternawall™ is the stock thickness.

Standard sizes: 4' x 8' and 4' x 10'. Special lengths available upon request in one foot increments from 4' x 7' to 4' x 16'. Special sizes (length and width) available on special order basis.


FIRE HAZARD CLASSIFICATION

3/8", 1/2" and 5/8" gypsum board consisting of gypsum core, surfaced on both sides with paper or with a vinyl facing on one side


Flame Spread	15	25
Fuel Contributed	15	10
Smoke Developed	0	20-50

Classified by Underwriters' Laboratories, Inc.
UL labeled Eternawall available.

EDGE DETAIL



Modified Beveled Edge




Color coated stainless steel nails are available to match all Standard colors and woodgrains. Trim accessories are available in 8' and 10' lengths to match all standard colors and woodgrains.

Matching moldings are available for the new Eternawall™ colors and textures from Keller Products, Inc., 41 Union Street, Manchester, New Hampshire 03103. Snap-on type moldings are not available for the new special order colors. Plastic moldings are available from Georgia-Pacific for all standard colors.

TRIM ACCESSORIES



Snap-On Corner Bead





Snap-On Interior Trim

END

ENDS—Eternawall™

Gypsum board Surfaced. These fire and sound rated vinyl-surfaced gypsum board systems eliminate the need for battens. Firestop® Eternawall™ is laminated directly to G-P 1/4" incombustible Gypsum Sound Deadening Board. They are not only simple to install but they are inexpensive and provide a very durable wall, and very high STC ratings.




Fire Test U.L. U312
Fire Rating—1 Hour Combustible
STC 50 System =106
Fire Test U.L. U410
Fire Rating—1 Hour Incombustible
STC 50 System =306

*Insulation not required for fire rating.


SGP 0023312




Black Design GP-700




Willow Green GP-701




Snowdrift White GP-651




Bolt GP-704




Tangerine GP-702



Walnut Design GP-682




Alabaster GP-703




Fawn GP-652



Cherry Design GP-684



Flax Design GP-686




Beige GP-687



Gold GP-684




Pecan Design GP-683




White GP-686




Avocado GP-685




Pebble White GP-101




Honey Maple GP-206




Desert Yellow GP-110




Powder Brown GP-102




Teak Design GP-686




Smokey Mint GP-114



Chocolate Malt GP-107



Rosewood Design GP-696




Spanish Haze GP-112




Autumn Orange GP-105




Oak Design GP-697




Winter Green GP-115



Burnt Sugar GP-108



Shadow Beige GP-205



Tarnished Gold GP-111

SGP 0023313

**TS TECHNICAL SUPPORT
CC CODE ACCEPTABILITY, CERTIFICATION**

Georgia-Pacific



U.S. AND CANADIAN SPECIFICATION DIRECTORY - GYPSUM BOARD PRODUCTS

Product	Thick- ness	Width	Length	ASTM & CSA Standards	USDA Federal Specification	Applied Under
G-P REGULAR GYPSUM BOARD Tapered Edge	1/4" 3/8"	4'	6' to 12' 6' to 16'	C 36 ■ CSA A82.27	SS-L-30d Type III—Grade R	ANSI A97.1
Square, Tapered or Round Edge	1/2" 5/8"	4'	6' to 16' 6' to 16'			
G-P INSULATING GYPSUM BOARD Square, Tapered Edge or Round Edge	3/8" 1/2" 5/8"	4'	6' to 16' 6' to 16' 6' to 16'	C 36 ■ CSA A82.27	SS-L-30d Type III—Grade R	ANSI A97.1
		4'	6' to 16'			
ETERNALWALL™ GYPSUM BOARD Modified Beveled Edge	1/2" 5/8"	4'	8' Std.† 8' Std.†	C 36 ■ CSA A82.27	SS-L-30d Type III—Grade R or Grade X Class III	ANSI A97.1
		4'	8' Std.†			
FIRESTOP® GYPSUM BOARD Square, Tapered Edge or Round Edge	1/2" 5/8"	4'	6' to 16' 6' to 16'	C 36 ■ CSA A82.27	SS-L-30d Type III—Grade X	ANSI A97.1
		4'	6' to 16'			
FIRESTOP® INSULATING GYPSUM BOARD Square, Tapered Edge or Round Edge	1/2" 5/8"	4'	6' to 16' 6' to 16'	C 36 ■ CSA A82.27	SS-L-30d Type III—Grade X	ANSI A97.1
		4'	6' to 16'			
G-P TILE BACKER BOARD Tapered Edge	1/2" 5/8"	4'	8', 11' and 12'	C 630 ■ CSA A82.27	—	—
G-P GYPSUM SOUND DEADENING BOARD Square Edge	1/4"	4'	8' Std.†	C 442 ■ CSA A82.35	SS-L-30d Type IV—Grade R	—
G-P BACKER BOARD Square or T & G Edge	3/8" 1/2" 5/8"	4' 2' 2'	8' Std.† 8' Std.† 3' Std.†	C 442 ■ CSA A82.35	SS-L-30d Type IV Grade R Grade X	—
FIRESTOP® GYPSUM SHEATHING Long-Edges - Square Edge Core-treated or non core-treated	1/2"	4'	8' & 9'	C 79 ■ CSA A82.27	SS-L-30d Type II Grade R&W	—
Tongue and Groove Core-treated or non core-treated	1/2"	2'	8' Std.†	C 79 ■ CSA A82.27		
DENS-COTE® BASE	1/2" 5/8"	4'	6' to 12'	C 588 ■ CSA A82.27	—	—
FIRESTOP® DENS-COTE® BASE	5/8"	4'	6' to 12'	C 588 ■ CSA A82.27	—	—
DENS-COTE® PLASTER				C 587	—	—

Brand	Product	ASTM Standards	Federal Spec.	Applied Under
G-P	JOINT SYSTEM MATERIALS	C 475	SS-J-570a 10/24/66	ANSI A97.1
G-P	METRO-MIX™	C 317	—	ANSI A59.1
G-P	FORM BOARD	C 318	Type V SS-L-30d Grade R	ANSI A59.1

†Standard Length—Other Lengths on Order.
*All ASTM Standards—Per Latest Revision.
■All Canadian Standards in Blue

Any questions not answered by the information on this page or available from local sources should be referred to Georgia-Pacific, Gypsum Division, 900 S.W. Fifth, Portland, Oregon 97204.

**CC CODE ACCEPTABILITY
CERTIFICATION WARRANTY**

The assemblies and information in this brochure have been developed based on practical construction methods.
However, since the Georgia-Pacific Gypsum Division does not have any prior knowledge of a specific building design and its construction or the methods of application used with its products, no warranty of performance is made. All tests

have been obtained under controlled laboratory testing conditions where environmental variables are reduced to a minimum. In the field, such laboratory conditions are not always met, since many other variables may be produced. Laboratory results may exceed field test results but the laboratory tests under controlled conditions are the only logical way to compare the performance of different assemblies.

The Gypsum Division of the Georgia-Pacific Corporation makes no warranty that the performance of assemblies in the field will have a performance equal to or better than that developed in the test.

DISTRIBUTION OFFICES **United States**

ALABAMA
*irmingham
3400 Ball St.
(205) 841-0415
Huntsville
570 Highway 20 East
Madison, Alabama
(205) 772-9681
Mobile
3451 Georgia-Pacific Ave.
(205) 479-0604
Montgomery
4542 Baldwin Ave.
(205) 268-7280

ALASKA
Fairbanks
272 Illinois St.
(907) 452-2183

ARIZONA
Phoenix
4801 West Colter St.
(602) 939-1413
Tucson
450 E. Irvington Rd.
(602) 869-5701

ARKANSAS
Ft. Smith
6901 Jenny Lind Road
(501) 646-4381
Little Rock
3101 Dugan St.
(501) 374-0212

CALIFORNIA
Anaheim
1700 Lewis St.
(714) 633-2301
Fresno
5286 East Home Ave.
(209) 251-8471

LOS ANGELES
14750 Neilson Ave.
City of Industry
(213) 968-5551

OAKLAND
2300 Polvorosa Ave.
San Leandro
(415) 352-5100

RIVERSIDE
1450 Citrus Ave.
(714) 684-5353

SACRAMENTO
2951 Orange Grove Ave.
North Highlands
(916) 481-4444

SALINAS
1031 Industrial Ave.
(408) 758-0913

SAN DIEGO
901 West 24th St.
National City
(714) 262-9955

SAN FERNANDO
7891 Deering Ave.
Canoga Park
(213) 987-3211

SAN JOSE
680 East Gish Rd.
(408) 297-7800

SANTA ROSA
3417 Standish Road
(707) 544-3040

COLORADO
Denver
3900 Uvalde St.
(303) 371-1500

CONNECTICUT
Hartford
776 North Main St.
Manchester, Conn.
(203) 646-8700

WALLINGFORD
805 North Colony St.
(203) 269-8725

DELAWARE
Wilmington
Rittenhouse Ind. Pk
Terminal Ave. & Christiana
(302) 656-8203

FLORIDA
Ft. Myers
3587 Work Drive
(813) 333-3857

JACKSONVILLE
1333 Rialto St.
(904) 356-9711

MIAMI
3201 N.W. 110th St.
(305) 688-6803

ORLANDO
2721 Regent Ave.
(305) 293-5781

PENSACOLA
4801 McCoy Dr.
(904) 434-5501

TALLAHASSEE
889 Mabry St.
(904) 576-2148
Tampa
3701 East Columbus Dr.
(813) 621-1351

WEST PALM BEACH
900 West 15th
Riviera Beach
(305) 844-6371

GEORGIA
Albany
1013 Worth St.
(912) 432-5106

ATLANTA
2351 Button Gwinnett Dr.
Norcross, Ga.
(404) 449-7400

AUGUSTA
1153 Gordon Highway
(404) 724-0578

COLUMBUS
1401 Blanchard Dr.
(404) 327-6521

MACON
7591 N.E. Ind. Blvd.
(912) 781-9700

SAVANNAH
Telfair Rd.
and SCL Drive
(912) 233-0071

IDAHO
Boise
1875 Commercial Ave.
(208) 345-6441

IOWA
Des Moines
5631 Northeast 17th St.
(515) 265-5251

ILLINOIS
Chicago
10450 Waveland Ave.
Franklin Park
(312) 876-2990

17040 LATHROP AVE.
Harvey
(312) 928-3336

BLOOMINGTON
422 White Oak Rd.
Normal, Illinois
(309) 452-9422

QUAD CITIES
300 East Fourth Ave.
Milan, Ill.
(309) 787-6121

INDIANA
Elkhart
225 Collins Rd.
(219) 294-5481

EVANSVILLE
520 North Congress Ave.
(812) 477-6123

FORT WAYNE
7803 Neilson Rd.
(219) 749-9618

INDIANAPOLIS
310 South Kitley Ave.
(317) 357-8754

KANSAS
Wichita
401 West 47th St. South
(316) 522-4831

KENTUCKY
Louisville
4820 Allmond Ave.
(502) 368-1681

LOUISIANA
Baton Rouge
1011 Leesville St.
(504) 343-7461

LAFAYETTE
814 S. W. Evangeline
Thruway
(318) 232-2551

NEW ORLEANS
7500 Almonaster Ave.
(504) 241-2380

SHREVEPORT
2801 Valley View Dr.
(318) 688-8771

MAINE
Bangor
Bennett St. & Hildreth
(207) 947-0142

PORTLAND
508 Warren Ave.
(207) 797-5564

MARYLAND
Baltimore
6813 Quad Ave
(301) 285-4700

SALLABURY
Armstrong Parkway &
Marvel Rd.
(301) 548-2161

MASSACHUSETTS
Boston
250 Ballardvale St.
Wilmington
(617) 444-6300

SPRINGFIELD
121 Memorial Drive
Memorial Ind. Park
(413) 781-7030

MICHIGAN
Detroit
11800 Sears Ind. Dr.
Livonia
(313) 522-5100

GRAND RAPIDS
825 Buchanan Ave., S.W.
(616) 241-1826

Saginaw
3720 E. Wash. Rd.
(517) 752-8134

MINNESOTA
Minneapolis
8175 County Line Rd. 18
(612) 425-6811

MISSISSIPPI
Jackson
555 Gulf Line Rd.
(601) 838-6420

MISSOURI
Cape Girardeau
Nash Road
(314) 334-0533

KANSAS CITY
1445 Taney St.
North Kansas City
(816) 842-3366

ST. LOUIS
6025 Byzance Dr.
Hazelwood
(314) 731-0181

SPRINGFIELD
3229 East Cherry St.
(417) 888-1841

MONTANA
Billings
600 Daniel St.
(406) 245-3136

GREAT FALLS
901 River Drive S.
(406) 453-5471

NEBRASKA
Lincoln
545 "L" St.
(402) 432-7525

NEW HAMPSHIRE
Manchester
300 Gay St.
(603) 627-3881

NEW JERSEY
Clifton
400 Allwood Rd.
(201) 773-1000

TRENTON
530 U.S. Route #130
Yardville
(609) 585-1100

NEW MEXICO
Albuquerque
1820 Bellamah N.W.
(505) 242-2791

NEW YORK
Albany
Brown and Ind. Rds.
(518) 456-8080

SINGHINGTON
Broome Ind. Pk.
Kirkwood
(807) 775-1120

BUFFALO
2585 Walden Ave.
(716) 685-2323

LONG ISLAND
175 Underhill Blvd.
Syosset
(516) 921-7200

NEW YORK CITY
1 Hudson River Dr
Croton-on-Hudson
(914) 271-6201

ROCHESTER
1460 East Henrietta Rd.
(716) 442-1800

SYRACUSE
Midler Park Dr.
(315) 437-1201

NORTH CAROLINA
Asheville
Route #2, Azalea Road
(704) 298-5274

CHARLOTTE
3300 Parkside Dr.
(704) 394-3171

GREENSBORO
3005 Flagstone Dr.
(919) 275-8431

RALEIGH
3501 Tarheel Dr.
(919) 876-4430

WILMINGTON
319 Marlboro St.
(919) 798-8200

OHIO
Akron
2644 Gilchrist Rd.
(216) 784-1140

CINCINNATI
4710 Dues Dr.
(513) 874-4123

CLEVELAND
19100 Holland Rd.
(216) 234-1376

COLUMBUS
2100 Refugee Rd.
(614) 445-8256

DAYTON
5150 Webster St.
(513) 278-5886

TOLEDO
2815 Hill Ave.
(419) 536-3721

OKLAHOMA
Oklahoma City
5519 N.W. Fourth St.
(405) 946-0737

TULSA
5717 North Mingo
(918) 272-2211

OREGON
Eugene
3445 W. 1st Ave.
(503) 345-4356

PORTLAND
10515 S.W. Allen Ave.
Beaverton
(503) 235-4178

PENNSYLVANIA
Lancaster
3630 Hempfield Rd.
(717) 285-4544

PHILADELPHIA
801 First Ave.
King of Prussia
(215) 265-4800

PITTSBURGH
Hunker Rd. and Rt. 119
New Stanton
(412) 242-9100

SCRANTON
150 Pittston Ave.
Yatesville-Pittston
(717) 865-2801

RHODE ISLAND
Providence
170 Jefferson Blvd.
Warwick
(401) 463-7700

SOUTH CAROLINA
Charleston
Bennett Ind. Park
(803) 554-8191

COLUMBIA
855 Brookwood Dr.
(803) 256-1501

GREENVILLE
Hayward Road
(803) 268-2020

TENNESSEE
Bristol
100 Paty Indus. Blvd.
(615) 968-4121

CHATTANOOGA
201 East 28th St.
(615) 698-8076

KNOXVILLE
1301 Mitchell St., N.E.
(615) 548-4441

MEMPHIS
4287 Pilot Dr.
(901) 365-2100

NASHVILLE
331 28th Ave., N.
(615) 363-7160

TEXAS
Austin
2418 East Sixth St.
(512) 478-7406

BEAUMONT
8550 Oakcrest Drive
(713) 892-6720

CHARLOTTE
230 Omaha Dr.
(512) 884-3231

DALLAS
1800 John Connally Dr.
Carrollton
(214) 242-4281

EL PASO
6990 Market St.
(915) 778-6353

FORT WORTH
4747 Mark IV Parkway
(817) 625-2351

HOUSTON
650 Gellhorn Dr.
(713) 875-1721

LUBBOCK
702 East 44th St.
(806) 747-3626

SAN ANTONIO
535 North W. White Rd.
(512) 333-8110

TYLER
8th Street & Lawton Ave.
Owensboro
(214) 877-3161

UTAH
Salt Lake City
2875 S. 300 W.
(801) 468-6261

VERMONT
Burlington
Pine Haven Shore Road
Shelburne, Vt.
(802) 965-2511

VIRGINIA
Lynchburg
Graves Mill Rd.
Timberlake
(804) 236-9241

NORFOLK
200 Price St.
Virginia Beach
(804) 498-6861

RICHMOND
Corner Dabney &
Bathlehem Rds.
(804) 355-6167

WASHINGTON
Bellingham
629 Cornwall Avenue
(206) 733-8000

SEATTLE
12815 N.E. 178th St.
Woodinville
(206) 466-0741

SPOKANE
6815 E. Mission
(509) 828-3030

TACOMA
2302 Ross Way
(206) 383-4578

WASHINGTON, D.C.
Washington, D.C.
8121 Ardwick-Ardmore Road
Landover, Maryland
(301) 322-2270

WEST WASHINGTON, D.C.
11800 Balls Ford Rd.
Manassas, Virginia
(703) 361-5147

WEST VIRGINIA
Charleston
Rock Branch Ind. Pk.
Poca, W. Va.
(304) 755-8443

WISCONSIN
Madison
703 Mayfair Ave.
(608) 241-3874

MILWAUKEE
5059 North 119th St.
(414) 464-7900

WASCO
809 S. 62nd Ave.
(715) 842-0651

CANADIAN BRANCHES
Georgia-Pacific Building
Materials, LTD.

CALGARY, ALBERTA
8206-30th Ave. S.E.
(403) 278-4436

TORONTO, ONTARIO
55 Doney Crescent
Concord
(416) 669-9700

VANCOUVER, B.C.
916 River Dr., Richmond
(604) 273-7621

WINNIPEG, MANITOBA
1500 Clarence Ave.
Fort Gary
(204) 453-9027

SGP 0023315

GYPSUM/SALES OFFICES

CALIFORNIA
2300 Polvorosa Ave.
P.O. Box 24373
Oakland—415/352-5100

DELAWARE
Wilmington Marine Terminal
P.O. Box 310
Wilmington—302/688-7221

GEORGIA
125 Otley Drive N.E.
P.O. Box 13806 Sta. K.
Atlanta—404/873-8351

ILLINOIS
10450 Waveland Ave.
Franklin Park—312/678-8945

TEXAS
1800 John Connally Drive
Carrollton—214/242-4281

WASHINGTON, D.C.
8121 Ardwick-Ardmore Road
P.O. Box 1485
Landover, Md.—301/773-3320

GYPSUM EXPORT DEPT.
PENNSYLVANIA
1805 Race St.
Philadelphia, Pa.—215/588-7811

Georgia-Pacific

900 S.W. Fifth Avenue
Portland, Oregon 97204

Litho in U.S.A.

Georgia Pacific



SGP 0023316