

URGENT

A FURTHER WORD OF CAUTION

WITH REFERENCE TO THE SIGNS YOU MAY BE GETTING
MADE UP CONCERNING ASBESTOS DUST, WE CALL YOUR
ATTENTION TO THE FACT THAT YOUR SIGN SHOULD
COMPLY WITH SPECIFICATIONS UNDER RULE AND
REGULATION NO. 1926.200, A COPY OF WHICH IS PRINTED
ON THE REVERSE FOR YOUR CONVENIENCE. THE SIGN
FOR THE DUST HAZARD SHOULD BE AS IS SHOWN IN
FIGURE G-2. PLEASE BE GUIDED ACCORDINGLY.

WE ALSO CAUTION YOU THAT ACCIDENT PREVENTION
TAGS CAN NOT BE USED IN PLACE OF OR AS A SUBSTITUTE
FOR THE SIGNS.

OVER

77--00002

Subpart G—Signs, Signals, and Barricades

§ 1926.200 Accident prevention signs and tags.

(a) *General Signs* and symbols required by this subpart shall be visible at all times when work is being performed, and shall be removed or covered promptly when the hazards no longer exist.

(b) *Danger signs.* (1) Danger signs (see Figure G-1) shall be used only where an immediate hazard exists.

(2) Danger signs shall have red as the predominating color for the upper panel; black outline on the borders; and a white lower panel for additional sign wording.

(c) *Caution signs.* (1) Caution signs (see Figure G-2) shall be used only to warn against potential hazards or to caution against unsafe practices.

(2) Caution signs shall have yellow as the predominating color; black upper panel and borders; yellow lettering of "caution" on the black panel; and the lower yellow panel for additional sign wording. Black lettering shall be used for additional wording.

Figure G-1.




Figure G-2.



(d) *Exit signs.* Exit signs, when required, shall be lettered in legible red letters, not less than 6 inches high, on a white field and the principal stroke of the letters shall be at least three-fourths inch in width.

(e) *Safety instruction signs.* Safety instruction signs, when used, shall be white with green upper panel with white letters to convey the principal message. Any additional wording on the sign shall be black letters on the white background.

(f) *Directional signs.* Directional signs, other than automotive traffic signs specified in paragraph (g) of this section, shall be white with a black panel and a white directional symbol. Any additional wording on the sign shall be black letters on the white background.


(g) *Traffic signs.* (1) Construction areas shall be posted with legible traffic signs at points of hazard.

(2) All traffic control signs or devices used for protection of construction workmen shall conform to American National Standards Institute D6.1-1971, Manual on Uniform Traffic Control Devices for Streets and Highways.

(h) *Accident prevention tags.* (1) Accident prevention tags shall be used as a temporary means of warning employees of an existing hazard, such as defective tools, equipment, etc. They shall not be used in place of, or as a substitute for, accident prevention signs.

(2) Specifications for accident prevention tags similar to those in Table G-1 shall apply.

Table G-1



White tag - White letters on red square

White tag - White letters on red oval with a black square

Yellow tag - Yellow letters on a black background

White tag - White letters on black background

Basic Stock (Background)	Safety Colors (Ink)	Copy Specification (Letters)
White	Red	Do Not Operate
White	Black and Red	Danger
Yellow	Black	Caution
White	Black	Out of Order Do Not Use

(1) *Additional rules.* American National Standards Institute (ANSI) Z35.1-1968, Specifications for Accident Prevention Signs, and Z35.2-1968, Specifications for Accident Prevention Tags, contain rules which are additional to the rules prescribed in this section. The employer shall comply with ANSI Z35.1-1968 and Z35.2-1968 with respect to rules not specifically prescribed in this subpart.

§ 1926.201 Signaling.

(a) *Flagmen.* (1) When operations are such that signs, signals, and barricades do not provide the necessary protection on or adjacent to a highway or street, flagmen or other appropriate traffic controls shall be provided.

(2) Signaling directions by flagmen shall conform to American National Standards Institute D6.1-1971, Manual on Uniform Traffic Control Devices for Streets and Highways.

(3) Hand signaling by flagmen shall be by use of red flags at least 18 inches square or sign paddles, and in periods of darkness, red lights.

(4) Flagmen shall be provided with and shall wear a red or orange warning garment while flagging. Warning garments worn at night shall be of reflectorized material.

(b) *Crane and hoist signals.* Regulations for crane and hoist signaling will be found in applicable American National Standards Institute standards.

§ 1926.202 Barricades.

Barricades for protection of employees shall conform to the portions of the American National Standards Institute D6.1-1971, Manual on Uniform Traffic Control Devices for Streets and Highways, relating to barricades.

§ 1926.203 Definitions applicable to this Subpart.

(a) "Barricade" means an obstruction to deter the passage of persons or vehicles.

(b) "Signs" are the warnings of hazard, temporarily or permanently affixed or placed, at locations where hazards exist.

(c) "Signals" are moving signs, provided by workers, such as flagmen, or by devices, such as flashing lights, to warn of possible or existing hazards.

(d) "Tags" are temporary signs, usually attached to a piece of equipment or part of a structure, to warn of existing or immediate hazards.

77--00003

5/10/71

NON-CASEIN TAPING COMPOUND

<u>RAW MATERIALS</u>	<u>POUNDS</u>	<u>UNIT COST</u>	<u>TOTAL COST</u>
B-48 SUPERNOURALTEX SC/200	1.0	.876	.876
B-35 CELLOSIZER QP 10,000 H	2.0	.760	1.520
W-89 WHITING	622.0	.011	6.842
W-121 LOVE CLAY	150.0	.018	2.700
W-51-1203 MICA	80.0	.054	4.320
VANICIDE 51-2 PRESERVATIVE	.5	1.200	.600
COVOL 9772 POLYVINYL ALCOHOL	28.5	.441	12.569
R-65-329 STARCH	10.0	.150	1.500
JM COLLINGA FLOATS ASBESTOS	60.0	.033	1.980
UNION CARBIDE SG-210 ASBESTOS	20.0	.055	1.100
PD-7 DEFUMER	1.0	.340	.340
CRYSTAL TALC	25.0	.020	.500
TOTALS	1000.0 LBS.		\$ 34.847

RAW MATERIAL COST / 1000 LBS. — \$ 34.847

1% LOSS — \$ 35.200

RAW MATERIAL COST / 100 LBS. — \$ 3.52

MFG CHARGE — \$ 1.00

PACKAGING COST / 100 LBS. — \$.32

TOTAL COST / 100 LBS. — \$ 4.84

COST PER 25 LB. BAG — \$ 1.21

+ 11% — \$ 1.343

77-00005

8/10/71

NON-CASEIN TAPING COMPOUND

<u>RAW MATERIALS</u>	<u>POUNDS</u>	<u>UNIT COST</u>	<u>TOTAL COST</u>
B-45 SUPERNORALTEX JC/200	1.0	.876	.876
D-35 CELLOSIZ E GP 10,000 H	2.0	.760	1.520
M-60 TRF-7 ASBESTUS	120.0	.047	5.640
N-82 WHITING	608.0	.011	6.688
P-121 LOVE CLAY	150.0	.018	2.700
R-17 1203 MICA	80.0	.054	4.320
S-1012 61-2 PRESERVATIVE	.5	1.200	.600
T-101 97121 POLYVINYL ALCOHOL	28.5	.441	12.569
U-34 329 STARCH	10.0	.150	1.500
TOTALS	1000.0 LBS.		\$ 36.413

RAW MATERIAL COST / 1000 LBS. — \$ 36.413

1% LOSS — \$ 36.777

RAW MATERIAL COST / 100 LBS. — \$ 3.68

MFG. CHARGE — \$ 1.00

PACKAGING COST / 100 LBS. — \$.32

TOTAL COST / 100 LBS. — \$ 5.00

COST PER 25 LB. BAG — \$ 1.25

11% LOSS — \$ 1.39

00006