

ZONE
88-III

EFFECTIVE JULY 15, 1966
SUBJECT TO CHANGE WITHOUT NOTICE

SUGGESTED
WHOLESALE
PRICE LIST

**GLIDDEN PAINTS
SPRED PRODUCTS**

Glidden

Glidden

INTERIOR WALL, CEILING AND WOODWORK FINISHES

SPRED[®] SATIN Y-3400 LINE

(100% Latex Interior Paint)

Original 100% latex base paint for interior walls, ceilings, woodwork. Excellent for masonry, interior plaster, porous wallboards, acoustical tile, wallpaper. The ideal latex paint for schools, hospitals, residences, offices, motels, hotels, apartments, housing projects, etc. Extremely fast, easy application; self priming, cuts pointing time in half. No disagreeable odor. Guaranteed washable. May be tinted with DRAMATONE Tinting Colors.

	Gals.	Qts.	Pts.	½ Pts.
3400 High Hiding White	5.93	1.91	—	—
3470 Ceiling Flat White and Ready-Mixed Colors	5.93	1.91	—	—
\$3418 Decorator Tinting White (Pastel Tint Base)	5.74	1.86	—	—
(124 oz.) (31 oz.)				
\$3480 Deep Tint Base (120 oz.) (30 oz.)	5.35	1.68	—	—
\$3487 Intermediate Tint Base (122 oz.) (30.5 oz.)	5.52	1.78	—	—
For Tinting Special Colors				

SPRED SATIN DEEP COLORS

3434 Charcoal Black	5.93	1.91	—	—
3482 Beaver Brown	5.93	1.91	—	—
3484 Cherry Red	7.63	2.25	—	—

APPLICATION—Brush, Roller, Spray

DRYING TIME—20 minutes; may be recoated in 4 hours

THINNER—Water

COVERAGE—Up to 500 Sq. Ft. per gallon over most surfaces

*CRAFTSMAN LATEX PAINT Y-3050 LINE

A specially formulated ready-to-use interior latex paint for application by brush or roller for plaster, wallboard, acoustical tile, masonry and wallpaper.

*SPRED STIPPLE TEXTURE AND BLOCK FILLER Y-3090

(Silicated Latex for Masonry and Dry-Wall Construction)

Ready to use on new or old surfaces. Gives all the advantages of texture and all the beauty of paint in one application. Hides irregular surfaces on plaster, wallboard, masonry blocks and wallpaper, seals spackled nail heads and tape joints. Easily applied with brush or roller. May be stippled or lightly textured in a variety of patterns and techniques. Especially made for texturing and stippling and for filling masonry blocks, pores and voids, to eliminate "pinholing" in finish coat, to assure better water repellency and to develop excellent appearance on interior and exterior masonry. May be tinted with DRAMATONE Tinting Colors.

Bone White	4.91	1.67	—	—
-------------------------	------	------	---	---

APPLICATION—Brush for texturing, followed by stipple brush, sponge, trowel, whisk broom, comb, etc., as desired. Use roller for stipple effect. Brush, roll or spray when used as a block filler

DRYING TIME—Overnight

THINNER—Water

COVERAGE—Texturing and filling blocks—75 to 100 Sq. Ft. per gallon. Stippling—175 to 200 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

SPRED FLAT Y-3000
(OIL EMULSION INTERIOR PAINT)

One gallon makes six quarts of paint when mixed with two quarts of water. Easy to apply over wallpaper, new or old plaster, wallboard, painted surfaces, cement and rough tile walls. Has limited washability

White

4.67

1.67

—

—

APPLICATION—Brush, Roller, Spray

DRYING TIME—30 minutes; recoat 4 to 12 hours, depending upon surface

THINNER—Water

COVERAGE—Up to 650 Sq. Ft. per gallon

BRUSH-DAY-LITE ALKYD FLAT ENAMEL
Y-5700 LINE

Beautiful, completely washable, flat alkyd enamel for interior wall surfaces, including plaster, wood, concrete, wallboard and metal. Can be applied quickly with a wide brush or roller. Flows out smoothly. One coat is usually sufficient. Colors match SPRED SATIN

White and Colors

5.21

1.70

—

—

APPLICATION—Brush, Roller, Spray

DRYING TIME—4 hours; overnight for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

§5718 Tinting White (Pastel Tint Base) (124 oz.) (31 oz.)

5.09

1.61

—

—

§5787 Intermediate Tint Base (122 oz.) (30.5 oz.)

5.00

1.58

—

—

§5780 Deep Tint Base (120 oz.) (30 oz.)

4.91

1.56

—

—

For Tinting Brush-Day-Lite Alkyd Flat Enamel Colors

UNDERCOATERS AND PRIMERS FOR
WALLS, CEILINGS AND WOODWORK

***SPRED PRIMER-SEALER Y-3416**
(A Latex Vapor-Barrier)

An excellent latex primer for porous surfaces of dry-wall construction, plaster, masonry and asbestos covered pipes. Seals high-suction plaster, most water stains, "hot spots" and discolored surfaces. Assures positive sealing and holdout for succeeding finishing coats of either latex or oil base paints. May be intermixed with latex paints for color, or tinted with DRAMATONE Tinting Colors. An approved vapor barrier which helps to prevent outside paint failures

APPLICATION—Brush, Roller, Spray

THINNER—Water

DRYING TIME—20 minutes; may be recoated in 4 hours

COVERAGE—Up to 400 Sq. Ft. per gallon on plaster; 100 Sq. Ft. per gallon on porous wallboard

5.54

1.78

—

—

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.
§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

***GLIDDENCOAT (White Enamel Undercoat) Y-555**

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with DRAMATONE Tinting Colors

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

6.20

2.03

1.22

.75

RIPOLIN UNDERCOAT Y-2555

A perfect first coater for new wood or previously painted surfaces. Dries to a firm opaque film. Especially designed for use with Ripolin Semi-Gloss and Gloss Enamels. Completely hides and seals a surface so that finishing coats of Ripolin Enamel produce full luster and depth of gloss. Requires only light sanding. May be tinted with DRAMATONE Tinting Colors

APPLICATION—Brush, Spray

DRYING TIME—Overnight for sanding and recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

6.98

2.21

1.31

—

***SPRED WALL ALKYD INTERIOR BASECOAT Y-4516**

A ready-to-use, low odor, alkyd-type primer-sealer for new and old interior wall surfaces of plaster, masonry or wallboard. Also for previously painted walls in poor condition and patched areas. Its remarkable ease of brushing and exceptional filling, sealing, hiding and alkali-resisting properties are gained through the use of special resins, pigments and oils

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 450 Sq. Ft. per gallon

5.30

1.76

—

—

ENAMELS - SEMI-GLOSS

***SPRED LUSTRE SEMI-GLOSS ENAMEL
Y-4600 LINE**

(Interior-Exterior Washable Alkyd Enamel)

Ready to use. Covers most surfaces in One Coat. Requires no other primer on new plaster or new wood. Ideal for kitchens, bathrooms, hallways, walls, furniture, plaster, woodwork and metal. Washes like tile. Colors match SPRED SATIN. May be tinted with DRAMATONE Tinting Colors.

4600 Super White

7.35

2.27

1.32

—

4600 Ready-Mixed Colors

7.27

2.25

—

—

\$4618 Tinting White (Pastel Tint Base) (124 oz.) (31 oz.)

7.18

2.17

—

—

\$4680 Deep Tint Base (120 oz.) (30 oz.)

6.59

2.00

—

—

\$4687 Intermediate Tint Base (122 oz.) (30.5 oz.)

6.76

2.08

—

—

For Tinting Special Colors

*AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

SPRED LUSTRE DEEP COLORS

4634 Charcoal Black	7.27	2.25	—	—
4682 Beaver Brown	7.27	2.25	—	—
4684 Cherry Red	9.31	2.59	—	—

APPLICATION—Brush, Roller, Spray

DRYING TIME—Dust free 3 to 4 hours; recoat overnight

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 550 Sq. Ft. per gallon

RIPOLIN ENAMEL SEMI-GLOSS (Quick Drying) Y-2950

One of the oldest and finest enamels with world-wide acceptance. Architects and painters recognize RIPOLIN as the finest enamel for interior and exterior decorating. May be tinted with DRAMATONE Tinting Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—6 to 8 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

*CRAFTSMAN SEMI-GLOSS ENAMEL WHITE AND COLORS Y-6650 LINE

A self-priming semi-gloss enamel in white and in colors matching Craftsman Latex Colors. Recommended for interior use on woodwork, furniture, kitchen and bathroom walls and cabinets

ENAMELS - GLOSS

JAPALAC ENAMEL Y-1200 LINE

(QUICK-DRYING, ALKYD GLOSS)

An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces—walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors.

Ultra White, Brilliant Black, Flat Black and Colors	9.14	2.66	1.49	.89
§1218 Pastel Tint Base (124 oz.) (31 oz.)	8.90	2.57	—	—
§1280 Deep Tint Base (120 oz.) (30 oz.)	8.54	2.48	—	—
§1287 Intermediate Tint Base (122 oz.) (30.5 oz.)	8.78	2.52	—	—
For Tinting Special Colors				

APPLICATION—Brush, Roller, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Approx. 500 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

RIPOLIN ENAMEL GLOSS (Quick Drying) Y-2900

One of the oldest and finest enamels with world-wide acceptance. Architects and painters recognize RIPOLIN as the finest enamel for interior and exterior decorating. May be tinted with DRAMATONE Tinting Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—6 to 8 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

9.50

2.93

1.67

1.07

***CRAFTSMAN GLOSS ENAMEL WHITE Y-6500**

A quality gloss enamel recommended for interior use on woodwork, furniture, kitchen and bathroom walls and cabinets

**DRAMATONE MULTI-PURPOSE
TINTING COLORS Y-1750 LINE**

(FOR TINTING LATEX, ALKYD AND OTHER PAINTS)

Tinting colors for use with SPRED SATIN Latex Paint, Alkyd Semi-Gloss Enamel, Alkyd Flat Enamel and Other Paints. See Dramatone displays for wide range of colors.

1750 (N-T) Neutral Toner

1751 (F-R) Fast Red

1752 (Y-OX) Yellow Oxide

1753 (L-Y) Lemon Yellow

1754 (YE-G) Yellow Green

1755 (T-GR) Thalo Green

1756 (T-BL) Thalo Blue

1757 (VIO) Violet

1758 (R-O) Rich Orange

1782 (BLK) Black

1786 (OX-R) Oxide Red

1.oz.
Per tube

Qts.

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

.69

—

—

—

WOOD FINISHING MATERIALS

WOOD STAINS, FILLERS, VARNISH STAINS

***Glid-Tone Redwood Stain Y-31**

A penetrating flat Redwood Stain and Sealer designed especially to protect and beautify natural exterior wood such as siding, shingles, shakes, panels, doors, fences, picnic tables and yard furniture. If gloss finish is desired use Clear Redwood Finish Y-30

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon, first coat. 2nd Coat: Up to 600 Sq. Ft. per gallon. 3rd Coat: Up to 800 Sq. Ft. per gallon.

Gals.

Qts.

Pts.

½ Pts.

5.21

1.70

—

—

*AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

GLID-TONE WOOD STAIN Y-242 LINE

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

Stains, All Colors

APPLICATION—Wiping Cloth, Brush

DRYING TIME—12 hours

THINNER—Mineral Spirits....

Gals.

Qts.

Pts.

½ Pts.

5.57

1.85

1.13

.71

GLID-TONE RE-GRAIN GROUND COAT Y-260

An enamel undercoater that produces a firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Re-Grain Process Folder

—

2.30

1.31

.80

GLID-TONE VARNISH STAIN Y-1201-02-03

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof

APPLICATION—Brush, Spray

DRYING TIME—4 to 6 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

6.89

2.12

1.22

.76

GLID-TONE WOOD FILLER Y-700

For use on all open-grained wood such as oak, chestnut, walnut and mahogany. Has pure siliceous base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine

APPLICATION—Brush, Cloth

THINNER—Turpentine, Naphtha

5.48

1.76

—

.71

XPRT SPRAY OIL STAINS Y-4801 LINE

Permanent pigment stains for staining new wood. They give traditional-modern tones for interior and exterior wood surfaces

(4 oz.)
.77

—

—

—

WOOD FINISHING KITS AND AVAILABLE COMPONENTS

549 ANTIQUE KIT

This beautiful antique finish may be applied directly over old finishes or on new, unfinished wood

Components of Kit available separately:

507 Antique Base Coat

508 Patina Glaze

(per kit)
3.56

—

—

—

—

—

1.71

—

—

—

—

1.12

651 MARBLEIZING KIT

This is a beautiful finish which can be used in many areas of the home. Colors are available in the tones and hues of authentic marble

Components of Kit available separately:

657 M-1 Base

(per kit)
4.48

—

—

—

—

—

—

.85

Glidden

652 VENETIAN GOLD KIT

A lavish and elegant finish which may be applied to almost any sound surface. It is a dramatic accent for feature walls, table tops, doors, furniture and decorative panels

Components of Kit available separately:

653 V-1 Base

654 V-2 Gold

Gals.	Qts.	Pts.	½ Pts.
-------	------	------	--------

(per kit)

5.93

—

—

—

—

—

—

.71

—

—

—

1.12

CLEAR VARNISHES AND FLOOR SEALERS

GLID-TONE GLOSS VARNISH Y-1

A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed

APPLICATION—Brush

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

8.27

2.48

1.40

.87

GLID-TONE SATIN SHEEN VARNISH Y-47

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS

APPLICATION—Brush

DRYING TIME—2 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

7.34

2.21

1.31

.80

GLID-TONE SPAR VARNISH Y-48

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use—spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces

APPLICATION—Brush

DRYING TIME—8 hours; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

8.81

2.57

1.52

.89

*ROCKSPAR VARNISH Y-50

Heavy bodied varnish for all interior surfaces. One coat equivalent to two coats of ordinary varnish. No shrinkage on drying. Dries with deep high gloss

APPLICATION—Brush

DRYING TIME—Overnight; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 700 Sq. Ft. per gallon

7.37

2.30

1.34

.80

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

**CLEAR WOOD FINISHES—
POLYURETHANE**

***GLID-TONE POLYURETHANE REDWOOD FINISH
CLEAR Y-30**

A brilliant gloss finish for redwood, red cedar, pine and other exterior wood surfaces. Mildew and fume resistant. Provides a tough, erosion resistant film that maintains flexibility and resists checking, cracking, hardening

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Mineral Spirits, Turpentine, VM & P Naphtha

COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon. Second Coat: 500-600 Sq. Ft. per gallon. Third Coat: 600-800 Sq. Ft. per gallon.

Gals.

Qts.

Pts.

½ Pts.

7.91

2.30

—

—

**XPERT POLYURETHANE LIQUID PLASTIC
SATIN SHEEN Y-37**

Clear plastic satin-sheen finish for interior-exterior use. Outwears conventional interior finishes two to one. Provides 25% more durability for exteriors. For use on floors, furniture, paneling or exterior redwood, doors, shutters, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding

10.34

2.93

1.67

—

**XPERT POLYURETHANE LIQUID PLASTIC
CLEAR GLOSS Y-51**

Clear, high gloss plastic finish that will outwear conventional lacquers and varnishes two to one for interior use. Gives up to 25% greater durability for exteriors. May be used on floors, furniture, paneling or exterior redwood, cedar doors, etc. Not recommended over shellac, lacquer sanding sealers, lacquer or for large areas of exterior siding

8.60

2.48

1.49

—

**XPERT SATIN SHEEN POLYURETHANE
CLEAR SPRAY Y-4035**

A clear, low-gloss polyurethane protective coating for finishing wood surface.

(13 oz.)

1.61

—

—

—

**METAL PROTECTIVE PRIMERS
AND ENAMELS**

JAPALAC SCREEN AND IRON ENAMEL Y-1222

Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters, andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting

APPLICATION—Brush, Spray or Special Applicator

DRYING TIME—6 to 8 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

4.67

1.58

.95

.62

***METALLITE ALL-PURPOSE ALUMINUM Y-592**

An extremely smooth, chrome-like aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Will not tarnish under ordinary conditions. It maintains its brilliance. Makes an excellent sealer over asphalt. Retards corrosion caused by fumes and moisture. Withstands heat up to 500°F. Hides with one coat. Easily cleaned. Reflects light...

APPLICATION—Brush, Roller, Spray

DRYING TIME—2 to 4 hours; 24 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—650 Sq. Ft. per gallon

6.47

2.03

1.22

.71

Glidden

RUSTMASTER GLOSS ENAMEL Y-470 LINE

A high quality versatile enamel of excellent quality. It has exceptional ease of application and may be applied by brushing or spraying as a finish coat over metal with Y-470 or Y-471 Rustmaster Primer. Rustmaster Gloss Enamel guards against rusting of machinery and equipment in the factory and on the farm as well as metal surfaces around the home and schools such as metal window frames and casings, iron fences, railings, bicycles, lawn mowers, playground equipment, etc.

Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum.... 8.27 2.48 1.49 .89
Suntone, Flare Red 8.27 2.48 1.49 .89
White 8.27 2.48 1.49 .89

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for Brushing; VM & P Naphtha for Spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

RUSTMASTER METAL PRIMER Y-470

A new, unexcelled, fast drying corrosion resistant exterior and interior metal primer containing revolutionary Phenolic Resin Penetrating (U.S. Patent No. 2978424) that cuts through rust and seals metal pores, locking out air and corrosive moisture. A finish coat of Rustmaster Enamel will provide an exceptionally durable coating

APPLICATION—Brush, Spray

DRYING TIME—Overnight

THINNER—Turpentine or Mineral Spirits for brushing; VM & P Naphtha for spraying

COVERAGE—Up to 500 Sq. Ft. per gallon

RUSTMASTER GALVANIZED PRIMER Y-471

Provides longer-lasting protection for galvanized metal and aluminum. Use on new galvanized steel without chemical treatment. This prime coat may be used as a finish coat or recoated with Rustmaster Enamel, Endurance House Paint or Japalac.

APPLICATION—Brush, Roller, Spray

DRYING TIME—48 hours

THINNER—Turpentine, Mineral Spirits

COVERAGE—Approx. 350 Sq. Ft. per gallon

PAINT AND VARNISH REMOVERS

*AD-EL-ITE PAINT AND VARNISH REMOVER Y-70

A top-quality remover. Contains no alkalis, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan

GLID-STRIP (Non-Flammable) Y-74 (Wash-Away Paint and Varnish Remover)

A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID-STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal

	Gals.	Qts.	Pts.	½ Pts.
Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum....	8.27	2.48	1.49	.89
Suntone, Flare Red	8.27	2.48	1.49	.89
White	8.27	2.48	1.49	.89
RUSTMASTER METAL PRIMER Y-470	8.27	2.48	1.49	.89
RUSTMASTER GALVANIZED PRIMER Y-471	8.27	2.48	1.49	.89
*AD-EL-ITE PAINT AND VARNISH REMOVER Y-70	3.41	1.22	.86	.55
GLID-STRIP (Non-Flammable) Y-74 (Wash-Away Paint and Varnish Remover)	6.71	2.12	1.22	.74

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

Glidden

SPRAY ENAMELS AND PRIMER

JAPALAC SPRAY ENAMEL Y-4000—LINE In Ready-to-Spray Cans

All-purpose, interior-exterior enamel in pressurized aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold and a clear finish.

White, All Colors and Clear

APPLICATION—Spray

DRYING TIME—10 minutes

Gals.

Qts.

Pts.

½ Pts.

(16 oz.)

1.43

(4 oz.)

.77

—

—

RUSTMASTER PRIMER Y-4030 (Spray Can)

Same quality as Rustmaster Metal Primer Y-470, packed in handy spray can for easy, instant use. Ideal for hard-to-reach areas

APPLICATION—Spray

DRYING TIME—Overnight for recoating

(13 oz.)

1.70

—

—

—

MISCELLANEOUS

SPRED SURFACENE Y-66 (Liquid Surface Conditioner and Brush Cleaner)

A clear liquid that can be applied to old enameled, painted or varnished surfaces to clean the surface, dull the glass and insure good adhesion for a new finish coat. Eliminates the work and dust of sanding and prepares surfaces for refinishing in one easy operation. SURFACENE may also be used as a brush cleaner

APPLICATION—Cloth or Brush

4.58

1.49

.95

—

SPRED PATCH Y-3475 (100% Latex Spackling Compound)

A ready-to-use spackling compound. Will not bleed through paint or flash. Does not shrink. Dries to a "puff" which may be easily sanded. Does not clog sandpaper. Excellent adhesion

APPLICATION—Putty Knife

DRYING TIME—30 minutes

THINNER—Water

4.39

1.55

—

.63

SILICONE SLICK SPRAY Y-58 (Miracle Lubricant with 1001 Uses)

A new, spray lubricant that protects and preserves while it lubricates. An excellent ice and water repellent. Push button spray lubricates hard-to-reach parts and areas. Makes windows, drawers, doors and other sticking items slide freely. Stops squeaks

(16 oz.)

2.33

(6 oz.)

1.43

—

—

SPRED BRUSH AND ROLLER CLEANER Y-60

A new easy way to clean Varnish, Enamel, Epoxy, Lacquer, Urethane, Synthetics, Shellac, Polyester and Silicone from brushes and rollers

4.67

1.40

.95

—

BLOCKAID Y-1971

An all-purpose, water-resistant material for masonry filling, sealing, patching and coating — stops water seepage. Can be tinted with DRAMATONE Tinting Colors

(50# bag)

10.34

(12½# bag)

3.14

—

—

Glidden

***DRIWAL (Silicone) Y-534**

A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Keeps rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other lightweight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration. Not recommended for limestone surfaces

APPLICATION—Brush, Spray

DRYING TIME—2 hours

THINNER—None required

COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

Gals.

Qts.

Pts.

½ Pts.

4.64

—

—

—

SPRED CRETE Y-1955

A one part, pre-mixed latex-cement compound which offers outstanding advantages in patching and resurfacing masonry. Add water only. Repair concrete driveways, cement floors, masonry steps, loose bricks, loose mortar joints, stucco, set patio stones and blocks

(25# bag)

(12# bag)

5.66

4.41

—

—

PORCH AND DECK ENAMELS

**POLYURETHANE PLASTIC FLORENAMEL
Y-890 LINE**

A high quality enamel for interior and exterior floors of wood, metal and concrete.

White and Ready-Mixed Colors

§818 Pastel Tint Base (124 oz.) (31 oz.)

§880 Deep Tint Base (120 oz.) (30 oz.)

§887 Intermediate Tint Base (122 oz.) (30.5 oz.)
For Tinting Special Colors

7.70

2.30

—

—

7.19

2.21

—

—

6.80

2.07

—

—

6.92

2.16

—

—

APPLICATION—Brush, Roller

DRYING TIME—4-6 hours to touch, 24 hours for recoat

THINNER—Mineral Spirits

COVERAGE—Up to 600 Sq. Ft. per gallon

CRAFTSMAN FLORENAMEL Y-841 LINE

A high-gloss alkyl type enamel specially formulated for interior and exterior floors, steps and basement floors

APPLICATION—Brush, Roller

DRYING TIME—4-6 hours to touch; 24 hours for recoat

THINNER—Mineral Spirits or Turpentine

COVERAGE—600 Sq. Ft. per gallon

—

—

—

—

*AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.



EXTERIOR WOOD, MASONRY, SHINGLE AND SHAKE FINISHES

***SPRED HOUSE PAINT Y-3600 LINE**
(100% LATEX EXTERIOR PAINT)

A new blister-resistant house paint for exterior wood and masonry. May be applied without primer over sound previously painted surfaces which are in good condition. Has a remarkable fast drying time of thirty minutes, which practically eliminates damage from bugs, rain and dust. May be applied over damp surfaces. Has long lasting velvet-like sheen. Once the Spred House Paint system is used on a house, future paintings will require only one coat.

White and Colors
\$3625 White Tint Base (124 oz.) (31 oz.)
For Tinting Special Colors

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—4 hours for recoating

THINNER—Water

COVERAGE—Approx. 450 Sq. Ft. per gallon on smooth surface

***SPRED PRIME COAT Y-3651**
(Thin with Mineral Spirits)

Spreed Primecoat provides a firm foundation on new or unpainted exterior surfaces. The ideal undercoat that creates the finest possible two coat paint job when porous surfaces have been previously painted. This Primecoat has been especially formulated for Spreed House Paint.

APPLICATION—Brush, Roller, Spray Gun

DRYING TIME—48 hours

THINNER—Turpentine or Mineral Spirits

COVERAGE—450-550 Sq. Ft. per gallon

***SPRED GLIDE-ON Y-3500 LINE**

(Vinyl-Latex Exterior Masonry Paint)

An exterior vinyl-latex masonry paint, unaffected by the alkalinity found in all masonry surfaces. Designed for use on stucco, concrete, brick, concrete block, cinder block, asbestos shingle and panel siding, unglazed tile and primed metal. Keeps out moisture yet the surface "breathes" to let vapor escape from inside. A tough vinyl film that resists driving rains, hottest sunshine, mildew, snow and ice, sea air and salt water spray, strongest smog, dust and chemical fumes. Resists cracking, peeling, fading, blistering, acid and alkali action.

White and Colors.....

§3518 Pastel Tint Base (124 oz.) (31 oz.)

\$3580 Deep Tint Base (120 oz.) (30 oz.)

\$3587 Intermediate Tint Base (122 oz.) (30.5 oz.)
For Tinting Special Colors

APPLICATION—Brush, Roller, Spray

DRYING TIME—Overnight for recoating

THINNER—Water

COVERAGE—Up to 400 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS

AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Glidden

***ENDURANCE® HOUSE PAINT Y-1800 LINE**

(For Siding, Trim and Shutters)

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew; magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

1800 Outside White	—	—	—	—
1800 Regular Colors and Black	—	—	—	—
1892 Non-Chalking Trim White	—	—	—	—
1828 Crylite Green	—	—	—	—
1861 Shutter Green	8.24	2.49	1.45	—
1872 Dark Walnut	7.10	2.21	1.32	—
1871 Dark Blue	7.10	2.21	1.32	—
§1818 Pastel Tint Base (124 oz.) (31 oz.)	—	—	—	—
§1877 Intermediate Tint Base (122 oz.) (30.5 oz.)	—	—	—	—
§1880 Deep Tint Base (120 oz.) (30 oz.)	—	—	—	—
For Tinting Special Colors				

APPLICATION—Brush, Spray, Roller

DRYING TIME—16 hours; recoat in 72 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

***ENDURANCE IMPERIAL ONE-COAT Y-1867
WHITE HOUSE PAINT (Alkyd Fortified)**

Premium quality self-cleaning white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty

APPLICATION—Brush, Spray

THINNER—Mineral Spirits or Turpentine

DRYING TIME—48 hours

COVERAGE—550 Sq. Ft. per gallon

***ENDURANCE EXTERIOR BASECOAT Y-1851**

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs

APPLICATION—Brush, Spray

DRYING TIME—48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—450 to 500 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.
§SHORT FILLED TO ALLOW ADDITION OF COLORANT.

Gals.	Qts.	Pts.	½ Pts.
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
8.24	2.49	1.45	—
7.10	2.21	1.32	—
7.10	2.21	1.32	—
—	—	—	—
—	—	—	—
—	—	—	—
8.54	2.57	—	—
—	—	—	—
—	—	—	—

Glidden

GLID-TONE® WOOD STAINS—EXTERIOR Y-290

A completely new type stain with maximum beauty and durability for wood surfaces that are subjected to outdoor exposure

APPLICATION—Brush

DRYING TIME—24 hours under normal conditions

THINNER—Mineral Spirits

COVERAGE—200-300 Sq. Ft. per gallon

Gals.

Qts.

Pts.

½ Pts.

5.63

1.76

—

—

*ENDURANCE VELVET (Flat Exterior Finish) Y-2700 LINE

FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture.

White and Colors

\$2718 Pastel Tint Base (124 oz.) (31 oz.)

\$2787 Intermediate Tint Base (122 oz.) (30.5 oz.)

\$2780 Deep Tint Base (120 oz.) (30 oz.)

For Tinting Special Colors

APPLICATION—Brush, Spray

DRYING TIME—Dust-free 1 hour; 48 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—Up to 550 Sq. Ft. per gallon

6.80

2.12

—

—

6.71

2.07

—

—

6.55

1.98

—

—

6.47

1.89

—

—

*ENDURANCE BARN PAINT RED Y-500

A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal

APPLICATION—Brush, Spray

DRYING TIME—Overnight; 36 hours for recoating

THINNER—Mineral Spirits or Turpentine

COVERAGE—500 Sq. Ft. per gallon

5.00

1.67

—

—

*EVERON HOUSE PAINT Y-2200 WHITE

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT

APPLICATION—Brush, Roller, Spray

DRYING TIME—16 hours; recoat in 48 hours

THINNER—Mineral Spirits or Turpentine

COVERAGE—550 Sq. Ft. per gallon

—

—

—

—

*AVAILABLE IN 5-GAL. CANS

AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

§SHORT FILLED TO ALLOW ADDITION OF COLORANT.



	Gals.	Qts.	Pts.	½ Pts.
*CRAFTSMAN LATEX HOUSE PAINT Y-3040 A new water thinned house paint made by combining latex and alkyd resin. Dries tack free in 30 minutes. No primer required for sound painted surfaces. Unusually good, self-cleaning properties to maintain a freshly painted appearance APPLICATION —Brush, Roller DRYING TIME —4 hours for recoating THINNER —Water Only COVERAGE —400 Sq. Ft. per gallon on smooth surfaces; less on rough, porous surfaces	—	—	—	—
*CRAFTSMAN MILDEW RESISTANT WHITE HOUSE PAINT Y-2217 A house paint with unusual brushing qualities and elasticity making it ideal for all exterior painting on wood, asbestos, siding and metal. New self-cleaning properties make its brightness last. Helps protect surface from mildew	—	—	—	—
*CRAFTSMAN HOUSE PAINT WHITE Y-2218 An oil base exterior paint with easy brushing qualities making it perform well on wood, brick, stucco, concrete and metal	—	—	—	—
*CRAFTSMAN NON-CHALK WHITE Y-2240 An excellent bright white house paint. Recommended for areas adjacent to masonry or darkly painted areas as it eliminates streaks caused by weathering. May be tinted with DRAMATONE Tinting Colors	—	—	—	—
*STOCK FARM WHITE PAINT Y-596 An excellent low cost exterior paint for use on wood surfaces such as fences, barns, outbuildings, sheds, etc. This material, produced for use in stock farms, is formulated without lead pigments, and contains wood preservatives. The creosote-like odor tends to repel livestock APPLICATION —Brush, Spray DRYING TIME —Overnight, 24 hours for recoating THINNER —Mineral Spirits or Turpentine COVERAGE —Up to 450 Sq. Ft. per gallon depending upon surface condition	5.90	—	—	—
*SURFACE BOND Y-55 (SEALS POWDERY MASONRY SURFACES) A high quality, clear finish bonding coat. Designed to penetrate deeply into chalky surfaces left by previous coats of cement bondings or powder type paints on masonry surfaces. Dries hard to help prevent further chalking. Anchors old surface to make a perfect bond for SPRED GLIDE-ON, as well as other exterior and interior masonry paints APPLICATION —Brush, Spray DRYING TIME —1 to 4 days depending upon drying conditions THINNER —Turpentine or Mineral Spirits COVERAGE —300-400 Sq. Ft. per gallon NOTE: Although the formulations and recommendations contained in this price list have been established through careful evaluation, users of Glidden paints are urged to obtain specific information concerning their painting requirements. Seller's liability shall in no event exceed value of this material, which is warranted only to conform to formula or sample. Seller hereby expressly excludes all other express or implied warranties whatsoever.	6.47	2.03	—	—



Glidden

[illegible]

[illegible]

CODE NUMBER AND DESCRIPTION

Y-1 Glid-Tone Gloss Varnish	Y-1201 Glid-Tone Var. Stain, Dk. Oak	Y-3053 Craftsman Latex Pt. Azalea	Y-4017 Japalac Spray Flat White
Y-30 Glid-Tone Redwood Cl. Finish	Y-1202 Glid-Tone Var. Stain, Walnut	Y-3054 Craftsman Latex Pt. Pewter Gray	Y-4019 Japalac Spray Tan Bark
Y-31 Glid-Tone Redwood Stain	Y-1203 Glid-Tone Varn. Stain, Mah.	Y-3055 Craftsman Latex Pt. Aqua	Y-4030 Rustmaster Primer
Y-37 Xpert Satin Sheen	Y-1207 Japalac Brilliant Black	Y-3056 Craftsman Latex Pt. Hemp	Y-4516 Interior Base Coat
Y-47 Glid-Tone Satin Sheen Varnish	Y-1208 Japalac Flat Black	Y-3057 Craftsman Latex Pt. Brook Blue	Y-4550 Speedenamel White
Y-48 Glid-Tone Spar Varnish	Y-1212 Japalac Bud Green	Y-3058 Craftsman Latex Pt. Maytime	Y-4551 Speedenamel Black
Y-50 Rockspat Varnish	Y-1217 Japalac Ultra White	Y-3059 Craftsman Latex Pt. Bone White	Y-4552 Speedenamel Orange
Y-51 Xpert Clear Gloss	Y-1218 Japalac Pastel Tint Base	Y-3090 Spread Stip. Text. Bone White	Y-4553 Speedenamel Deep Green
Y-55 Surface Bond	Y-1219 Japalac Dawn Gray	Y-3400 Spread Sat. High Hiding White	Y-4554 Speedenamel Med. Green
Y-58 Silicone Slick Spray	Y-1222 Japalac Screen Black	Y-3401 Spread Satin Pale Ivory	Y-4556 Speedenamel Fire Red
Y-60 Spread Brush & Roller Cleaner	Y-1246 Japalac Rich Blue	Y-3405 Spread Satin Confetti Yellow	Y-4559 Speedenamel Lt. Yellow
Y-66 Spread Surfacing	Y-1250 Japalac Delphinium	Y-3407 Spread Satin Pinefrst Green	Y-4560 Speedenamel Med. Yellow
Y-70 Adelite Paint & Var. Remover	Y-1255 Japalac Light Ivory	Y-3410 Spread Satin Spray Blue	Y-4561 Speedenamel Light Gray
Y-74 Glid-Strip Paint & Var. Remover	Y-1256 Japalac Vermilion	Y-3413 Spread Satin Bone White	Y-4562 Speedenamel Mach. Gray
Y-242 Glid-Tone Stain—Hon. Maple	Y-1260 Japalac Rose Pink	Y-3415 Spread Satin Blossom Pink	Y-4564 Speedenamel Imp. Blue
Y-243 Glid-Tone Stain—Fr. Prov.	Y-1263 Japalac Botany Brown	Y-3416 Spread Primer Sealer	Y-4565 Speedenamel Bright Red
Y-244 Glid-Tone Stain—Mod. Red Mahogany	Y-1267 Japalac Ribbon Blue	Y-3418 Spread Satin Dec. Tint White (Pastel Tint Base)	Y-4566 Speedenamel Light Green
Y-245 Glid-Tone Stain—Walnut	Y-1270 Japalac Lemon Yellow	Y-3434 Spread Satin Charcoal Black	Y-4569 Speedenamel Spring Gr.
Y-246 Glid-Tone Stain—Wheat	Y-1271 Japalac Greenbrier	Y-3441 Spread Satin Cheer	Y-4572 Speedenamel Neutral Gray
Y-247 Glid-Tone Stain—Blonde	Y-1280 Japalac Deep Tint Base	Y-3443 Spread Satin Cotton Candy	Y-4573 Speedenamel EZC Green
Y-248 Glid-Tone Stain—Brown Mah.	Y-1287 Japalac Int. Tint Base	Y-3447 Spread Satin Sandy Beige	Y-4575 Speedenamel Tint White
Y-249 Glid-Tone Stain—Platinum	Y-1750 (N-T) Neutral Toner	Y-3449 Spread Satin Oyster White	Y-4576 Speedenamel Deep Orange
Y-250 Glid-Tone Stain—Suntan	Y-1751 (F-R) Fast Red	Y-3452 Spread Satin Silver Tint	Y-4580 Speedenamel Deep Tint Base
Y-252 Glid-Tone Stain—Maple	Y-1752 (Y-OX) Yellow Oxide	Y-3453 Celadon Green	Y-4587 Speedenamel Int. Tint Base
Y-254 Glid-Tone Stain—Cherry	Y-1753 (L-Y) Lemon Yellow	Y-3457 Spread Satin Pebble Beach	Y-4600 Spread Lustre White
Y-258 Glid-Tone Stain—Fruitwood	Y-1754 (YE-G) Yellow Green	Y-3470 Spread Satin Ceil. Flat White	Y-4618 Spread Lustre Tinting White
Y-259 Glid-Tone Stain—Butternut	Y-1755 (T-GR) Thalo Green	Y-3472 Spread Satin Medallion Gold	Y-4641 Spread Lustre Crocus Yellow
Y-260 Glid-Tone Regrain Gr. Coat	Y-1756 (T-BL) Thalo Blue	Y-3475 Spread Patch	Y-4643 Spread Lustre Cotton Candy
Y-262 Glid-Tone Stain Charcoal	Y-1757 (VIO) Violet	Y-3477 Spread Satin Biscayne Blue	Y-4647 Spread Lustre Sahara
Y-266 Glid-Tone Stain Sagebrush	Y-1758 (R-O) Rich Orange	Y-3478 Spread Satin Aquaglow	Y-4649 Spread Lustre Oyster White
Y-267 Glid-Tone Stain Pinewood Gr.	Y-1782 (BLK) Black	Y-3479 Spread Satin Sherwood Green	Y-4651 Spread Lustre Congo Ivory
Y-290 Glid-Tone St. Ext. Extender	Y-1786 (OX-R) Oxide Red	Y-3480 Spread Satin Dramatone Tint. Base	Y-4652 Spread Lustre Silver Tint
Y-292 Glid-Tone Stain Ext. Charcoal	Y-1800 Endurance House Paint White	Y-3482 Spread Satin Beaver Brown	Y-4653 Spread Lustre Celadon Green
Y-293 Glid-Tone St. Ext. Fr. Prov.	Y-1802 Endurance House Paint Black	Y-3484 Spread Satin Cherry Red	Y-4655 Spread Lustre Springtime
Y-294 Glid-Tone St. Ext. Cherry	Y-1813 End. H.P. Tobacco Brown	Y-3487 Spread Satin Int. Tinting Base	Y-4657 Spread Lustre Woodland
Y-295 Glid-Tone Stain Ext. Walnut	Y-1818 End. H.P. Pastel Tint Base	Y-3501 Spread Glide-On Bamboo	Y-4660 Spread Lustre Zircon
Y-296 Glid-Tone St. Ext. Sagebrush	Y-1828 End. H.P. Crylite Green	Y-3504 Spread Glide-On Silver Smoke	Y-4663 Spread Lustre Smoky White
Y-298 Glid-Tone St. Ext. Fruitwood	Y-1851 End. Basecoat Mildew & Fume Res.	Y-3506 Spread Glide-On Tang Red	Y-4665 Spread Lustre Pink Haze
Y-299 Glid-Tone Stain Ext. Platinum	Y-1855 End. H.P. Castle Red	Y-3510 Spread Glide-On Jewel Green	Y-4667 Spread Lustre Pebble Beach
Y-470 Rustmaster Primer	Y-1856 End. H.P. Ivory	Y-3513 Spread Glide-On Gray Violet	Y-4672 Spread Lustre Medallion Gold
Y-471 Rustmaster Galv. Primer	Y-1857 End. H.P. Cream	Y-3516 Spread Glide-On Mist Brown	Y-4677 Spread Lustre Biscayne Blue
Y-472 Rustmaster Aluminum	Y-1859 End. H.P. Light Gray	Y-3518 Spread Glide-On Pastel	Y-4678 Spread Lustre Aquaglow
Y-475 Rustmaster White	Y-1860 End. H.P. Medium Gray	Y-3519 Spread Glide-On Cascade	Y-4679 Spread Lustre Sherwood Gr.
Y-476 Rustmaster Black	Y-1861 End. H.P. Shutter Green	Y-3525 Spread Glide-On Non-Chalk White	Y-4680 Spread Lustre Dramatone Tinting Base
Y-477 Rustmaster Flat Black	Y-1867 End. H.P. Imperial White	Y-3580 Spread Glide-On Deep Tint Base	Y-4682 Spread Lustre Beaver Brown
Y-478 Rustmaster Suntone	Y-1871 End. H.P. Dark Blue	Y-3600 Spread Latex H.P. White	Y-4684 Spread Lustre Cherry Red
Y-479 Rustmaster Royal Blue	Y-1872 End. H.P. Dark Walnut	Y-3603 Spread Latex H.P. Taffy	Y-4687 Spread Lustre Tinting Base
Y-480 Rustmaster Greenfield	Y-1877 End. H.P. Int. Tint Base	Y-3606 Spread Latex H.P. Dover Gray	Y-5700 Brush-Day-Life Super White
Y-481 Rustmaster Flare Red	Y-1886 End. H.P. Light Canary	Y-3607 Spread Latex H.P. Bayberry	Y-5713 Brush-Day-Life A. Flat Buhrstone
Y-482 Rustmaster Slate	Y-1880 End. H.P. Deep Tint Base	Y-3608 Spread Latex H.P. Bark	Y-5718 Brush-Day-Life A. Flat Tinting White
Y-500 Endurance House Paint Barn Red	Y-1887 End. H.P. Pastel Green	Y-3612 Spread Latex H.P. Evergreen	Y-5747 Brush-Day-Life A. Flat Taupe
Y-507 Glid-Tone Stain Exterior Antique Base Coat	Y-1892 End. H.P. Non-Chalk. White	Y-3613 Spread Latex H.P. Onyx	Y-5780 Brush-Day-Life A. Flat Dramatone Tinting Base
Y-508 Glid-Tone Stain Antique Patina Glaze	Y-1971 End. H.P. Blockaid	Y-3616 Spread Latex H.P. Polo Tan	Y-5787 Brush-Day-Life A. Intermediate Tinting Base
Y-549 Glid-Tone Stain Antique Kit	Y-1955 Spread Crete	Y-3620 Spread Lat. H.P. Cape Cod Red	Y-6500 Craftsman Gloss En. White
Y-555 Gliddencoat En. Und. White	Y-2200 Everon House Paint White	Y-3625 Spread H.P. Tinting White	Y-6650 Craftsman Alkyd Semi-Gloss En. Alaska White
Y-651 Glid-Tone Stain Marbleizing Kit	Y-2217 Craftsman H.P. Mild. Resis.	Y-3651 Spread Prime Coat No. 1	Y-6651 Craftsman Alkyd Semi-Gloss En. Tusk Ivory
Y-652 Glid-Tone Stain Venetian Kit	Y-2218 Craftsman House Paint White	Y-4000 Japalac Spray Enamel White	Y-6652 Craftsman Alkyd Semi-Gloss En. Spearmint
Y-653 V-1 Base	Y-2240 Craftsman Non-Chalk. White	Y-4001 Japalac Spray En. Flat Black	Y-6653 Craftsman Alkyd Semi-Gloss En. Azalea
Y-654 V-2 Gold	Y-2555 Ripolin Undercoat White	Y-4002 Japalac Spray En. Gloss Bl.	Y-6654 Craftsman Alkyd Semi-Gloss En. Pewter Gray
Y-657 M-1 Base	Y-2718 Endurance Velvet Pastel Base	Y-4003 Japalac Spray Enamel Delphinium	Y-6655 Craftsman Alkyd Semi-Gloss En. Aqua
Y-592 All-Purpose Metalite Alum. Pt.	Y-2750 End. Velvet H.P. White	Y-4004 Japalac Spray Enamel Dawn Gray	Y-6656 Craftsman Alkyd Semi-Gloss En. Hemp
Y-596 Stock Farm Paint White	Y-2751 End. Vel. H.P. Mayflower Yel.	Y-4005 Japalac Spray Enamel Bud Green	Y-6657 Craftsman Alkyd Semi-Gloss En. Brook Blue
Y-700 Glid-Tone Natural Wood Filler	Y-2752 End. Vel. H.P. Sterling Gray	Y-4006 Japalac Spray Enamel Vermilion	Y-6658 Craftsman Alkyd Semi-Gloss En. Maytime
Y-800 Poly. Florenamel White	Y-2756 End. Vel. H.P. Cottage Ivory	Y-4008 Japalac Spray Aluminum	Y-6659 Craftsman Alkyd Semi-Gloss En. Bone White
Y-818 Poly. Florenamel Pastel Tint Base	Y-2757 End. Vel. H.P. Granada Red	Y-4009 Japalac Spray Gold	
Y-841 Craftsman Flor. Deck Red	Y-2759 End. Vel. H.P. Shrub Green	Y-4010 Japalac Spray Clear Plastic	
Y-842 Craftsman Flor. Deck Gray	Y-2761 End. Vel. H.P. Brown Antique	Y-4011 Japalac Spray Copper Tone	
Y-843 Craftsman Flor. Tile Green	Y-2764 End. Velvet Shadow Green	Y-4015 Japalac Spray Enamel Lemon Yellow	
Y-844 Craftsman Flor. Dark Oka	Y-2765 End. Vel. H.P. Oxford Gray	Y-4016 Japalac Spray Enamel Greenbrier	
Y-880 Poly. Flor. Deep Tint Base	Y-2766 End. Velvet H.P. Safari		
Y-887 Poly. Florenamel Int. Tint Base	Y-2780 End. Velvet Deep Tint Base		
Y-891 Poly. Florenamel Tile Red	Y-2787 End. Velvet Int. Tint Base		
Y-892 Poly. Florenamel Tile Green	Y-2900 Pipolin Ultra White		
Y-983 Poly. Florenamel Harbor Gray	Y-2950 Ripolin Semi-Gl. En. White		
Y-894 Poly. Florenamel Chat. Gray	Y-3000 Spread Flat White		
Y-895 Poly. Florenamel Spice Wood	Y-3040 Craftsman Latex H.P. White		
	Y-3050 Craftsman Latex Pt. Alaska White		
	Y-3051 Craftsman Latex Pt. Tusk Ivory		
	Y-3052 Craftsman Latex Pt. Spearmint		

THE GLIDDEN COMPANY
National Headquarters
900 Union Commerce Building
Cleveland, Ohio 44115

SALES OFFICES AND FACTORIES: New York • San Francisco • Los Angeles
Minneapolis • Dallas • Chicago • St. Louis • New Orleans • Cleveland
Atlanta • Portland • Reading • Canada: Toronto and Montreal
Branches in principal cities throughout the United States