

DATE: _____ LOT _____

ESTIMATED WEIGHT: 4021#

COMTYP JOB NAME: 01YE735DMK

EQUIP MENT	NAME: HOLYBDATE ORANGE	SE LBS	N-CODE	ACCT LBS
PREP	1 OBTAIN FOR S-34	315	4-A	315
1	2 OBTAIN FOR S-24	42	108-A	42
	3 OBTAIN FOR S-38	105	3-A	105
	4 OBTAIN FOR S-40	58	32-D	58
	5 OBTAIN FOR S-42	168	15-A	168
	6 OBTAIN FOR S-44	47	3-A	47
	7 DISSOLVE IN 30 G WATER AT 100-120°F IN DRUM FOR S-48	17	765-A	17
	8 DISSOLVE IN 30 G WATER AT 100-120°F IN DRUM FOR S-52	60	994-A	60
355 2	9 WEIGH IN OPTR _____, MK <u>2</u> , <u>32.00%</u> OPTR _____, MK _____, _____%	<u>78</u>	28-D	<u>2520</u>
351 3	10 WEIGH IN OPTR _____, MK <u>24</u> , <u>38.18%</u> OPTR _____, MK _____, _____%	<u>3235</u>	10-D	<u>4407</u> <u>1426</u>
359 4	11 WEIGH IN OPTR _____, MK <u>48</u> , <u>38.15%</u> OPTR _____, MK _____, _____%	<u>592</u>	423-D	<u>252</u> <u>226</u>
SV 5	12 FLUSH DISTRIBUTOR LINES UNTIL WATER COMES OUT ALL JETS RECORD: _____ (OK)			
	13 RUN IN 40" (1992 G) WATER			
	14 RUN IN FROM V-354. REC: OPTR: <u>31</u> , MK <u>473</u> , <u>13250</u> <u>2.68%</u> , PH <u>2.7</u> (2.8-3.7), G/ML _____ (1.270-1.328). SEE SUPV IF NOT IN RANGE.		41-D	3800
	15 ADJ TO 3350 GAL AT 67-69°F. RECORD: <u>67</u> °F (67" IN V-240 & 246; 69" IN V-241, 242, 245)		57-A	
	16 STIR 5MIN. & RECORD: PH <u>3.6</u> (2.8-3.6)			
	17 IF NECESSARY, ADJ TO PH 3.8-3.9 ASSUME 32% & RECORD: PH <u>3.9</u> (3.8-3.9) ASSUME 50% NOTE: DILUTE N-7-D 10:1 WITH WATER BEFORE ADDING	<u>2</u>	28-D 7-D	<u>1</u>
	18 RECORD: <u>1.118</u> G/ML (1.116-1.118) NOTE: IF G/ML OUT OF LIMITS, FILL OUT CHECK LIST & ATTACH			
	19 STIR AT 67-69°F FOR S-30. TAKE 1 QT SAMPLE.			
358 6	20 RUN 2" (110 G) WATER INTO V-358			
	21 RUN V-359 INTO V-351			
	22 PUMP V-351 INTO V-358			
	23 TURN ON AGITATOR			
	24 SIFT IN N-108-A FROM S-2			
	25 ADJUST TO 68" (3216 G) AT 67-69°F RECORD: <u>69</u> °F			
	26 STIR 3 MIN. & RECORD: PH <u>9.5</u> (9.0-9.5)			
	27 IF NECESSARY, ADJ. TO PH 9.0-9.5 ASSUME 32% & RECORD: PH _____ ASSUME 50%		28-D 7-D	
	28 RECORD: G/ML <u>1.060</u> (1.059-1.060) NOTE: G/ML OUT OF LIMITS FILL OUT CHECK LIST & ATTACH			
	29 STIR AT 67-69°F FOR S-30. TAKE 1 QT SAMPLE.			

EQUIP	PAGE 2 CG 01 YE-735-D EST WGT 4021#	USE LBS	N- CODE	USE LBS
130	OBTAIN 1 QT SAMPLES OF S-21 & S-29 SOLUTIONS & TITRATE TWICE RECORD: LOWEST PH <u>2.82</u> & ML N-10-D <u>2.84</u> LOWEST PH <u>2.81</u> & ML N-10-D <u>2.86</u> NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 7.8-8.2 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS) DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE			
SV 7	131 WHEN TITRATION IN S-30 OK, STRIKE V-358 THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV IN 21-23 MIN. RECORD: START <u>12:05</u> TOTAL MIN. <u>71</u> (67-71*) NOTE: STRIKE TIME UP WHEN 1/2 V-358 BOTTOM SHOWS & BUBBLES APPEARS IN SIGHT GLASSES 132 IMMEDIATELY AT END OF STRIKE WASH IN V-358 133 SET TIMER FOR <u>15</u> MIN. POUR IN N-28-D FROM S-9 A.F.A.P. 134 DUMP IN N-4-A FROM S-1 A.F.A.P. 135 AFTER N-4-A IS ADDED, STIR 2 MIN. 136 TAKE 8 OZ SAMPLE & RECORD: PH <u>2.4</u> (2.4-2.5) PBXS, <u>+</u> (MUST BE +) 137 STIR <u>15</u> MIN AFTER ADDITION OF N-4-A 138 DUMP IN N-3-A FROM S-3 139 STIR 3 MIN 140 POUR IN N-32-D FROM S-4 141 STIR 2 MIN. 142 DUMP IN N-15-A S-5 143 STIR 3 MIN. 144 DUMP IN N-3-A FROM S-6 145 STIR 3 MIN. 146 RECORD: PH <u>6.0</u> (5.8-6.0) 147 IF NECESSARY, ADJUST TO PH 5.8-6.0 RECORD: PH <u> </u> ASSUME 32% 148 POUR IN N-765-A SOLN FROM S-7 149 STIR 5 MIN 150 RECORD: PH <u>6.0</u> (5.8-6.0) 151 IF NECESSARY, ADJUST TO PH 5.8-6.0 & RECORD: PH <u> </u> ASSUME 32% 152 POUR IN N-994-A SOLN FROM S-8 (MUST BE DISSOL- VED) 153 STIR 20 MIN. 154 DURING S-53 DUMP IN 155 FLOOD TO 153" (7619 G) 156 STOP AGITATOR START FINISH OPTR HELPER <u>5:30pm</u> <u> </u> <u>301</u> <u>267</u> <u>11:00pm</u> <u>12:15pm</u> <u>237</u> <u>58</u>			
		200	3-A 28-D 3-A 28-D 128-A	 200

RECEIVED V-241-AT 8:30 pm