

SCHNACKE, INC.


1101 N. Governor St.

Evansville, Ind.


Manufacturers of Compressors and Condensing Units for commercial refrigeration and for industrial air conditioning and comfort cooling. The industry's unique line of compressors from 5 to 60 hp, with 100 per cent interchangeability of all wearing parts. Forced feed lubrication, Modern Automotive design for high efficiency and satisfactory service.

The Industry's Low Cost, Compact and Rugged Compressors


Ideal for multiple installation in close space requirements. Known for high efficiency and low price. Direct drive compressors available in 15, 30, and 60 hp. Designed for use with Freon-12 or Methyl-Chloride refrigerant.




MODEL T COMPRESSOR
5 hp to 15 hp




MODEL F COMPRESSOR
10 hp to 30 hp




MODEL E COMPRESSOR
20 hp to 60 hp



MODEL TC CONDENSING UNIT
5 hp to 15 hp



MODEL FC CONDENSING UNIT
10 hp to 30 hp



MODEL EC CONDENSING UNIT
20 hp to 60 hp


THERMATROL

or Cylinder Unloading Capacity Control
Schnacke patented Thermatrol provides modern capacity control with utmost simplicity—self contained cylinder unloading at start or for capacity control also available for the actual degree of control required.

Aladdin Heating Corporation

2272 San Pablo Ave., Oakland 12, Calif.


Manufacturers of Centrifugal Blowers,
Heating and Ventilating Equipment.



BB Fans



FC Fans




RB Fans


BB FAN—Backwardly inclined blade fan with non-overloading horsepower characteristic. Manufactured in 22 sizes, single and double width, all arrangements, 2 classes of construction. Request Bulletin 605-A, 605-B.

FC FAN—Forward curved fan, slow speed for quiet operation. Manufactured in 22 sizes, single and double width, all arrangements, 2 classes of construction. Request Bulletin 605-A, 605-C.


RB FAN—Radial blade fan well suited for handling grease or other sticky materials. Manufactured in 13 sizes, single width only, all arrangements, 2 classes of construction. Request Bulletin 450-B.



EX Fans



Utility Sets




FC Junior Fans


EX FAN—Radial blade fan used chiefly for conveying materials, fume exhaust, etc. Manufactured in 15 sizes, single width only, all arrangements, 5 classes of construction, 3 wheel types. Request Bulletin 461.

UTILITY SETS—Self contained units for a wide variety of ventilating applications. Manufactured in 12 sizes with forward curved rotors, 10 sizes with backwardly inclined blade rotors, single width only. Request Bulletins 610, 611.


FC JUNIOR FANS—Self contained direct connected fans with forward curved rotors. Manufactured in 4 sizes with 9 motor speeds, single width only. Request Bulletin 421.



HV Units



Fuseair Ceiling Outlets



HV UNITS—Heating and ventilating unit of universal design. Can be furnished with air filters, face and by-pass dampers or mixing box. Manufactured in 7 sizes with unlimited flexibility as to arrangement. Request Bulletin 510.

CEILING DIFFUSERS—Fuseair ceiling outlets are available in several types to provide rapid temperature equalization and draftless diffusion for a number of varied job requirements. Type SE and RE are provided with anti-smudge extensions; type A combines vortex flow with a variable air pattern and features a volume damper as an integral part of the unit. Request Bulletins 520, 522 and 615.