S.V. 4 (V-242) DATE PRINTED: 5/08/81

CG 01 CODE YE-698-D MAY -0-81-E1430 PROCESSES ( ) YE-698-D (S) APPROVED BY FWP 04/14/81

(DATE) (LOT NUMBER) ( ) ( ) ( ) ( )

COMTYP JOB NAME: 01YE698DMS

ESTIMATED WGT 5632 LBS. STANDARD HRS. _____ TIME _____M

EQUIPMENT		NAME: MOLYBDATE ORANGE	USE LBS	N-CODE	ACCT LBS
PREP	1	OBTAIN FOR S-22	84	108-A	84
	2	WEIGH FOR S 25 65.04%	77	33-D	56
	3	OBTAIN FOR S-30	734	4-A	734
	4	OBTAIN FOR S-34	146	3-A	146
	5	OBTAIN FOR S-36	237	32-D	237
	6	OBTAIN FOR S-38	367	15-A	367
	7	OBTAIN FOR S-40	243	3-A	243
	8	WEIGH IN DRUM FOR S-42 M2, 32.00%	219	28-D	70
	9	OBTAIN FOR S-42	70	711-B	70
351 2	10	WEIGH INTO V-351 CHECKED BY:# M54, 38.81%	4857	10-D	1885
359 3	11	WEIGH INTO V-359 CHECKED # M50, 35.61% V-360	857	423-D	303
SV 4	12	RUN 20* (996 G) WATER INTO V-242			
	13	RUN IN FROM V-354 CHECKED BY# M22, 29.90%	17080	41-D	5110
		RECORD: G/ML 1334 (1.270-1.328)			
		RECORD: PH 2.0 (2.2-3.7)			
	14	ADJ TO 79* (3770G) AT 67-69*F			
		RECORD: TEMP 67 *F	3330	57-A	990
	15	STIR 5 MIN & RECORD: PH 2.0 (2.2-3.7)			
	16	IF NECESSARY, ADJ TO PH 3.0-3.1 ASSUME 60%	—	33-D	—
		RECORD: PH 3.0			
		NOTE: DILUTE N-7-D 10:1 WITH WATER BEFORE ADDING ASSUME 50%	10	7-D	5
	17	RECORD: 1.138 G/ML (1.135-1.138)			
		NOTE: IF G/ML OUT OF LIMITS FILL OUT CHECK LIST & ATTACH			
	18	STIR AT 67-69*F FOR S 28			
358 5	19	RUN 10* (500 G) WATER INTO V-358			
	20	RUN V-359 INTO V-351 & PUMP IN V-351			
	21	ADJ TO 55* (2600 G)			
	22	SIFT IN N-10B-A FROM S 1			
	23	STIR 5 MIN & RECORD: PH 9.2 (9.0-10.0)			
	24	ADJ TO PH 9.8-9.9 & RECORD: PH 9.8			
		ASSUME 50%	2	7-D	1
		ASSUME 60%	—	33-D	—
	25	ADD N-33-D FROM S 2 (PUMP FROM V-351, FLUSH WITH 1000# WATER)			
	26	ADJ TO 66* (3121 G) AT 67-69*F			
		RECORD: VOL 66* & 67 *F			
	27	STIR 5 MIN & RECORD: PH 7.4 (7.4-7.6) & G/ML 1.083 (1.080-1.083)			
		NOTE IF G/ML OUT OF LIMITS FILL OUT CHECK LIST & ATTACH			

MAY 13 1981

EQUIP		PAGE 2 CG 01 YE-698-D EST WGT 5632#	USE LBS	N-CODE	USE LBS
	28	OBTAIN 1 QT SAMPLES OF S-18 & S-27 SOLUTIONS & TITRATE TWICE			
		RECORD: LOWEST PH _____ & ML N-10-D _____			
		LOWEST PH _____ & ML N-10-D _____			
		NOTIFY SUPV IF ML N-10-D IS NOT IN RANGE 6.8-7.1 OR IF THE TWO TITRATIONS DIFFER BY MORE THAN 0.10 ML N-10-D (IF YES, FLUSH ALL EQUIPMENT & REPEAT TITRATIONS)			
		DO NOT PROCEED IF N-10-D TITRATION IS OUT OF RANGE 2.15			
		ADJUST V-358 TO OBTAIN A TITRATION PH = ~~2.05~~ ~~(2.00-2.10)~~ 2.10-2.20	___	33-D	___
			___	7-D	___
	29	WHEN S-28 TITRATION OK , STRIKE V-358 THRU BOTH UNDERSURFACE DISTRIBUTORS INTO SV IN 16-18 MIN			
SV 6		RECORD: START 12:30 PM, TOTAL MIN 18			
		NOTE: STRIKE TIME UP WHEN 1/2 VAT BOTTOM SHOWS & BUBBLES APPEAR IN SIGHT GLASSES			
	30	IMMEDIATELY DUMP IN N-4-A FROM S 3 & SET TIMER FOR 15 MINUTES			
	31	DURING S 30, WASH IN V-358			
	32	STIR 2 MIN & RECORD PH 2.1 (1.8-2.5)			
		PBXS, + (MUST BE +)			
	33	STIR TOTAL OF 15 MIN FROM S-30 & RECORD: TEMP 71 °F (67-73°F)			
	34	DUMP N-3-A FROM S-4			
	35	STIR 3 MIN			
	36	POUR IN N-32-D FROM S-5			
	37	STIR 2 MIN			
	38	DUMP IN N-15 FROM S-6			
	39	STIR 3 MIN			
	40	DUMP IN N-3 FROM S-7			
	41	STIR 4 MIN FOR S-44			
DRUM 7	42	DURING S-41 SIFT N-711-B FROM S-9 INTO DRUM OF N-28-D FROM S-8 IN 1-2 MIN.			
	43	STIR 1-2 MIN WITH PADDLE TO MILKY SOLUTION			
SV 8	44	WHEN S-41 COMPLETE, IMMEDIATELY POUR N-711-B SOLUTION GRADUALLY OVER 5 MIN PERIOD INTO SV			
		WATCH FOAM!!! IF FOAMING IS EXCESSIVE, STOP POURING UNTIL FOAM SUBSIDES			
	45	DUMP IN	350	128-A	350
	46	STIR 10 MIN			
	47	RECORD: PH 6.0 (5.8-6.0)			
	48	IF NECESSARY, ADJ TO PH 5.8-6.0 ASSUME 50%	___	7-D	___
		& RECORD: PH- ASSUME 66%	___	33-D	___
	49	RECORD: TIME 1:45 PM			
	50	FLOOD TO 153* (7619 G)			
	51	STOP AGITATOR			

START 10:00 AM FINISH 1:45 PM OPTR 237 64 HELPER _____

DUP050096023