

NOTICE: If the film image
is less clear than this
notice, it is due to the
quality of the document
being filmed

00057

NLI 112910



NOTICE: If the film image is less clear than this notice, it is due to the quality of the document being filmed

00057

NIJ 112911

DUTCH BOY All-Purpose Soft Paste



NOTICE: If the film image is less clear than this notice, it is due to the quality of the document being filmed

: 00057

NLI 112912

TINTING WHITE-LEAD PAINT

MIXING DIRECTIONS

1. After the paint has been mixed, it should be allowed to stand for 24 hours before use.
2. The paint should be mixed in a clean, dry container.

PAINTING HINTS

1. The paint should be applied with a brush or roller. It should be applied in a thin, even coat. It should be allowed to dry for 24 hours before a second coat is applied.

2. The paint should be applied to a clean, dry surface. It should not be applied to a surface that is dirty or greasy.

3. The paint should be applied to a surface that is free of moisture. It should not be applied to a surface that is wet or damp.

4. The paint should be applied to a surface that is free of dust. It should not be applied to a surface that is dusty or sandy.

5. The paint should be applied to a surface that is free of oil. It should not be applied to a surface that is oily or greasy.

SOFT AND HEAVY PASTE

1. The paint should be applied with a brush or roller. It should be applied in a thin, even coat. It should be allowed to dry for 24 hours before a second coat is applied.

2. The paint should be applied to a clean, dry surface. It should not be applied to a surface that is dirty or greasy.

3. The paint should be applied to a surface that is free of moisture. It should not be applied to a surface that is wet or damp.

4. The paint should be applied to a surface that is free of dust. It should not be applied to a surface that is dusty or sandy.

5. The paint should be applied to a surface that is free of oil. It should not be applied to a surface that is oily or greasy.

PAINTING EXTERIOR WOOD

1. The paint should be applied with a brush or roller. It should be applied in a thin, even coat. It should be allowed to dry for 24 hours before a second coat is applied.

2. The paint should be applied to a clean, dry surface. It should not be applied to a surface that is dirty or greasy.

3. The paint should be applied to a surface that is free of moisture. It should not be applied to a surface that is wet or damp.

4. The paint should be applied to a surface that is free of dust. It should not be applied to a surface that is dusty or sandy.

5. The paint should be applied to a surface that is free of oil. It should not be applied to a surface that is oily or greasy.

PAINTING INTERIOR WOOD

1. The paint should be applied with a brush or roller. It should be applied in a thin, even coat. It should be allowed to dry for 24 hours before a second coat is applied.

2. The paint should be applied to a clean, dry surface. It should not be applied to a surface that is dirty or greasy.

3. The paint should be applied to a surface that is free of moisture. It should not be applied to a surface that is wet or damp.

4. The paint should be applied to a surface that is free of dust. It should not be applied to a surface that is dusty or sandy.

5. The paint should be applied to a surface that is free of oil. It should not be applied to a surface that is oily or greasy.

Formulas

100% White Lead	100% Zinc Oxide	100% Titanium Dioxide	100% Barium Sulfate	100% Calcium Hydroxide
100% Zinc Oxide	100% Titanium Dioxide	100% Barium Sulfate	100% Calcium Hydroxide	100% Zinc Oxide
100% Titanium Dioxide	100% Barium Sulfate	100% Calcium Hydroxide	100% Zinc Oxide	100% Titanium Dioxide
100% Barium Sulfate	100% Calcium Hydroxide	100% Zinc Oxide	100% Titanium Dioxide	100% Barium Sulfate
100% Calcium Hydroxide	100% Zinc Oxide	100% Titanium Dioxide	100% Barium Sulfate	100% Calcium Hydroxide

NOTICE: If the film image
is less clear than this
notice, it is due to the
quality of the document
being filmed



*The
Place Worth Calling
HOME is Worth
Protecting with
Dutch Boy.*

The Dutch Boy Paint Company, New York, N.Y., is the only company in the world that has been manufacturing the Dutch Boy brand of paint for over 100 years.

00057

NLI 112913

1159