

Doug Wood

Julius Nemeth

Sept. 28, 1973

Dear Julius;

The attached report from Industrial Testing Laboratories is for your information. Please pass their invoice on for payment. I have retained a copy of this report for my files.

Best regards,

Doug Wood

DW/bp
enc:



INDUSTRIAL TESTING LABORATORIES inc.

2350 Seventh Blvd. • St. Louis, Missouri 63104

Chemists

Engineers

Metallurgists

314/PROspect 1-7111

ALLAN M. SIEGEL, Director

Report No. 28-5-140E

May 14, 1974

Evaluation of worker exposure to airborne asbestos.

Reardon Company
3616 Scarlet Oak Drive
Kirkwood, Missouri 63122

Attn: Mr. Doug Wood.

TEST REPORT

On May 10, 1974 worker exposure to airborne asbestos was determined by personnel monitoring in accordance with OSHA Sampling Data Sheet No. 2 (revised). The operators exposure was monitored during his period of maximum exposure.

Time of Test:	11:04 A.M. - 11:12 A.M.
Operator Monitered:	Andrew Mayberry
Operation:	Charging ingredients for Permaroof
Mixer:	No. 8 Machine
Sampling Rate:	2 liters per minute
Sample Volume:	16,000 cubic centimeters
Asbestos Concentration:	0.2 fibers per cubic centimeter

Conclusion:

The operator's exposure is well below the 5 fibers per cubic centimeter maximum specified by Part 1910.93a of the Code of Federal Regulations.

Respectfully submitted,

INDUSTRIAL TESTING LABORATORIES, INC.

Michael F. Fuller
Michael F. Fuller
Environmental Group Leader

/hj



INDUSTRIAL TESTING LABORATORIES inc.

2350 Seventh Blvd. • St. Louis, Missouri 63104

Chemists

Engineers

Metallurgists

314/PROspect 1-7111

Report No. 28-5-140E

May 14, 1974

Evaluation of worker exposure to airborne asbestos.

Heardon Company
3616 Scarlet Oak Drive
Kirkwood, Missouri 63122

Attn: Mr. Doug Wood.

TEST REPORT

On May 10, 1974 worker exposure to airborne asbestos was determined by personnel monitoring in accordance with OSHA Sampling Data Sheet No. 2 (revised). The operator's exposure was monitored during his period of maximum exposure.

Time of Test:	11:04 A.M. - 11:12 A.M.
Operator Monitored:	Andrew Mayberry
Operation:	Charging ingredients for Fernarroof
Mixer:	No. 8 Machine
Sampling Rate:	2 liters per minute
Sample Volume:	16,000 cubic centimeters
Asbestos Concentration:	0.2 fibers per cubic centimeter

Conclusion:

The operator's exposure is well below the 5 fibers per cubic centimeter maximum specified by Part 1910.93a of the Code of Federal Regulations.

Respectfully submitted,

INDUSTRIAL TESTING LABORATORIES, INC.

Michael F. Fuller

Michael F. Fuller
Environmental Group Leader

/h