



MISCELLANEOUS ACCESSORIES AND COMPONENTS



A-c Solenoids

APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS


Size	Push Type						Pull Type					
	Dimensions in Inches					Ship. Wt. Lbs.	Dimensions in Inches					Ship. Wt. Lbs.
	Wide	High ① B	Deep C	Mounting			Wide A	High ① B	Deep C	Mounting		
				D	E					D	E	
WALL MOUNTED												
AA	---	---	---	---	---	---	1½	2¼	2½	1¾	1¼	2
A	2¾	3¾	2¼	1¾	1¾	2	2¾	2¾	2¼	1¾	1¼	2
B	2¾	4¾	3	2¾	2	2½	2¾	3¾	3	2½	2	2½
C	3	6¾	4¾	3¾	2¾	5	3	4¾	4¾	3¾	2¾	5
D	4	6¾	4¾	3¾	2¾	7	4	4¾	4¾	3¾	2¾	7
FLOOR MOUNTED												
B	3¾	4¾	3	2¼	1½	2½	3¾	3¾	3	2¼	1½	2½
C	3½	6¾	3¾	3¾	1¾	5	3½	4¾	3¾	3¾	1¾	5
D	3¾	6¾	3¾	3¾	2¼	7	3¾	4¾	3¾	3¾	2¼	7
3rd	---	---	---	---	---	---	6¾	15	7¼	5¾	5½	48
4th	---	---	---	---	---	---	7¼	20	9¾	7¾	6	100



D-c Solenoids

WHEN ORDERING SPECIFY

- Catalog number



SMALL SIZES—CONTINUOUS AND INTERMITTENT DUTY—WITH PROTECTING SWITCH



Size	Voltage	Operating Data									Pull Type				Push Type			
		② Magnetic Force in Lbs.						Maxi- mum Stroke In Inches	Current		Catalog Numbers							
		Horiz. Position		With Gravity		Against Gravity			Inrush	Sealed	Floor Mounting		Wall Mounting		Floor Mounting		Wall Mounting	
		At 100% Voltage	At 89% Voltage	At 100% Voltage	At 89% Voltage	At 100% Voltage	At 89% Voltage				Cat. No.	Price	Cat. No.	Price	Cat. No.	Price	Cat. No.	Price
B	115	3.5	2.5	3.8	2.8	3.2	2.2	1	3.8	.102	10360- H57	\$24.	10360- H93	\$24.	10360- H60	\$25.	10360- H96	\$25.
	230	3.5	2.5	3.8	2.8	3.2	2.2	1	1.9	.050	H58	24.	H94	24.	H61	25.	H97	25.
	550	3.5	2.5	3.8	2.8	3.2	2.2	1	.75	.020	H59	24.	H95	24.	H62	25.	H98	25.
C	115	7.	6.	8.	7.	6.	5.	1¼	5.9	.157	H63	29.	H99	29.	H66	31.	H102	31.
	230	7.	6.	8.	7.	6.	5.	1¼	3.24	.078	H64	29.	H100	29.	H67	31.	H103	31.
	550	7.	6.	8.	7.	6.	5.	1¼	1.68	.0323	H65	29.	H101	29.	H68	31.	H104	31.
D	115	12.5	10.	13.75	11.25	11.25	8.75	1¼	8.5	.172	H69	43.	H105	43.	H72	46.	H108	46.
	230	12.5	10.	13.75	11.25	11.25	8.75	1¼	4.8	.085	H70	43.	H106	43.	H73	46.	H109	46.
	550	12.5	10.	13.75	11.25	11.25	8.75	1¼	2.56	.0353	H71	43.	H107	43.	H74	46.	H110	46.

② Recommended selection of solenoid on basis of 89% voltage values.

APPROXIMATE DIMENSIONS AND SHIPPING WEIGHTS

Size	Push Type						Pull Type					
	Dimensions in Inches					Ship. Wt. Lbs.	Dimensions in Inches					Ship. Wt. Lbs.
	Wide	High B	Deep	Mounting			Wide	High B	Deep	Mounting		
				D	E					D	E	
WALL MOUNTED												
B	2 3/4	4 3/8	4 1/8	2 5/8	2	4	2 3/4	3 3/8	4 1/8	2 1/8	2	4
C	3	6 1/8	5 5/8	3 3/8	2 3/8	5	3	4 1/8	5 1/8	3 3/8	2 3/8	5
D	3 3/8	6 1/8	5 5/8	3 3/8	2 3/8	7	3 3/8	4 1/8	5 1/8	3 3/8	2 3/8	7
FLOOR MOUNTED												
B	3 3/8	4 7/8	4	2 1/2	1 1/2	4	3 3/8	3 3/8	4	2 1/2	1 1/2	4
C	3 3/8	5 7/8	4 1/4	3 3/8	1 1/4	5	3 3/8	4 1/8	4 1/4	3 3/8	1 1/4	5
D	3 3/8	5 7/8	4 1/4	3 3/8	2 1/4	7	3 3/8	4 1/8	4 1/4	3 3/8	2 1/4	7

① In sealed state.



DISCOUNT SCHEDULE 1 CD