Form Approved OMB No. 44-R1387
Approval Expires: July 30, 1972

U.S. DEPARTMENT OF LABOR

Form No. OSHA-20
May, 1971

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME: MONSANTO COMPANY	EMERGENCY TELEPHONE NO: (314) 694-1000
ADDRESS (Number, Street, City, State, and ZIP Code): 800 North Lindbergh Boulevard, St. Louis, Missouri 63166	
CHEMICAL NAME AND SYNONYMS: Mixture	TRADE NAME AND SYNONYMS: Aroclor 1016, MCS 1016
CHEMICAL FAMILY: Chlorinated aromatic	FORMULA: Mixture

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)

SECTION III PHYSICAL DATA

BOILING POINT (°F.) 760 mm	325°C	SPECIFIC GRAVITY (H_2O = 1) (25/15.5°C)	1.367
VAPOR PRESSURE (mm Hg.) (155-195°C)	3 mm	PERCENT VOLATILE BY VOLUME (%)	N.A.
VAPOR DENSITY (AIR = 1)	Not Avail	EVAPORATION RATE (n-BuAc = 1)	<1
SOLUBILITY IN WATER 20°C negligible	<0.01%		
APPEARANCE AND ODOR	colorless oil	slight aromatic odor	

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used) C.O.C. 180°C	FLAMMABLE LIMITS	LEL N.A.	UEL N.A.

EXTINGUISHING MEDIA: Water, foam, CO_2 or dry chemical

SPECIAL FIRE FIGHTING PROCEDURES: Respiratory protection when fighting fires where exposure to vapors or gases is possible.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Highly toxic gases (chlorides and chlorine) can be evolved in fires of this product.

DSW 267238

STLCOPCB4062651

Aroclor MCS 1016

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE
Skin irritation in the form of chloracne, systematic intoxication leads to nausea, vomiting, loss of weight, edema and abdominal pain.

EMERGENCY AND FIRST AID PROCEDURES

SECTION VI REACTIVITY DATA

STABILITY			CONDITIONS TO AVOID
	UNSTABLE		
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*

HAZARDOUS DECOMPOSITION PRODUCTS CO, CO_2, smoke, soot, chlorides and chlorine

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	MAY OCCUR		
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Absorb on clay, sawdust or other absorbant material. Place in drums. Bury in approved chemical landfill in accordance with local and state regulations.

WASTE DISPOSAL METHOD Burn in an approved incinerator in accordance with local and state regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)
Bureau of Mines approved respirator for organic vapors.

VENTILATION		
	LOCAL EXHAUST Yes - for vapors	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES	EYE PROTECTION
rubber	chemical goggles

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Avoid skin and eye contact. Avoid inhalation of vapors.

OTHER PRECAUTIONS

DSW 267239

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, MONSANTO COMPANY MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

JAG:HOH:JTG:WBP 1/25/72

STLCOPCB4062652