



Hayes Furnace Mfg. & Supply Co.

1942 Artesia Blvd., Torrance, Calif.

(Telephone FAculy 13294)

STAINLESS STEEL HEAT EXCHANGERS



SED-S

Duct Furnace, 45,000 to 675,000 BTU Input
—End Surface




SEU-V

Vertical Unit Heater, 70,000 to 245,000
BTU Input



SED-VF

UP Vertical Duct Furnace, 70,000 to 280,000
BTU



SED-E

Duct Furnace, 45,000 to 675,000 BTU Input
—Side Surface




SEC

Forced Air Furnace, 70,000 to 245,000 BTU
Input



SED-CF

Counter Flow Duct Furnace, 70,000 to
280,000 BTU Input



MZ

Gas fired multizone unit from 200,000 to
840,000 BTU

Blower cabinets for SED-E & SED-S Duct furnaces can be
furnished to meet specified performance requirements.

ILG ELECTRIC VENTILATING CO.


2880 N. Pulaski Road Chicago 41, Illinois

Offices in 60 Principal Cities

Member of Air Moving and Conditioning Association, Inc. (AMCA)


ILG UNIT HEATERS—STEAM, HOT WATER, ELECTRIC OR GAS

Tested and rated by IUA and ASHVE Codes. "One-Name-Plate" guarantee.




1½ to 7½ kw

ILG ALL-ELECTRIC UNIT HEATERS—new design for 1½ to 36 kw. features black heat type steel-sheathed elements and Ilg's quiet Type "Q" fan wheel. Built-in thermal cutout and direct-connected, totally enclosed motors. Heavy-duty construction throughout for heating isolated areas, temporary or auxiliary heating, stand-by




9 to 36 kw


freeze prevention. Hanger brackets are standard on sizes 1½ KW to 7½ KW. Optional on sizes 9 KW and larger. Sizes 1½ to 7½ KW are listed by the Underwriters' Laboratories, Inc. Send for Bulletin DBS-100.




ILG VERTICAL-TYPE UNIT HEATERS—new design. Totally enclosed ball-bearing motors. Heating surface features similar to horizontal type. Type "V" for standard outlet temperatures, Type "VL" for low outlet temperatures. 15 capacity sizes. Send for Bulletin DB4-101.



ILG HORIZONTAL-TYPE UNIT HEATERS—four side pipe connections for simplified piping. Suitable for hot water and steam to 150 lb. pressure... tubes air-tested to 90 lb. Motor totally enclosed, continuous-duty type. 19 capacity sizes. Send for Bulletin DB4-101.



CABINET HEATERS—SERIES A (Steam & Hot Water)—SERIES AE (Electric)—designed for maximum flexibility of arrangement and operation. Can be furnished for floor, wall, ceiling or inverted mounting. Available in seven basic unit sizes, 35 models. Blow-through type with direct fan assembly and draw-through type with belt-drive assembly. Send for Bulletin 1306. (Steam & Hot Water) and Bulletin DBS-300 (Electric)



ILG GAS-FIRED UNIT HEATERS—use natural, manufactured, mixed, butane-air mixtures; propane, or butane gas. Available in 10 basic model sizes, 2 types: Propeller Type (Series M); or Blower Type (Series MB) for use with duct work. Safety pilot, automatic control valve, electric limit switch. Motor has thermal overload protection. Send for Bulletin 286 (Propeller Type) and Bulletin 1501 (Blower Type).