Ind Hyg - Ash

FROM E. B. PARKER

ROCKDALE WORKS

TO MR. MICHAEL J. VANDREUIL

PITTSBURGH OFFICE

PLAINTIFF'S EXHIBIT AL-80

1980 September 02

RE: ASBESTOS REPLACEMENT PROGRAM

Attached is an updated copy of an inventory of asbestos-containing items used at Rockdale.

Several items have been deleted from the list published 1979-11-29, and one item has been added.

Deleted items are:

1. Ebony asbestos for pot cover insulation
2. Asbestos mittens

Added item is:

1. JM 88 Firewall material used to make the flexible connection between anode baking furnace flues and the waste gas manifold.

Replacement materials for Items 2 and 6 are being sought. Otherwise, there is no replacement activity being carried on at Rockdale.

E. B. PARKER

EBP:cw
Attachment
Copy - W. J. Drake/G. H. Lantz
A. G. Clayton
F. R. Hubbard
W. D. Essary
E. C. Remaley
N. D. Fernandes
W. T. Eckert
H. McLaughlin, III
T. J. Randall
D. L. Smith
J. R. Fry/J. A. Taylor

ALCOA

SF-4563

ROCKDALE WORKS

Date 80-09-02

ASBESTOS SURVEY

Item	Product Description[1]	Specific Application	Dept.	Dust Generated?[2] Yes	No	Don't Know
1	Brake Linings	Crane and vehicle brakes	Mech. Maint.			X
2	Marinite, Pre-cut	Molten aluminum handling	Ingot		X	
3	Transite Pipe	Potroom fume duct	Potrooms		X	
4	Garlock Gasket Material	Misc. gaskets - plantwide	Mech. Maint.		X	
5	Asbestos Sheet Gasket Material	Misc. gaskets - plantwide	Mech. Maint.		X	
6	Silbestos Gasketing	Properzi spouts	Properzi		X	
7	Asbestos Tape Gasketing	Fume exhaust fan housing gaskets	Mech. Maint.		X	
8	Asbestos Dresser Coupling Gaskets	A446 inlet piping joints	Mech. Maint.		X	
9	Graphited Braided Asbestos Packing	Misc. packing applications	Mech. Maint.		X	
10	Teflon Coated Braided Asbestos Packing	Misc. packing applications	Mech. Maint.		X	
11	Garlock Packing Yarn	Valve packing - plantwide	Mech. Maint.		X	
12	Ebony Asbestos	Superstructure foot insulation	Potrooms		X	
13	JM88 Firewall Material	Flexible connector, waste gas manifold	Carbon Plant		X	
14						
15						

Note 1 - List should include specifications for all asbestos products currently being purchased and used. It should not include previously installed asbestos materials that are still in place but for which non-asbestos replacements are currently being used.

Note 2 - Should be answered in light of currently available information. A product will be considered capable of generating significant airborne concentrations of asbestos fibers if the measured or estimated fiber concentrations are in excess of 0.1 fiber per cc (eight-hour time-weighted average.) In resonding to this question, it will be necessary to consider the possibility of dust being generated not only during installation, but also during use and, where applicable, dismantling.

ARD 003779