

MATERIAL SAFETY DATA SHEET

MC-X-01046 (3/85)



SPEC./MSDS NUMBER

DATE

Nov. 4, 1985

PRODUCT IDENTIFICATION

TRADE NAME Asbestos	GENERIC NAME Chrysotile Asbestos
MANUFACTURER'S NAME - Minerals Marketing Corp. of Zimbabwe as agents for Shabanie & Mashaba Mines (Pvt) Ltd.	CAS NUMBER 12001-29-5
ADDRESS (STREET) P.O. Box 552	PHONE NUMBER (EMERGENCY) (011-263-9) 76635
CITY Bulawayo, Zimbabwe	STATE
ZIP	CHEMICAL STRUCTURE $Mg_3(Si_2O_5)(OH)_4$

I • PRODUCT INGREDIENTS

CHEMICAL AND/OR COMMON NAME	CAS NUMBER	%	TLV/PEL
Asbestos	12001-29-5	100.0	*
*Occupational Exposure Limits			
PEL	TLV		
2.0 f/cc -8 hr. TWA	2.0 f/cc		
Ceiling conc.	ACGIH, Documentation of		
10.0 f/cc	TLV's at 27		
OSHA Standard			
at 29 CFR 1910.1001			

II • PHYSICAL DATA

BOILING POINT n/a	VAPOR PRESSURE n/a	SPECIFIC GRAVITY 2.4-2.6	MELTING POINT n/a
SOLUBILITY IN WATER n/a	VAPOR DENSITY (AIR = 1) n/a	PERCENT VOLATILE n/a	EVAPORATION RATE (= 1) n/a

APPEARANCE AND ODOR
white fibrous dry material - no odor

III • FIRE AND EXPLOSION DATA

FLASH POINT n/a	FLAMMABLE LIMITS n/a	FLAMABLE LIMITS n/a	LEL n/a	UEL n/a
--------------------	-------------------------	------------------------	------------	------------

EXTINGUISHING MEDIA
non-flammable. No fire or explosion hazard.

SPECIAL FIREFIGHTING PROCEDURES
none

UNUSUAL FIRE OR EXPLOSION HAZARDS
none

IV • HEALTH HAZARD INFORMATION

HAZARD BY ROUTES OF EXPOSURE (Indicate chronic and acute)

INHALATION - Chronic - Avoid inhalation. Overexposure can cause asbestosis, a scarring of the lung. Pleural thickening, effusion and plaques are nondisabling conditions, seen separately or together that have been associated with exposure. The IARC has determined that there is sufficient evidence for the carcinogenicity of asbestos in humans. Caution is advised as breathing asbestos may cause serious bodily harm.

INGESTION
no increased hazard evidenced.

EYE

Acute - may cause eye irritation.

SKIN CONTACT/ABSORPTION

Acute - may cause skin irritation.

SIGNS AND SYMPTOMS ASSOCIATED WITH EXPOSURE OVER TLV - Asbestosis is associated with symptoms of labored breathing, chest pain, weakness and chest tightness. Symptoms are not usually manifest until 15-20 years after exposure.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED

Respiratory ailments.

D 004160

ANY OF PART I LISTED AS CARCINOGENS? (NTP, IARC, OSHA)

Yes

NOV. 25 1985

HEALTH HAZARD INFORMATION CONTINUED ON BACK

BRAKEGATE LIMITED

6 Broad Street Place, London EC2M 7ND England

R.S.A.: P.O. Box 784521, Sandton 2146
Transvaal, South Africa
Tel: (27-11) 788-4313 • Tlx: 4-27186 SA

U.S.A.: P.O. Box 14095
West Allis, Wisconsin 53214
414/383-2020

November 21, 1985

Mr. E. E. Wang
J-M A/C PIPE CORPORATION
1051 Sperry Road
Stockton, CA 95206

Subject: C&G Asbestos Fiber

Dear Mr. Wang:

Please find enclosed manufacturer supplied Material Safety
Data Sheet to comply with OSHA enacted Hazard Communication
Standard (29 CFR 1910.1200).

Should you have any questions or need further information,
please advise us.

Sincerely yours,

BRAKEGATE LIMITED

B. Heering

Enclosure

cc: Darrel Wilkinson, Stockton
Harold Stone, Denison

NOV. 25 1985

Director: Bernard Heering

D 004162

V • HEALTH HAZARD INFORMATION (Continued)

EMERGENCY/FIRST AID PROCEDURES

INHALATION-Avoid breathing dust when handling, dumping, and mixing. Use respirator if airborne concentrations exceed OSHA limits (see Sec. VI).

INGESTION

EYE CONTACT

In case of eye irritation, gently rinse with water. If irritation persists get medical help.

SKIN CONTACT

Remove asbestos slivers from skin promptly. If irritation persists get medical help.

SKIN ABSORPTION

n/a

VI • CONDITIONS FOR SAFE USE (When over TLV)

RESPIRATORY PROTECTION-Reusable or single use air purifying respirator-for exposures which do not exceed the PEL (see sec.1) by more than 10X. Powered air purifying respirator-for exposures more than 10X but less than 100X, the PEL. Type "C" continuous flow or pressure demand, supplied air respirator for exposures more than 100X PEL. All respirators must be NIOSH appr

EYE PROTECTION

(see "Other.." this Sec.)

PROTECTIVE GLOVES

(See "Other.." this Sec.)

OTHER PROTECTIVE CLOTHING/EQUIPMENT-If the ceiling concentration (see Sec. 1) limit is exceeded, cloth providing whole body covering must be supplied and its use required.

VENTILATION REQUIREMENTS-Local ventilation if engineering controls are inadequate. (See Title 29 CFR Part 1910.1001, c (i) & (ii)).

VII • REACTIVITY DATA

IS MATERIAL STABLE?

Yes

WILL HAZARDOUS POLYMERIZATION OCCUR?

No

INCOMPATIBILITY

n/a

CONDITIONS TO AVOID

Avoid creating and breathing dust.

HAZARDOUS DECOMPOSITION PRODUCTS

None

VIII • SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED-Avoid creating or breathing dust. Collect dust by HEPA vacuum or in wet state(wet sweeping,wet wiping) to prevent emission of airborne fibers.

WASTE DISPOSAL METHOD-Bags,waste and scrap should be disposed of in a manner which all avoid airborne concentrations of asbestos, such as the use of dust-tight trash bags or containers. Ensure that disposal complies with all applicable federal,state and local regulations.

RCRA REGULATED
☐ Yes ☐ No

RCRA NUMBER

CERCLA (Superfund) REPORTABLE QUANTITY

DOT REGULATED
☒ Yes ☐ No

DOT PROPER SHIPPING NAME
Asbestos

DOT HAZARD CLASS
ORM-C

DOT NUMBER
-

IX • SPECIAL PRECAUTIONS

SPECIAL PRECAUTIONS FOR HANDLING AND STORAGE-Do not create or breath dust. Do not dry sweep or use air hose for cleaning. Do not take protective clothing or equipment home. Use no hooks in loading or unloading. Protect containers from damage. Prevent dust release without providing proper enclosure or control measures. Use dust suppression control measures, such as ventilation or wetw at all stages of handling, use and disposal. Follow good housekeeping practices, such as wet wi dusty surfaces, to prevent accumulation of asbestos containing dust. Avoid inhalation.

OTHER PRECAUTIONS-Substantial medical evidence indicates that smoking increases the risk from asbestos exposure. Those working with asbestos should not smoke.

PREPARED BY

PHONE NO.

TITLE

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, THE MANUFACTURER MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

D 004161