

STAMP PT. NO. W-16043 ON THIS SIDE OF BRAKE BLOCK

313 ± .010 (DEPTH @ CENTER OF THE HOLES)

+.010
-.000

.281 DIA.
.068 C'DRILL
6 HOLES

5 1/16

4 11/16

2 3/16

1 5/16

1 1/16

82°

6° R.

45°

5 ± .001
D ± .000

6 1/2

2 1/8

2 1/8

W 16043

BRAKE BLOCK
MAT'L: FRICTION MATERIAL
PER SPEC. 550900-305

INSP. PLAN

MED
MME-2
MPC-3
MPA
MPP-2
2/77
221
263
TOR
UK

REVISION DESCRIPTION
BY
DATE
A 10-15-68 LCHG SPEC # 349 TO 2-03-41
13 2-17-73 REVISED INVT DRILL (COUNT & DIMS. (CD 31855))
65 ± 1/32 ARC ON OACK

TOLERANCE FOR FINISHED SURFACES
DECIMAL DIMENSIONS ± .001
WHOLE INCHES AND FRACTIONAL DIMENSIONS ± .005

UNLESS OTHERWISE SPECIFIED

THE ELECTRIC CONTROLLER & MFG. CO.
CLEVELAND OHIO

REV. _____

TITLE 16" TYPE WD BRAKE

71133

2-21-55

alw