

THE LAW OFFICES OF
STUART CALWELL, PLLC
405 Capitol Street
Suite 607
Post Office Box 113
Charleston, West Virginia 25321
Telephone: (304) 343-4323
FAX: (304) 344-3684
Toll Free: 1-800-876-5529
Email: stuartcalwell@calwell-law.com

Stuart Calwell
John H. Skaggs
Mary McQuain
Shirley A. Skaggs

David H. Carriger *
John H. Kozak
D. Christopher Hedges
*Also admitted in VA

FACSIMILE COVER SHEET

DATE:

8/16/2001

TO:

Dr. Eigleman

FROM:

J. SKAGGS

FACSIMILE NUMBER:

1.425.699.7033

TELEPHONE NUMBER:

COMMENTS:

RE Carbide. TYNDAL EFFECT
MAY BE OTHER REFERENCES.
MAYE HAWKS NEST PROJECT
UNDERWAY. REGARDS

Original mailed to recipient: Yes ☐ No ☐

A total of _____ pages, excluding the cover sheet, is being transmitted. If you are having difficulties with reception, please call telephone number (304)-343-4323 and ask for _____.

CONFIDENTIALITY NOTICE

The information contained in this facsimile message is legally privileged and confidential information intended only for the use of the individual or entity named above. If the reader of this message is not the intended recipient, you are hereby notified that any dissemination, distribution, or copy of this telecopy is strictly prohibited. If you have received this telecopy in error, please immediately notify us by telephone and return the original message to us at the address listed above via the United States Postal Service. Thank you.

INTERNAL CORRESPONDENCE

UNION CARBIDE CORPORATION

270 PARK AVENUE, NEW YORK, NEW YORK 10017

To (Name) Messrs: C. Benjamin
Division F. F. Frangos
Location B. E. Godard
J. L. Myers
J. A. Riddle ✓
N. J. Setter
J. T. Sinclair
J. R. Stickney
W. S. Young

Copy to

Date April 3, 1969
Originating Dept. Medical Department
Answering letter date
Subject Asbestos

RECEIVED

APR 7 1969

U.C.C. CHEM. & PLASTICS

Gentlemen:

Both because of changes in regulations and availability of data developed after the issuance of our report in 1964, Dr. Dernehl and I have revised the asbestos memorandum. A copy of the revision is enclosed.

The major changes are the decrease in the Threshold Limit Value from 5 million particles per cubic foot of air to 2 million particles per cubic foot of air. (There is also a provision for another method of counting but it does not appear applicable to our short fiber asbestos.) We briefly discuss mesotheliomas, but data is too scanty as yet for a definite policy to be established. It is worth mentioning that the American Conference of Governmental Industrial Hygienists considered in 1968 a requirement that airline respirators be required for all contact with crocidolite asbestos. The resolution did not pass, but may come up again in future meetings.

Any questions or comments will be welcome.

Very truly yours,

R. S. Lane
R. S. Lane, M.D.
Assistant Medical Director

KSL:lk
Enclosure

A03137

705031

ASBESTOS TOXICOLOGY REPORT

It has been known for years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level.

It has been generally accepted that a worker will not develop asbestosis if he is exposed to no more than 5 million particles per cubic foot of air, even if this exposure continues for his entire working lifetime. Although no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, the ACGIH (which sets the threshold limit value (TLV) in the U. S. A.) has indicated they intend to lower the TLV for asbestos to 2 million particles per cubic foot in an effort to increase the safety factor incorporated in the limit. The U. S. Department of Labor has already issued a regulation under the Walsh-Healy Act placing the TLV for asbestos at 2 million particles per cubic foot for public contracts in which they have jurisdiction. This concentration of dust is generally not visible in the average work area unless a

A03137

705032

-2-

beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot (MPPCF) before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestosis. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value.

A type of cancer named mesothelioma has been noted to be associated with asbestos exposure in recent years. These tumors, while rather few in number to date, may occur in individuals with histories of only slight exposures, and that as much as twenty to forty years earlier. There is considerable evidence that crocidolite is most frequently associated with mesotheliomas. From the data available it appears that the TLV of 5 MPPCF is not low enough to protect against mesothelioma, and it is quite possible that 2 MPPCF is not, either. Research on the problem continues.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems,

A0313

705033

-3-

wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In paper manufacturing, it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the pulp slurry. Concentrations should also be determined where dusting occurs in finishing products. While initial dust determinations should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

Pre-employment and periodic physical examination of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of paper products would be harmless to the consumer. Total dusting would

A03140

705031

have to be well in excess of any levels acceptable to the
concern for the asbestos concentrations to approach the
Threshold Limit Value.

In conclusion, while asbestos dust in excess of the
Threshold Limit Value is potentially harmful, as are many
other dusts encountered in industry, it is as readily
controlled as other such dusts and it can be used safely
with appropriate precautions.

Industrial Medicine And
Toxicology Department
Union Carbide Corporation

A03141

705035

UNION CARBIDE CORPORATION

270 PARK AVENUE, NEW YORK, N.Y. 10017

ASBESTOS TOXICOLOGY REPORT

It has been known for many years that some persons working in asbestos production were prone to develop a disabling lung disease. In time, this condition became known as asbestosis and was related to exposure to high concentrations of asbestos dust. With further experience, it was found that men could work with asbestos without development of lung disease if dust concentrations were kept below a certain level. It is now generally accepted that a man can work a 40-hour week for a lifetime without developing asbestosis if the asbestos dust particle count is kept at or below 5 million particles per cubic foot of air. This dust concentration of 5 million particles per cubic foot of air is the Threshold Limit Value for asbestos, and no cases of asbestosis are known to have occurred when exposures have been maintained at or below this level, despite large-scale utilization (now approaching one million tons per year in the U.S.A.). This concentration of dust is generally not visible in the average work area unless a beam of light causing a Tyndall effect is present. Usually the dust concentration must be from 8-10 million particles per cubic foot before its presence is visible in average lighting conditions.

Several years ago, it was reported that there was an increase in the incidence of cancerous tumors, especially of the lung, associated with asbestos. Recently there have been reports of some cancers occurring in individuals exposed to asbestos dust, but who have not developed clinical asbestosis. It is believed by most authorities that these cases have been associated with exposures significantly exceeding the Threshold Limit Value. A major manufacturer of asbestos products who also mines asbestos has not been able to show an increase in cancerous growths in men working where dust concentrations were maintained at the Threshold Limit Value.

Control of asbestos dust exposure is therefore necessary. The control methods are the standard ones applicable to a variety of dusty operations. They include closed flow systems, wet processes where possible, and adequate exhaust ventilation where openings in the system are necessary. Pelletizing is sometimes used to improve the handling characteristics of otherwise dusty materials. Where satisfactory containment to stay within the Threshold Limit Value is impractical or impossible, efficient and reliable respirators are available for the protection of the employee. A program of environmental monitoring is highly desirable to determine that Threshold Limit Values are not being exceeded. In paper manufacturing, it would be desirable to know the dust concentrations where the asbestos is dumped from bags into the pulp slurry. Concentrations should also be determined where dusting occurs in finishing products. While initial dust determinations should be made at frequent intervals, once the level has been established as satisfactory, the frequency may be extended to occasional tests to assure continuation of a satisfactory condition.

A03'4..

705044

-2-

Pre-employment and periodic physical examinations of workers are desirable. These should include chest X-rays to insure that the worker has no chest condition prior to work with asbestos and to determine that no lung changes are resulting from work with asbestos.

It is believed that the addition of asbestos at the proposed levels during the manufacture of paper products would be harmless to the consumer. Total dusting would have to be well in excess of any levels acceptable to the consumer for the asbestos concentration to approach the Threshold Limit Value.

In conclusion, while asbestos dust in excess of the Threshold Limit Value is potentially harmful, as are many other dusts encountered in industry, it is as readily controlled as other such dusts and it can be used safely with appropriate precautions.

Carl U. Bernehl, M. D.
Director of Toxicology

K. S. Lane, M. D.
Assistant Director of Toxicology

40314

705045