

FILE NAME: General Motors (GM)

DATE: 1963

DOC#: GM019

DOCUMENT DESCRIPTION: Book Excerpt - Potential Exposures in Industry -
Industrial Hygiene and Toxicology

boards
386-76
285-52

INDUSTRIAL HYGIENE AND TOXICOLOGY

Second Revised Edition

FRANK A. PATTY, *Editor*

1963

VOLUME II

TOXICOLOGY

David W. Fassett and Don D. Irish, Editors

Index by MRS. KATHLEEN KUMLER

Authors

W. B. DEICHMANN
D. W. FASSETT
H. W. GERARDE
C. L. HAKE
D. O. HAMBLIN
L. W. HAZLETON

F. W. HEYROTH
C. H. HINE
D. D. IRISH
R. A. KEHOE
M. L. KEPLINGER
F. A. PATTY

V. K. ROWE
H. E. STOKINGER
W. L. SUTTON
J. F. TREON
R. J. WEIR
M. A. WOLF

INTERSCIENCE PUBLISHERS

a division of John Wiley & Sons, Inc., New York • London • Sydney

AUTHORS of Volume II

- William B. Deichmann, Ph.D.**, *Professor and Chairman, Department of Pharmacology, School of Medicine, University of Miami, Coral Gables, Florida.*
- David W. Fassett, M.D.**, *Director, Laboratory of Industrial Medicine, Eastman Kodak Company, Rochester, New York.*
- Horace W. Gerarde, M.D., Ph.D.**, *Senior Research Associate, Medical Research Division, Esso Research and Engineering Company, Linden, New Jersey.*
- C. L. Hake, Ph.D.**, *Head, Chemistry Research Department, Pitman-Moore Company, Division of The Dow Chemical Company, Indianapolis, Indiana.*
- Donald O. Hamblin, M.D.**, *Formerly Medical Director, American Cyanamid Company, New York, New York.*
- Lloyd W. Hazleton, Ph.D.**, *President, Hazleton Laboratories, Falls Church, Virginia.*
- Francis F. Heyroth, M.D.**, *(Deceased), Assistant Director, Kettering Laboratory of Applied Physiology, College of Medicine, University of Cincinnati, Cincinnati, Ohio.*
- Charles H. Hine, M.D.**, *Associate Clinical Professor of Occupational Medicine and Toxicology, School of Medicine, University of California, San Francisco, California.*
- Don D. Irish, Ph.D.**, *Biochemical Research Laboratory, The Dow Chemical Company, Midland, Michigan.*
- Robert A. Kehoe, M.D.**, *Director, Department of Preventive Medicine and Industrial Health, College of Medicine, University of Cincinnati, Cincinnati, Ohio.*
- M. L. Keplinger, Ph.D.**, *Toxicologist, Medical Department, Hercules Powder Company, Wilmington, Delaware.*
- Frank A. Patty, Formerly Director, Industrial Hygiene Department, Personnel Staff, General Motors Corporation, Detroit, Michigan.**
- V. K. Rowe, M.S.**, *Biochemical Research Laboratory, The Dow Chemical Company, Midland, Michigan.*
- Herbert E. Stokinger, Ph.D.**, *Chief, Toxicology Section, Division of Occupational Health, United States Public Health Service, Cincinnati, Ohio.*
- William L. Sutton, M.D.**, *Laboratory of Industrial Medicine, Eastman Kodak Company, Rochester, New York.*
- Joseph F. Treon, Ph.D.**, *Manager, Biological Sciences Section, Chemical Research Department, Atlas Chemical Industries, Wilmington, Delaware.*
- Robert J. Weir, Ph.D.**, *Toxicologist, Hazleton Laboratories, Falls Church, Virginia.*
- M. A. Wolf, M.S.**, *Biochemical Research Laboratory, The Dow Chemical Company, Midland, Michigan.*

CONTENTS

xxix

2145	N-Substituted Morpholines	2204
2145	Hexamethylenetetramine	2206
2146	Quinolone	2207
2146	Azides	2208
2147	General Considerations	2208
2147	Sodium Azide	2210
2148	Hydrazoic Acid	2212
2148	Diazomethane	2213
2149	Nitrosomethylurethane	2215
2149	Dimethylnitrosamine	2216
2150	Hydrazines	2218
2150	General Considerations	2218
2151	Hydrazine	2222
2151	1,1-Dimethylhydrazine	2225
2152	Phenylhydrazine	2227
2152	β -Chloroethylamines	2230
2153	General Considerations	2230
2153	Methyl-bis(β -chloroethyl)amine	2233
2154	Tris(β -chloroethyl)amine	2233
2154	Dimethyl- β -chloroethylamine	2233
2154	Diethyl- β -chloroethylamine	2234
2155	XLIX. Potential Exposures in Industry: Their Recognition and Control. By	
2155	FRANK A. PATTY	2235
2157	Abrasive Blasting	2235
	Abrasives Manufacture and Use	2236
	1. Artificial Abrasives	2236
	2. Sand Abrasives	2237
	Acetylene Manufacture	2237
	Acid Manufacture and Recovery	2238
	1. Hydrochloric Acid	2238
	2. Nitric Acid	2239
	3. Sulfuric Acid	2239
	Aircraft Manufacture, Maintenance, and Repair	2239
	Aluminum Manufacturing	2240
	Ammonia Manufacture and Use	2241
	Aniline Manufacture, Distillation, and Handling	2242
	Anodizing	2242
	Armature Workers	2243
	Art-Metal Casting	2243
	Asbestos Workers	2243
	Asphalt (Mineral Pitch)	2244
	Automobile Manufacture	2244
	Battery Manufacture	2246
	Beer Vat Coating	2248
	Bleaching	2248
	Beryllium Processing Operations	2248
	Brick and Tile Manufacture	2249
	Broom Manufacture	2249
	Carpentry	2249
	Carroting	2250

Armature Workers

Lead "tinning" baths and lead pots, when small and equipped with temperature controls, may not present serious lead exposures. However, the larger operations, especially when no temperature control is in use, can offer serious exposures. Wherever there is any question of exposure, the operation should either be provided with mechanically induced air flow to remove or dilute the lead fumes before they can be inhaled, or else air, blood, or urine samples should be collected and analyzed for lead to establish whether ventilation is necessary.

Waterproof varnishes, especially those made from cashew nutshell liquid-formaldehyde resins, may cause dermatitis. This may result from contact with the wet varnish, from the varnish dust dispersed in grinding armatures, or from skin contact with dirty solvent baths for dipping and cleaning old armatures. The solvent bath should not be permitted to become badly contaminated and skin contact must be avoided. In the case of wet or dry varnish, good personal cleanliness is an effective preventive measure, and varnish dust should be controlled by process ventilation. Protective creams and clothing may be useful in some instances.

Art-Metal Casting

Art-metal casts for displays, trophies, medals, and the like are usually cast from white metal or britannia metal, which are alloys of tin, antimony, and copper, often having some zinc and bismuth, occasionally lead, and possibly arsenic. The alloys are melted in pots, temperatures rarely exceeding 300 or 400°C. Burring, filing, belt "sanding," and buffing may be done and, unless controlled, significant exposures to mechanically generated metal dusts may result. At the temperatures ordinarily employed there is little likelihood of an exposure to metal fumes, however. Where uncertainties exist, exposures should be evaluated and, when found excessive, controlled. Other possible exposures in the industry involve plating baths and cyanide dips. Soldering operations are usually at low temperatures to avoid fusing the low-melting-point alloys, and therefore are not conducive to the formation of metal fumes.

Asbestos Workers

Dustiness around asbestos workers is sometimes above the proposed standard of 5 million particles per cubic foot. Perhaps mining offers the greatest exposure to dust, and in fabrication plants the operations, listed in the probable, decreasing order of dustiness, are: screening, picking, stacking, and willowing in the preparation room; carding, dry weaving, spinning, twisting, winding, and warping. The sawing, filing, drilling, and grinding of brake linings is ordinarily well controlled. Grinding, mixing, and bagging asbestos cement and insulating material, and the sawing or beveling of asbestos board, are dusty operations unless properly engineered. The asbestos content of these dusts frequently is not high but diatomaceous

earth in considerable quantities may accompany it, thus complicating the exposure with free silica. It is desirable in asbestos exposures to keep the dust count down to 5 million particles, or less, per cubic foot of air.

Asphalt (Mineral Pitch)

The name "asphalt" applies to bitumen or to earth or rocks impregnated with bitumen and to a residue from certain petroleum, coal tar, lignite tar, etc. (artificial asphalt). It is a black solid formed in the earth from slow decomposition of organic matter. It is composed chiefly of hydrocarbons along with varying amounts of oxygen, nitrogen, and sulfur compounds.

Asphalt is used principally for water-excluding coatings upon roads, floors, or roofs. It is employed as a rust preventive in ducts, collectors, tanks, and so forth to protect metals from corrosive (acid) liquids and gases. For such application it is commonly dissolved in benzene.

Vapors and gases from heated asphalt are obnoxious and toxic, containing among other compounds some hydrogen sulfide. Dermatitis from contact with asphalt has been reported as common, with the entire body sometimes affected. Skin cancer has also been reported, but statistics are lacking. Some authorities attribute most of the poisoning that has occurred from the use of asphalt to the solvents employed with it (benzene, phenol, etc.).

Grinding operations and hot processes should have exhaust ventilation. Personal cleanliness is the heart of any program for preventing skin disease.

Automobile Manufacture

The manufacture of automobiles has few operations that are peculiar to the industry. There are many exposures and potential exposures common to other industries.

These are discussed elsewhere under specific headings such as: Abrasive Blasting, Anodizing, Battery Manufacture, Electroplating, Foundry Operations, Forging and Iron Working, Garages, Grinding and Polishing, Heat Treating, Industrial X-Ray, Lead Workers, Metal Cleaning, Metalizing, Motor Testing, Painting and Decorating, Pickling, Plastics and Resins, Radio Manufacture and Repair, Welding, etc.

Body polishing by the use of tripoli polishing compounds is an operation more or less peculiar to the production of highly polished automobile bodies. No harmful effects have been associated with this operation. However, any dust arising from the polishing, and especially from compressed-air blowoff operations, and from the cleaning of the brushes should be controlled. There seems no logical excuse for condoning such dust in concentrations of more than 5 million particles per cubic foot of air. Since the tripoli polish is applied as a slurry, dust control has not been a difficult problem.

Anotl
solder. Th
metal by l
years past
closures a
blood or u
exposures
ciently hig
are adequ
take care o
cient air ex
plied-air h
removal of
fore intoxic
with lead
coupled wi
0.08 mg. lea
encountere

Contact
bile manuf
that are in

A stati
tact with tl
the highest
exposed pe
screw-mach
titis—on tl
"soluble oils

Some
each of the
primary in
nitrophenol
amines, and
objectionab

It is in
sterilization
desirable. In
where they
teurization
that certain
odors withou

The mo
effective wa