No. 63DP

EFFECTIVE DECEMBER 15, 1960
SUBJECT TO CHANGE WITHOUT NOTICE

Suggested

RETAIL

PRICE LIST

Glidden Paints
SPRED PRODUCTS

QUALITY PRODUCTS

THE GLIDDEN COMPANY, NATIONAL HEADQUARTERS, CLEVELAND 14, OHIO

GLD026763

INDEX

Product — Page

A

Ad-El-ite Paint and Varnish Remover — 3
Alkali-Resisting Primer No. 6419 — 3
Alkyd Enamels — 3
Aluminum Asphalt Roof Paint — 3
Aluminum, Metallite — 17
Spray Enamel, Japalac — 16
Asbestos Shingle Paint — 3

B

Bar Top Varnish, Glid-Tone Gloss — 8
Barn Paint, Endurance — 5
Basecoats:
- Alkali-Resisting 6419 — 3
- Endurance — 6
- Gliddencoat — 8
- Ripolin Undercoat — 18
- Rustmaster — 19
- Speed-wall, Interior — 20
- SPRED Primer-Sealer — 13
- Surface Bond — 13

Basement Paints:
- Pli-Namel — 18
- Florenamel — 7
- SPRED Satin — 11
- SPRED Tred — 13
- SPRED Glide-On — 13

Black Asphaltum — 3
Bleach, Glid-Tone Wood Bleach — 15
Blending Colors—Dramatone — 11
- Colors-In-Oil — 4

Boat Varnish, Glid-Tone Spar Varnish — 10
Brick Paint, SPRED Glide-On — 13
Brush-Day-Lite Alkyd Flat Enamel — 4
Brush-Day-Lite Tint White 5788 — 4
Brush Restorer, Glid-Strip — 8
Brushing Lacquer, Glid-Tone Crystalacq — 8

C

Canvas Preservative, Neva-Rot — 17
Cement and Stucco Paint:
- SPRED Glide-On — 13

Cleaner, Glid-N Liquid — 8
Cleaner-Polish-Wax, Renovite — 21
Colors-In-Oil — 4
Concrete Paint:
- Pli-Namel — 18
- SPRED Tred — 13
- SPRED Glide-On — 13

Crack and Crevice Filler, SPRED Patch — 14
Creosote Paint, Stock Farm White — 21
Crystalacq, Glid-Tone — 8

D

Deck Paint, Florenamel — 7
Deep Colors—SPRED Satin — 11
Detergents, Glid-N Liquid Cleaner — 8
Dramatone Tinting Colors — 11
Driwel Clear, Silicone — 5

E

Enamel:
- Florenamel — 7
- Japalac — 15-16
- Japalac Spray — 16
- Pli-Namel — 18
- Ripolin — 18
- Speedenamel — 20
- SPRED Lustre — 15

Enamel Undercoater:
- Gliddencoat — 8
- Ripolin Undercoat — 18

Endurance:
- Barn Paint — 5
- Basecoat — 6
- House Paint — 6
- Imperial — 6
- Mildew & Fume Resistant — 6
- & Shutter Colors — 6
- or Flat — 7

Everen House Paint — 7
Exterior Basecoat — 6

F

Farm Building Paints:
- Endurance Paints — 5-7
- Metallite — 17
- Rustmaster Metal Paints, Primers — 19
- SPRED Products — 12-14
- Stock Farm White — 21

Fence Paints:
- Black Asphaltum — 3
- Endurance House Paints — 5-7
- Metallite — 17
- Stock Farm White — 21

Filler, Glid-Tone — 15
Florenamel — 7
Floor Finishes:
- Florenamel — 7
- Glid-Tone Gloss Varnish — 8
- Pli-Namel — 18
- SPRED Tred — 13

G

Four Hour Enamel: Japalac — 16
Gliddencoat — 8
Glid-N Liquid Cleaner (Detergent) — 8
Glid Strip (Non-Flammable) — 8
Glid-Tone Crystalacq — 8
Glid-Tone Gloss Varnish — 8
Glid-Tone Products — 8-10, 15
Glid-Tone Re-Grain Ground Coat — 9
Glid-Tone Redwood Finish — 9
Glid-Tone Satin-Sheen Varnish — 9
Glid-Tone Spar Varnish — 10
Glid-Tone Stain — 10
Glid-Tone Varnish Stain — 10
Glid-Tone Wood Bleach — 15
Glid-Tone Wood Filler — 15
Glide-On, SPRED — 13
Gloss Finishes:
- Florenamel — 7
- Japalac — 16
- Ripolin — 18
- Speed-wall — 20

Gold, Spray—Japalac — 16
Granulets — 12
Gymnasium Floor Finish — 15

H

Heat Resisting Aluminum — 17
House Paint:
- Endurance — 5-7
- everen — 7
- SPRED Glide-On — 13
- SPRED House Paint — 12

I

Imperial House Paint — 6
Interior Aluminum, Metallite — 17
Interior Varnishes — 8-10

J

Japalac Enamel — 16
Japalac Screen and Iron Enamel — 15
Japalac Spray Enamel — 16

L

Lacquer, Glid-Tone Crystalacq — 8
Latex Paints — 12-14
Linoleum Coating, Crystalacq — 8
Liquid Cleaner Glid-N — 8
Liquid Red Lead — 16
Lubricant, Silicone Slick Spray — 20

M

Machinery Enamel:
- Rustmaster Gloss Enamel — 19
- Japalac — 16

Masonry Finishes:
- Driwel — 5
- SPRED Glide-On — 13
- SPRED House Paint — 12

Metal Primer:
- Red Lead — 16
- Rustmaster — 19

Metal Protective Paints:
- Glid-Tite — 9
- Metallite — 17
- Red Lead — 16
- Rustmaster — 19

Metallite, Interior-Exterior — 17
Mildew-Resisting Paints:
- Endurance — 6
- SPRED Glide-On — 13
- SPRED House Paint — 12

N

Neva-Rot — 17

O

Oil Colors:
- Colors-In-Oil — 4

One-Coat House Paint, Endurance Imperial — 6

P

Paint and Varnish Remover — 3, 8
Paste Wood Filler, Glid-Tone — 15
Patching Plaster, SPRED Patch — 14
Pli-Namel — 18
Porch and Deck Enamel, Florenamel — 7

Product — Page

Primers and Sealers:
- Alkali-Resisting 6419 — 3
- Endurance Basecoat — 6
- Gliddencoat — 8
- Interior Basecoat — 20
- Ripolin Undercoat — 20
- Rustmaster — 19
- SPRED Primer Sealer — 13-18
- Speed-Wall Alkyd Interior-Basecoat — 20
- Surface Bond — 13

R

Red Lead — 16
Redwood Finish — 9
Ren-O-Vite Plus — 21
Ripolin Enamel — 18
Ripolin Undercoat — 18
Rockspar Varnish — 19
Roof Paints:
- Aluminum Asphalt — 3
- Metallite — 17
- SPRED Glide-On — 13

Rustmaster Enamel, Primers — 19

S

Screen Enamel, Japalac — 15
Semi-Gloss Enamels:
- Speed-Wall — 20
- SPRED Lustre — 11

Silicone Slick Spray — 20
Spackling Compound, SPRED Patch — 14
Spar Varnish, see Glid-Tone Spar — 10
Speed-Wall Alkyd Interior Basecoat — 20
Speed-Wall Gloss White Enamel — 20
Spray Enamel, Japalac — 16
SPRED Products — 11-14
SPRED Flat — 14
SPRED Glide-On — 13
SPRED Granulets — 12
SPRED House Paint — 12
SPRED Lustre — 11
SPRED Patch — 14
SPRED Primer-Sealer — 13
SPRED Satin — 11
SPRED Stipple Texture — 14
SPRED Surfacene — 14
SPRED Texture — 14
SPRED Tred — 13
Stains:
- Glid-Tone, Wood — 10

Stipple Texture, SPRED — 14
Stock Farm White Paint — 21
Stove and Iron Enamel, Japalac — 15
Super Ren-O-Vite Plus — 21
Surface Bond — 13
Surface Conditioner, SPRED Surfacene — 14

T

Table Top Varnish, Glid-Tone Gloss — 8
Texture Paint, SPRED — 14
Tile Roof Paint, SPRED Glide-On — 13
Tinners' Paint — 21
Tinting Colors — 4, 11
Trim and Shutter Colors, Endurance — 6
Tube Colors — 4

U

Undercoaters:
- Alkali-Resisting Primer No. 6419 — 3
- Endurance Exterior Basecoat — 6
- Gliddencoat — 8
- Ripolin Undercoat — 18
- Rustmaster — 19
- Speed-Wall Interior Basecoat — 20
- SPRED Primer-Sealer — 13
- Surface Bond — 13

V

Vapor Barrier, SPRED Primer-Sealer — 13
Varnishes:
- Glid-Tone Gloss — 8
- Glid-Tone Satin Sheen — 9
- Glid-Tone Spar — 10
- Japalac Clear Spray Finish — 16
- Rockspar — 19

Varnish Remover — 3, 8
Vinyl-Latex, SPRED Glide-On — 13
Vismatic Green Chalkboard Coating — 22

W

Wood Bleach — 15
Wood Filler — 15
Wood Preservative, Neva-Rot — 18
Wood Stain — 10

GLD026764

[redacted]

	Gals.	Qts.	Pts.	½ Pts.
***AD-EL-ITE PAINT AND VARNISH REMOVER** A top-quality remover. Contains no alkalies, acids, oils or water. Does not raise the grain or discolor the wood. Evaporates very slowly. Very effective in removing old paint, enamel, lacquer and baked japan	3.08	1.22	.78	.59
***ALKALI-RESISTING PRIMER No. 6419** An easy to apply masonry primer-sealer for interior newly plastered or damp walls, and exterior masonry, brick, stucco and concrete blocks, which are to be painted with synthetic rubber-base or oil base paints. Penetrates deeply into the pores and adheres firmly to the surface, to create perfect bond for finish coat. Resists moisture and alkali. Seals in active lime. Prevents fresh plaster from burning through and discoloring the finish coat	7.55	2.38	—	—
APPLICATION—Brush, Spray THINNER—Turpentine DRYING TIME—16 hours Covers 350-400 Sq. Ft. per gal. **(Also See SPRED Primer-Sealer Alkali-Resisting Primer)**				

ALKYD ENAMELS

See: Brush-Day-Lite Alkyd Flat and Tint White; Japalac; Florenamel; Rustmaster; Ripolin; Speed-Wall Gloss White; Spred Lustre.

***ALUMINUM ASPHALT ROOF PAINT** Recommended for tar paper, composition and asphalt roofs. Will rejuvenate weathered roofs and insulate with a silvery sheet of aluminum, in one coat. Made with selected asphalts, finest grade aluminum flakes and solvents	5.39	—	—	—
APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turp. DRYING TIME—10 hours Covers 275-400 Sq. Ft. per gal., depending on surface.				

ALUMINUM PAINTS

See: Metallite; Japalac Spray Enamel

ASBESTOS SHINGLE PAINT

See: SPRED House Paint; SPRED Glide-On

BARN PAINT

See: Endurance Barn Paint

BASECOATS (Primers)

For Exteriors—See SPRED House Paint Primecoat #1; SPRED House Paint Primecoat #2; Rustmaster Metal Primer; Rustmaster Galvanized Primer, Endurance House Paint

For Interiors—See: Gliddencoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Ripolin Undercoat, Alkali-Resisting 6419

BASEMENT PAINTS

For Floors—See: Pli-Namel; Florenamel; SPRED Tred

For Walls—See: SPRED SATIN; SPRED Glide-On

***BLACK ASPHALTUM** A weather-resisting, quick-drying, gloss black asphaltum base paint. Recommended for exterior iron work, fences, metal sash and other exterior metal surfaces where an economical finish is desired	3.75	1.33	.84	.56
APPLICATION—Brush, Spray DRYING TIME—2 to 3 hours THINNER—Mineral Spirits or Turp. Covers 400-500 Sq. Ft. per gal.				

*AVAILABLE IN 5-GAL. CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

[redacted] 3

GLD026765

	Gals.	Qts.	Pts.	½ Pts.

BLACKBOARD FINISHES
See: Vismatic Green Chalkboard Coating
BLEACH
See: Glid-Tone Wood Bleach
BLENDING COLORS
See: SPRED Dramatone Tinting Colors; Colors-In-Oil
BRICK PAINTS
See: SPRED House Paint; SPRED Glide-On

BRUSH-DAY-LITE ALKYD FLAT ENAMEL

Beautiful, completely washable, flat alkyd enamel for interior wall surfaces, including plaster, wood, concrete, wallboard and metal. Can be applied quickly with a wide brush or roller. Flows out smoothly. One coat is usually sufficient. Colors match SPRED SATIN.

White and Colors	5.45	1.78	—	—

APPLICATION — Brush, Roller, Spray
DRYING TIME — 4 hrs; overnight for recoating
THINNER — Mineral Spirits or Turpentine
COVERAGE — Up to 550 sq. ft. per gal.

BRUSH-DAY-LITE ALKYD FLAT ENAMEL TINT WHITE 5780 For tinting Brush-Day-Lite Alkyd Flat Enamel Colors.	5.10	1.63	—	—

BRUSHING LACQUER
See: Glid-Tone Crystalacq
BRUSH RESTORER
See: Glid-Strip
CANVAS PRESERVATIVE
See: Neva-Rot
CEMENT AND STUCCO PAINT
See: SPRED House Paint; SPRED Glide-On
CLEANER, LIQUID
See: Glid-N Liquid Cleaner

COLORS-IN-OIL

Unexcelled for tinting flat wall paints, Semi-Gloss and Gloss enamels, glazing liquids, white lead and white paste paint. Ground extremely fine in special pale linseed oil for quick and positive dispersion. The finest pigments are used to develop perfect tone and strength of color. Not to be used in latex, emulsion paints, or lacquer.

	Gals.	Qts.	½ Pts.	1" x 5" Tubes
Raw Umber, Burnt Umber	8.00	2.38	.87	.49
Raw Sienna, Burnt Sienna	8.85	2.59	.91	.49
Ivory Drop Black	—	2.48	.90	.49
Lamp Black	6.65	2.05	.83	.43
Prussian Blue	—	2.48	.90	.49
Chrome Green, Light; Chrome Green, Medium	12.30	3.45	1.18	.55
Perma-Green	—	5.43	1.67	.59
Chrome Yellow, Light and Medium	—	4.68	1.44	.58
Chrome Yellow, Dark	—	5.28	1.62	.58
Yellow Ochre	8.85	2.59	.91	.49
Venetian Red	6.89	2.15	.86	.44
American Vermilion (Interior Use Only)	—	4.68	1.44	.58
Perma Blue	—	4.88	1.50	.58

CONCRETE PAINT
See: SPRED House Paint; SPRED Glide-On; Pli-Namel; SPRED Tred
CRACK AND CREVICE FILLER
See: SPRED Patch
CREOSOTE PAINT
See: Stock Farm Paint

GLD026766

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

DECK PAINT
See: Florenamel

DEEP COLORS
See: SPRED SATIN; SPRED SATIN Dramatone Tint Base; SPRED LUSTRE Dramatone Tint Base

DETERGENTS
See: Glid-N Liquid Cleaner

DRAMATONE MULTI-PURPOSE TINTING COLORS
See: SPRED Products Section

---

*DRIWAL (Clear)

A damp-resisting, stain-resisting material designed for application on limestone, stucco, sandstone, concrete and other porous surfaces of masonry. It penetrates pores of surface and coats them with an insoluble substance which makes them fully water-repellent. Does not change texture nor discolor surface. Contains no paraffine. Especially recommended for limestone surfaces ——— 3.89 — — —

APPLICATION—Brush, Spray
DRYING TIME—2 hours
THINNER—None Required
COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

---

*DRIWAL (Silicone)

A transparent, water-repellent finish for exterior, above-ground brick, stone and masonry. Does the job in ONE COAT. Repels rain water from penetrating the pores. Resists efflorescence and staining. Masonry surfaces show no visible change in color or texture when treated with this material. Recommended for use on brick and mortar, concrete, cement-base paints, asbestos-cement combinations, sandstone, stucco and stones other than limestone. Not to be used on cinder block or other light weight aggregate concrete blocks with extremely porous surfaces. This invisible water-repellent coating contains silicone to combat masonry deterioration. Not recommended for limestone surfaces ——— 4.75 — — —

APPLICATION—Brush, Spray
DRYING TIME—2 hours
THINNER—None Required
COVERAGE—125 to 275 Sq. Ft. per gallon depending on porosity of surface

---

ENAMELS
See: Japalac; Ripolin; Brush-Day-Lite Alkyd Flat; Florenamel; Pli-Namel; SPRED Lustre; Rustmaster

ENAMEL UNDERCOATER
See: Gliddencoat; Ripolin Undercoat; Interior Basecoat

---

*ENDURANCE BARN PAINT – No. 500 Red

A new, highest quality paint with excellent hiding power. It dries to a tough glossy film that withstands the rigors of the roughest weather. Provides long-lasting protection for barns, sheds, granaries, silos, water tank exteriors, storehouses, fences, etc. Use it on exterior wood and metal ——— 4.79 1.62 — —

APPLICATION—Brush, Spray
DRYING TIME—Overnight; 36 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—500 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

[redacted]

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

*ENDURANCE EXTERIOR BASECOAT

Exterior primer for new wood and previously painted wood that is badly weathered or chalked. Use it to spot-prime bare spots resulting from peeling and flaking. Made from specially prepared oils to produce the elasticity, adhesion and control penetration necessary for finest exterior paint jobs ——— — — — —

APPLICATION—Brush, Spray DRYING TIME—48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—450 to 500 Sq. Ft. per gallon

*ENDURANCE HOUSE PAINT

For Siding, Trim and Shutters

Contains more heavy-bodied, pure linseed oil per gallon for longer life; pure white lead for added strength, water-resistance and extra durability; titanium for whiteness and hiding; zinc oxide to combat mildew, magnesium silicate for protection against cracking and checking. The exclusive Glidden formula makes this the finest, longest-lasting, self-cleaning exterior house paint manufactured. May be tinted with DRAMATONE Tinting Colors.

Outside White No. 1800	—	—	—	—
Regular Colors and Black	—	—	—	—
Non-Chalking Trim White No. 1892	—	—	—	—
Crylite Green No. 1828	—	—	—	—
Deep Turquoise No. 150	12.89	3.72	2.01	—
Shutter Green No. 71	8.89	2.68	1.51	—
Chestnut Brown No. 92; Dark Blue No. 158	7.59	2.33	1.37	—

APPLICATION—Brush, Spray, Roller
DRYING TIME—16 hours; recoat in 72 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

*ENDURANCE HOUSE PAINT

Mildew and Fume-Resistant

A deluxe, Super White House Paint—ideal for the finest homes. Excellent for exterior wood, masonry and metal in any climate. A Non-Staining House Paint that stays white and bright for years. Especially suited for industrial areas, where homes are subjected to chemical fumes, heavy smog and smoke. Its formulation makes it ideal for farm buildings and fences. Combats mold, mildew and the roughest year-round weather ——— — — — —

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine
DRYING TIME—16 hours; 72 hours for recoating
COVERAGE—Up to 550 Sq. Ft. per gallon

ENDURANCE HOUSE PAINT, PASTEL COLORS

Pastel colors are easily obtained by tinting existing colors of ENDURANCE HOUSE PAINT or NON-CHALKING TRIM WHITE No. 1892 with DRAMATONE Tinting Colors. See ENDURANCE HOUSE PAINT Color Card.

*ENDURANCE IMPERIAL ONE-COAT

White House Paint (Alkyd Fortified)

Premium quality white exterior paint. Gives extra hiding and coverage with its built-in second coat. Has depth and richness of enamel. Easy brushing. Once over is enough with this amazing one-coat paint! Fortified with alkyds to give extra durability and lasting beauty ——— 8.99 2.68 — —

APPLICATION—Brush, Spray THINNER—Mineral Spirits or Turpentine
DRYING TIME—48 hours
COVERAGE—550 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

[redacted]

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

*ENDURANCE VELVET (Flat Exterior Finish)

FOR WOOD SHINGLES, SHAKES, WOOD SIDING AND TRIM. May be used also on metal surfaces. It brushes easily and will produce a beautiful flat finish in one coat over most previously painted surfaces if the color contrast is not great. Dries dust free in one hour. It provides a "breather type" film which aids the elimination of internal moisture.

White and Colors	6.75	2.13	—	—

APPLICATION—Brush, Spray
DRYING TIME—Dust-free 1 hr.; 48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 550 Sq. Ft. per gallon

*EVERON HOUSE PAINT (White)

An excellent paint that stays clean and bright because of its special formula which provides controlled chalking. A superior finish for all wood surfaces exposed to weather and changing climatic conditions. Resists fumes in industrial areas! EVERON HOUSE PAINT brushes easily, penetrates deeply when used as a primer, adheres tenaciously as a finish coat, dries with an elastic, high gloss finish that remains firm and durable. EVERON is truly the economical HOUSE PAINT

	6.20	1.99	—	—

APPLICATION—Brush, Roller, Spray
DRYING TIME—16 hours; recoat in 48 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—550 Sq. Ft. per gallon

FARM BUILDING PAINTS

For Exteriors—See: Endurance Paints, Metallite, SPRED House Paint; SPRED Glide-On, Stock Farm White
For Interiors — See: SPRED Products

FENCE PAINTS

See: Stock Farm White; Metallite; Rustmaster, Black Asphaltum

FILLER, WOOD

See: Glid-Tone Wood Filler

FLOOR FINISHES

See: Pli-Namel; Florenamel; Gymnasium Floor Finish; Glid-Tone Gloss Vornish; SPRED Tred

*FLORENAMEL (Alkyd)

An alkyd enamel with extra durability, for use on porches, floors of wood and concrete, canvas decks, railings—inside and outside. Will not waterspot; standing pools of water do not affect it. FLORENAMEL gives concrete basement floors and walls a mirror-like enamel finish. It's scrubbable. FLORENAMEL is made to take the roughest wear and weather. May be tinted with DRAMA-TONE Tinting Colors. All colors

	7.50	2.38	—	—

APPLICATION—Brush, Spray
DRYING TIME—12 hours
THINNER—Turpentine or Mineral Spirits
COVERAGE—500 to 600 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026769

	Gals.	Qts.	Pts.	½ Pts.

*GLIDDENCOAT (White Enamel Undercoat)

A perfect enamel undercoat for woodwork. Produces a firm opaque film to hold out succeeding coats of finishing enamel, making it possible to secure full luster and depth of gloss. Works easily, flows evenly without showing brush marks and requires only light sanding. Can be tinted with colors in oil or DRAMATONE Tinting Colors ..... 6.35 2.03 1.19 .80

APPLICATION—Brush, Spray
DRYING TIME—Overnight for sanding and recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—500 Sq. Ft. per gallon

GLIDE-ON, SPRED
See: SPRED Products Section

GLID-N LIQUID CLEANER (Detergent)

An excellent degreaser as well as cleaner. Does a remarkably easy job on walls, woodwork, floors, linoleum, tile, windows, dishes, mirrors and automobiles. Dries free from streaks. Harmless to the skin. Requires only two to three teaspoonsful to a gallon water ..... 4.08 1.22 .77 —

GLID STRIP (Non-Flammable)

Wash Away Paint and Varnish Remover

A non-flammable, water-flush paint and varnish remover that stays wet longer and permits working on larger areas. Has less tendency to run and sag on upright surfaces due to its heavy body. Easy to use. Just brush it on, wait a few minutes, then wash it off with water. GLID STRIP also acts as a cleaner for old, hardened nylon and pure bristle paint and varnish brushes. Will soften latex paints for easy removal ..... 6.79 2.25 1.24 .79

GLID-TONE CRYSTALACQ (Brushing Lacquer)

A crystal clear, quick-drying, water and wear-resistant lacquer finish for brush application. Easy to use. Excellent for floors, woodwork, furniture, linoleum, etc. ..... 7.55 2.32 1.34 —

APPLICATION—Brush
DRYING TIME—1 to 6 hours, depending on surface
THINNER—Glid-Tone Crystalacq Reducer
COVERAGE—300 Sq. Ft. per gallon

GLID-TONE CRYSTALACQ REDUCER
Special Thinner for Crystalacq ..... — — 1.07 —

GLID-TONE GLOSS VARNISH

A deluxe, general-purpose interior varnish. Epoxy resins give it extreme abrasion resistance, durability, and lasting beauty. Excellent on all interior wood surfaces, bar and tabletops, woodwork, furniture and floors. Especially suitable over newly stained woodwork where Glid-Tone Stains have been applied. May be rubbed ..... 8.75 2.62 1.47 .91

APPLICATION—Brush
DRYING TIME—6 to 8 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—650 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026770

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

*GLID-TONE REDWOOD STAIN (No. 31)

A penetrating flat Redwood Stain and Sealer designed especially to protect and beautify natural exterior wood such as siding, shingles, shakes, panels, doors, fences, picnic tables and yard furniture. If gloss finish is desired use Clear Redwood Finish No. 30 ..... 5.25 1.68 — —

APPLICATION—Brush, Spray
DRYING TIME—Overnight
THINNER—Mineral Spirits, Turpentine, VM & P Naphtha
COVERAGE—First Coat on rough, new wood: 200-300 Sq. Ft. per gallon. Finished Wood: 300-400 Sq. Ft. per gallon, first coat. 2nd Coat: Up to 600 Sq. Ft. per gallon. 3rd Coat: Up to 800 Sq. Ft. per gallon

---

*GLID-TONE REDWOOD FINISH (Clear Polyurethane No. 30)

A brilliant gloss finish for redwood, red cedar, pine and other exterior wood surfaces. Mildew and fume resistant. Provides a tough, erosion resistant film that maintains flexibility and resists checking, cracking, hardening ..... 7.95 2.35 — —

APPLICATION—Brush, Spray
DRYING TIME—Overnight
THINNER—Mineral Spirits, Turpentine, VM & P Naphtha
COVERAGE—Same as Redwood Finish No. 25 Clear

GLID-TONE RE-GRAIN GROUND COAT

An enamel undercoater that produces a firm, opaque film, renews worn out finishes as described in "Step 1" in the Glid-Tone Re-Grain Process folder. For more detailed information see Glid-Tone Regrain Process Folder 04-112 ..... — 2.03 1.19 .80

GLID-TONE SATIN-SHEEN VARNISH

A new satin sheen varnish that dries free from all cloudiness and preserves the natural beauty of the wood. Excellent for use over GLID-TONE stains and for all interior work where a dull finish or rubbed effect is desired. Sufficiently pale for use over light modern stains. DO NOT USE ON FLOORS ..... 7.65 2.28 1.32 .85

APPLICATION—Brush
DRYING TIME—2 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—650 Sq. Ft. per gallon

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GL0026771

	Gals.	Qts.	Pts.	½ Pts.

GLID-TONE SPAR VARNISH

Extra durable spar varnish for exterior surfaces exposed to weather. Recommended as the finest varnish available for exterior use—spars, hulls, decks, house sidings, paneling, porch ceilings, outdoor furniture, etc. Makes perfect finish over Glid-Tone Stain on exterior surfaces ..... 9.40 2.73 1.54 .98

APPLICATION—Brush
DRYING TIME—8 hours; 48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—650 Sq. Ft. per gallon

GLID-TONE VARNISH STAIN

Stains and varnishes in one operation. Dries quickly, to a high lustre. For use on furniture, woodwork and floors. Unusually waterproof ..... 7.20 2.25 1.29 .85

APPLICATION—Brush, Spray
DRYING TIME—4 to 6 hours; 24 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—600 Sq. Ft. per gallon

GLID-TONE WOOD STAIN

An all-purpose, pigmented wiping stain for all types of wood, plywood and veneer, exterior and interior surfaces. Especially suitable for knotty pine wood paneling in recreation rooms. Excellent for use on new or old furniture, woodwork, cabinets, wall paneling and floors. GLID-TONE Stain heightens the beauty of the wood grain. Holds color evenly. May be coated with varnish, shellac or lacquer. May be tinted with DRAMATONE Tinting Colors to produce additional beautiful colors.

APPLICATIONS—Wiping Cloth, Brush
DRYING TIME—12 hours Stains, All Colors ..... 5.65 1.86 1.13 .75
THINNER—Glid-Tone Stain Reducer

GLID-TONE STAIN REDUCER ..... 3.40 1.27 .82 .63

GLD026772

SPRED SATIN

AND SPRED RELATED PRODUCTS

Glidden

	Gals.	Qts.	Pts.	½ Pts.
SPRED SATIN				
(100% Latex Interior Paint)				
Original 100% latex base paint for interior walls, ceilings, woodwork. Excellent for masonry, interior plaster, porous wallboards, acoustical tile, wallpaper. The ideal latex paint for schools, hospitals, residences, offices, motels, hotels, apartments housing projects, etc. Extremely fast, easy application; self priming, cuts painting time in half. No disagreeable odor. Guaranteed washable. May be tinted with DRAMATONE Tinting Colors.				
3418 Decorator White	6.69	2.15	1.20	.79
3470 Ceiling Flat White and Standard Colors	6.69	2.15	—	—
3480 Dramatone Tint Base	6.05	1.92	—	—
DEEP COLORS				
3434 Charcoal Black	6.69	2.15	1.20	.79
3436 Sunglow Yellow	9.95	2.94	1.67	1.02
APPLICATION—Brush, Roller, Spray				
DRYING TIME—20 minutes; may be recoated in 4 hours				
THINNER—Water				
COVERAGE—Up to 500 Sq. Ft. per gallon over most surfaces				
***SPRED LUSTRE SEMI-GLOSS ENAMEL**				
(Interior-Exterior Washable Alkyd Enamel)				
Ready to use. Covers most surfaces in One Coat. Requires no other primer on new plaster or new wood. Ideal for kitchens, bathrooms, hallways,—walls, furniture, plaster, woodwork and metal. Washes like tile. Colors match SPRED SATIN. May be tinted with DRAMATONE Tinting Colors.				
4600 White and Colors; 4618 SPRED Lustre Pastel Tinting White	8.35	2.53	1.44	—
4680 SPRED Lustre Dramatone Tint Base	7.55	2.28	—	—
APPLICATION—Brush, Roller, Spray				
DRYING TIME—Dust free 3 to 4 hours; recoat overnight				
THINNER—Mineral Spirits or Turpentine				
COVERAGE—Approx. 550 Sq. Ft. per gallon				

	Qts.	2 Oz. Paks	1 Oz. Paks	¼ Oz. Paks	⅛ Oz. Paks
DRAMATONE MULTI-PURPOSE TINTING COLORS					
(For Tinting Latex, Alkyd and Other Paints)					
Tinting colors for use with SPRED SATIN Latex Paint, Alkyd Semi-Gloss Enamel, Alkyd Flat Enamel and Other Paints. See Dramatone displays for wide range of colors.		Per Pak.	Per Pak.	Per Pak.	Per Pak.
1781 Blue; 1782 Lamp Black; 1783 Umber Brown; 1784 Green; 1786 Red Oxide; 1787 Ruby Red; 1788 Yellow Oxide	—	.60	.50	.40	.38
1791 Hansa Yellow; 1792 Light Green; ‡1793 Bright Orange	—	.70	.58	.47	.45

*AVAILABLE IN 5-GAL. CANS AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

‡FOR INTERIOR USE ONLY.

Glidden

	Gals.	Qts.	Pts.	½ Pts.
***SPRED HOUSE PAINT** **(100% Latex Exterior Paint)** A new blister-resistant house paint for exterior wood and masonry. Has a remarkable fast drying time of twenty minutes, which practically eliminates damage from bugs, rain and dust. May be applied over damp surfaces. Has long lasting velvet-like sheen. Once the Spred House Paint system is used on a house, future paintings will require only one coat. White and Colors APPLICATION—Brush, Roller, Spray Gun DRYING TIME—4 hours for recoating THINNER—Water COVERAGE—Approx. 450 Sq. Ft. per gal. on smooth surface	7.98	2.45	—	—
***SPRED PRIMECOAT #1** **(Thin With Mineral Spirits)** Spred Primecoat #1 provides a firm foundation on new or unpainted exterior surfaces. The ideal undercoat that creates the finest possible two coat paint job when used under Spred House Paint. Excellent also for recoating badly weathered or porous surfaces that have been previously painted. This primecoat has been especially formulated for Spred House Paint APPLICATION—Brush, Roller, Spray Gun DRYING TIME—48 Hours THINNER—Turpentine or Mineral Spirits COVERAGE—450-550 Sq. Ft. per gallon	7.98	2.45	—	—
***SPRED PRIMECOAT #2** **(Thin With Water)** Spred Primecoat #2 is an especially prepared undercoat for Spred House Paint, to be used over previously painted exterior surfaces. Dries to touch in one hour! This unusually fast drying time helps keep it bug-free and aids in preventing damage to paint from rain and windstorms. Easiest of all house paint primers to apply! Allows interior household moisture to pass through the paint film, to provide strongest defense against blisters! Produces a remarkable strong, adhesive sealer film APPLICATION—Brush, Roller, Spray Gun DRYING TIME—6-9 Hrs., depending on temperature THINNER—Water COVERAGE—Up to 500 Sq. Ft. per gallon	7.98	2.45	—	—
SPRED GRANULETS **(For Producing Sand-Type Finishes)** Treated mineral particles for adding to SPRED SATIN, or SPRED TEXTURE PAINT, to create a durable sand finish. For use on interior walls of plaster, wallboard, concrete, masonry and all types of dry-wall construction	3.00	1.18	—	—

*AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL PRICES.

GLD026774

Glidden

	Gals.	Qts.	Pts.	½ Pts.
***SPRED GLIDE-ON**				
(Vinyl-Latex Exterior Masonry Paint)				
An exterior vinyl-latex masonry paint, unaffected by the alkalinity found in all masonry surfaces. Designed for use on stucco, concrete, brick, concrete block, cinder block, asbestos shingle and panel siding, unglazed tile and primed metal. Keeps out moisture yet the surface "breathes" to let vapor escape from inside. A tough vinyl film that resists driving rains, hottest sunshine, mildew, snow and ice, sea air and salt water spray, strongest smog, dust and chemical fumes. Resists cracking, peeling, blistering, acid and alkali action.				
White and Colors	6.90	2.13	—	—
APPLICATION—Brush, Roller, Spray DRYING TIME—Overnight for recoating THINNER—No. 3520 GLIDE-ON MIXING LIQUID COVERAGE—Up to 400 Sq. Ft. per gallon				
***SPRED GLIDE-ON MIXING LIQUID No. 3520**				
For mixing with SPRED GLIDE-ON when painting over new and porous surfaces, not previously painted	3.95	1.45	—	—
SPRED TRED				
(100% Latex Floor Paint)				
For Interior-Exterior Surfaces: A durable LATEX finish for floors, steps, wall dadoes (lower part of wall) of concrete, masonry, plaster, wood, metal. Not recommended for exterior wood surfaces exposed to direct sunlight. Has no paint odor—no fire hazards. Under normal drying conditions, dries in 20 to 30 minutes—ready to walk on hour after drying. May be mildly cleaned the first week and scrubbed after 10 days curing. Colors may be tinted with DRAMATONE Multi-Purpose Tinting Colors.				
White and Colors	7.55	2.32	—	—
Village Green, ‡Parquet Red	8.35	2.53	—	—
APPLICATION—Brush, Roller DRYING TIME—20 minutes; recoat overnight THINNER—Water COVERAGE—400-450 Sq. Ft. per gallon				
SPRED TRED MIXING LIQUID	—	2.48	—	.92
***SPRED PRIMER-SEALER**				
(A Latex Vapor-Barrier)				
An excellent latex primer for porous surfaces of dry-wall construction, plaster, masonry and asbestos covered pipes. Seals high-suction plaster, most water stains, "hot spots" and discolored surfaces. Assures positive sealing and hold-out for succeeding finishing coats of either latex or oil base paints. May be intermixed with latex paints for color, or tinted with DRAMATONE Tinting Colors. An approved vapor barrier which helps to prevent outside paint failures	5.85	1.88	—	—
APPLICATION—Brush, Roller, Spray THINNER—Water DRYING TIME—20 minutes; may be recoated in 4 hours COVERAGE—Up to 400 Sq. Ft. per gallon on Plaster; 100 Sq. Ft. per gallon on porous wallboard				
***SURFACE BOND**				
(Seals Powdery Masonry Surfaces)				
A high quality, clear finish bonding coat. Designed to penetrate deeply into chalky surfaces left by previous coats of cement bondings or powder type paints on masonry surfaces. Dries hard to help prevent further chalking. Anchors old surface to make a perfect bond for SPRED GLIDE-ON, as well as other exterior and interior masonry paints	5.90	1.86	—	—
APPLICATION—Brush, Spray DRYING TIME—1 to 4 days depending upon drying conditions THINNER—Turpentine or Mineral Spirits COVERAGE—300 to 400 Sq. Ft. per gallon				

*AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL PRICES.
‡FOR INTERIOR USE ONLY.

GLD026775

	Gals.	Qts.	Pts.	½ Pts.
***SPRED STIPPLE TEXTURE AND BLOCK FILLER** **(Silicated Latex For Masonry and Dry-Wall Construction)** Ready to use on new or old surfaces. Gives all the advantages of texture and all the beauty of paint in one application. Hides irregular surfaces on plaster, wallboard, masonry blocks and wallpaper, seals speckled nail heads and tape joints. Easily applied with brush or roller. May be stippled or lightly textured in a variety of patterns and techniques. Especially made for texturing and stippling and for filling masonry blocks, pores and voids, to eliminate "pinholing" in finish coat, to assure better water repellency and to develop excellent appearance on interior and exterior masonry surfaces. May be tinted with DRAMATONE Tinting Colors. White and Colors APPLICATION—Brush for texturing, followed by stipple brush, sponge trowel, whisk broom, comb, etc., as desired. Use roller for stipple effect. Brush, roll or spray when used as a block filler. DRYING TIME—Overnight THINNER—Water COVERAGE—Texturing and filling blocks—75 to 100 Sq. Ft. per gallon. Stippling: 175 to 200 Sq. Ft. per gallon	5.09	1.72	—	—
SPRED SURFACENE **(Liquid Surface Conditioner and Brush Cleaner)** A clear liquid that can be applied to old enameled, painted or varnished surfaces to clean the surface, dull the gloss and insure good adhesion for a new finish coat. Eliminates the work and dust of sanding and prepares surfaces for refinishing in one easy operation. SURFACENE may also be used as a brush cleaner APPLICATION—Cloth or Brush	4.49	1.53	.94	—
***SPRED TEXTURE** **(Texture Base For Latex Paints)** Latex semi-paste base, neutral in color, for mixing with SPRED SATIN and other latex paints to produce a variety of textured effects on interior walls and ceilings. 100% latex type base, when mixed with latex paint, hides minor wall cracks and is particularly effective in covering tape joints in dry wall construction. It is an excellent finish on plaster board, plaster, masonry block and wallpaper. Used by itself, it makes a good spackling compound for patching small imperfections before texturing	4.29	1.52	—	—
SPRED PATCH **(100% Latex Spackling Compound)** A ready-to-use spackling compound. Will not bleed through paint, or flash. Does not shrink. Dries to a "puff" which may be easily sanded. Does not clog sandpaper. Excellent adhesion APPLICATION—Putty Knife DRYING TIME—30 minutes THINNER—Water	4.60	1.63	—	.67
SPRED FLAT **(Oil-Emulsion Interior Paint)** One gallon makes six quarts of paint when mixed with two quarts of water. Easy to apply over wallpaper, new or old plaster, wallboard, painted surfaces, cement and rough tile walls. Has limited washability. White APPLICATION—Brush, Roller, Spray DRYING TIME—30 minutes; recoat 4 to 12 hours, depending upon surface THINNER—Water COVERAGE—Up to 650 Sq. Ft. per gallon	4.59	1.58	—	—

*AVAILABLE IN 5-GAL CANS
AT 15¢ PER GALLON LESS THAN 1-GAL. PRICES.

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

GLID-TONE WOOD BLEACH

Has the amazing properties of bleaching practically any type of wood from its original color to an almost natural white and without any deposit of a salt of any kind in the pores of the wood, necessary to the production of the blond effects so popular and modern at present.
Available in two size units. Large unit consists of 1 gallon of No. 1 Solution and 1 quart of No. 2 Solution. Small unit consists of 1 quart of No. 1 Solution and ½ pint of No. 2 Solution

	Large Unit	Small Unit		
	10.50	4.18	—	—

APPLICATION—Mop, Cloth, Waste
DRYING TIME—12 hours or more

GLID-TONE WOOD FILLER

	Gals.	Qts.		

For use on all open-grained wood such as oak, chestnut, walnut and mahogany. Has pure silex base and will not shrink or break away from the pores of the wood when dry. Furnished in paste form. Must be reduced with naphtha or turpentine

	4.99	1.72	—	.69

APPLICATION—Brush, Cloth
THINNER—Turpentine, Naphtha

GLOSS FINISHES

See: Japalac; Ripolin; Florenamel; Speed-Wall; Rustmaster

GYMNASIUM FLOOR FINISH

A penetrating finish made especially for gymnasium floors made of maple, beech or birch wood. Approved by Maple Flooring Manufacturers' Association

	6.29	1.93	—	—

APPLICATION—Brush, Mop
DRYING TIME—24 hours
THINNER—Mineral Spirits
COVERAGE—Up to 600 Sq. Ft. per gallon

HEAT RESISTING ALUMINUM
See: Metallite

HOUSE PAINT
See: SPRED House Paint; Endurance Paints; SPRED Glide-On; Everon

IRON PRIMER
See: Liquid Red Lead; Rustmaster Metal Primers

IMPERIAL ONE-COAT WHITE HOUSE PAINT
See: Endurance Imperial

INTERIOR ALUMINUM
See: Metallite All-Purpose Aluminum

JAPALAC SCREEN AND IRON ENAMEL

Gloss black, solid-covering enamel for exterior screens, wood and metal sash, wrought iron, decorative lamps, etc. Also ideal for interior ironwork, pipes, grills, furnaces, stoves, heaters andirons, etc. Will not clog screen mesh. Resists weather and protects metal from rusting

	4.79	1.60	1.01	.68

APPLICATION—Brush, Spray or Special Applicator
DRYING TIME—6 to 8 hours
THINNER—Mineral Spirits or Turpentine
COVERAGE—600 Sq. Ft. per gallon

GLD026777

[redacted]

JAPALAC ENAMEL

Quick-Drying, Alkyd Gloss

An extra-durable, alkyd enamel in brilliant colors that cover in ONE COAT. Bright hues and muted tones give new life and sparkle to old surfaces—walls, ceilings, woodwork and furniture. JAPALAC Quick-Drying Alkyd Enamel is formulated for the finest enameling inside and outdoors. It looks, wears and washes like baked enamel. Colors may be tinted with DRAMATONE Tinting Colors.

	Gals.	Qts.	Pts.	½ Pts.	¼ Pts.
Ultra White, Brilliant Black, Flat Black and Colors	9.79	2.88	1.62	1.00	.65

APPLICATION—Brush, Roller, Spray
DRYING TIME—4 to 6 hours; 24 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Approx. 500 Sq. Ft. per gallon

JAPALAC SPRAY ENAMEL

In Ready-To-Spray Cans

All-purpose, interior-exterior enamel in pressurized, aerosol cans ready for immediate spraying. Extra-durable, quick-drying enamel of brilliant beauty. Gives professional appearance to porch and lawn furniture, bicycles, toys, tables, chairs, etc. Ideal for wickerwork. Colors match regular JAPALAC Alkyd Enamel colors. In addition, JAPALAC SPRAY ENAMEL is available in ready-to-spray interior-exterior Aluminum, rich Gold, and a clear finish.

	16 Av. Oz. Can
White, All Colors, and Clear	1.89

APPLICATION—Spray
DRYING TIME—Ten minutes

LACQUER

See: Glid-Tone Crystalacq (Brushing Lacquer)

LATEX PAINTS

See: SPRED Products Section

LINOLEUM COATING

See: Glid-Tone Crystalacq

LIQUID CLEANER

See: Glid-N Liquid Cleaner

*LIQUID RED LEAD (Modified)

Recommended whenever a shop coat of red lead is specified. Comes ready to apply, is extremely elastic and is an excellent rust preventative

	Gals.	Qts.	Pts.	½ Pts.
	8.75	2.66	1.54	.98

APPLICATION—Brush, Spray
DRYING TIME—16 hours; 48 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—500 to 600 Sq. Ft. per gallon

MACHINERY ENAMEL

See: Rustmaster Enamel; Japalac

MASONRY FINISHES

See: SPRED House Paint; Clear Driwal; Silicone Driwal; SPRED Glide-On

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026778

	Gals.	Qts.	Pts.	½ Pts.

*METALLITE ALL PURPOSE ALUMINUM (No. 592)

An extremely smooth, chrome-like aluminum finish for use on radiators, furnace jackets, airducts, hot water tanks and heaters, pipes and other interior surfaces. Will not tarnish under ordinary conditions. It maintains its brilliance. Makes an excellent sealer over asphalt. Retards corrosion caused by fumes and moisture. Withstands heat up to 500°F. Hides with one coat. Easily cleaned. Reflects light ..... 6.89 2.15 1.27 .81

APPLICATION—Brush, Roller, Spray
DRYING TIME—2 to 4 hours: 24 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—650 Sq. Ft. per gallon

METAL PRIMER
See: Liquid Red Lead; Rustmaster Metal Primer

MILDEW-RESISTING PAINTS
See: SPRED Glide-On; Endurance Mildew and Fume-Resistant Paint

METAL PROTECTIVE PAINTS
See: Rustmaster; Metallite, Liquid Red Lead

---

*NEVA-ROT

(Wood and Canvas Preservative)

A preservative that combats mold, fungus, mildew, termites, ants, beetles, bacteria, rot and decay. Equally effective on wood, canvas and rope. Highly recommended for new or old lumber, hand rails, porches, columns, stairways, fence posts, cribs, barns, foundation timbers, ropes, lines, canvas awings—wherever non-metal surfaces require protection from insects and bacterial damage. NEVA-ROT has been tested and approved by the U. S. Navy as a preservative. It is odorless and non-toxic to humans, will not irritate eyes or skin.

Neva-Rot Clear	5.50	1.78	—	—
Neva-Rot Green	4.20	1.62	—	—

APPLICATION—Brush, Spray, Dip, Swab
DRYING TIME—Overnight
THINNER—None Required
COVERAGE—200 Sq. Ft. per gallon

ONE-COAT HOUSE PAINT
See: Endurance Imperial

OIL COLORS IN TUBES
See: Colors-in-Oil

PAINT AND VARNISH REMOVER
See: Glid-Strip; Ad-El-ite

PATCHING PLASTER
See: SPRED Patch

*AVAILABLE IN 5-GAL CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026779

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

PLI-NAMEL (Synthetic Rubber-Base Paint)

A rubberized paint made especially for concrete floors, masonry walls and metal surfaces. Used extensively on basement floors, in laundry and shower areas, recreation rooms, semi-exposed areas such as concrete patios, porches, terraces, etc. Excellent for industrial use—floors, stairs, corridors, loading docks; especially effective protective coating in industrial washing machines, degreaser tanks and equipment. PLI-NAMEL resists acids, alkalies, severe fumes and chemicals, rust and water.

Regular Colors	8.55	2.63	—	—
White	9.05	2.72	—	—

APPLICATION—Brush, Roller, Spray
DRYING TIME—Overnight; 24 hours for recoating
THINNER—Toluol or Turpentine
COVERAGE—500 Sq. Ft. per gallon

PORCH AND DECK ENAMEL

See: Florenamel

PRIMERS AND SEALERS

See: Alkali-Resisting Primer No. 6419; Endurance Exterior Basecoat; Speed-Wall Interior Basecoat; SPRED Primer-Sealer; Gliddencoat Enamel Undercoat; Ripolin Undercoat; Surface Bond

RED LEAD (Liquid)

See: Liquid Red Lead

RIPOLIN ENAMEL (Quick-Drying White)

One of the oldest and finest enamels with world-wide acceptance. Architects and painters recognize RIPOLIN as the finest enamel for interior and exterior decorating. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors.

Gloss, Semi-Gloss (White Only)	10.10	3.13	1.77	1.02

APPLICATION—Brush, Roller, Spray
DRYING TIME—6 to 8 hours; 24 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—600 Sq. Ft. per gallon

RIPOLIN UNDERCOAT

A perfect first coater for new wood or previously painted surfaces. Dries to a firm opaque film. Especially designed for use with Ripolin Semi-Gloss and Gloss Enamels. Completely hides and seals a surface so that finishing coats of Ripolin Enamel produce full luster and depth of gloss. Requires only light sanding. May be tinted with Colors-In-Oil or DRAMATONE Tinting Colors

	7.25	2.28	1.34	—

APPLICATION—Brush, Spray
DRYING TIME—Overnight for sanding and recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—500 Sq. Ft. per gallon

RIPOLIN YACHTING FINISHES

(PRICES UPON REQUEST)

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026780

[redacted]

	Gals.	Qts.	Pts.	½ Pts.
***ROCKSPAR VARNISH**				
Heavy bodied varnish for all interior surfaces. One coat equivalent to two coats of ordinary varnish. No shrinkage on drying. Dries with deep high gloss	7.95	2.43	1.41	.89
APPLICATION—Brush				
DRYING TIME—Overnight; 24 hours for recoating				
THINNER—Mineral Spirits or Turpentine				
COVERAGE—Up to 700 Sq. Ft. per gallon				
RUSTMASTER GLOSS ENAMEL				
A high quality versatile enamel of excellent quality. It has exceptional ease of application and may be applied by brushing, or spraying as a finish coat over metal paint with No. 470 or No. 471 Rustmaster Primer. Rustmaster Gloss Enamel guards against rusting of machinery and equipment in the factory and on the farm as well as metal surfaces around the home and schools such as metal window frames and casings, iron fences, railings, bicycles, lawn mowers, playground equipment, etc.				
Royal Blue, Greenfield, Slate, Gloss Black, Flat Black, Aluminum	8.70	2.63	1.51	.95
Suntone, Flare Red	9.59	2.82	1.61	.99
White	9.20	2.76	1.52	.96
APPLICATION—Brush or Spray				
DRYING TIME—Overnight				
THINNER—Turpentine or Mineral Spirits for Brushing; VM & P Naphtha for Spraying				
COVERAGE—Up to 500 Sq. Ft. per gallon				
RUSTMASTER METAL PRIMER 470				
A new unexcelled fast drying corrosion resistant exterior and interior metal primer containing revolutionary Phenolic Resin Penetrating Liquid (Glidden Patent Pending) that cuts through rust and seals metal pores, locking out air and corrosive moisture. A finish coat of Rustmaster Enamel will provide an exceptionally durable coating	8.70	2.63	1.51	.95
APPLICATION—Brush or Spray				
DRYING TIME—Overnight				
THINNER—Turpentine or Mineral Spirits for Brushing; VM & P Naphtha for Spraying				
COVERAGE—Up to 500 Sq. Ft. per gallon				
RUSTMASTER PRIMER 4030 (Spray Can)	16 Oz. Can			
Same quality as Rustmaster Metal Primer No. 470, packed in handy spray can for easy, instant use. Ideal for hard-to-reach areas	1.89	—	—	—
APPLICATION—Spray				
DRYING TIME—Overnight for recoating				
RUSTMASTER GALVANIZED PRIMER 471	Gals.			
Provides longer-lasting protection for galvanized metal and aluminum. Use on new galvanized steel without chemical treatment. This prime coat may be used as a finish coat or recoated with Rustmaster Enamel, Endurance House Paint or Japalac	8.70	2.63	1.51	.95
APPLICATION—Brush, Roller, Spray				
DRYING TIME—48 hours				
THINNER—Turpentine, Mineral Spirits				
COVERAGE—Approx. 350 Sq. Ft. per gallon				

*AVAILABLE IN 5-GAL. CANS
AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

[redacted] 19

GLD026781

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

ROOF PAINTS. See: Aluminum Asphalt Roof Paint; Nev-A-Rust; Metallite All-Purpose Aluminum

SCREEN ENAMELS. See: Japalac Screen and Iron Enamel

SEMI-GLOSS ENAMELS. See: Ripolin; SPRED Lustre

SILICONE SLICK SPRAY

(Miracle Lubricant With 1001 Uses)

A new, spray lubricant that protects and preserves while it lubricates. An excellent ice and water repellent. Push button spray lubricates hard-to-reach parts and areas. Makes windows, drawers, doors and other sticking items slide freely. Stops squeaks

6 Oz. Can	16 Oz. Can
1.59	2.95

SPACKLING COMPOUND. See: SPRED Patch

SPAR VARNISH. See Glid-Tone Spar Varnish

S'NUF FIRE EXTINGUISHER

(In aerosol, Ready-to-Spray Cans)

Handy, easy-to-use fire extinguisher. Extinguishes flames instantly upon contact. A safe, reliable fire fighter for homes, autos, boats, shops, etc.

16 Oz. Can
1.98

*SPEED-WALL ALKYD INTERIOR BASECOAT

Gals.	Qts.		

A ready-to-use, low odor, alkyd-type primer sealer for new and old interior wall surfaces of plaster, masonry or wallboard. Also for previously painted walls in poor condition and patched areas. Its remarkable ease of brushing and exceptional filling, sealing, hiding, and alkali-resisting properties are gained through the use of special resins, pigments, and oils

5.30	1.71	—	—

APPLICATION—Brush, Roller, Spray
DRYING TIME—Overnight for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 450 Sq. Ft. per gallon

*SPEED-WALL GLOSS WHITE

Highly water-proof, resists steam, [illegible]sture, and washing. The white resists yellowing. Practical for kitchen, bathroom and similar household uses. It may be applied to plaster, cement, wood, wallboard, or metal surfaces. Applies easily, may be tinted with Colors-In-Oil or DRAMATONE Tinting Colors

7.70	2.37	—	—

APPLICATION—Brush, Spray
DRYING TIME—Overnight for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 550 Sq. Ft. per gallon

SPRED PRODUCTS

See: SPRED Products Section

STAINS

See: Glid-Tone Stain

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

[redacted]

	Gals.	Qts.	Pts.	½ Pts.

*STOCK FARM WHITE PAINT

An excellent low cost exterior paint for use on wood surfaces such as fences, barns, outbuildings, sheds, etc. This material, produced for use in stock farms, is formulated without lead pigments, and contains wood preservatives. The creosote-like odor tends to repel livestock ..... 5.95 — — —

APPLICATION—Brush, Spray
DRYING TIME—Overnight; 24 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 450 Sq. Ft. per gallon depending upon surface condition

SUPER REN-O-VITE PLUS (Cleaner–Polish–Wax)

This is a one-operation cleaner, polish and wax. Unique, film-forming, it gives a tough, extra long wearing plastic finish to automobiles, yachts and other painted or enameled surfaces. Easy to use, requires less rubbing, yet cuts through oxidized surfaces in a flash! Quickly removes grease, oil, chalking, bug deposits and other stains. Use on enamel, lacquer, chrome and ceramic tile surfaces ..... — 2.22 1.27 —

STOVE AND IRON ENAMEL. See: Japalac Screen and Iron Enamel

SURFACE CONDITIONER. See: SPRED Surfacene; Surface Bond

TILE ROOF PAINT. See: SPRED Glide-On

*TINNER'S PAINT (Red)

For use on metal roofs, flashings, gutters, downspouts and for work inside tin shops. Equally satisfactory for wood and brick surfaces. Permanent in color. Sufficiently elastic not to chip or crack when the metal is bent ..... 4.89 1.66 — —

APPLICATION—Brush, Spray
DRYING TIME—Overnight; 36 hours for recoating
THINNER—Mineral Spirits or Turpentine
COVERAGE—Up to 550 Sq. Ft. per gallon

TINTING COLORS
See: Dramatone Multi-Purpose Tinting Colors; Colors-In-Oil

TRIM AND SHUTTER COLORS
See: Endurance House Paint

TUBE COLORS
See: Dramatone Multi-Purpose Tinting Colors; Colors-in-Oil

UNDERCOATERS
See: Gliddencoat, Ripolin Undercoat, Surface Bond, Speed-Wall Interior Basecoat; SPRED Primer-Sealer, Endurance Exterior Basecoat; Rustmaster Metal Primer 470; Rustmaster Galvanized Primer 471.

VAPOR BARRIER. See: SPRED Primer-Sealer

VARNISHES
See: Glid-Tone Spar; Glid-Tone Satin Sheen; Glid-Tone Gloss; Rockspar

VARNISH REMOVER
See: Ad-El-ite; Glid-Strip

VINYL-LATEX PAINT
See: SPRED Glide-On

*AVAILABLE IN 5-GAL. CANS AT 15c PER GALLON LESS THAN 1-GAL. PRICES.

GLD026783

[redacted]

	Gals.	Qts.	Pts.	½ Pts.
VISMATIC GREEN CHALKBOARD COATING A lusterless matte finish, green in color. Extremely popular in a large number of America's finest school, college and university classrooms. It is used to paint black chalkboards in a new light-reflecting color that is easy on the eyes. This green finish achieves maximum visibility and minimum light wave vibration of chalk lines and letters. Easy to apply	9.05	2.64	1.53	—

APPLICATION—Brush, Spray
DRYING TIME—Overnight for recoating
THINNER—Mineral Spirits
COVERAGE—Up to 500 Sq. Ft. per gallon

WOOD, BLEACH

See: Glid-Tone Wood Bleach

WOOD FILLER

See: Glid-Tone Wood Filler

WOOD FINISHES

See: Glid-Tone Products

WOOD PRESERVATIVE

See: Neva-Rot

WOOD STAIN

See: Glid-Tone Stain

YACHT AND BOAT FINISHES (Ripolin)

(PRICES UPON REQUEST)

NOTE: Although the formulations and recommendations contained in this price list have been established through careful evaluation, users of Glidden paints are urged to obtain specific information concerning their painting requirements. Seller's liability shall in no event exceed value of this material, which is warranted only to conform to formula or sample. Seller hereby expressly excludes all other express or implied warranties whatsoever.

[redacted]

Glidden Branches and Distributing Points

ALABAMA
Birmingham 3—2301-07 Sixth Ave., South
Mobile—1610 Government Street
Montgomery—523 W. Fairview Ave.

ARKANSAS
Little Rock—605 W. Markham St.

CALIFORNIA
Alhambra—9 West Main st., P.O. Box 190)
Fresno (W.)—1916 East McKinley Ave.
Huntington Park—7522 Pacific Blvd.
Lakewood—4812 Paramount Blvd.
Monrovia—610 S. Myrtle Ave.
North Hollywood—4907 Lankershim Blvd.
Oakland—4252 Broadway
Sacramento—2500 16th Street
San Diego 4—4101 30th Street P.O. Box 4145
San Francisco 7—1000 Sixteenth Street
San Jose—1641 West San Carlos Street
Santa Cruz—1129 Soquel Avenue
Whittier—1127 Quad Way

COLORADO
Denver 9—324 South Broadway Ave.

CONNECTICUT
Elmwood 10—941 New Britain Ave. (Hartford)

DELAWARE
Dover—Dover Bypass (Box 382)

FLORIDA
Clearwater—1455 Gulf-to-Bay Blvd.
Fort Lauderdale—1113 Sunrise Blvd.
Jacksonville 2—344 Riverside Ave.
Miami 7—3400 Northwest Second Ave.
Orlando—2000 E. Colonial Drive
Tampa 2—3120 Grand Central Ave.

GEORGIA
Albany—944 Oglethorpe Ave.
Atlanta 18—P.O. Box 2325 Station D
Atlanta 13—375 Luckie Street, N.W.
Augusta—1725 Walton Way
Macon—1395 Georgia Ave.

HAWAII
Honolulu—373 N. Nimitz Highway

ILLINOIS
Broadview—2224 W .Roosevelt Rd.
Chicago 16—1833 South Normal Ave.
Joliet—1501 Plainfield Rd.
Mt. Vernon—1022 Jordan Street
Peoria—616 N. Jefferson St.
Rockford—1140 Charles Street
Waukegan—316 N. Genessee Street

INDIANA
Gary—640 Washington St.
Evansville 2—Fourth and Chestnut
Fort Wayne 6—2608 S. Calhoun Street
Hammond—7101 Indianapolis Blvd.
Indianapolis 4—609 N. Delaware Ave.

IOWA
Davenport—2906 Brady St.
Des Moines—2013 Ingersoll Avenue
Sioux City—1909 Pierce Street

KANSAS
Wichita—219 So. Francis St.

KENTUCKY
Louisville 2—100 W. Broadway

LOUISIANA
New Orleans 13—424 Josephine St., P.O. Box 980

MARYLAND
Baltimore 18—2834 Loch Raven Rd.
Glen Burnie—141 Delaware Ave.
Wheaton—11242 Georgia Ave.

MASSACHUSETTS
Natick—309 Worcester Turnpike
Quincy—233 Parkingway Street
Waltham 54—805 Main Street

MICHIGAN
Detroit 2—7502-06 Woodward Ave.
Grand Rapids—2114 S. Division Ave.

MINNESOTA
Duluth 2—210 West First Street
Minneapolis—4519 France Ave.
Minneapolis—1901 E. Hennepin Ave.
St. Paul 4—271 N. Snelling Ave.

MISSOURI
Kansas City 10—1214 East 47th Street
St. Louis 2—106 Gratiot Street
Springfield—738 S. Glenstone

MONTANA
Billings (W)—1701 Montana Ave.
Great Falls—725 First Ave., N.

NEBRASKA
Omaha 5—31st and Leavenworth Sts.

NEW JERSEY
Atlantic City—2225 Atlantic Ave.
Camden—1420 Kings Highway, Haddon Hts.
South Hackensack—368 Huyler Street

NEW MEXICO
Albuquerque—117 Bryn Mawr Dr. S. E.

NEW YORK
Albany—61 Colvin Ave.
Binghamton—Vestall Parkway
Buffalo 14—2697 Main Street
Glens Falls—31 Warren St.
New York 17—Room 310, 52 Vanderbilt Ave.
Rochester 20—566 South Clinton Ave.
Syracuse 3—2516 Erie Blvd. East
Utica—3 Center St., New Hartford Shopping Center
West Hempstead—450 Hempstead Turnpike

NORTH CAROLINA
Asheville—Merrimon and Coleman Ave.
Charlotte 6—1001 S. Independence Blvd..
Charlotte—3945 N. Independence Blvd.
Durham—610 Ninth St., P.O. Box 96
Fayetteville—805 Bragg Blvd.
Greensboro—1225 Battleground Road
Greenville—108 W. 10th st.
New Bern—905 Broad St.
Raleigh—713 West Peace St.

NORTH DAKOTA
Fargo—528 Sixth Avenue, North

OHIO
Akron—315 East Market Street
Cincinnati 29—4466 Reading Rd.
Cleveland 2—11001 Madison Ave.
Columbus 15—342 East Long Street
Dayton—2327 East Third St.
East Cleveland 12—13538 Euclid Ave.
Lakewood 7—15314 Detroit Ave.
Lorain—2542 West 21 Street
Mansfield—1472 Lexington Ave.
Rocky River 16—21190 Center Ridge Rd.
South Euclid 21—4422 Mayfield Rd.
Springfield—411 E. Main St.
Toledo 4—102 South Summit Street
Willoughby—36212 Euclid Ave.
Youngstown 12—4440 Market Street

OKLAHOMA
Oklahoma City 3—900 N. Robinson Ave.
Tulsa—2703 S. Harvard Ave.

OREGON
Portland 5—1615 S. W. Jefferson St.

PENNSYLVANIA
Allentown—1401 Union Blvd.
Altoona—600 Logan Blvd.
Camp Hill—3609 Market St.
Erie—1002 Parade St.
Glenside—230 Keswick Ave.
Harrisburg—1309 North Third Street
Harrisburg—3970 Jonestown Rd., Rt. #22
Johnstown—Bel-Air Shopping Plaza, Windber Road
Lebanon—723 Cornwall Rd.
Lewistown—11 Valley St.
Pittsburgh 33—1020 Western Ave.
Pottstown—408 High Street
Reading—Third & Bern Sts., P.O. Box 1097
Reading—1901 Centre Ave.
Scranton 3—224 Wyoming Street
Williamsport—1311 Washington Blvd.

RHODE ISLAND
Providence—154 Elmwood Ave.
Warwick—961½ Namquid Drive

SOUTH CAROLINA
Greenville—626 N. Main St.

TENNESSEE
Chattanooga 2—901 Central Ave.
Knoxville 10—319 Wall Ave.
Memphis 4—412 North Cleveland St.
Memphis 17—4693 Poplar Ave.
Nashville 3—1201 Church Street

TEXAS
Austin—5605 Burnet Road
Corpus Christi—4125 S. Alameda
Dallas 9—5023 Lemmon Avenue
Dallas 30—324 Preston Forest Village
El Paso—700 Montana Ave.
Fort Worth 4—550-556 Hemphill St.
Houston 2—2300 So. Main Street
Lubbock—2611 34th Street
Midland—20 E Village Circle
San Antonio 12—4211 Blanco Road

UTAH
Salt Lake City—921 South Second W.

VIRGINIA
Newport News—7311 Virginia Ave.
Norfolk 13—3449 Military Highway
Richmond 20—117 West Broad St.
Roanoke—4915 Williamson Rd. N.W.

WEST VIRGINIA
Parkersburg—182 Park Center Drive

WASHINGTON
Seattle 9—408 Eighth Ave., North

WISCONSIN
Green Bay—517 West Mason St.
Madison—911 Regent Street
Milwaukee 16—6401 W. Capitol Drive

DISTRICT OF COLUMBIA
Washington 2—1323 Fourth St., N.E.

CANADA

ALBERTA
Calgary—1011 17th Ave., S.W.
Edmonton—10127 104th Street

BRITISH COLUMBIA
Vancouver—1280 Granville St.
Victoria—840 Fort St.

MANITOBA
Winnipeg—1041 Erin Street

NEW BRUNSWICK
Moncton—230 Botsford Street
St. John—664 Rothesay Ave.

ONTARIO
Guelph—Speedvale Ave., at Woolwich
Hamilton—1629 Main St., W.
London—247 Dundas St.
Ottawa—1314 Bank Street
Port Arthur—16 St. Paul Street
St. Thomas—571 Talbot St.

QUEBEC
Toronto 9—351 Wallace Ave.
Windsor—670 Goyeau St.
Montreal—5833 Sherbrooke St.
Montreal 32—133 Elmslie St., Ville La Salle
Quebec City—865 De La Reine
Sherbrooke—137 Wellington St.

SASKATCHEWAN
Regina—1630 Albert St.

GLIDDEN INTERNATIONAL

PANAMA
Republic de Paneme—P.O. Box 3275, Panama

PUERTO RICO
Fernandez, Juncs Station—P.O. Box 8558
Santurce Ponce—P.O. Box 764

Glidden — Quality Products

Form 80159

Printed in U.S.A.

GLD026785