

ANGUS FIRE ARMOUR CORP -- 41017EXT ALCOSEAL 3/6% @ AR-FFFP EXTINGUISHER
GRADE ---

===== Product Identification =====

Product ID:41017EXT ALCOSEAL 3/6% @ AR-FFFP EXTINGUISHER GRADE

MSDS Date:07/19/1994

FSC:NIIN:Submitter:F BT

Status Code:A

MSDS Number: CJYSD

=== Responsible Party ===

Company Name:ANGUS FIRE ARMOUR CORP

Address:ANGIER-KENNEBEC RD AND BROAD ST

Box:879

City:ANGIER

State:NC

ZIP:27501

Country:US

Info Phone Num:919-639-6151

Emergency Phone Num:919-639-6151

CAGE:63317

=== Contractor Identification ===

Company Name:ANGUS FIRE ARMOUR CORP

Address:ANGIER-KENNEBEC RD AND BROAD ST

Box:879

City:ANGIER

State:NC

ZIP:27501

Country:US

Phone:919-639-6151

CAGE:63317

===== Composition/Information on Ingredients =====

Ingred Name:HYDROLIZED PROTEIN

< Wt:30.

Ingred Name:SURFACE ACTIVE AGENTS & FLUOROSURFACTANTS

< Wt:5.

Ingred Name:PRESERVATIVE

< Wt:2.

Ingred Name:HEXYLENE GLYCOL

CAS:107-41-5

RTECS #:SA0810000

< Wt:10.

ACGIH STEL:C121 MG/M3;C25 PPM

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: BALANCE

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INGESTION: LOW ORAL RISK WHEN USED AS
INTENDED. EYES/SKIN: IRRITANT. INHALATION: MAY CAUSE IRRITATION.

Effects of Overexposure: IRRITATION, NAUSEA, VOMITING

===== First Aid Measures =====

First Aid: SKIN: WASH OFF W/LARGE QUANTITY OF WATER. EYES: IMMEDIATELY FLUSH W/LARGE QUANTITY OF WATER FOR 15 MINS, INCLUDING UNDER EYELIDS. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES .

===== Fire Fighting Measures =====

Flash Point Method: PMCC
Flash Point: >54.4C, 130.F
Extinguishing Media: NOT FLAMMABLE
Fire Fighting Procedures: NOT FLAMMABLE

===== Accidental Release Measures =====

Spill Release Procedures: IF REGULATIONS PERMIT, FLUSH INTO SEWER AT 0.1% CONCENTRATION/LESS. LARGE: SHOULD BE ABSORBED ON INERT MATERIAL, TRANSFERRED TO SUITABLE CONTAINERS & DISPOSED IN SANITARY LANDFILL.

===== Handling and Storage =====

Handling and Storage Precautions: STORE AT 25-120F. USE ORIGINAL CONTAINER/STAINLESS STEEL, FIBER GLASS/BITUMEN LINED TANKS.
Other Precautions: FOR INDUSTRIAL & MUNICIPAL FIRE DEPARTMENT USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT NORMALLY REQUIRED
Ventilation: ADEQUATE LEVELS TO PREVENT BUILD UP OF ODOR.
Protective Gloves: IMPERVIOUS; NEOPRENE
Eye Protection: SAFETY GLASSES, GOGGLES/FACE SHIELD OF AN APPROVED TYPE.
Supplemental Safety and Health
PRODUCT IS A MIXTURE OF HYDROLYZED PROTEIN SOLUTION CONTAINING FLUOROSURFACTANTS & GLYCOL SOLVENT, USED FOR FIRE FIGHTING FOAM CONCENTRATE.

===== Physical/Chemical Properties =====

Boiling Pt: =100.C, 212.F
Melt/Freeze Pt: =-7.2C, 19.F
Spec Gravity: 1.09
pH: 6.5-7.5
Solubility in Water: COMPLETE
Appearance and Odor: DARK BROWN VISCOUS LIQUID, ORGANIC ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
ANY MATERIALS WHICH HAVE VIOLENT REACTIONS W/WATER.

===== Ecological Information =====

Ecological: UNDER EPA CERCLA RELEASES TO AIR, LAND/WATER WHICH EXCEED THE REPORTABLE QUANTITY MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN SANITARY LANDFILL/DISPOSE OF IN
ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:NOT REGULATED.

===== Regulatory Information =====

SARA Title III Information:NONE
Federal Regulatory Information:NONE

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.