

NOTICE: If the film image
is less clear than this
notice, it is due to the
quality of the document
being filmed

16

**DUTCH BOY
LEAD MIXING OIL**

*for sealing
and finishing*

**PLASTER
STUCCO
CONCRETE
AND BRICK**



00055

N1360

NLI 111/24

NOTICE: If the film image is less clear than this notice, it is due to the quality of the document being filmed



DUTCH BOY LEAD MIXING OIL

A special vehicle for mixing with white-lead. Makes a paint that seals and finishes either inside or outside porous surfaces. Makes a paint that gives a perfect brush job on plaster walls. Makes a paint that waterproofs and beautifies concrete and stone.



... then, my motto are my mottoes—my mottoes. It breathes not breathlessly. . . . my mottoes near the solid, comely, flat surface. And its hard finish is a very durable under exposed building—standing up under the strongest service demanded by hospitals, schools and office buildings. Is for economy. . . . It spreads its broad flat square feet to the point—keeps well—gives an upright and such—gives no wall and outside.

General Recommendations for Interior Plaster

I liked and I think the Lord Young will do well to send for all those men as you place. I cannot get on two places at one time, but with that, the Lord Young will see to it that the pleasure of a good job. You can see, of course, nothing as important job.

First made with white lead and later by Lead White and Red, these pigments were during the drying period. The final effect is a white line with a very slight shade of single refinement. This paint also sets up slowly, gives all the tone needed in earthy tones.

proportion of food among all should be reduced to a minimum of one pound per week hundred pounds of a hundred.

is somewhat more permanent than enamel, having often been successfully used for a number of years as a paint for curbstones and stairs. Dark enamel and a corresponding paint to prevent discoloration, moisture cracks and surface staining. This combination of white-lead durability and lead curing oil's sealing results in a paint that keeps out dampness and moisture and gives lasting beauty with lead, being a white-lead paint. It weathers down slowly by gradual rubbing, losing a smooth even surface when repainting is eventually necessary.

Whitford and Hatch May Lead Wiring
It has all the eye-appealing, high-biting
features of your whitford point. There's
creativity, for the owner, too, in its long life
and low upkeep cost.

General Recommendations for Stress and Concrete

Signs and messages should be permitted to promote no greater than those in an outdoor letter being posted. In exceptional cases larger advertising is desirable to obtain results from the sign being shown on

— does not all the school children

Two more are now in a rush in a very satisfactory job although these rats are recommended for the very best work. I use normal drying conditions, an exterior surface painted with spar-kiln and linseed. They last. Among the rats may be counted in forty-eight hours. If the weather is extremely hot and the paint sets up too quickly, some volatile thinner may be added. However, this reduces the cooling properties of lead lining and all should not be done unless absolutely necessary.

For Brick

Finish is important when brick is to be painted. Paint made with white-lead and Dutch-Flay Lead Wiring Oil dispenses that soft lustreless sheen found on the surface of the best face brick. It works the porous surface, too, and stands up under sun and storm. Straight lead wiring oil also makes a fine vehicle for brick color.

For Enamel Undercoater

Revenue is broken out as smoothly, because it gives the solid finish so necessary for a perfect enamel job, paint made with white-lead and flake-bleed. Lead Mining still is regarded as an essential industry.

ПОЧА

00055



NL1 111725

NOTICE: If the film image is less clear than this notice, it is due to the quality of the document being filmed

For Plaster and Wallboard

A STARTLING experience... that's the way you use white-bred and Dutch Boy Lead Mixing (1) on interior plaster or wallboard. For this is a radically different flat paint. It can be used for all coats on new plaster. It looks out beautifully... no brush marks over its soft, smooth flat surface. And its hard finish is extremely durable under repeated washings—standing up under the steams arising from hot pipes, radiators and other buildings. In fact economy... it spreads at least 800 square feet to the gallon—helps you save on paint and materials.

General Recommendations for Interior Plaster

White-bred and Dutch Boy Lead Mixing (1) should be used for all coats on new plaster. A second job on new plaster is not recommended at any time, but with Dutch Boy Lead Mixing (1) you have the pleasure of a good job. You make use, of course, without an equal job.

Paint made with white-bred and Dutch Boy Lead Mixing (1) has been proven during the drying period. The final result is a wall that with a very slight shine at night reflection. This paint dries up slowly... gives all the time needed to reach the most on early large structures.

Prepping, while not required, may be done when such a finish is desired. It is to be for a heavy step. The preparation of lead is to be followed in a sequence of two gallons per each hundred pounds of white-bred.

When maximum saving is required on interior work an white-bred should be used with lead mixing (1) on the ground coat. If surface is in particularly bad condition, Dutch Boy (1) and Primer can be used for priming followed by one or two coats of white-bred and lead mixing (1).

For Stucco and Concrete

White-bred and Dutch Boy Lead Mixing (1) has been successfully used for a number of years as a paint for concrete and stucco. Such surfaces need a corresponding paint to prevent discoloration, moisture cracks and surface staining. This combination of white-bred and lead mixing (1) is a paint that keeps out dampness and moisture and gives lasting beauty to work. And, being a white-bred paint, it washes down easily by gradual chalking, leaving a smooth even surface when repainting is occasionally necessary.

White-bred and Dutch Boy Lead Mixing (1) has all the easy spreading, high-hiding features of your white-bred paint. There's economy for the owner, too, in its long life and low upkeep cost.

General Recommendations for Stucco and Concrete

Stucco and concrete should be primed with... rather than those on the surface before being painted. In preparation from large structures it is desirable to dilute water from this may have enough any

paint over white-bred and lead mixing (1) which contains the chemical activity of any cement stains or moisture stains.

If the surface has previously been painted, any loose paint must be completely removed by thoroughly sanding the surface. The surface is then smoothed down to completely dry... not put on the surface but throughout. The next paint put after a heavy coat or a prolonged rainy spell. When time for the next is done out of the standard sequence.

Two coats on new work result in a very uniform very job although three coats are recommended for the very best work. A third coat during maintenance on exterior surfaces painted with white-bred and Dutch Boy Lead Mixing (1) may be required in long-term use. If the surface is extremely hot and the paint sets up too quickly, more white-bred may be added. However, this reduces the drying properties. If lead mixing (1) and should not be done unless absolutely necessary.

For Brick

Finish is important when brick is to be painted. Paint made with white-bred and Dutch Boy Lead Mixing (1) depicts the soft texture shown found on the surface of the brick face brick. It seals the porous surface, from and stands up against rain and storm. Nightly lead mixing (1) also makes a fine vehicle for brick work.

For Enamel Undercoater

Because it looks out so smoothly, because it gives that solid finish so necessary for a perfect enamel job, paint made with white-bred and Dutch Boy Lead Mixing (1) is excellent as an enamel undercoater.

00055

0 1006

NLI 111726

NOTICE: If the film image
is less clear than this
notice, it is due to the
quality of the document
being filmed

Formulas

The following formulas apply whether the substrate
used is soft or hard.

PLASTER AND GIPSBOARD

First Coat
100 lbs. Shellac dissolved
4 to 5 gals. Shellac has been mixed all
through the surface thoroughly in one coat or two
as needed.

Second Coat
100 lbs. Shellac dissolved
2 to 3 gals. Shellac has been mixed all
through the surface.

For Sanding
Same as usual sand above

For Sealing

100 lbs. Shellac dissolved
2 to 3 gals. Shellac has been mixed all
through the surface. It is recommended that one should
seal the surface first and finish with one or
two coats. The surface should be sealed, then up painted
plaster, then apply sand and finishing coats given
above. The material quantities stated above are
recommended when normal looking is necessary.

STUCCO, CHALK, BRICK, AND PLASTER

First Coat
100 lbs. Shellac dissolved
4 gals. Shellac has been mixed all
through the surface.

Second Coat
100 lbs. Shellac dissolved
2 gals. Shellac has been mixed all
through the surface.

Paint made with shellac and Shellac has been
mixed all through the surface. It is recommended that one should
seal the surface first and finish with one or
two coats. The surface should be sealed, then up painted
plaster, then apply sand and finishing coats given
above. The material quantities stated above are
recommended when normal looking is necessary.

NONAL

00055

0107

NLI 111727