

Copies to: [REDACTED]

E. I. du Pont de Nemours and Company
Haskell Laboratory for Toxicology and Industrial Medicine

HASKELL LABORATORY REPORT NO. 803-76 [REDACTED]

<u>Material Tested</u>	<u>Haskell No.</u>	<u>Sample Ready for Testing</u>	<u>Other Codes</u>	<u>Material Submitted by</u>
[REDACTED]	10,652	10/11/76	[REDACTED]	[REDACTED], Organic Chemicals Department, Jackson Laboratory

DEPARTMENT OF TRANSPORTATION SKIN CORROSION TEST ON RABBIT SKIN

Procedure: Six albino rabbits weighing between 2-3 kg were clipped free of hair on the back and placed in FDA-type stocks. 0.5 ml of the test material (as supplied) was applied under 1.5 by 1.5 inch, 12-ply cotton gauze pads and the trunk of each rabbit was then loosely wrapped with rubber sheeting. After four hours, the rabbits were removed from the stocks, the wrapping and gauze pads were removed and any skin reactions were evaluated. The test sites were then washed. Readings were again made at 24 and 48 hours after the initial application.

Results:

<u>Route of Administration</u>	<u>Number of Rabbits</u>	<u>Dose Level</u>	<u>Number of Rabbits with Skin Corrosion</u>
Skin contact	6	0.5 ml	0/6

Summary: When tested and classified according to the regulations of the Department of Transportation, [REDACTED] (H-10,652) was not found to be corrosive to skin.

[#] Department of Transportation, Hazardous Materials Regulations, Title 49 CFR, Section 173.240(a)(1), October 1, 1975.

Report by: Nancy C. Goodman
Nancy C. Goodman
Technician

Approved by: Raymond W. Morrow
Raymond W. Morrow
Chief, Dermal and Ocular Toxicology Section

CG:ms

Report No. 803-76

Date Issued: October 29, 1976