

Boler Petroleum Company

85 Old Eagle School Road P. O. Box 384 Wayne, Pennsylvania 19087 U.S.A.
Telephone 215-687-9030 TWX, 510-668-2578 Cable Address: CABOL

October 23, 1985

Mr. F. D. Zellner
GENSTAR ROOFING PRODUCTS
620 Aero Drive
P.O. Box 72
Shreveport, LA 71161

Dear Frank:

It was a pleasure meeting with you recently.

I am sorry that our recent offering was a little too high. We are able to offer Boler P-154 Paraffin Wax, slabs on pallets, in truckload quantities at \$.4250 per pound delivered to your plant. (A data sheet and Material Safety Data Sheet are attached.) This wax is a functional equivalent of Sun's 5512 wax.

I look forward to meeting with you in mid-late November to follow-up on our offering.

Very truly yours,

BOLER PETROLEUM COMPANY

Marty
Martin P. Clark


MPC/vjt

encl.

The INTERNATIONAL Group

BAYCHEM INTERNATIONAL, INC., Houston, TX • INTERNATIONAL WAXES LTD., Agincourt, Ont., Canada • MALCOLM NICOL & CO. INC., Lyndhurst, NJ

BIRD 005691



Boler Petroleum Company

85 Old Eagle School Road P. O. Box 384 Wayne, Pennsylvania 19087 U.S.A.
Telephone: 215-687-9030 TWX: 510-668-2578 Cable Address: CABOL

~~BOLER P-154~~

FULLY REFINED PARAFFIN WAX

order 3-27-86
43 & 44

#1435

TYPICAL PROPERTIES:

Melting Point (ASTM D-87)	158°F	152
Melting Point (AMP)	161°F	
Penetration (ASTM D-1321) @ 77°F	12	13
" " @100°F	20	24
Oil Content (ASTM D-721)	0.4%	.02
Color (ASTM D-156)	+30	+30
Saybolt Viscosity (ASTM D-445) @210°F	51 SUS	49

FDA STATUS:

Boler 1554 Fully Refined Paraffin Wax meets the FDA requirements and may be safely used in or on food under the provisions of 21 CFR 172.886. It may also be safely used as a component of nonfood articles in contact with food under the provisions of 21 CFR 178.3710.

1084

Paragon Industrial Wax

Division of Boler Petroleum Company

521 Bay-Shore Drive, P.O. Box 1220, Oshkosh, Wisconsin 54901
414-233-5500

"The information contained herein or on any attached document is submitted for your evaluation. The sale of any of these products by us to you shall be made without any warranty as to merchantability or fitness for a particular use or any other warranty, expressed or implied. No representative of ours has any authority to waive or change these provisions and any communication from you or any other source containing terms to the contrary shall not be binding upon us unless specifically accepted in writing by an authorized officer of our Company. This publication should not be taken as permission or recommendation to infringe upon an existing or future patent."

U. S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

Form Approved
OMB No. 44-R1387

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME BOILER PETROLEUM COMPANY		EMERGENCY TELEPHONE NO. 215-687-9030
ADDRESS (Number, Street, City, State, and ZIP Code) 85 Old Eagle School Road, P. O. Box 384, Wayne, PA 19087		
CHEMICAL NAME AND SYNONYMS Hydrocarbon	TRADE NAME AND SYNONYMS Boiler P-154	
CHEMICAL FAMILY Wax	FORMULA	

N/A

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
N/A					

SECTION III PHYSICAL DATA

BOILING POINT (°F.)	---	SPECIFIC GRAVITY (H ₂ O=1)	---
VAPOR PRESSURE (mm Hg.)	---	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR=1)	---	EVAPORATION RATE (---=1)	N/A
SOLUBILITY IN WATER	Nil		
APPEARANCE AND ODOR White Solid			

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used) 500°F, COC, ASTM D-92	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA Water, CO₂, Foam and Dry Material			
SPECIAL FIRE FIGHTING PROCEDURES None			
UNUSUAL FIRE AND EXPLOSION HAZARDS No unusual hazards			

SECTION V. HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	
EFFECTS OF OVEREXPOSURE	Minimal irritation to skin and eyes.
EMERGENCY AND FIRST AID PROCEDURES	Remove molten material and treat for burn if skin is contacted. Flush eyes with water; if irritation call physician. If swallowed call physician.

SECTION VI. REACTIVITY DATA			
STABILITY	UNSTABLE	No	CONDITIONS TO AVOID Open flame and sparks.
	STABLE	Yes	
INCOMPATIBILITY (Materials to avoid)		Strong oxidizers	
HAZARDOUS DECOMPOSITION PRODUCTS		CO, and other asphyxiants when combusted.	
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII. SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	
Scrape up solid after cooling. May be pumped while hot.	
WASTE DISPOSAL METHOD Remove to reprocessing unit. Burn under controlled conditions. Use approved landfill area.	

SECTION VIII. SPECIAL PROTECTION INFORMATION		
RESPIRATORY PROTECTION (Specify type) Not ordinarily required.		
VENTILATION	LOCAL EXHAUST	Not ordinarily required.
	MECHANICAL (General)	---
SPECIAL		None
OTHER		---
PROTECTIVE GLOVES	When handling hot.	EYE PROTECTION Goggles to prevent splashing in eyes.
OTHER PROTECTIVE EQUIPMENT Normal equipment for handling hot, molten materials.		

SECTION IX. SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Avoid Skin contact with molten material. Treat as combustible material.
OTHER PRECAUTIONS	Use normal good hygiene.