

PLAINTIFF'S
EXHIBIT

OWENS-CORNING
FIBERGLAS
TRADE MARK - PAT. OFF.

O-C 660

INSULATING CEMENT

With rust inhibitor.
For temperatures up to 1800° F.

INSTRUCTIONS

1. Remove all dust, dirt, grease and paint from surface to be insulated.
2. Mix contents of this bag (50 lbs.) with 12 gallons of clean fresh water.
3. Provide heat in equipment if possible, to accelerate drying.

4. Apply first coat by sparring on to thickness of 1/4 to 1 and allow to set-up.
5. Apply additional coats as required, allowing each coat to set-up before applying next.

6. Trowel last coat to a smooth even finish when required thickness is obtained.
7. Note! Do not cover O-C 660 with Mastic Coating until fairly dry.

This Mineral Fiber Insulation conforms to
COMMERCIAL STANDARD CS-117-49
as issued by
U.S. DEPARTMENT OF COMMERCE

Net Weight 50 lbs.

6/30/64 "A mineral fiber product formerly known as Fencel in the West"
D-1024-3
S-10309 B-4

OWENS-CORNING
FIBERGLAS

O-C 660

INSULATING CEMENT

INSULATING
CEMENT

O-C 660

OWENS-CORNING
FIBERGLAS

C02136