

One U. S. Standard
Gallon

24-23 • BEIGE



DUTCH BOY

SHAKE & SHINGLE PAINT

EXTERIOR FLAT FINISH

Dutch Boy SHAKE AND SHINGLE PAINT

Modern Flat Finish for Shakes, Shingles and Rough-Textured Siding

This low-sheen, flat finish paint lends a distinctive charm to wooden shingles, shakes or rough-textured siding. Unique properties of Shake and Shingle Paint give excellent coverage and ease of application on rough-textured, porous wood surfaces. It remains intact and firmly adherent to the surface even under severe moisture conditions which would ordinarily cause blistering and peeling.

Note: Cedar wood contains oils which can cause unsightly staining of painted surfaces. A properly applied coat of Dutch Boy 017 Primer-Undercoater reduces the transmission of these oils to the surface of the paint.

FOLLOW DIRECTIONS—STIR WELL

Surface Preparation: Make sure all surfaces to be painted are clean and dry. Remove any loose or scaling paint. Be certain the paint is **stirred and well mixed**.

Application: On new unpainted wood and over previously painted surfaces which are chalky and porous, first apply a full coat of Dutch Boy 017 Shake and Shingle Primer-Undercoater.

according to label directions. Allow the primed surface to dry at least three days in good drying weather. Apply a finish coat of Shake and Shingle Paint at package consistency.

To produce a stain for shingles, add one-half gallon of linseed oil and one-half gallon of mineral spirits or turpentine to each gallon of Shake and Shingle Paint and stir thoroughly.

COMPOSITION OF PAINT BY WEIGHT

PIGMENT 55.6%

Titanium Dioxide 29.4%
Basic Silicate White Lead
48% PbO Type 8.6%
Calcium Carbonate 35.9%
Silica and Silicates 26.1%
*and tinting materials

VEHICLE 44.4%

Processed Linseed Oil ... 43.6%
Liquid Drier 5.0%
Mineral Spirits 1.4%
*Less than 5% of the total pigment.

PAINTING HINTS

Seal cracks and other openings, repair leaky flashings, downspouts and roofs to prevent entrance of water. Ventilate areas where moisture condenses within the walls.

Paint in good weather—not when it is damp, stormy or there is likelihood of a temperature drop to near freezing. Avoid painting in the late evening or in an intense sun.

Apply a good full coat of paint, covering the surface thor-

oughly and evenly. Allow about one gallon of paint for 300 to 450 square feet, depending on surface porosity. Putty nailholes and similar defects before applying finish coat.

Stains from exposed copper, bronze or iron screens, gutters, hardware, etc., which are not the fault of the paint, can be minimized by coating such surfaces with Dutch Boy Exterior Marine Spar Varnish or Screen Enamel.

CAUTION! Keep away from heat and open flame. Contains lead and mercury. Harmful if eaten. Do not apply on toys, furniture or interior surfaces which might be chewed by children. Use with adequate ventilation. Avoid breathing of vapor or spray mist or prolonged contact with skin. Wash thoroughly after using and before eating or smoking. Close can after using. **KEEP OUT OF REACH OF CHILDREN.**

NATIONAL LEAD COMPANY

GENERAL OFFICES: NEW YORK, N.Y.