THERMINOL®
Monsanto
MONSANTO INDUSTRIAL CHEMICALS CO.
a unit of Monsanto Company
800 N. Lindbergh Boulevard
St. Louis, Missouri 63166
Phone: (314) 694-1000

4-5

GASKETS AND PACKING FOR THERMINOL HEAT TRANSFER FLUIDS

Gaskets

Recommended flange gasketing for high temperature heat transfer fluid systems should be spiral-wound type conforming to API specification 601 (see piping specifications). Standard materials for spiral wound flange gaskets are Type 304 stainless steel and asbestos.

Important to non-leak performance with spiral wound gaskets is the use of raised-face flanges, alloy steel bolting and even compression of gasket during bolt pull up.

An acceptable alternate for many applications is a pure graphite gasket from Union Carbide, called Grafoil.

Generally, sheet asbestos gasketing with various binders is unacceptable for Therminol fluid applications because of temperature limitations or incompatibility of binder with Therminol fluids.

Ring joint flanging is not required for Therminol fluids unless frequent disassembly is necessary, thus justifying the added cost of this type flange joint.

Listed below are several manufacturers of spiral-wound gaskets:

Company	Gasket
Flexitallic Gasket Company Box 680 Point & Linden Streets Camden, N. J. 08101	Styles CG or CGP
Garlock, Inc. 402 Main St. Palmyra, N. Y. 14522	Type CR Guardian, Style 555

0471134

"Nothing contained herein is to be construed as a recommendation to use any product in conflict with any patent. MONSANTO MAKES NO WARRANTIES AS TO THE FITNESS OR MERCHANTABILITY OF ANY PRODUCTS REFERRED TO. no guarantee of satisfactory results from reliance upon contained information or recommendations, and disclaims all liability for any resulting loss or damage."

TOWOLDMON0032697
WATER_PCB-00017166

see cover Akron Gasket Packing Co silicone-?

2 Dave Roy — 633-3742

041135

Johns-Manville 22 East 40th St. New York, N. Y. 10016	Style 913
Melrath Supply & Gasket Co. Inc. 3500 Aramingo Ave Philadelphia, Pa. 19134	Style 50
Sterling Packing & Gasket Co. 8220 Mosley P.O. Box 264 Houston, Texas 77001	Spiroflex Type GR

Has Viton A — see footnote → Viton A gasket Material

240 —

Use Viton A 1st Choice

may be ? → Silicone 450°C

Graphite Gaskets Available From:

Union Carbide Corporation Carbon Products Div. 270 Park Avenue New York, N. Y. 10017	15 or 30 mil. thick sheet

Packing

Various types of packing are used to seal valve stems and small pump shafts on high temperature Therminol systems. Flexible metal or solid graphite packings give the best service.

Graphite or Teflon impregnated, short fiber asbestos gasketing is used also, but leak-free service is not always achieved at the higher temperatures with this type packing.

Generally, five rings of packing are specified on valve stems to assure a reasonable seal.

The use of metal bellows steam seals on valves is increasing and would, of course, provide absolute leak-free service.

This type seal is more expensive than the conventional flexible stem packing above and our experience at this time is limited.

Listed below are several manufacturers of valve stem and small pump shaft packing for Therminol application. We do not guarantee absolute leak-free service on Therminol by use of these examples; valve maintenance may be required occasionally.

TOWOLDMON0032698
WATER_PCB-00017167