

EN-1029



E. I. DU PONT DE NEMOURS & COMPANY

WILMINGTON, DELAWARE 19886

ENGINEERING DEPARTMENT

CC: B. B. Lewis
H. D. Boyce
E. Hooton, Jr.
J. C. Lang
R. K. Mason
W. C. Weaver
C. A. Parks
W. H. Zane, Design
Site Safety Supvr.

November 7, 1966

FIELD PROJECT MANAGERS

W. S. BRIGGS, BEAUMONT
G. E. BUBB, BREVARD
A. D. DAY, CAPE FEAR
C. S. ANDERSON, CHAMBERS WORKS
W. S. FREE, CHATTANOOGA
H. S. STANTON, JR., CIRCLEVILLE
W. G. HARRIS, COLUMBUS SHOPS
W. C. MANNEAR, F.S., FLORENCE
J. T. WALLACE, JOHNSONVILLE
R. H. DAVIS, KINSTON
R. G. STERNBERGER, LOUISVILLE
J. E. EARLEY, MARTINSVILLE
W. A. SAMANS, MAY

F. C. BAYLIS, MEMPHIS
H. F. REDMILE, OLD HICKORY
W. S. LEWIN, PARLIN
C. D. BROWN, PONTCHARTRAIN
E. M. VASS, SABINE RIVER
H. J. FEINEN, SAVANNAH RIVER
R. C. REBER, SEAFORD
R. A. MINIARD, SPRUANCE
S. V. HINSON, VICTORIA
W. BLAKE, WASHINGTON WORKS
S. KREWATCH, WAYNESBORO
G. E. BARLOW, JR., WILM. AREA
J. R. BALDER, SUPT., WILM. SHOPS

SAFETY - APPLICATION LIMPET INSULATION

We have been advised of the inherent health hazard exposure resulting from asbestos fibrous materials. The method we are presently using when applying Limpet insulating material by the use of air pressure and spray gun causes an extensive amount of the asbestos fibrous material to become air-borne. The employee health hazard created is the exposure for the human body absorbing these fibrous materials through inhalation or orally. In recognition of this potential when applying the Limpet material with a spray gun, the following precautions should be implemented and followed:

1. The application of Limpet material should be performed in an isolated or remote location on the project, free from exposing buildings or other personnel on the project not directly associated with the application. Air-borne fibers can be wind blown or taken into buildings through the ventilation air intake systems, and therefore, must be controlled to eliminate exposure to personnel unrelated to the Limpet application work.
2. Personnel exposed to the application of Limpet material shall be provided with respiratory protection consisting of either a fresh air supply hood or MSA cartridge type respirator using an ultra-high filter Type H, 50 micron density. It should be noted that when using the recommended MSA cartridge filter, that it will be extremely hard for the individual to breathe through especially if required to do work of heavy exertion.

(OVER)

DUP 0995197

2

Field Project Managers

Your usual cooperation is anticipated in implementing the above work procedures when applying this subject material.

CONSTRUCTION DIVISION

KE Keuper

K. E. Keuper
Division Safety Supt.

KEK:mhp

FIELD PROJECT MANAGER

CONSTRUCTION

DUP 0995198

DU 048348