FILE NAME: Henry Company (HC)

DATE: 1976 Jan 7

DOC#: HC003

DOCUMENT DESCRIPTION: Exhibit 11 - Letter from Henry Co to Mobil Oil Corp

ADHESIVES-SEALERS
HENRY
ROOF COATINGS

THE W. W. HENRY COMPANY

5508 SOTO STREET, HUNTINGTON PARK, CALIF. 90255, (213) 583-4961

January 7, 1976

Mobil Oil Corporation
150 E. 42nd Street
New York, New York 10017
Attention: Mr. D.E. Miller, Manager Safety and Fire Protection

Dear Mr. Miller:

Your request of December 1, 1975 to Williams Lumber Company about OSHA Standard 1910.93a in reference to Henry #208 Wet Surface Plastic Roof Cement has been sent here for response.

The #208 Plastic Roof Cement is an asphalt base product that binds any asbestos fibers into a sticky mass that prevents the fibers from becoming airborne. The product is designed to be used in either dry or wet weather but the fibers are never "dry" being permanently imbedded in an asphalt matrix that keeps them "wetted" and securely bound. In the event that someone would try to drill, saw or abrade #208, their equipment would immediately become gummed up with sticky asphalt and ineffectual.

As far as supplying "conclusive air test data" is concerned, OSHA Standard 1910.93a specifies that any tests be performed at the site where the employee works.

If you should need any further information we will be happy to be of help.

Sincerely,

Larry A. Balling
Technical Director

LAB:nb

OTHER PLANTS: • 3233 W. 36th Street, Chicago, Ill. 60632, (312) 254-3510
• 165 W. Broadway, Dover, Ohio 44622, (216) 343-4535
•• Foot of Whitehead Ave., South River, New Jersey 08882, (201) 254-2424

PENGAD 800-631-6989
EXHIBIT
LENDLER
11
2-28-17