

FILE NAME: Chrysler (CHRY)

DATE: 1978 July 27

DOC#: CHRY139

DOCUMENT DESCRIPTION: Memo RE Asbestos Survey at Toledo Machining
with Results



File Code

Date

July 27, 1978

To—Name & Department

Division

Plant/Office

CIMS Number

R. Normandin
From—Name & Department

Plant Manager

General Mfg.

Toledo
Machining

474-00-00

Division

Plant/Office

CIMS Number

W. D. Watt

Industrial Hygiene

Employee &
Ind. RelationsChrysler
Center

417-05-19

Subject:

ASBESTOS SURVEY AT TOLEDO MACHININGSummary

Investigation of the brake assembly operation in Department 9847 reveals that employees continue to be exposed to measurable concentrations of asbestos. Industrial Hygiene recommends that a down draft ventilated table be provided for the unloading and stacking of brake pads.

Discussion

On Tuesday, June 13, 1978, the writer investigated employee exposure to asbestos. Ralph Olson, Employment Supervisor, participated in the investigation. The investigation complies with the periodic survey required by the OSHA General Industry Standards, 29CFR 1910.1001.f.2.ii.

Department 9847

Results of the survey are similar to the previous survey of December 1977. The atmosphere in the work station of one employee was above the 8-hour permissible exposure limit during the sampling period, however, the time-weighted average concentration was within the OSHA Permissible Exposure Limit. In addition, the employee was wearing a respirator, which reduced his actual exposure considerably. Several other employees were exposed to measurable amounts of asbestos. Measurable concentrations of asbestos appear to be confined to the pad unload and stacking operation and the first two positions on the brake assembly lines.

Employees exposed to measurable amount of asbestos dust must be provided with annual physical examinations in compliance with the OSHA General Industry Standards 29CFR 1910.1001 (j). Details of the examination are contained in the Standard. The following employees should be given physical examinations:

C. Brant
B. Comer
M. Wagner
F. W. Smith

SS # 284-34-7508
SS # 282-48-5048
SS # 289-22-4742
SS # 292-32-0398



CHRYSLER 002428

TF-194

Re: Asbestos Survey at Toledo Machining

T. Randall and D. Di Lucia were exposed to measurable amount of asbestos; however, they are already receiving annual asbestos physical examinations from a previous exposure (see report of January 16, 1978).

Excessive loose asbestos dust on brake pads continues to be a problem. Incoming shipments of pads should be inspected by the foreman of Department 9847 or the safety administrator, and a written record retained. This is especially important until engineering controls are provided at the unload operation. Excessively dusty shipments should be refused and returned to the vendor. Chemical Division has been reminded of the need for better cleaning and inspection of their brake pads.

Pads which are not visibly dirty are still capable of producing dust. Engineering methods are recommended to reduce airborne dust levels. It is recommended that downdraft table combined with a Work-O-Matic bin be installed for the brake pad unloading and stacking operations. This has the potential for reducing manpower and should be reviewed by Industrial Engineering. A similar system is in use for the "pad only inspection station" at Chemical Division. Plans are not available for the system, however, Chemical Division has agreed to forward a picture of the system. The downdraft table should have an exhaust volume of 2000 cfm.

A review of this report and previous reports shows that the airborne dust concentration near Mr. T. Randall are much higher than comparable concentration near other workers performing the same task on the other line or in the same location on other shifts. This suggests that Mr. Randall's work habits are partially to blame for the high concentration. All workers handling brake pads, in particular Mr. Randall, should be instructed in proper methods for handling asbestos products to avoid creating dust. If this does not result in lower dust levels at Mr. Randall's work station, he should be changed to another job to protect both his health and the health of those working near him.

Because the exposure levels are within the Permissible Exposure Limit, respirators are not required in Department 9847. However, Industrial Hygiene recommends that respirators should continue to be available for all workers involved in unloading and stacking of brakes or working in the first two brake assembly positions and their use encouraged.

CHRYSLER 002503

