

CONFIDENTIAL (For use of Salesmen only)

Price List

Marine Paint.

1. 100
2. 100
3. 100
4. 100
5. 100
6. 100
7. 100
8. 100
9. 100
10. 100
11. 100
12. 100
13. 100
14. 100
15. 100
16. 100
17. 100
18. 100
19. 100
20. 100
21. 100
22. 100
23. 100
24. 100
25. 100
26. 100
27. 100
28. 100
29. 100
30. 100
31. 100
32. 100
33. 100
34. 100
35. 100
36. 100
37. 100
38. 100
39. 100
40. 100
41. 100
42. 100
43. 100
44. 100
45. 100
46. 100
47. 100
48. 100
49. 100
50. 100
51. 100
52. 100
53. 100
54. 100
55. 100
56. 100
57. 100
58. 100
59. 100
60. 100
61. 100
62. 100
63. 100
64. 100
65. 100
66. 100
67. 100
68. 100
69. 100
70. 100
71. 100
72. 100
73. 100
74. 100
75. 100
76. 100
77. 100
78. 100
79. 100
80. 100
81. 100
82. 100
83. 100
84. 100
85. 100
86. 100
87. 100
88. 100
89. 100
90. 100
91. 100
92. 100
93. 100
94. 100
95. 100
96. 100
97. 100
98. 100
99. 100
100. 100

THE SHERWIN-WILLIAMS CO.
NEW YORK, N. Y.

0007-SWP-042708

SECTION 2

PAINTER CRAFT

24312
JUN 20 1941

F. O. B. POINTS
OAKLAND, CALIF.
SAN FRANCISCO, CALIF.

Rev. ord 6/16/41



THE SHERWIN-WILLIAMS CO.

ADMINISTRATION OFFICES CLEVELAND, OHIO
SALES OFFICES, FACTORIES AND WAREHOUSES
IN PRINCIPAL CITIES

0007-SWP-042710

0007-SWP-000126064

LIQUID OZLO

—63109—

This ore is refined in the Sherwin-Williams' smelters under 2000

COMMONWEALTH STUCCO PAINT

Full oil paint manufactured especially for exterior use on concrete, brick and stucco surfaces. Can also be used for interior

ONE-COAT STUCCO PAINT

This product, as the name implies, is a one coat finish for exterior, masonry and concrete surfaces.

It is formulated to give solid covering and excellent adhesion in road work and may be used on all types of surfaces where high quality non-salt work, such as is recommended by our Brick and Concrete Institute is practicable.

Only Cent. Stucco Paint is not subject to the same degree of discoloration for retaining common to the so-called "water" or "casing"

Microfilm 16mm. 1 reel. W 16mm

File # 68108
Team # 03106

100-443887-100

Effective June 17, 1941
 Bureau File No. 781 CP (5) CRM

LEAD-ZINC-TITANOX PASTE

As the name implies, it is a combination of Lead, Zinc and Titanox in the proper proportion to give maximum covering and durability when used for exterior exposure. Ground in pure Refined Linseed Oil.

Gallons (Net weight 25 lbs. per gal.)	3.6
5 Gal. (Net weight 125 lbs. per gal.)	3.7

OUTSIDE WHITE PASTE No. 60

May be used wherever an outside paste is required, or it may be used to fortify interior or exterior paints.

20s Per Cwt.	11
50s Per Cwt.	10
100s Per Cwt.	10

MASTER PAINTERS PASTE WHITE

A high quality exterior white paste. It should be recommended wherever first quality white pastes are demanded. The painter who prefers paste paints will find in Master Painters Paste White those easy-working and good covering qualities demanded in this type product.

20s Per Cwt.	13
50s Per Cwt.	13
100s Per Cwt.	13

SPECIALTIES

SPARTITE MIXING SEALER

Spartite Mixing Sealer is a high quality clear Spar, giving additional toughness and tightness when mixed with interior or exterior finishes.

Spartite Mixing Sealer is an excellent reinforcing vehicle when used with outside semi-paste paints or Lead in Oil.

Especially useful when humid or other adverse weather conditions make it necessary to speed up the drying.

Read the label directions for use in Flat Wall Paints, Enamels, Dercoaters, and as a preventative for screen rust.

Gallons	2
5 Gal.	1

FLATTING OIL

Where the "hand-mix" method for obtaining flat finishes is desired, we recommend S-W Flattening Oil as the most dependable and economical product on the market. When combined with White I (ODP) it produces a paint that works freely under the brush, nicely, retains a satisfactory wet edge to avoid laps and brush marks and dries to a flat finish.

In mixing, add a little Flattening Oil at a time, stirring constantly.

Gallons	2
5 Gal.	1

Effective June 17, 1941
Conf. Price Book 78 CP (5) CRM

0007-SWP-042712

0007-SWP-000126066